

Polo; manual gearbox

Sichtprüfung

- ◆ Vacuum hoses connected
- ◆ Crankcase breather connected
- ◆ Lambda probes connected
- ◆ Electrical wiring for fuel mixture preparation and ignition systems connected
- ◆ Line for activated charcoal filter system connected
- ◆ Exhaust gas recirculation system connected
- ◆ Exhaust system must be free of leaks
- ◆ Catalytic converters installed and undamaged
- ◆ Restricted fuel tank filler neck installed

Test and setting conditions

- Test for readiness of operation (readiness code) generated

Notes

- Only check idling speed (not adjustable)

Prüfwerte für Abgasuntersuchung

Motoröltemperatur	mind. 80 °C
Leerlaufdrehzahl	740 ... 940 /min
Erhöhte Leerlaufdrehzahl	2500 ... 3000 /min
Lambdasondenwert	0,970 ... 1,030
Lambda im erhöhten Leerlauf	0,970 ... 1,030
CO-Gehalt im erhöhten Leerlauf	max 0,2 Vol. %
Lambdasonde	Breitbandsonde (Lambda)
Warmlaufzeit für Katalysator	2 min.

Strichcode für Abgasuntersuchung



76575808074009402530097010300970103020022002

Engine oil quantities

with filter change 3,2 l

Spark plugs

VW/Audi	101 000 062 AB
Manufacturer's designation	PZFR 5D-11
Electrode gap	1,0-1,1mm
Specified torque	30Nm
Change interval	60000 km