Team YT: possession from automatic tracking

More Than a Hack 2027, Phase 1. Barcelona (H) vs Athletic Club (A).

In one line: players stop running when the ball is dead, and a team has the ball when one of its players stays on it with the ball moving *with* him. Everything else is bookkeeping.


The submission `YT.csv` is rebuilt from the data by one command (section 8). No model is trained, no labels of any kind are used, and nothing is tuned on the public window. Every threshold below is either a physical quantity or read off a label-free statistic of the match, and is stated with its source.

Tags: **[measured]** found by running code on the data, **[derived]** arithmetic, **[assumed]** a choice we made and did not fit.

---

1. Approach

The ranking metric (spellF1) rewards recovering *whole possessions*, so the two things that matter are where possessions start and end. A possession ends in one of two ways: the other team takes control, or the ball goes dead. We detect the two separately and combine them in a small state machine:



We chose rules over a learned model because there is nothing legitimate to learn from: hand labels on this game are forbidden, the public 5 minutes are not a training set, and the private truth is private. Rules also make the possession definition explicit, which is what the technical document is asked to explain.

2. Data, and what we found in it

Used: the tactical ATD (`*_tactical_atd.txt`) and its metadata (`*_tactical_atd.xml`), and the tactical Smart Tagging. **Dropped:** both videos (labels must not come from watching them and we built no vision model), the homography (not needed for a tracking-only method), and everything broadcast (not synchronised to the submission timeline).

Facts we checked on the data rather than assumed:

ATD records / video frames	199,319 / 199,319, `video_frame = frame_id - 1` [measured]
Home side	`Score/@idLocalTeam` = Barcelona. 24 home slots, 22 away, one goalkeeper slot each [measured]
Barcelona attacks	left to right in the first half (metadata)
Third ball value	ball speed (`BallChannelRef s`), NaN on 91% of visible frames, so unused [measured]
Ball visible, graded frames	94,214 / 158,857 = 59.3% [measured; matches DATA.md]

Our baseline rebuild	`starter/baseline.py` output is byte-identical to the shipped baselines; public spellF1 0.0378 / 0.2868 / 0.3256 / 0.4242 as published [measured]
Second-half kick-off	graded block starts at 110,808, kick-off is at about 113,742 (detected 113,734). The 117 s before it are pre-match and labelled D [measured]
Smart Tagging time base	consistent in both halves: the kick-off tag starts 3.5 s (half 1) and 3.3 s (half 2) before the kick [measured]

The ball gaps are long, and mostly stoppages (`reports/gaps.md`). The 150 gaps in the graded frames have a median of 10.7 s; 85% of the missing frames are in gaps longer than 10 s and only 0.1% in gaps of 25 frames or fewer. So short-gap interpolation, the usual first fix, is close to worthless here. But while the ball is missing the players are slow (median p90 player speed 1.58 m/s, against 3.41 m/s when the ball is visible): the tracker loses the ball mostly when it is out of play. On frames our detector calls live the ball is missing only 14.1% of the time.

The public window is unrepresentative [measured]: the ball is visible on 88% of its frames, against 59% over the match. Scores on it say little about the hard parts of the full match.

3. Dead ball

Signal. For every frame, the 90th percentile of the players' speeds, smoothed with a 1 s centred median ("activity"). Over the whole match its histogram is clearly bimodal [measured]: a stoppage mode at 1.25–1.75 m/s, a live mode around 3 m/s, and a valley at 2.0–2.25 m/s. No labels are needed to see it.

Core. A stoppage *core* is a stretch where activity falls below 2.0 m/s (the valley) and stays below 2.5 m/s (hysteresis), lasting at least 2 s, with cores less than 1 s apart merged.

Veto for slow build-up. Players also walk while a team circulates the ball at the back. A core is dropped if, over its first half, the ball is visible, at least 3 m inside every line and moving faster than 3 m/s on more than 60% of frames. A dead ball is still, missing, or out; a live one keeps moving between players.

Edges. The core lags the whistle, so its edges are moved to events:

- *onset*: the last moment the ball crossed a line (tracked position more than 1 m outside the pitch; the ATD places the ball about 1.5 m inside the touchline even at throw-ins [measured]), else the moment the tracker lost the ball, else the peak of player activity in the 5 s before the core (the players start to decelerate at the whistle);
- *restart*: the last "kick" (ball speed from below 2 m/s to above 5 m/s) between 4 s before and 2 s after the core ends.

Self-calibration for edges we cannot see. When no kick is visible (83 of 139 restarts), or the deceleration peak sits at the very start of the search window (activity already falling, 22 onsets), the edge is placed using a lag measured on this match from the edges we *can* see. Where the ball is seen to go out or be lost, the core starts a median of 46 frames (1.8 s) later. Where a kick is visible, the core ends a median of 8 frames (0.3 s) after it [measured]. The ball itself is the reference, and no labels are involved.

Kick-offs. The first kick from within 5 m of the centre spot after both teams have stood in their own halves for 2 s. Everything in the half before it is dead.

Smart Tagging as a prior. Inside a tagged set-piece window, a shorter (1 s) and shallower (below 2.5 m/s) dip also counts, but only if the ball is placed (below 0.5 m/s for 0.5 s) and only where the base rule found nothing, so the tags can add a quick restart but never stretch or move a stoppage we already found. Tags are automatic and not ground truth; this is the only way they touch the dead mask.

Label-free checks [measured]: 55 of the 59 tagged set pieces overlap a detected stoppage (the remaining ones include the opening kick-off, which is the start of the graded block). The dead share of graded frames is 46.9%, which is plausible: LaLiga's effective playing time is commonly reported to be low, around 52–55 minutes per match (a public figure we did not verify).

4. Control

Our definition: **a team has control when one of its players stays close to the ball for 0.4 s, no opponent is challenging, and the ball is moving with the player.** Concretely, on frames with a visible ball:

- *close*: the nearest player is within 2.0 m to take control and within 2.5 m to keep it;
- *uncontested*: no opponent within 1.5 m;
- *with the player*: the ball's velocity and the player's differ by less than 4 m/s (velocities from 5-frame smoothed positions; slot swaps only make this noisy on the swap frame);
- *held*: 10 consecutive frames.

A confirmed run is stamped from the frame the player first came within range, not from the frame the relative-speed test first passed, because a ball arriving from a pass is still fast for a few frames after the receiver reaches it. We use track slots only to read the team.

Variants compared (all with the same dead-ball detector and state machine, submitted settings otherwise):

variant	rule	possessions (full match)	mean length	public macroF1	public spellF1 [90% bootstrap interval]
C1	nearest player within 2 m, 10-frame dwell	415	8.1 s	0.842	0.442 [0.295, 0.579]
C2	C1 + contest test + hysteresis	440	7.7 s	0.850	0.508 [0.368, 0.649]
C3	C2 + ball moves with the player	**302**	**11.2 s**	0.853	0.506 [0.353, 0.659]

On the public window the variants are indistinguishable (the bootstrap intervals are 0.3 wide). We chose C3 on two other grounds. First, it implements the challenge's own "not control" cases (a touch without control, a deflection that does not intercept). Second, its possession rate is closer to what the public truth implies once the dead share is accounted for. The public window has 3.4 possessions per minute with 80% of its frames live. At our full-match live share of 53.1%, that scales to about 2.3 possessions per minute [derived]; C3 gives 2.9 and C2 4.2.

Where C2 and C3 disagree (11.6% of the frames both call live) the cause is almost always a short run that C2 accepts and C3 rejects [measured, full match]:

frames	C2	C3	why
40,413–40,708	A	H	C2 accepts a 14-frame A run at 1.9 m with the ball 10.3 m/s faster than the player: a ball flying past. The ball then vanishes for 9 s and C2 holds the wrong team throughout
76,433–76,858	A	H	19-frame A run at 2.1 m, relative speed 4.4 m/s, just before a 16 s ball gap. C3 keeps the H player who had it at 1.1 m, moving with it
163,686–164,017	H	A	an H player 1.1 m from the ball, but the ball leaves at 5 m/s relative to him: a deflection. C3 keeps the A possession that preceded it
155,925–156,045	H	A	an 11-frame H run at 1.9 m with relative speed 7.8 m/s and no opponent within 36 m: a pass skimming past a player
126,213–126,357	A (C2)	H (C1)	C1 vs C2: a 13-frame A run at the 2 m entry edge that C2 keeps through its 2.5 m hold radius and C1 drops

Sensitivity grid, declared before scoring (dwell {8,10,12,14} × entry radius {1.5,2.0,2.5} × contest radius {1.0,1.5,2.0}, C2, run at v1 settings): public macroF1 stays within 0.829–0.852 in all 36 cells. The full-match possession count moves from 290 to 507 and depends mostly on the entry radius, because a larger radius accepts more balls passing near an opponent. We did not pick a cell by public score; the defaults are the values we wrote down before running anything.

Why the control detector abstains, share of live graded frames (C3): control 29.8%, ball missing 14.1%, nobody within 2 m (a pass in flight or a loose ball) 39.6%, contested 2.5%, ball not moving with the player 12.6%, run shorter than the dwell 1.3%. Abstaining is not a problem in itself, because the last owner keeps the ball.

5. State machine

1. A dead frame is `D`, with no owner.
2. In play, possession changes only on the first frame of a confirmed control run by the other team. The dwell is applied once, inside the control detector, so boundaries do not drift late.
3. Between control runs, including through ball gaps and loose or contested phases, the last owner keeps the ball (the challenge's rule for loose balls).
4. After a stoppage, the owner from the restart frame is the restarting team: the team of the player nearest the ball (within 3 m) around the restart kick. If the ball is not visible there, the team on the corner, free-kick or goal-kick tag is used. If neither is available, the team of the

first control run is back-filled to the restart frame. On the 13 tagged restarts where we have both, our own estimate agrees with the tag on 11.
5. The owner resets at each half. Frames outside the graded halves are `X`.
6. A possession shorter than 1 s is merged into its neighbours only when both neighbours are the same team in the same live stretch. It is never merged across a dead ball, so `H D H` stays two possessions.
7. We never write `X` on a graded frame once an owner is known. Under spellF1 an `X` repeats the last label anyway, and under macroF1 it is a guaranteed miss.

6. Evaluation and what we did not do

Every version is logged in `reports/ablation.csv` with its commit and settings, its public-window scores, and label-free proxies for the full match: dead share, possessions per minute, mean possession length, share of possessions under 1 s, and in-play home share. We changed one thing at a time.

version	change	public macroF1	public spellF1	full-match possessions	dead share
published floor	baseline_smooth50	0.6207	0.3256		
v1_C2	dead ball + C2 + state machine	0.8502	0.5081	431	46.0%
v1_C3	C3 control	0.8539	0.5059	297	46.0%
v2	second-half pre-kickoff dead	0.8539	0.5059	293	47.5%
v3	Smart Tagging prior and restart teams	0.8539	0.5059	299	47.7%
v4 (submitted)	self-calibrated edges where no event is visible	0.8533	0.5059	302	46.9%

These are public-window numbers on 17 possessions, and the organisers measured that one missed possession moves spellF1 by about six points. They show the pipeline is aligned and the labels mean what we think. They are not evidence that one version beats another, and we did not use them that way.

Disagreements with the public truth (the organisers asked to hear about them). We list them, and did not change anything to remove them:

- **11,351–11,477.** The truth switches to H at 11,351. The ATD shows an away slot (one tracklet covering 9,632–36,673) dribbling the ball at 0.7–1.2 m with no home player closer than 2 m until 11,470. Team counts are 10 against 10. We believe the uncorrected ball or that track differs from the corrected tracking here. This one case puts our first three boundaries 5–8 s late.
- **12,800–12,850.** The truth says A while a home player is 1.1 m from the ball and the nearest away player is 4.4 m away, just before a stoppage. This looks like the same kind of difference.
- **17,380.** The truth goes dead at 17,380, about a second after the players had already slowed to walking pace. Our onset (17,302) is 3 s early.
- **17,838.** The truth goes live on what looks like a short corner tap, about 1.4 s before the clear kick at 17,873 where we restart.

Not done:

- We did not estimate the ball position from player movement during gaps. Gaps in live play are rare (14% of live frames), and only 2 of 84 such gaps longer than 1 s end with the other team in control.
- We did not use the video in any way.
- We did not tune on the public window.

7. Limitations

- **Blind restarts.** 83 of 139 restarts have no visible kick. They are placed with the median kick-to-activity lag from the visible ones, but that lag varies (interquartile range about -0.7 to +1.2 s), and a late or early restart moves the start of the next possession. We tried to do better from the players alone, and tested it without labels. On the 52 restarts outside the public window where the kick is visible, we hid the ball and estimated the kick from player movement, fitting each method's offset on one half and testing it on the other [measured]. The current lag rule has a median error of 0.96 s (62% within 1 s). None of the four alternatives beat it once early calls are counted: when activity bottoms out (0.96 s), the steepest acceleration of the players (0.86 s, but 18 early calls over 1 s against 12), the players near the last-seen ball speeding up (1.20 s), or a jump in the share of running players (1.10 s). Neither did a median of three of them (0.96 s; better on 9 restarts, worse on 11). So we kept the lag rule. A restart's timing seems to need the ball, or the video.
- **Onset timing** depends on which event comes first. When players slow before the whistle (an advantage being played, or a slow attack stopped by a foul), the deceleration onset fires early.
- **The ATD ball near the touchline** sits about 1.5 m inside, so "out" uses a 1 m margin beyond the line. Some balls that leave the pitch are never seen to.
- **Slot teams are trusted.** A tracklet that switches between players of opposite teams would put control on the wrong side. We measured how often the tracking shows signs of this, over the whole match [measured]. Of 3.25 million consecutive slot positions, 83 move more than 2 m in one frame (five times sprint speed) and none move more than 5 m. A home and an away slot stay within 0.5 m of each other for at least 1 s 51 times (1.1% of graded frames), mostly far from the ball (94 frames within 3 m of it), which is consistent with tight marking rather than one player tracked twice. Only 4 of our 165 direct possession changes have either sign within 2 s near the ball. The two public-window disagreements in section 6 show neither sign, so the tracking cannot reveal them, and we built no correction for them.
- **Distances are 2D.** Aerial balls look close to players they fly over. The contest and relative-speed tests remove most of them, but not all.
- **With more time** we would add: (1) team-shape evidence (the team in possession spreads out and pushes up) to place restarts when the ball is invisible; (2) the challenge's "more than two consecutive passes" proxy as a second confirmation of a change of possession; (3) an explicit goal and celebration detector, so the long stoppages after goals have clean edges.

8. Reproduction

Python 3.13, `pip install -r requirements.txt` (numpy and pandas, pinned). Unpack the data bundle into `data/` (or point `MTAH_DATA_DIR` at it), then:

```
python run_pipeline.py --out YT.csv
```

This builds the file, runs `evaluation/validate_submission.py` on it, and prints the public-window scores and the full-match proxies. It takes about 20 s, and the first run also caches the parsed tracking in `data/cache/`. `scripts/clean_clone_check.sh YT.csv` clones the repository into a temporary folder, rebuilds the file from the raw tracking with `--no-cache` and compares SHA-256 hashes. It passes on the submitted commit. `python -m unittest discover tests` runs 26 unit tests.

Code map: `yt/load.py` (parsing and alignment), `yt/features.py`, `yt/dead.py`, `yt/control.py`, `yt/tags.py`, `yt/machine.py`, `yt/evalkit.py` (scoring wrapper, proxies, ablation log), `yt/gaps.py` (gap report), `run_pipeline.py`.

Training data: none. No labelled data of any kind, from this game or any other, is used.