

## Table of Contents

01	Title & Notes
02	Notes & Block Diagram
03	FS26
04	MCU PWR
05	MCU IOs
06	JTAG/SWD/CORTEX DEBUG+ETM
07	ON BOARD DEBUG - K26
08	CAN/LIN PHY
09	USER PERIPHERALS
10	ARDUINO HDRS

## Revision History

Rev	Description	Date	Approved/Designer
X	Initial Schematic	07/2021	Jesús Sánchez
X1	A055 Released	07/2021	
X1	A070 Released	07/2021	Jesús Sánchez
X2	0ohm res added, ThruHole TP added on VTRKx nets.	07/2021	Jesús Sánchez
A	A085 Released	08/13/2021	Jesús Sánchez
B	D18 added, R602 deleted	09/2021	Jesús Sánchez



# XS32K312EVB-Q172

Customer Evaluation Board

### CAUTION:

This schematic is provided for reference purposes only. As such, NXP does not make any warranty, implied or otherwise, as to the suitability of circuit design or component selection (type or value) used in these schematics for hardware design using the NXP S32K family of Microprocessors. Customers using any part of these schematics as a basis for hardware design, do so at their own risk and NXP Semiconductors does not assume any liability for such a hardware design.

3 Different test points used in design:

TPVx - Through Hole Pad small



TPHx - Through Hole Pad Large (for standard 0.1" header). Also used on IO Matrix (IOMx)



TPX - Surface Mount Wire Loop



### Notes:

- All components and board processes are to be ROHS compliant
- All connectors and headers are denoted Jx/Fx and are 2.54mm pitch unless otherwise stated
- All jumpers are denoted Jx. Jumpers are 2mm pitch
- Jumper default positions are shown in the schematics. For 3 way jumpers, default is always posn 1-2.
- 2 Pin jumpers generally have the "source" on pin 1.
- All switches are denoted SWx
- All test points (SMT wire loop style) are denoted TPx
- Test point Vias (just through hole pads) are denoted TPVx

Signals (ports) have not been routed via busses as this makes it harder to determine where each signal goes.


User notes are given throughout the schematics.

**Specific PCB LAYOUT notes are detailed in ITALICS**

		Automotive Product Group	
6501 William Cannon Drive West Austin, TX 78735-6596			
This document contains information proprietary to NXP and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of NXP Semiconductors.			
© NXP SEMICONDUCTORS		Classification: <FCP>	X
Designer: Jesús Sánchez		Drawing Title: XS32K312EVB-Q172	
Drawn by: Jesús Sánchez		Page Title: TITLE PAGE	
Approved: Jesús Sánchez	Size B	Document Number SCH-50892 PDF: SPF-50892	Rev B
Date: Tuesday, September 14, 2021		Sheet 1 of 10	



## 1. DNP Table

REF DES	ASSY OPT	PAGE NAME
R1940,J14,J10,J413,R1319,J15, J400,R27,R31,R1320,J11,J414, J2	DNP	03. FS26
R88,C113,TP88,C88,C127,J7, C3865,R89,J31,C91,R78,J13, TP114,R94,TP80,R79,R85,C115, TP253,U71,R80,R108,J15,C116, R81,R305,Q6,R72,R82,R1090, TP116,J19,R1973,U6,R1985,R86, R73,C109,R1091,R1971,C87, C268,C84,C94,TP84,R615,C111, R1051,TP85,C95,R1981,R333, C128,R107,C266,C3864,C86,R60, R77,R349,R1983,C267,TP87	DNP	04. MCU PWR
R2082,R1975,R130,R1240,R1108, R2178,R2175,R2081,R1979	DNP	05. MCU PORTS1
P200,R1949,R1950,R146	DNP	06. JTAG/SWD/CORETEX DEBUG+ETM
R260,J3,R1958,R202,R593,R240, J689,R1959,R594,R595,R592, C172,J682,R257,R254,R596	DNP	07. OPENSDA K26
R1331,R1205,R1202,C150,R1885, R2037,C3839,C3876,R1333,C149 J411	DNP	08. CAN/LIN PHY
R2150,R1816,R2084,R2088, R1965,R2168,R1814,R2180, R2012,R1963,R1810,R2148, R2152,R2171,R2156,R2078, R2077,R2021,R2161,R1811, R2172,R2158,R2169,R2174, R2164,R2022,R2151,R2162, R2173,R2166,R1967,R2182, R2079,R2167,R2152	DNP	09. USER PERIPHERALS 10. ARDUINO HDRS






## **2. Jumper Default configuration**

REF DES	JUMPER(DEFAULT)	PAGE NAME
J26	1-2 Closed	03. FS26
J22,J1,J5	1-2	03. FS26
J30	OPEN	03. FS26
J18,J10	1-2 Closed	04. MCU PWR
J9,J8	1-2	04. MCU PWR
J7,J31,J13,J15,J19	OPEN	04. MCU PWR
J44	OPEN	07. OPENSND A K26
J20,J24	OPEN	08. CAN/LIN PHY



## FS26 - Power Supply




SMPS-based SBC



NXP		Automotive Product Group
6500 VEHICLE CONTROL DRIVE WEST		Vehicle Control Drive West
This document contains information proprietary to NXP and shall not be used for engineering design, manufacturing or production purposes without prior written permission of NXP.		Classification: <input checked="" type="checkbox"/> C2D
© NXP SEMICONDUCTOR	Document No.	X332K312EVB-D172
Date Issued:	Sheet No.	Page No.
Initials:	Page Number:	FS26 SBC Power Supply
Approved:	Rev.:	Document Number: X332K312EVB-D172


S32K312 Microcontroller - 172MaxQFF

## **Power Supply Pins**



	<b>Automotive Product Group</b> 6555 Wilshire Center Drive West Santa Monica, CA 90403-1406 USA
<p>This document contains information proprietary to NXP and is not to be used for engineering design, reproduction or manufacture in whole or in part without the express written permission of NXP Semiconductors.</p>	
 	
Jesus Sanchez <small>Design Engineer</small>	<b>X32ZB28EV-Q172</b> <b>S32XXX - MCU POWER Supply Pins</b>
Design No: S32XXX - MCU POWER Supply Pins	Page No.: 00000000000000000000000000000000
Approved: Jesus Sanchez	Date: 05/05/2024
Document Number: SCIA000000000000000000000000000000	File Type: PDF - SPP - 00000000





**Automotive Product Group**  
6501 William Cannon Drive West  
Austin, TX 78735-5000

This document contains information proprietary to NXP and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of NXP Semiconductors.

© NXP SEMICONDUCTORS Classification: <ECP> <EURO> <PUE>

Designer: Javier Sánchez Drawing Title: M200M210TMD\_SATE

Jesus Sanchez XS32K312EVB-Q172


Drawn by: Page Title: ITAG/CORTEX Dedua : ETM  
Jesus Sanchez



JTAG/Cortex Debug+ETM


Approved: Jesús Sánchez Date: 3/26/2024 Document Number: SCH-50892 PDF: SPF-50892 Rev: B


Date: Tuesday, September 14, 2021 Sheet 6 of 10

2 | 1









<b>NXP</b>		Automotive Product Group
600 VDC Rated Diode West		600 VDC Rated Diode East
This document contains information proprietary to NXP and shall not be used for engineering design, manufacturing, test or production purposes without prior written permission from NXP.		
© NXP SEMICONDUCTORS	Classification:	CONF
Design Name: Jesse Sarker	Design Ver.: 1.0	Page No.: X32K312EVB-0172
Design Date: 2011-09-01	Design Rev.: 0000	ARDUINO Shield
Document Name: SCH-X32K312EVB-0172	Document Number: SCH-X32K312EVB-0172	Page No.: 1
Issue Date: 2011-09-01	Issue Rev.: 0000	Sheet No.: 1 of 16
NXP reserves all rights. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in whole or in part, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the express prior written permission of NXP.		