In [ ]:

In [112]:

```python
# IMPORT LIBRARIES
import numpy  as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

In [113]:

```python
a=pd.read_csv(r"C:\Users\user\Downloads\Salesworkload1.csv")
a
```

Out[113]:

	MonthYear	Time index	Country	StoreID	City	Dept_ID	Dept. Name	HoursOwn	Hours
0	10.2016	1.0	United Kingdom	88253.0	London (I)	1.0	Dry	3184.764	
1	10.2016	1.0	United Kingdom	88253.0	London (I)	2.0	Frozen	1582.941	
2	10.2016	1.0	United Kingdom	88253.0	London (I)	3.0	other	47.205	
3	10.2016	1.0	United Kingdom	88253.0	London (I)	4.0	Fish	1623.852	
4	10.2016	1.0	United Kingdom	88253.0	London (I)	5.0	Fruits & Vegetables	1759.173	
...	...	...	...	...	...	...	...	...	
7653	06.2017	9.0	Sweden	29650.0	Gothenburg	12.0	Checkout	6322.323	
7654	06.2017	9.0	Sweden	29650.0	Gothenburg	16.0	Customer Services	4270.479	
7655	06.2017	9.0	Sweden	29650.0	Gothenburg	11.0	Delivery	0	
7656	06.2017	9.0	Sweden	29650.0	Gothenburg	17.0	others	2224.929	
7657	06.2017	9.0	Sweden	29650.0	Gothenburg	18.0	all	39652.2	

7658 rows × 14 columns

```
a=a.head(10)
a
```

	MonthYear	Time index	Country	StoreID	City	Dept_ID	Dept. Name	HoursOwn	HoursLease
0	10.2016	1.0	United Kingdom	88253.0	London (I)	1.0	Dry	3184.764	0.0
1	10.2016	1.0	United Kingdom	88253.0	London (I)	2.0	Frozen	1582.941	0.0
2	10.2016	1.0	United Kingdom	88253.0	London (I)	3.0	other	47.205	0.0
3	10.2016	1.0	United Kingdom	88253.0	London (I)	4.0	Fish	1623.852	0.0
4	10.2016	1.0	United Kingdom	88253.0	London (I)	5.0	Fruits & Vegetables	1759.173	0.0
5	10.2016	1.0	United Kingdom	88253.0	London (I)	6.0	Meat	8270.316	0.0
6	10.2016	1.0	United Kingdom	88253.0	London (I)	13.0	Food	16468.251	0.0
7	10.2016	1.0	United Kingdom	88253.0	London (I)	7.0	Clothing	4698.471	0.0
8	10.2016	1.0	United Kingdom	88253.0	London (I)	8.0	Household	1183.272	0.0
9	10.2016	1.0	United Kingdom	88253.0	London (I)	9.0	Hardware	2029.815	0.0

In [115]:

```
# to find
a.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 14 columns):
 #   Column         Non-Null Count  Dtype
---  ------         --------------  -----
 0   MonthYear      10 non-null     object
 1   Time index     10 non-null     float64
 2   Country        10 non-null     object
 3   StoreID        10 non-null     float64
 4   City           10 non-null     object
 5   Dept_ID        10 non-null     float64
 6   Dept. Name     10 non-null     object
 7   HoursOwn       10 non-null     object
 8   HoursLease     10 non-null     float64
 9   Sales units    10 non-null     float64
 10  Turnover       10 non-null     float64
 11  Customer       0 non-null      float64
 12  Area (m2)      10 non-null     object
 13  Opening hours  10 non-null     object
dtypes: float64(7), object(7)
memory usage: 1.2+ KB
```

In [116]:

```
# to display summary of statastic
a.describe()
```

Out[116]:

	Time index	StoreID	Dept_ID	HoursLease	Sales units	Turnover	Customer
count	10.0	10.0	10.000000	10.0	1.000000e+01	1.000000e+01	0.0
mean	1.0	88253.0	5.800000	0.0	6.543725e+05	1.978511e+06	NaN
std	0.0	0.0	3.614784	0.0	9.914003e+05	2.861420e+06	NaN
min	1.0	88253.0	1.000000	0.0	5.491500e+04	2.904000e+05	NaN
25%	1.0	88253.0	3.250000	0.0	1.034225e+05	4.033612e+05	NaN
50%	1.0	88253.0	5.500000	0.0	2.615525e+05	5.770455e+05	NaN
75%	1.0	88253.0	7.750000	0.0	4.284400e+05	1.518067e+06	NaN
max	1.0	88253.0	13.000000	0.0	3.107935e+06	8.714679e+06	NaN

In [117]:

```
# to display colum heading
a.columns
```

Out[117]:

```
Index(['MonthYear', 'Time index', 'Country', 'StoreID', 'City', 'Dept_ID',
       'Dept. Name', 'HoursOwn', 'HoursLease', 'Sales units', 'Turnover',
       'Customer', 'Area (m2)', 'Opening hours'],
      dtype='object')
```

```
sns.pairplot(a)
```

```
<seaborn.axisgrid.PairGrid at 0x20b06f67c10>
```

```python
sns.displot(a["HoursOwn"])
```

```
<seaborn.axisgrid.FacetGrid at 0x20b0ad88610>
```

```python
b=a[['MonthYear', 'Time index', 'StoreID','Dept_ID',
       'Sales units', 'Turnover']]
b
```

	MonthYear	Time index	StoreID	Dept_ID	Sales units	Turnover
0	10.2016	1.0	88253.0	1.0	398560.0	1226244.0
1	10.2016	1.0	88253.0	2.0	82725.0	387810.0
2	10.2016	1.0	88253.0	3.0	438400.0	654657.0
3	10.2016	1.0	88253.0	4.0	309425.0	499434.0
4	10.2016	1.0	88253.0	5.0	165515.0	329397.0
5	10.2016	1.0	88253.0	6.0	1713310.0	5617137.0
6	10.2016	1.0	88253.0	13.0	3107935.0	8714679.0
7	10.2016	1.0	88253.0	7.0	213680.0	1615341.0
8	10.2016	1.0	88253.0	8.0	54915.0	290400.0
9	10.2016	1.0	88253.0	9.0	59260.0	450015.0

In [121]:

```
sns.heatmap(b.corr())
```

Out[121]:

`<AxesSubplot:>`

In [123]:

```
x=a[['MonthYear', 'Time index', 'StoreID','Dept_ID',
      'Sales units', 'Turnover']]
y=a['HoursOwn']
```

In [124]:

```
from sklearn.model_selection import train_test_split

x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.3)
```

In [125]:

```
from sklearn.linear_model import LinearRegression
lr=LinearRegression()
lr.fit(x_train,y_train)
```

Out[125]:

`LinearRegression()`

In [126]:

```
lr.intercept_
```

Out[126]:

-615.501770111332

```
coeff=pd.DataFrame(lr.coef_,x.columns,columns=['Co-efficient'])
coeff
```

|	Co-efficient
MonthYear	0.000000e+00
Time index	-1.141877e-08
StoreID	-7.954593e-10
Dept_ID	2.824382e+02
Sales units	7.103682e-04
Turnover	1.236540e-03

```
prediction = lr.predict(x_test)
plt.scatter(y_test,prediction)
```

<matplotlib.collections.PathCollection at 0x20b0c513af0>

```
lr.score(x_test,y_test)
```

-0.1897424986365066

```
lr.score(x_train,y_train)
```

0.9797989937763778

In [131]:

```python
from sklearn.linear_model import Ridge,Lasso
```

In [132]:

```python
rr=Ridge(alpha=10)
rr.fit(x_test,y_test)
```

Out[132]:

```
Ridge(alpha=10)
```

In [133]:

```python
rr.score(x_test,y_test)
```

Out[133]:

```
1.0
```

In [134]:

```python
la=Lasso(alpha=10)
la.fit(x_test,y_test)
```

Out[134]:

```
Lasso(alpha=10)
```

In [135]:

```python
la.score(x_test,y_test)
```

Out[135]:

```
0.9999999966322987
```

In [ ]: