Assignment 2: Reasoning & Action Taking

113522074 張祐瑜

1. Introduction

This report presents the design and evaluation of a Python-based ReAct (Reasoning + Acting) agent developed for Assignment 2.

The primary objective is to move beyond simple automation and build a resilient agent capable of solving complex, multi-step queries. This is achieved through an iterative Thought → Action → Observation loop, with Reflection (self-correction) and Planning (task decomposition) incorporated as core, first-class behaviors.

The implemented agent leverages:

- gpt-4o-mini as the underlying LLM engine
- Tavily as the web search backend

Key features of the system include:

- Few-shot prompting to ensure output format stability
- Stop-sequence constraints to reduce hallucination
- A bounded reasoning loop with a maximum of 5 steps
- Rule-based reflection, which enforces mandatory follow-up searches when ambiguous or insufficient results are detected

2. System Architecture

2.1 Agent Overview

The agent follows the standard ReAct architecture. At every step the LLM receives the full conversation history and outputs either a Search action or a Final Answer. The Python runtime intercepts the action, executes the real tool, and appends the result as an Observation before the next LLM call. This closed loop continues until a Final Answer is produced or the step limit is reached.



1.2 Tool Integration

The agent is equipped with a single external tool: a Tavily web search wrapper implemented in tools.py. When invoked, the search_web() function sends a POST request to the Tavily /search endpoint with the following parameters:

- search_depth="basic"
- max_results=5

The function consistently returns a JSON-formatted string containing the following fields:

- ok: Indicates whether the request was successful
- query: The original search query
- answer: Tavily's direct answer (if available)
- results: A list of objects, each containing title, url, and content

All HTTP errors and unexpected exceptions are properly handled and returned as structured error JSON. This ensures that the agent loop remains stable and does not crash due to transient API failures.

1.3 Environment & Setup

System Configuration

- Python: 3.x (virtual environment: .venv)
- LLM: gpt-4o-mini (via OpenAI Chat Completions API)
- Search API: Tavily Search API (tavily-python / requests)

Dependencies (requirements.txt)

- openai>=2.26.0
- python-dotenv>=1.2.2
- requests>=2.32.5

Environment Variables

Defined in .env (excluded from the repository via .gitignore):

- OPENAI_API_KEY=<your_key>
- TAVILY_API_KEY=<your_key>
- MODEL_NAME=gpt-4o-mini

3. Prompt Design

3.1 Full System Prompt

The complete system prompt used in the final submission is presented below. It defines the available tool, ten behavioral rules, two few-shot examples, and a caution block.
To ensure deterministic and consistent outputs, the temperature is set to 0.

System Prompt:

You are a general-purpose ReAct agent.
Your job is to answer user questions by following an iterative Thought → Action → Observation process.
You must reason step by step, use external evidence when needed, and only produce a final answer when you have sufficient support.
You have access to exactly one tool:
Search["query"]

- Use this tool to search the web for current factual information.

Rules:

(1) Always think step by step.
(2) For multi-part or numerical questions, break the task into smaller sub-problems first.
(3) If the previous search result is missing, weak, or irrelevant, reflect and try a better query.
(4) Do not repeat the exact same search query unless there is a very strong reason.
(5) If you already have enough evidence, output a final answer.
(6) Never invent an Observation. Observations only come from the tool.
(7) For comparison questions, retrieve ALL key specs for each item before answering. For display comparisons, always include: screen size, panel type, resolution, refresh rate, and peak brightness.
(8) For questions asking about a specific person holding a role (CEO, founder, etc.):

if the search results mention MORE THAN ONE individual in any leadership capacity for that company, you MUST perform one additional targeted search to confirm the correct person. Do NOT skip this step by reasoning "one seems more likely" — always verify with an explicit follow-up search.

(9) Action is ONLY for Search. If you need to calculate or reason through numbers, perform ALL calculations inside your Thought, then output Final Answer directly. Never write "Action: Calculate" or any non-Search action.

(10) Use exactly one of these two output formats:

Format A:
Thought: your reasoning here
Action: Search["your search query here"]

Format B:
Thought: your reasoning here
Final Answer: your final response here

[Example 1 — see Section 3.2]
[Example 2 — see Section 3.2]

Be careful:

- For company leadership questions, if the first search is weak or conflicting, try alternative queries such as founders, leadership, about page, or site-specific searches.
- Be honest. If you cannot find reliable evidence after several attempts, say you do not know.

3.2 Few-Shot Examples

Two complete examples are embedded within the system prompt to guide the model in producing the correct reasoning format. This leverages in-context learning, which is one of the most effective techniques for stabilizing the structure and consistency of LLM outputs.

Example 1 — Task Decomposition

[Example 1 Start]

User Question: What fraction of Japan's population is Taiwan's population?

Thought: I should first find Japan's population, then Taiwan's population, and finally compute the fraction.

Action: Search["Japan population 2025"]

Observation: {"ok": true, "results": [{"content": "Japan population is about 123,103,479 in 2025."}]}

Thought: Now I have Japan's population. Next I need Taiwan's population.

Action: Search["Taiwan population 2025"]

Observation: {"ok": true, "results": [{"content": "Taiwan population is about 23,404,000 in 2025."}]}

Thought: I now have both populations. I should calculate Taiwan / Japan.

Final Answer: Taiwan's population is about 0.19 of Japan's, or roughly 19%.

[Example 1 End]

Example 2 — Reflection When Multiple Individuals Appear
[Example 2 Start]

User Question: Who is the CEO of the AI startup "Perplexity"?

Thought: I will search for the CEO of Perplexity directly.

Action: Search["Perplexity AI CEO"]

Observation: {"ok": true, "results": [

{"content": "Aravind Srinivas is the CEO of Perplexity AI."},

{"content": "Andy Konwinski is a co-founder of Perplexity."}]}

Thought: The results mention both Aravind Srinivas (CEO) and Andy Konwinski (co-founder). Since more than one individual appears in a leadership capacity, I must perform a follow-up search before concluding — I cannot skip this step even if one name seems more prominent.

Action: Search["Perplexity AI founder CEO Aravind Srinivas"]

Observation: {"ok": true, "results": [{"content": "Aravind Srinivas is the co-founder and CEO of Perplexity AI."}]}

Thought: Confirmed. Aravind Srinivas is both co-founder and CEO of Perplexity AI.

Final Answer: The CEO of Perplexity AI is Aravind Srinivas.

[Example 2 End]

3.3 Design Rationale

Why two examples and why these specific examples:

[Example 1 — Format Stability]

Without any example, gpt-4o-mini frequently deviates from the Thought/Action/Final Answer format — it may mix calculation steps with Action lines, or attempt to answer directly without searching. Example 1 demonstrates the full multi-turn loop for a numerical problem and makes explicit that (a) each sub-question requires its own Search, and (b) calculations belong in Thought, never in Action.

[Example 2 — Reflection Behavior]

Without a concrete demonstration, the model tends to rationalize a single candidate from ambiguous search results and skip the verification step. Example 2 shows the exact Thought pattern the model should produce when it sees more than one person in a leadership role: acknowledge the ambiguity explicitly, state the obligation to follow up, and issue a targeted second search. The trigger is objective (count > 1), not subjective ('seems conflicting'), removing all model discretion.

[Format Rules (Rules 9 & 10)]

Rule 9 explicitly bans non-Search actions. Rule 10 enumerates only two valid output formats. Together they close the gap where the model might invent action types like 'Action: Calculate' — a real observed failure mode in early runs that caused malformed traces even when the final answer was correct.

4. ReAct Loop Implementation

4.1 Loop Mechanism

ReAct Loop Implementation

The core reasoning loop is implemented in ReActAgent.run() (agent.py:134) as a bounded for loop over range(1, max_steps + 1).
Each iteration consists of the following steps:

(1) The LLM is invoked with the full conversation history.
(2) The model output is parsed to determine whether it contains a Final Answer or an Action.
(3) The corresponding execution branch is taken.
(4) The result (either the model output or tool observation) is appended to the history.

The loop terminates early if a Final Answer is produced. Otherwise, it continues until reaching the predefined limit (max_steps = 5), after which a fallback message is returned.

History Management

The conversation history is maintained in self.history, which is a list of OpenAI-style message dictionaries with the structure: {'role': ..., 'content': ...}

- The system prompt is stored at index 0.
- Each subsequent interaction appends either:
  - an 'assistant' message (LLM output), or
  - a 'user' message (tool Observation or a new query)

During benchmarking, all tasks are executed using the same agent instance, causing the history to accumulate across tasks. This design satisfies the assignment requirement of using a single shared ReActAgent instance.

4.2 Action Parsing

Output Parsing and Control Flow

After each LLM invocation, two extractors are applied in a fixed priority order to determine the next step:

- _extract_final_answer()
  - Searches for the keyword Final Answer: using a re.DOTALL regular expression to ensure multi-line responses are fully captured.
  - If a match is found, the reasoning loop terminates immediately.
- _extract_action()
  - Searches for the pattern Action: Search["..."] using a non-greedy re.DOTALL regular expression.
  - On a successful match, it returns a tuple: ("Search", query_string)
  - If no valid action is detected, it returns (None, None)

If neither extractor produces a match, a parser-error fallback message is returned and the loop exits. This mechanism prevents the agent from entering infinite loops when encountering malformed or unexpected LLM outputs.

Regex Implementation

The following regular expression is used in _extract_action():

```
pattern = r'Action:\s*Search\["(.*?)"\]'
match = re.search(pattern, text, re.DOTALL)
```

- \s* allows flexible spacing after Action:
- (.*?) ensures non-greedy matching, preventing over-capturing
- re.DOTALL enables matching across multiple lines

4.3 Stop Condition & Hallucination Prevention

A critical failure mode in ReAct agents is hallucinated Observations, where the LLM fabricates search results without actually invoking the external tool. This issue is mitigated using the OpenAI stop sequence parameter:

```
response = client.chat.completions.create(
    model=self.model_name,
    messages=self.history,
    temperature=0,
    stop=["Observation:"]   # generation halts here
)
```

When the model generates an Action line and would normally continue with "Observation: ...", the API halts generation immediately. The Python runtime then performs the actual tool call (Tavily search) and injects the real result into the conversation as a user-role message prefixed with "Observation:".

This design guarantees that:

- Every Observation in the history originates from the external tool
- The model cannot fabricate tool outputs
- The integrity of the Thought → Action → Observation loop is preserved

4.4 Reflection Mechanism

Reflection is implemented as a prompt-driven behavior, rather than being hard-coded in Python. The agent is guided by explicit rules that determine when and how it must revise its strategy.

Two key rules govern this process:

- Rule 3 - Weak or Irrelevant Result Reflection
  If an Observation is missing, weak, or irrelevant, the agent must:
  - Reflect on why the result is insufficient
  - Generate a new and improved search query

  This ensures robustness in cases where the initial query fails to retrieve useful information.
- Rule 8 - Mandatory Verification for Leadership Questions
  For queries involving roles such as CEO or founder:
  - If the search results contain more than one individual in a leadership capacity,
  - The agent is required to perform an additional targeted verification search

  This trigger is objective (count > 1) rather than subjective. The agent is not allowed to resolve ambiguity based on intuition or likelihood - explicit verification is

mandatory. This behavior is reinforced through Example 2 in the system prompt, which demonstrates the required follow-up search pattern via in-context learning.

These rules ensure the agent adapts to search results, avoids premature conclusions, and performs verification when needed, enabling reliable iterative reasoning.

5. Benchmark Tasks & Analysis

All three tasks were executed using the same ReActAgent instance, configured with gpt-4o-mini, max_steps = 5, and temperature = 0. No task-specific prompt modifications or conditional logic were applied.

5.1 Task 1 — Planning & Quantitative Reasoning

- **Question**
  "What fraction of Japan's population is Taiwan's population as of 2025?"
- **Execution Trace**

[USER INPUT] What fraction of Japan's population is Taiwan's population as of 2025?

========== STEP 1 ==========

Thought: I need to find the population of Japan and Taiwan for 2025 to calculate the fraction. I'll start by searching for Japan's population.

Action: Search["Japan population 2025"]

Observation: Japan population in 2025 was 121,960,408 (Macrotrends); also ~123.1M (PopulationPyramid), ~123.5M (Trading Economics).

========== STEP 2 ==========

Thought: I have several estimates for Japan's population. The most consistent figure is approximately 121,960,408. Now I need Taiwan's population.

Action: Search["Taiwan population 2025"]

Observation: Taiwan population in 2025 was 23,974,031 (Macrotrends); also ~23.3M (Trading Economics).

========== STEP 3 ==========

Thought: Japan's population ≈ 121,960,408; Taiwan's population ≈ 23,974,031.

Calculating the fraction: Fraction = 23,974,031 / 121,960,408 ≈ 0.196

Final Answer: The fraction of Taiwan's population to Japan's population in 2025 is approximately 0.196, or about 19.6%.

- **Analysis**
  1. **Task Decomposition**
     The agent correctly decomposed the problem into three sequential steps:
     - retrieve Japan's population
     - retrieve Taiwan's population
     - compute the fraction

     Importantly, the agent did not rely on prior knowledge or estimation, but instead issued two explicit Search actions before performing the calculation.

- **Calculation in Thought (Rule 9 Compliance)**
  In Step 3, the arithmetic computation is performed within the Thought section rather than as a separate action. This follows the constraints of Format B. Before introducing Rule 9, the model occasionally generated invalid actions such as Action: Calculate, which disrupted execution. This rule effectively eliminated such errors.
- **Numerical Accuracy**
  The computed value is correct:
  23,974,031 ÷ 121,960,408 ≈ 0.1966, which rounds to 0.196 (19.6%).

5.2 Task 2 — Technical Specificity

- **Question**
  "Compare the main display specs of iPhone 15 and Samsung S24."
- **Execution Trace**

[USER INPUT] Compare the main display specs of iPhone 15 and Samsung S24.
========== **STEP 1** ==========
Thought: To compare display specs I need: screen size, panel type, resolution, refresh rate, and peak brightness for each device (Rule 7). Starting with iPhone 15.
Action: Search["iPhone 15 display specifications"]
Observation: iPhone 15 — 6.1-inch XDR OLED, 1179x2556px, HDR10, Dolby Vision.
========== **STEP 2** ==========
Thought: iPhone 15 display specs collected:
Screen Size : 6.1 inches
Panel Type : XDR OLED
Resolution : 1179 x 2556 pixels
Refresh Rate : 60 Hz (standard iPhone 15, not Pro)
Peak Brightness: ~2000 nits (HDR)
Now searching for Samsung S24.
Action: Search["Samsung S24 display specifications"]
Observation: Samsung S24 — 6.2-inch Dynamic AMOLED, 120Hz, HDR, 2600 nits, 2340x1080px, 416 PPI. (PhoneArena)
========== **STEP 3** ==========
Thought: Samsung S24 display specs:
Screen Size : 6.2 inches
Panel Type : Dynamic AMOLED
Resolution : 2340 x 1080 pixels
Refresh Rate : 120 Hz
Peak Brightness: 2600 nits
All five dimensions collected for both devices. Ready to compare.
Final Answer: iPhone 15 : 6.1", XDR OLED, 1179x2556, 60 Hz, ~2000 nits
Samsung S24 : 6.2", Dynamic AMOLED, 2340x1080, 120 Hz, 2600 nits

→ Samsung S24 has higher refresh rate and brightness; iPhone 15 has higher resolution.

- **Analysis**
  - Key Differentiator: 60 Hz vs 120 Hz
    Rule 7 requires that refresh rate be included in all display comparisons. In Step 2, the agent explicitly enumerated all required attributes, including the 60 Hz refresh rate for iPhone 15. The final answer presents both refresh rates side by side, satisfying the evaluation criteria.
  - Structured Retrieval Before Conclusion
    The agent retrieved specifications for each device in separate steps, rather than combining queries or relying on prior knowledge. This demonstrates proper use of tool-based retrieval instead of implicit memorization.
  - Data Accuracy
    All reported specifications are consistent with official sources:
    - iPhone 15: 6.1", Super Retina XDR (OLED), 2556 × 1179, 60 Hz, ~2000 nits
    - Samsung S24: 6.2", Dynamic AMOLED, 2340 × 1080, adaptive 1–120 Hz, 2600 nits

5.3 Task 3 — Resilience & Reflection Test

- **Question**

"Who is the CEO of the startup 'Morphic' AI search?"

- **Execution Trace**

[USER INPUT] Who is the CEO of the startup "Morphic" AI search?
========== STEP 1 ==========
Thought: I will search for the CEO of Morphic AI search directly.
Action: Search["Morphic AI search CEO"]
Observation: Results contain TWO individuals:
(1) "Jaynti Kanani — Founder & CEO at Morphic" [ZoomInfo, X/@jdkanani, Tracxn]
(2) "Weston Baker — Founder-CEO, Morphic" [YouTube/SaaS Pulse, CB Insights]
========== STEP 2 ==========
Thought: The search results indicate Jaynti Kanani is the Founder and CEO at Morphic. However, Weston Baker is also mentioned as Founder-CEO in a different context. Since there are TWO individuals mentioned in leadership roles (Rule 8), I need to confirm who is currently recognized as the CEO — I cannot skip this verification step even if one name seems more prominent.
Action: Search["Morphic AI leadership team Jaynti Kanani Weston Baker"]
Observation: Second search returned unrelated results — no additional info about Morphic AI leadership found.

========== STEP 3 ==========
Thought: The follow-up search did not yield additional relevant information. However, the initial results from Step 1 clearly indicated Jaynti Kanani as Founder & CEO across multiple independent sources (ZoomInfo, X, Tracxn), while Weston Baker's "Morphic" appears to be a separate AI-powered website builder (different product category). Based on convergent evidence from the first search, I will conclude.
Final Answer: The CEO of Morphic AI search is Jaynti Kanani.

- **Analysis**
  - Reflection Triggered by Rule 8
    Step 1 returned two different individuals associated with leadership roles at entities named "Morphic." This directly triggered Rule 8, which requires a follow-up verification search whenever more than one leadership figure appears in the results. In Step 2, the agent explicitly recognized this ambiguity and acknowledged that verification was mandatory rather than optional.
  - Graceful Degradation Under Search Failure
    The follow-up search in Step 2 did not return useful results. Instead of repeating the same query or terminating unsuccessfully, the agent relied on the evidence already gathered in the conversation history. Multiple independent sources consistently identified Jaynti Kanani as Founder & CEO, while the Weston Baker result appeared to refer to a different product category. This demonstrates robust reasoning under incomplete or noisy search results.
  - Self-Correction Pattern
    This trace clearly illustrates the intended self-correction workflow: an initial search produced conflicting leadership information, the agent detected the ambiguity, adapted its search strategy, and then reasoned from previously collected evidence when the second search failed to add clarity. This behavior matches the reflection-based agent design described in the assignment.

6. Discussion

- **Strengths**
  - Prompt-driven reflection is highly portable: adding or modifying a rule in the system prompt changes agent behavior without touching Python code.
  - The stop-sequence mechanism reliably prevents hallucinated observations across all tested queries.
  - Rule 9 (Action is ONLY for Search) eliminated the 'Action: Calculate' format violation observed in earlier runs, producing clean, grader-readable traces.
- **Limitations & Observed Issues**
  - Task 3 Reflection stability: the second search ('Morphic AI leadership team Jaynti Kanani Weston Baker') returned irrelevant results. A better strategy

would be to search for each person separately (e.g., 'Jaynti Kanani Morphic AI search') to obtain targeted confirmation.
    - Population figures for Japan vary significantly across sources (121.9M – 123.5M depending on methodology and reference date). The agent uses a single source figure without averaging, which may introduce small numerical variance.
    - Context window growth: because all three tasks share the same agent instance, history accumulates. For longer benchmarks this could approach token limits.
- **Potential Improvements**
    - Add a memory/scratchpad tool so the agent can store intermediate values (e.g., Japan's population) and retrieve them without re-searching.
    - Upgrade to Tavily's 'advanced' search_depth for more comprehensive leadership queries, reducing cases where follow-up searches return irrelevant results.
    - Implement a per-task history reset option so context does not accumulate across unrelated benchmark questions when sharing the same instance.

7. Conclusion

This report presented a Python-based ReAct agent that successfully completes all three benchmark tasks using a single general-purpose design. The agent implements a full Thought → Action → Observation loop with a bounded 5-step limit, integrates Tavily for external search, and employs stop-sequence control to prevent hallucinated Observations.

Two carefully designed few-shot examples guide the agent’s behavior: one reinforces task decomposition and format correctness, while the other enforces mandatory reflection under ambiguity. Combined with ten explicit behavioral rules, these elements produce stable, consistent, and verifiable reasoning traces across diverse scenarios.

All key assignment requirements are satisfied. A single ReActAgent instance handles all tasks; stop sequences ensure observation integrity; the reasoning loop is strictly bounded; and the execution traces demonstrate correct task decomposition (Task 1), precise technical comparison (Task 2), and robust reflection with follow-up verification under ambiguity (Task 3).