

Teach Formal Languages Together With Graph Querying for Great Power

Semyon Grigorev
!!!@corporation.com
Institute for Clarity in Documentation
Dublin, Ohio, USA

Egor Orachev
The Thørvöld Group
Hekla, Iceland
larst@affiliation.org

Vadim Abzalov
The Thørvöld Group
Hekla, Iceland
larst@affiliation.org

Rustam Azimov
The Thørvöld Group
Hekla, Iceland
larst@affiliation.org

Ekaterina Shemetova
The Thørvöld Group
Hekla, Iceland
larst@affiliation.org

ABSTRACT

Formal languages has deep interconnection with graph structured data analysis: respective knowledges are necessary to develop both query processing engines frontend (parser and lexer) and to develop formal language constrained path querying (FLPQ) evaluation algorithms. Efficient solution of respective problems requires deep theory knowledge and applied skills not only in formal languages, but also other areas such as graph theory and high-performance computing. We propose a course that is developed for software engineers, and focused on formal language related aspects of graph analysis, including query parsing and FLPQ evaluation algorithms.

CCS CONCEPTS

• **Computer systems organization** → **Embedded systems**; *Redundancy*; Robotics; • **Networks** → Network reliability.

KEYWORDS

Graph querying, formal language theory, formal language constrained path querying, education

ACM Reference Format:

Semyon Grigorev, Egor Orachev, Vadim Abzalov, Rustam Azimov, and Ekaterina Shemetova. 2018. Teach Formal Languages Together With Graph Querying for Great Power. In *Woodstock '18: ACM Symposium on Neural Gaze Detection, June 03–05, 2018, Woodstock, NY*. ACM, New York, NY, USA, 6 pages. <https://doi.org/10.1145/1122445.1122456>

1 INTRODUCTION

Bridging the gap between fundamental disciplines and applications is one of the important problems of education in software engineering. Graph structured data analysis involves broad range of areas including graph theory, high-performance computing, complexity analysis. Development of high-quality data analysis solutions requires both deep theory knowledge and strong applied experience.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Woodstock '18, June 03–05, 2018, Woodstock, NY

© 2018 Association for Computing Machinery.
ACM ISBN 978-1-4503-XXXX-X/18/06...\$15.00
<https://doi.org/10.1145/1122445.1122456>

It is a challenge for education to provide comprehensive view of the area and to develop the necessary skills.

One of the disciplines that has deep interconnection with graph structured data analysis is a formal language theory. Formal languages is a fundamental part of graph query languages in, at least, two senses. First of all, formal language theory is necessary to design query engines frontend, namely parser and lexer. The second one is that formal language constrained path querying is an important part of modern graph query languages. An ability to utilize regular languages to specify path constraints (RPQ) is a part of GQL query language that is an ISO standard¹, and it is a part of SPARQL that is W3C standard [1]. Context-free languages constrained path querying (CFPQ) is also studied intensively [5–7, 13] and respective proposal for OpenCypher query language exists².

Even these two directions should be investigated together to find the best way to design query language to be able to express respective formal language constraints. At the same time, to apply formal languages for graph analysis efficiently we should involve graph theory and high-performance computing. The answers on many questions were easier if utilize techniques from these disciplines together. For example, how should we restrict query language power to be able to provide evaluation algorithm? How can we represent a query evaluation result? How to build such a representation efficiently for huge graphs?

In this work we propose a course³ that is developed for software engineers, and focused on formal language related aspects of graph analysis, including query parsing and formal language constrained path query execution algorithms. This work is organized as follows.

- The first part is motivation where we argue why we do exactly what we do and why we do it exactly such a way.
- The second part is a course structure description that consists of technical environment description, high-level structure of the course, including exercises and tests examples.
- The third part is a discussion of existing course that includes current limitations and drawbacks, and comparison with other related courses.
- The last part is a brief conclusion and possible future improvements of the presented course.

¹ISO/IEC 39075:2024, GQL, <https://www.iso.org/standard/76120.html>

²OpenCypher Path Pattern Queries that allows one to specify context-free constraints: <https://github.com/opencypher/openCypher/pull/187>.

³Materials are available !!!

2 MOTIVATION

We are aimed to create an applied course with relatively low but strong fundamental prerequisites that allows students to learn interconnection between formal languages, graph analysis and high performance techniques and respective fundamentals.

Formal language theory centric view on graph query engine. The idea of the course is to apply formal languages to design query engines and allows students to touch at least two areas of formal languages application: parsing and graph querying.

Graph is a fundamental concept that arises in broad range of applications Static code analysis. Graph databases. Query languages.

Why formal language constrained path querying. Formal languages is not only parsing. But query engines requires parsing too. It allows us Smoothly combine different areas and demonstrate deep interconnection between them. Main: data analysis and formal languages. FLPQ part of the GQL ISO standard.

Immediate and direct usage of theory to solve practical tasks: Closure properties. Fundamental questions in graph query expressive power and query result representation. Formal language theory is necessary to answer !!! Languages intersection. Query results representation — languages representation. Any finite representation of regular language is a representation of an answer. A way to represent infinite result in convenient finite form with well-established tools for analysis. Complexity analysis.

At the same time, combination with graph analysis allows one to get a refreshed view on parsing algorithms and old problems that became actual again in new context. For example, incremental parsing, parallel parsing. In a new context (amount of data to process, variability of grammars, not only graphs etc). Another example is a grammar disambiguation that is classical problem for parser developers. On the one hand, generalized parsing is a base for querying algorithms. At the same time time ambiguity is not an evil: sometimes ambiguous queries faster then disambiguated versions. Especially for reachability querying. But not for parsing or path problems.

Linear algebra provides a suitable abstraction level. Application level independent optimizations !!! HPC, matrices, easy to abstract. One can easily replace one library with another without significant algorithm changes (but technical effort for different API-s). As a result, easy to apply for real-world data. Which also helps to solve a motivation problem (small synthetic tasks looks disconnected with real-world).

Significant part of the selected algorithms can be expressed in terms of boolean matrices and vectors: easy to start. No need to create custom semirings. At the same time, native description of these algorithms requires custom semirings introduction. Conversion techniques. Weaker than semirings structure: linear algebra, operation properties.

Language design and implementation. Tooling for language implementation. Well-established parsing algorithm (LR, LL). Actively developed promising Generalized GLL. Moreover, CFPQ algorithms is based on parsing algorithms [? ? ?]. One of the most popular tool ANTLR is not a magic.

Relations with other areas such as graph theory, dynamic graph problems, algebra, distributed graph processing.

Touch open problems (truly subcubic CFPQ) and motivate to study them (and respective fundamentals eg fine-grained complexity). Performance on real-life problems.

Thus based on strong general fundamentals of formal language theory we cover several applied aspects of graph query engines, such as query language parsing and formal language constrained path queries evaluation algorithms for different classes of languages. Also we touch other important applied and fundamental areas such as graph analysis, linear algebra, high-performance techniques.

3 THE COURSE

The course was initially designed for third year bachelor students studying software engineering. But with tiny modification was also used for first year masters in software engineering. Presented version of the course was used in two universities during several years but is still under development.

3.1 Prerequisites

This course is designed for programming engineers so it requires basic engineering skills in Git version control system and GitHub infrastructure, including GitHub actions for CI, code review mechanisms and so on.

We expect an intermediate level in Python programming, including experience with testing frameworks, linters, formatters, dependency managers.

We expect a basic level of linear algebra. Students should freely operates with matrices, vectors, semirings. They should know definitions and properties of matrix-matrix operations such as Kronecker product, elementwise operations, matrix-matrix multiplications, matrix-vector multiplication.

Basic level of graph theory is required, including definitions and properties of directed edge-labeled graphs and relative concepts like path and cycle.

We expect an experience in basic graph analysis algorithms analysis and implementation, such as traversal algorithms (BFS and DFS), path problems related, and reachability problem related algorithms (transitive closure computation, Dijkstra's algorithm, Floyd-Warshall algorithm).

Programming languages theory is also required. Particularly, basic knowledge in formal semantics, type systems, experience in interpreters implementation.

3.2 Learning Outcomes

Upon completing the course, students will be able to explain where and how formal language constrained path querying (including RPQ, CFPQ) can be applied, and how graph databases and static code analysis are interconnected.

Also students will be able to formulate FLPQ problem and explain differences between queries semantics. Additionally they will be able to explain interconnection between formal languages classes and fundamental aspects of FPLQ, including decidability and results representation.

Students will be able to operate with regular languages and its representations, particularly to convert regular expression to finite automata and back, to intersect regular languages, and to implement linear algebra based algorithms for RPQ.

The same for context-free languages and its representations. Students will be able to convert context-free grammar (CFG) to recursive state machine (RSM), to build derivation trees, to implement various algorithms for CFPQ, including linear algebra based and GLL based, and to explain how language and grammar properties interconnect with respective algorithms' properties.

Additionally, students will be able to use linear algebra for graph analysis. Particularly, they will be able to reduce RPQ and CFPQ related problems to boolean linear algebra, to analyze performance of respective algorithms, to explain importance of matrices formats and basic optimization techniques.

Finally, students will be able to develop query languages, including ability to use ANTLR parser generator to create parsers, to craft interpreters that use FLPQ algorithms to evaluate queries, provide type checking, and grammar (query) consistency checking. They will be able to explain basic parsing algorithms, including LL, LR, GLL, to describe differences between them, and limitations of respective tools.

3.3 The Structure

The course is structured with respect to typical formal language theory related course meaning that there is a hierarchy of languages and respective computation machines (Chomsky hierarchy) that often uses to organize materials. Almost all parts combine the theory, respective algorithms and its analysis, including discussion of performance-critical implementation details, possible optimization techniques. Brief content of the parts is provided below.

- (1) **Introduction to formal languages** that includes basic definitions such as alphabet, word, language, basic operations over words and languages, including set-theoretic ones. Here we also introduce the classical Chomsky hierarchy of languages and respective computation machines.
- (2) **Introduction to graphs and linear algebra** should be tuned with respect to initial level of students such that after this part students will be familiar with basic definitions and algorithms, such as definitions of directed and undirected edge-labelled graphs, paths, and cycles, formulation of reachability and paths problems, and respective algorithms. Additionally, graph representations, including adjacency matrix and its boolean decomposition, and basic graph analysis algorithms in terms of linear algebra, such as transitive closure and multiple-source BFS, should be introduced.
- (3) **Introduction to formal language constrained path querying.** This part introduces the formal language constrained path querying (FLPQ) [2] problem statement in the most general form, and describes different semantics including reachability, all-paths, all-pairs, multiple-sources. Fundamental problems, such as infinite number of paths, and, as a result, inability to represent the answer explicitly as a set in some cases, decidability for different languages classes, also discussed here. To bring the gap between two areas we demonstrate that string parsing or recognition problem is a partial case of FLPQ. At the same time we show that there is a number of differences with classical languages processing, such as the fact that language is not fixed in graph querying: while in classical language processing cases we assume

that the language is fixed and the string is varying, in graph querying both graph and language can vary. Also we discuss history of FLPQ from Mihalis Yannakakis and Thomas Reps to nowadays, including areas of applications, examples, difference and interconnection between static code analysis and graph databases.

- (4) **Regular languages** and ways to specify them, such as regular expression, regular grammars, and finite automata, with transformations between them. We discuss formal properties of languages and show how they relate with RPQ. For example, the fact that regular languages are closed under intersection is the base of RPQ that allows one to consider respective algorithms and query evaluation results representation. Respective algorithms introduced here.
- (5) **Context-Free languages** and ways to specify them, including grammars, recursive state machines (RSMs) and conversions between them. Similarly to regular languages, we introduce formal properties that are important for CFPQ, such as Bar-Hillel theorem that claims context-free languages are closed under intersection with regular ones, and respective algorithms. Also we discuss differences and interconnections between CFPQ and parsing.
- (6) **Discussion of well-known old challenges that became actual again.** Parallel and distributed parsing is not so hot problem, but parallel and distributed query processing is. Another problem is a handling changes in input that still actual for parsing but became more complex challenge in the context of graph querying. The main reason is that in FLPQ both graph and grammar can vary while in parsing only string can.
- (7) **Query language implementation** where we introduce classical LL(k) and LR(k) parsing algorithms, among with generalized algorithms like GLL, and provide a comparison of respective language classes. We describe typical language processing workflow: lexing, parsing, abstract syntax tree construction, and interpretation (with respect to previously introduced FLPQ algorithms). ANTLR as one of the modern production-quality parser generation tool is introduced.
- (8) **Beyond Context-Free languages and Chomsky hierarchy.** In this part language classes that are more expressive than context-free languages introduced. Namely, Multiple Context-Free languages (MCFL), Conjunctive and Boolean languages because these classes of languages are used for static code analysis [3, 15]. For now we discuss only basic definitions and properties without algorithms.

3.4 Exercises

Exercises are focused on FLPQ algorithms implementation and evaluation rather than basic concepts implementation. So we force students to use libraries such as PyFormLang and sciPy to operate with languages, automata, or matrices. The main part of exercises is focused on reachability problem for different classes of languages because the reachability problem is often simpler to implement than path problem. For example it does not require special semirings in linear algebra based algorithms, the boolean one is enough. Different variations, such as all-pairs and multiple source, included.

Almost all the tasks are conceptually interconnected: starting from basic FLPQ algorithms, through its evaluation, simple graph analysis system will be created as a result of the course. As an additional bonus, such scheme limits tasks skipping because some of them are necessary to complete another one.

Brief description of tasks are presented below in order that corresponds to the structure represented in the previous section.

- (1) Implementation of all-pairs RPQ with reachability semantics, using Kronecker product, that is the basic finite automaton intersection algorithm.
- (2) Implementation of multiple-source BFS-based RPQ algorithm, including different versions such as one-to-many and many-to-many.
- (3) RPQ algorithms evaluation and performance analysis including analysis of sparse matrix representation formats.
- (4) Hellings's CFPQ algorithm implementation that is a pretty simple algorithm without linear algebra and will be used as a baseline for evaluation.
- (5) Matrix multiplication based CFPQ algorithm implementation that requires grammar in Chomsky normal form.
- (6) Kronecker product based CFPQ algorithm implementation that utilizes RSM for grammar representation.
- (7) Implementation of GLL-based CFPQ algorithm that does not use linear algebra and utilize RSM for query representation.
- (8) Evaluation performance analysis of implemented CFPQ algorithms with focus on different algorithms comparison.
- (9) Implementation of parser for simple predefined graph query language using ANTLR. The language is focused on formal language constrained path querying, not a subset of GQL.
- (10) Interpreter of simple graph query language implementation that uses previously implemented algorithms for queries evaluation and provides some additional static query checks.

Exercises can be splitted in subtasks or equipped with additional introductory tasks, for example, with simple challenges aimed to investigate a new library.

All exercises also grouped in blocks that are three in total: Regular Languages, Context-Free Languages, and Parsing techniques. This division is formal to introduce tests. While blocks are almost synchronised with lectures, we do not separate introduction block because first two modules (1 and 2) size significantly varies with respect to initial level of students.

3.5 Tests

Each block equipped with short tests to check related basic knowledge. There is a bunch of questions for each block and each student randomly gets one of them and should provide an answer in 5 minutes. This allows us to check that student has mastered basics almost all of which were used to complete exercises from the respective block. Tests used to weight tasks. The main idea is that if the student can not pass test, then it is highly possible that exercises, even be passed, done with cheats. Examples of questions are presented below.

- (1) Show whether Kronecker product is commutative operation.
- (2) Convert the given regular expression to finite automaton.
- (3) Provide a derivation tree for the given string and grammar.
- (4) Convert the given context-free grammar to RSM.

3.6 Environment

The course designed for engineers and include a number of programming-related exercises that requires unified environment to for all students to simplify work of tutor and mentors.

We chose Python programming language as one of the most popular language, particularly among students. Additionally, all the required libraries available in Python and provide easy to use and well-documented interface. Namely, we need libraries for formal languages, sparse linear algebra, parsers creation, and we choose the following ones.

PyFormLang⁴ [11] is used to provide basic formal languages concepts such as regular expressions, finite automata, context-free grammars, recursive automata, and operations over them such as automata minimization, regular expression to finite automata conversion, grammar to normal forms conversion and so on.

SciPy⁵ is used for sparse boolean linear algebra. It provides different formats for sparse matrices representations, thus allows us to demonstrate correlation between matrix representation format and performance of matrix-based algorithms.

We use ANTLR⁶ [10] as a parser generation tool. ANTLR is one of the modern tools for parser development that supports Python as a target language: it can generate parser in Python and appropriate runtime libraries are provided.

Also we use CFPQ-Data⁷ for algorithms evaluation. This dataset allows us to provide real-world graphs and queries from such areas as RDF analysis and static code analysis.

Initial project structure with dependencies and checkers configured is provided as a GitHub repository⁸ to be forked by students. The repository contains configured actions for CI, supplementary code, placeholders for exercises, functions signatures to implement, and other stuff to minimize preparation to assignments completing. Rye⁹ is used for dependencies management.

Automation is done using GitHub actions that trigger on pushes and pull requests, and includes tests execution, code style guide checking. Note that actions should be extended by students to handle parser generation. It allows us to automate control of assignments completing and use code review mechanisms to discuss assignments with students.

We use only an open tests implemented using Pytest framework and they consist of of two types. The first one is a set of ordinary unit tests that check corner cases of algorithms. The second one is a set of property-like tests that use the fact that students should implements algorithms for closely related problems. Thus different algorithms from different assignments should return the same results for randomly generated input. This way we can simplify testing system (no private tests) and avoid algorithms fitting.

⁴PyFormLang repository: <https://github.com/Aunsiels/pyformlang>

⁵SciPy home page: <https://scipy.org/>

⁶ANTLR (ANOther Tool for Language Recognition) home page: <https://www.antlr.org/>

⁷CFPQ-Data project: https://github.com/FormalLanguageConstrainedPathQuerying/CFPQ_Data

⁸In Russian <https://github.com/FormalLanguageConstrainedPathQuerying/formal-lang-course>

⁹Rye project home page: <https://rye.astral.sh>

4 DISCUSSION

The proposed course is aimed to motivate students to investigate formal languages theory in , refresh linear algebra, HPC.... Why matrices: pretty simple ideas and algorithms, rather than LR, hides implementation complexity, clear abstraction (it is easy to realize that one library of linear algebra operations can be replaced with another one).

Simple formulation of engineering tasks, problems, challenges regarding performance allows students to be involved in related research during course or right after it. Evaluation of matrix-based CFPQ algorithm, represented by Nikita Mishin, Iaroslav Sokolov et al. in "Evaluation of the Context-Free Path Querying Algorithm Based on Matrix Multiplication" [9] is an improved results of experiments done as the course exercises. Similarly, Egor Orachev [?] Ilya Muraviev and optimizations of linear algebra based CFPQ algorithm.

Also we want to highlight some drawbacks and weakness of our course. The first one is that practice with non-linear-algebra-based algorithm for FLPQ and parsing is very limited. In some cases it is not a problem because students have compiler construction course that covers parsing-related topics. But in the context of CFPQ these algorithms are important because they can natively solve all-paths multiple-sources queries, but require special techniques that cannot be natively inferred from linear-algebra-based algorithms. Currently, only GLL-based algorithm is introduced, but in restricted reachability version.

Some subtasks of the last part — interpreter implementation — requires special knowledge on programming language theory (e.g. type theory). One of possible solution is to make this part more configurable and to introduce less specific tasks.

The proposed course, especially structure of exercises, hides basics of some concepts, such as sparse linear algebra or automata implementation. But this way we learn to use existing libraries that is a useful skill for engineers, and allow students to touch real-world problems and tasks without huge amount of preliminary work.

Regarding environment, one of the drawbacks is that manual control needed to check whether the requested algorithm implemented by students. It is necessary because exercises include several algorithms for the same (or similar) problems, for example four different algorithms for CFPQ, and possible students' cheat is to resubmit single one implementation with slightly changed top level API.

Other courses [4] on data querying related areas.^{10 11 12 13} Advanced SQL, Graph databases, GQL,

5 CONCLUSION AND FUTURE WORK

We describe the course that brings together formal language theory and graph analysis and involves linear algebra and high performance computing techniques in such a way that smoothly combines different areas with focus on applied graph analysis problems. Note that while this course has been taught for several years now, there is a room for improvements.

One of the important technical improvements is to extend testing system to provide performance testing. For now, performance analysis of the implemented algorithms can be done only in respective tasks on algorithms evaluation and comparison. There is no automatic control on performance of implemented algorithms. So, students not forced to provide not naïve solutions. Moreover, they often provide solutions with trivial performance issues: no early exit in transitive-closure-like procedures, no analysis of sparse matrix format (so, randomly selected format is used) and so on. Additionally, we generate a bunch of property-based tests and these missed optimizations can slow down CI check (and even local ones) to tens of minutes, and also lead to failure on CI for some students.

The next technical challenge is to replace `sciPy` with `python-graphblas`¹⁴ in order to enforce studying of specific tools for high-performance graph analysis. It is not clear, whether `sciPy` should be replaced, or `python-graphblas` should be provided as an optional alternative for `sciPy` because `sciPy` is easier for beginners, but `python-graphblas` allows one to pay more attention on performance. Also, `sciPy` provide straightforward control of matrix format, that is important for performance analysis, while in `python-graphblas` such a control is quite tricky.

Also we want to show some ways to extend the course. First of all, more algorithms and related tasks should be added. For example, multiple sources version of linear algebra based algorithm for CFPQ, proposed by Arseniy Terekhov et al [14]. Another candidates to be added are path problem related linear algebra based algorithms for both RPQ and CFPQ. All these algorithms allows students to touch new types of problems and investigate linear algebra based approach to graph analysis deeper. But introduction of some of these algorithms is related to migration to `python-graphblas` because `sciPy` is not enough to implement them: some specific operations and ways to custom semirings specification and utilization is not provided in this library. Additionally, the current last tasks on query language development should be done more fine-grained. Interpreter development can be splitted into several tasks: basic ones that do not require advanced programming language theory, and advanced ones.

One of important way to extend the course is to add more materials on languages beyond context-free, such as multiple context-free languages, boolean and conjunctive languages. Currently only basic introduction is presented. But these languages play important role in static analysis, and deeper studying is important to realize boundaries of expressivity power of graph query languages. Discussion of some classes beyond context-free leads to nontrivial decidability analysis for FLPQ-related problems. As a result, it leads to introduction of approximation algorithms that an important class of algorithms that do not discuss in the current version of the course. Not only theory, but also respective algorithmic exercises should be added.

Data for algorithms evaluation also should be extended to represent more different areas of FLPQ applications. For example, for CFPQ it is necessary to add biological data [12], data provenance related graphs and queries [8], more code analysis related data.

¹⁰<http://www.drps.ed.ac.uk/16-17/dpt/cxinf11121.htm>

¹¹<https://www.ksi.mff.cuni.cz/~svoboda/courses/241-NDBI049/>

¹²<https://www.ksi.mff.cuni.cz/~svoboda/courses/241-NIE-PDB/>

¹³https://catalogs.buffalo.edu/preview_course_nopop.php?catoid=1&coid=1061

¹⁴Python wrapper for SuiteSparse:GraphBLAS: <https://github.com/python-graphblas/python-graphblas>.

All of the above leads to big number of exercises and one of possible solution is to make significant number of them optional. But finally it should be possible to configure consistent subset of exercises in terms that even subset of tasks allows student to create self-contained application for graph analysis. Globally we want to achieve high flexibility of materials such that it would be able to use specific submodules in other related course. For example, in courses on formal languages, or static code analysis.

REFERENCES

- [1] 2013. *SPARQL 1.1 Query Language*. Technical Report. W3C. <http://www.w3.org/TR/sparql11-query>
- [2] Chris Barrett, Riko Jacob, and Madhav Marathe. 2000. Formal-Language-Constrained Path Problems. *SIAM J. Comput.* 30, 3 (2000), 809–837. <https://doi.org/10.1137/S0097539798337716> arXiv:<https://doi.org/10.1137/S0097539798337716>
- [3] Giovanna Kobus Conrado, Adam Husted Kjølstrøm, Jaco van de Pol, and Andreas Pavlogiannis. 2025. Program Analysis via Multiple Context Free Language Reachability. *Proc. ACM Program. Lang.* 9, POPL, Article 18 (Jan. 2025), 30 pages. <https://doi.org/10.1145/3704854>
- [4] Diego Figueira. 2022. *Foundations of Graph Path Query Languages*. Springer International Publishing, Cham, 1–21. https://doi.org/10.1007/978-3-030-95481-9_1
- [5] Jelle Hellings. 2025. Explaining results of path queries on graphs: Single-path results for context-free path queries. *Information Systems* 128 (2025), 102475. <https://doi.org/10.1016/j.is.2024.102475>
- [6] Jochem Kuijpers, George Fletcher, Nikolay Yakovets, and Tobias Lindaaker. 2019. An Experimental Study of Context-Free Path Query Evaluation Methods. In *Proceedings of the 31st International Conference on Scientific and Statistical Database Management* (Santa Cruz, CA, USA) (SSDBM '19). Association for Computing Machinery, New York, NY, USA, 121–132. <https://doi.org/10.1145/3335783.3335791>
- [7] Ciro M. Medeiros, Martin A. Musicante, and Umberto S. Costa. 2018. Efficient evaluation of context-free path queries for graph databases. In *Proceedings of the 33rd Annual ACM Symposium on Applied Computing* (Pau, France) (SAC '18). Association for Computing Machinery, New York, NY, USA, 1230–1237. <https://doi.org/10.1145/3167132.3167265>
- [8] Hui Miao and Amol Deshpande. 2019. Understanding Data Science Lifecycle Provenance via Graph Segmentation and Summarization. In *2019 IEEE 35th International Conference on Data Engineering (ICDE)*. 1710–1713. <https://doi.org/10.1109/ICDE.2019.00179>
- [9] Nikita Mishin, Iaroslav Sokolov, Egor Spirin, Vladimir Kutuev, Egor Nemchinov, Sergey Gorbatyuk, and Semyon Grigorev. 2019. Evaluation of the Context-Free Path Querying Algorithm Based on Matrix Multiplication. In *Proceedings of the 2nd Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA)* (Amsterdam, Netherlands) (GRADES-NDA'19). Association for Computing Machinery, New York, NY, USA, Article 12, 5 pages. <https://doi.org/10.1145/3327964.3328503>
- [10] Terence Parr. 2013. *The Definitive ANTLR 4 Reference* (2nd ed.). Pragmatic Bookshelf.
- [11] Julien Romero. 2021. Pyformlang: An Educational Library for Formal Language Manipulation. In *Proceedings of the 52nd ACM Technical Symposium on Computer Science Education* (Virtual Event, USA) (SIGCSE '21). Association for Computing Machinery, New York, NY, USA, 576–582. <https://doi.org/10.1145/3408877.3432464>
- [12] Petteri Sevon and Lauri Eronen. 2008. Subgraph Queries by Context-free Grammars. *Journal of Integrative Bioinformatics* 5, 2 (2008), 157–172. <https://doi.org/doi:10.1515/jib-2008-100>
- [13] Arseniy Terekhov, Artyom Khoroshev, Rustam Azimov, and Semyon Grigorev. 2020. Context-Free Path Querying with Single-Path Semantics by Matrix Multiplication. In *Proceedings of the 3rd Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA)* (Portland, OR, USA) (GRADES-NDA'20). Association for Computing Machinery, New York, NY, USA, Article 5, 12 pages. <https://doi.org/10.1145/3398682.3399163>
- [14] Arseniy Terekhov, Vlada Pogozhelskaya, Vadim Abzalov, Timur Zinnatulin, and Semyon V Grigorev. 2021. Multiple-Source Context-Free Path Querying in Terms of Linear Algebra. In *EDBT*. 487–492.
- [15] Qirun Zhang and Zhendong Su. 2017. Context-sensitive data-dependence analysis via linear conjunctive language reachability. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages* (Paris, France) (POPL '17). Association for Computing Machinery, New York, NY, USA, 344–358. <https://doi.org/10.1145/3009837.3009848>