Technical specification

Gasketed plate heat exchanger

Project ref.:	KROST Ingenieria SAC		
Line ref.:	Water Heater T10 BFM (Hot side - 40m3/h)		
Model:	**T10-BFM**		Page: 1(2)
No. of units:	**1**		Date: 2024-09-04

		Hot side		Cold side
Fluid:		Water		Water
Density:	kg/m³	986,3		991,3
Specific heat capacity:	kJ/(kg·K)	4,17		4,18
Thermal conductivity:	W/(m·K)	0,642		0,624
Viscosity inlet:	cP	0,465		1,06
Viscosity outlet:	cP	0,640		0,503
Volume flow rate:	m³/h	40,00		20,00
Inlet temperature:	°C	60,0		18,0
Outlet temperature:	°C	41,2		55,0
Pressure drop:	kPa	65,6		40,2
Heat exchanged:	kW		857,4	
LMTD:	K		11,9	
Heat transfer coefficient:	W/(m²·K)		7 326	
Heat transfer area:	m²		9,88	
Relative directions of fluids:			Countercurrent	
Connection positions and flow directions:		S1->S2		S3->S4
Connections: S1,S2,S3,S4			Flange EN 1092-1 PN10 DN100 lining TI	
Number of passes:		1		1
Effective margin:	%		0,0	
Effective fouling resistance * 10000:	m²·K/W		0,000	
External loads according to API:			Not specified	
Design pressure (MAWP):	bar	10,0		10,0
Test pressure:	bar	14,3		14,3
Design temperature max.:	°C	60,0		55,0
Design temperature min. (MDMT):	°C	0,0		0,0
Channel arrangement:		1*20 HWi		1*19 HNa
Pressure vessel approval:			PED Article 4.3	
Fluid classification group:		2		2
Fluid with vapour pressure >0.5 barg at max. design temp.:		No		No
Number of plates:			40	
Nominal A-measurement:	mm		121.0	
Extension capacity:			23 plates	
Plate material/thickness:			Titanium/0,5 mm	
Gasket material and attachment:		NBRB ClipGrip™		NBRB ClipGrip™
Approx. outer dimensions (L x W x H)	mm		Type of package:	
Approx. weight, empty/operating:	kg			

Technical specification

Gasketed plate heat exchanger

Project ref.:	KROST Ingenieria SAC	
Line ref.:	Water Heater T10 BFM (Hot side - 40m3/h)	
Model:	**T10-BFM**	Page: 2(2)
No. of units:	**1**	Date: 2024-09-04

500 x 480 x 1 050		Skid base + box
304 / 330		
Approx. packed weight:	kg	353

Technical specification

Gasketed plate heat exchanger

Project ref.:	TyM TechSol - Walter Chung	
Line ref.:	Water Heater T10 BFM (Hot side - 40m3/h)	
Model:	**T10-BFM**	Page: 3(2)
No. of units:	**1**	Date: 2024-09-04

	Quantity
Accessories added to configuration	
Accessories	
Equipment	
Protection tube Plastic	1
Documents and services	
Documents	
Documents English-Alfa Laval-Installation manual	1