

~~6010107~~ 9102125

— 鞍 鋼 股 份 有 限 公 司
Angang Steel Company Limited

产品质量证明书
INSPECTION CERTIFICATE



中国鞍山市铁东区团结街42号 邮编 114002
No.42 Tuanjie Street Tiedong District 114002
Anshan, P. R. China
Tel 0086-8008300858 Fax 0086-0412-6728486

正原重一氏、其 一

[illegible]

鞍钢股份有限公司
Angang Steel Company Limited

产品质量证明书
INSPECTION CERTIFICATE



中国辽宁省鞍山市铁西区鞍钢厂内 邮编: 114003
Angang Production Area, Tiexi District, Anshan City,
Liaoning Province, China
Tel: 400-688-0898 Fax: 0412-6128486

正副各一份 共一页

订货单位 Buyer	鞍钢集团国际经济贸易有限公司	产品名称 Product	热轧切边 Hot rolled steel sheet	证明书编号 Certificate No.	KG2407020018
收货单位 Consignee	鞍钢股份有限公司 (韩国海外出口)	交货状态 Delivery Condition	热轧	合同编号 Contract No.	82465555005
客户名称 Customer	鞍钢集团国际经济贸易有限公司	计量方式 Weight Mode	实际重量 Actual Weight	购单号 Purchase No.	2A4ATC24W52523A01A
标准 Specification	ATA B08505	发货日期 Date of Delivery	20240702	质检批次号 Inspection No.	
牌号 Grade	A36	规格 Nominal Dimension	厚度*宽度*长度 Thickness*Width*Length	9*1500*3000 mm-mm-mm	

序号 No.	物料号 Pack No.	熔炼号 Heat No.	重量(kg) Weight	张数 Sheets	化学成分 C.C.T.															力学性能 Tensile Test										冲击试验 Impact Test																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
					C		Si		Mn		P		S		屈服强度 Y.S.		抗拉强度 T.S.		伸长率 EL (%)		屈服比 Y.S./T.S.		冷弯试验 Bend Test		方向 Direction		温度 ℃		冲击功 (J)		冲击试样尺寸 Sample Size(mm)		冲击缺口面积 Impact SA %		平均 Ave																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
					10	-2	10	-2	10	-2	10	-3	10	-3	285	445	38		285	445	38		1	2	3	Ave	1	2	3	Ave	1	2	3	Ave	1	2	3	Ave																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
1	K237E0170A	2A403779	4510	14	0	18	11	32	14	3						285	445	38																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															

序号 No.	物料号 Pack No.	批号 Batch No.	取样位置 Sample Location	方向 Direction	屈服 Y.S.	抗拉 T.S.	伸长率 EL (%)	屈服比 Y.S./T.S.	冷弯试验 Bend Test	方向 Direction	温度 ℃	冲击功 (J)	冲击试样尺寸 Sample Size(mm)	冲击缺口面积 Impact SA %	平均 Ave
1	K237E0170A	H324502815	B	T	285	445	38					1	2	3	Ave
2	K237E0170B	H324502815	B	T	285	445	38					1	2	3	Ave
3	K237E0170C	H324502815	B	T	285	445	38					1	2	3	Ave
4	K237E0170D	H324502815	B	T	285	445	38					1	2	3	Ave
5	K237E0170E	H324502815	B	T	285	445	38					1	2	3	Ave
6	K237E0170F	H324502815	B	T	285	445	38					1	2	3	Ave

化学成分 (C.C.T.=Chemical Composition Type): 0=熔炼分析 Heat Analysis 1=产品分析 Product Analysis.
拉伸试验 (Tensile Test): Y.S.=Yield Strength T.S.=Tensile Strength EL=Elongation G.L.=Gauge Length.
取样位置 (Sample Location): B=Bottom 底部 T=Top 顶部 M=Middle 中部.
方向 (Direction): L=Long(纵向) T=Trans(横向) 3=30° To The Rolling Direction(与轧制方向成30°)
D=45° To The Rolling Direction(与轧制方向成45°).

备注
Remarks

上述元素仅列出参与复合公式的有效添加元素, 但复合元素结果是严格按照公式计算得出。

说明
Description

质量保证书
Quality Manual

鞍钢股份有限公司
Angang Steel Company Limited

产品质量证明书 INSPECTION CERTIFICATE



中国辽宁省鞍山市铁西区鞍钢厂区 邮编 114003
Angang Production Area, Tiexi District, Anshan City,
Liaoning Province, China
Tel 400-688-0898 Fax 0412-6728486

正页 第 1 页, 共 1 页

鞍钢股份有限公司热轧带钢厂
Hot Rolled Strip Steel Mill of ANSTEEL

证明书编号
Certificate No. B02407020018

订货单位 Buyer	鞍钢集团国际经济贸易有限公司	产品名称 Product	热轧切板 Hot rolled steel sheet	合同编号 Contract No.	82460655005	证明书签号 B02407020018
收货单位 Consignee	鞍钢股份有限公司 (鲅鱼圈外贸出口)	交货状态 Delivery Condition	热轧 Hot	购单号 Purchase No.	24AHTC2HRS052384014	
客户名称 Customer	鞍钢集团国际经济贸易有限公司	计量方式 Weight Mode	实际重量 Actual Weight	商检批号 InsLocNo.		
标准 Specification	ATA B0R505	发货日期 Date of Delivery	20240702			
牌号 Grade	A36	规格 Nominal Dimension	厚度*宽度*长度 Thick*Width*Length	9*1500*3000 mm*mm*mm		

序号 No.	物料号 Pack No.	熔炼号 Heat No.	重量(kg) Weight	张数 Sheets	成分 类型 C, C.T.	化学成分										总张数 Total Sheets	83																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
						C		Si		Mn		P		S																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
						10	-2	10	-2	10	-2	10	-3	10	-3																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
1	R237E0170A	24AD3779	4510	14	0	18	11	32	14	3																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								

序号 No.	物料号 Pack No.	批号 Batch No.	取样 位置 Sample Location	标准: 50mm					Bend Test	Impact Test					Sample size(mm)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
				方向 Direction	屈服 Y.S.		抗拉 T.S.	伸长率 EL (%)		屈服比 Y.S./T.S.	a = d =	方向 Direction	温度 C°	冲击功 (J) Impact Energy			冲击剪切面积 Impact SA %			方向 Direction	温度 C°	剪切比 SA %																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
					Rp0.2	MPa								1	2	3	Ave	1	2			3	Ave	1	2	Ave																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
1	R237E0170A	H324602815	B	T	285		445	38																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		</

备注 Remarks	上述元素仅列出参与复合公式的有意添加元素, 但复合元素结果是严格按照公式计算得出。		说明 Description	质量负责人 Quality Manager
注释 Notes	成分类型 (C.C.T.=Chemical Composition Type): 0 熔炼分析 Heat Analysis; 1 产品分析 Product Analysis; 拉伸试验 (Tensile Test): Y.S.=Yield Strength T.S.=Tensile Strength EL=Elongation G.L.=Gauge Length; 取样位置 (Sample Location): B=Bottom 底部; T=Top 顶部; M=Middle 中部; 方向 (Direction): L=Longitudinal 纵向; T=Transverse 横向; 3=30° To The Rolling Direction (与轧制方向成30°); D=45° To The Rolling Direction (与轧制方向成45°);		本产品已按GB/T 1591-2018和GB/T 29906-2013标准进行检验, 其结果符合标准要求。特此证明。 贵方如欲索取有关证书, 请与我公司联系。 We hereby certify that the material described herein has been manufactured and inspected in accordance with the requirements of the above mentioned standards. If you have any questions, please contact our company.	



中板有限公司

AO STEEL YINGKOU MEDIUM PLATE CO., LTD.

辽宁省营口市老边区金街1115605

Yingkou, Liaoning, P.R. China/115605

TEL 0417-3256081 FAX 0417-3256087 NO. DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



CUMIC STEEL LIMITED

CUMIC STEEL LIMITED



普通碳素结构钢

General carbon structural steel

YGRIZAN N240584003-01

技术标准/牌号
SPEC/GRADE

ASTM A36/A36M-2019

热轧(AR)

签发日期
DATE OF ISSUE

20240622

车号
TRAIN NO.

240622Z00278

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 DIMENSION	数量 QTY	重量 WEIGHT kg	分析 区域 AA	化学成分 CHEMICAL ANALYSIS %															A 0401 屈服 强度 ReL	B 0402 抗拉 强度 Rm	C 0403 断后 伸长 率 A50
							C	Si	Mn	P	S	Cr	Ni	Mo	Al	As	Sn	Cu	Nb	Ti				
$\times 10^{-2}$	$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-2}$	$\times 10^{-4}$	$\times 10^{-2}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-3}$	$\times 10^{-2}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-3}$	$\times 10^{-2}$	MPa	MPa	%						
2405241C	2405299	2405844001	22x2400x12000	1	2.235	L	173	190	832	190	61	98	390	8	10	1	20	20	33	200	662	25.5		
2405241C	2405299	2405844002	22x2400x12000	1	2.235	L	173	190	832	190	61	98	390	8	10	1	20	20	33	200	662	25.5		
2405241C	2405299	2405844003	22x2400x12000	1	2.235	L	173	190	832	190	61	98	390	8	10	1	20	20	33	200	662	25.5		

L: 熔炼成分 SMELTING COMPOSITION
拉伸试样(CAUGE LENGTH) Lo=200 mm
A0A01=YIELD STRENGTH
A0A02=TENSILE STRENGTH
A0A03=PERCENTAGE ELONGATION AFTER FRACTURE

According to EN 10204 3.1

本产品已按照标准要求制造和检验, 其结果符合要求, 特此证明。
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION

冶金技术处处长
DIRECTOR OF
METALLURGICAL
DEPARTMENT

殷新刚



29-02-25
plancha de 60x15

IN 62

MATERIAL TEST CERTIFICATE

INSPECTION CERTIFICATE DIN EN 10204/ 3.1


DATE: 2024/10/12

ORIGINAL

CUSTOMER		INAMESA		PO NO.:		24437																		
INVOICE NO.		JX240805		MAKER																				
CERTIFICATE		EN10204 3.1		ANALYSIS CERT. NO.																				
SPECIFICATION		ASTM A240		STEEL GRADE		304 / 304L																		
DESCRIPTION		Stainless Steel Sheet		DELIVERY CONDITION		/																		
NO.	HEAT NO.	QTY (PCS)	GRADE	SIZE (mm)			N.W. (Kg)	Chemical Composition % (Heat Analysis)								Finish	Tensile Test			Hardness				
				Thk	Width	Length		C	Si	Mn	P	S	Cr	Ni	Mo	Cu	N		YS _{0.2s} (Mpa)	TS (Mpa)	EL(AS0%)			
14	A0403456	46	AISI 304	1.20	1500	3000	1970	0.05	0.35	1.06	0.038	0.002	18.16	8.03	/	/	/		NO.4 PVC	310	696	59		HV 168
15	A1401436	83	AISI 304	1.50	1220	2440	2939	0.05	0.42	1.03	0.036	0.002	18.18	8.02	/	/	/		2B PAPER	284	695	54		HV 175
16	A0401626	286	AISI 304	1.50	1220	2440	10126	0.04	0.34	1.05	0.041	0.004	18.19	8.01	/	/	0.05		2B PVC	265	682	55		HV 166
17	A1401436	83	AISI 304	1.50	1220	2440	2939	0.05	0.42	1.03	0.036	0.002	18.18	8.02	/	/	/		NO.4 PVC	284	695	54		HV 175
18	A1403098	55	AISI 304	1.50	1500	3000	2944	0.04	0.33	1.32	0.035	0.002	18.13	8.02	/	/	/		2B PVC	273	673	52.5		HV 157
19	A1403098	55	AISI 304	1.50	1500	3000	2943	0.04	0.33	1.32	0.035	0.002	18.13	8.02	/	/	/		NO.4 PVC	273	673	52.5		HV 157
20	A2403134	106	AISI 304L	2.00	1220	2440	5004	0.022	0.50	1.61	0.030	0.002	18.20	8.1	/	/	0.05		2B PVC	288	655	54		HRBW 83
21	A2403134	108	AISI 304L	2.00	1220	2440	5098	0.022	0.50	1.61	0.030	0.002	18.20	8.10	/	/	0.05		NO.4 PVC	288	655	54		HRBW 83
22	A0403225	70	AISI 304L	2.00	1500	3000	4996	0.018	0.44	1.60	0.039	0.006	18.1	8.0	/	/	0.05		2B PVC	278	660	54		HRBW 77.5
23	A2403210	50	AISI 304L	2.50	1220	2440	2951	0.027	0.42	1.60	0.039	0.003	18.10	8.0	/	/	0.04		2B PVC	278	654	54		HRBW 80.5
24	A0403011	33	AISI 304L	2.50	1500	3000	2944	0.026	0.45	1.54	0.036	0.004	18.2	8.0	/	/	0.05		2B PVC	274	640	57		HRBW 84.0
25	A0403210	99	AISI 304L	3.00	1220	2440	7011	0.025	0.45	1.61	0.039	0.002	18.10	8.0	/	/	0.04		2B PVC	286	675	48		HRBW 83
26	A0403011	30	AISI 304L	3.00	1500	3000	3211	0.026	0.45	1.54	0.036	0.004	18.2	8.0	/	/	0.05		2B PVC	278	675	56		HRBW 82.5
Total		1,104					55,076																	



MAG GENERAL BUSINESS
MILL TEST CERTIFICATE



ORIGINAL

SUPPLIER: MAG GENERAL BUSINESS
BUYER: FIORELLA REPRESENTACIONES S.A.C.
GOODS: FITTINGS

INVOICE NO.: ABRS240208
CERTIFICATE NO.: MTC2240208C
CERTIFICATE ACCORDING TO EN10204-3.1

ORDER NO.: FR24-039
PAGE NO.: 1/1
ISSUE DATE: MAY. 09, 2024

PRODUCT			SPECIFICATION FOR MATERIAL						SPECIFICATION FOR STANDARD					Heat No.	Tensile Strength(Mpa) Min. 415	Yield Strength(Mpa) Min. 240	Elongation(%) Longitudinal(Round) Min. 22	Hardness(HB) Max.197						
FITTINGS			ASTM A234 WPB						ANSI B16.9															
Item No.	DESCRIPTION	Qty. (Pcs)	%C ≤0.30	%Si ≥0.10	%Mn 0.29-1.06	%P ≤0.050	%S ≤0.058	%Cu ≤0.40	%Cr ≤0.40	%Ni ≤0.40	%Mo ≤0.15	%V ≤0.08	%C.E.						Heat Treatment	Dimension Inspection	Suface Inspection	Remarks		
	BUTT-WELDING FITTINGS (ONLY SEAMLESS PIPE NOT OTHER, THIS ITEM NOT IN ERW FITTINGS) CONCENTRIC RED. SCH40 A234 WPB B16.9, WITH PAINT IN BLACK BRAND "FR"																							
8	3" X 1.1/2"	60	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
9	4" X 3"	450	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
10	5" x 2"	10	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
11	5" X 4"	70	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
12	6" X 2"	20	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
13	8" X 6"	70	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
14	10" X 6"	40	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
15	16" X 8"	10	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125	HOT FORMED WITH FINAL TEMPERATURE	GOOD	GOOD	MATERIAL MEET NACE		
16	16" X 12"	4	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
17	16" X 14"	6	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
18	16" X 14"	10	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
	BUTT-WELDING FITTINGS (ONLY SEAMLESS PIPE NOT OTHER, THIS ITEM NOT IN ERW FITTINGS) ECCENTRIC REDUCER SCH40 A234 WPB B16.9,WITH PAINT IN BLACK BRAND "FR"																							
19	2" X 1"	6	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125	AIR COOLING	GOOD	GOOD	2006		
20	4" X 2"	20	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
21	8" X 5"	4	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
22	18" X 16"	2	0.256	0.21	0.31	0.020	0.025	0.020	0.034	0.030	0.011	0.001	0.320	356	465	258	25	125		GOOD	GOOD			
	BUTT-WELDING FITTINGS (ONLY SEAMLESS PIPE NOT OTHER, THIS ITEM NOT IN ERW FITTINGS) CAPS SCH40 ASTM A234 WPB B16.9, WITH PAINT IN BLACK BRAND "FR"																							
23	1"	150	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
24	1.1/4"	850	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
25	1.1/2"	1350	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
26	3"	150	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
27	6"	250	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
28	10"	50	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
29	14"	12	0.220	0.26	0.31	0.021	0.026	0.022	0.034	0.030	0.011	0.001	0.284	137	435	260	25	125		GOOD	GOOD			
	BUTT-WELDING FITTINGS (ONLY SEAMLESS PIPE NOT OTHER, THIS ITEM NOT IN ERW FITTINGS) TEE EQUAL SCH40 ASTM A234 WPB B16.9, WITH PAINT IN BLACK BRAND "FR"																							
30	1"	20	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			
31	1.1/2"	150	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			
32	2"	200	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			
33	2.1/2"	40	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			
34	3"	150	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			
35	4"	120	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			
36	6"	200	0.210	0.28	0.33	0.025	0.021	0.020	0.034	0.020	0.011	0.001	0.277	816	453	268	27	128		GOOD	GOOD			

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MADE IN ACCORDANCE WITH THE ABOVE SPECIFICATION AND WITH THE REQUIREMENT CALLED FOR BY THE ABOVE ORDER AND HAS BEEN TESTED TO THE SATISFACTION OF THE MANUFACTURER'S Q.C.INSPECTOR.



MAG GENERAL BUSINESS

QUALITY CERTIFICATE

ORIGINAL

Purchase: FIORELLA REPRESENTACIONES S.A.C.

Order No: FR24-062

Invoice No.: HS24122M

Material Specification

ASTM/ASME(S)A234 WPB ED. 2019

Specification for inspection

ASME B16.9

BUTT WELDING PIPE FITTINGS BRAND FR

Certificate to: EN10204-3.1

Visual and Dimensional

Inspection GOOD

RT:(5)GOOD

Hardness

Max 197HB

ICC:(5)GOOD

Cr+Ni+Cr+Mo Cr+Mo

<or=1.00% <or=0.32%

PMI(5): GOOD

Product Description/Size		Quantity (Pcs)	Heat I.D.	Tension Test(1)			Chemical Composition %											Heat Treat- ment (3)	Raw Material	
				YS Mpa	TS Mpa	E %	C	Si	Mn	P	S	Cr	Mo	Ni	Cu	V	CE		Type (4)	HB
ECCN. REDUCER SCH40	11/2 X 1"	20	YK062 2321	286	495	27	0.22	0.25	0.56	0.0220	0.0020	0.04	0.01	0.03	0.04	0.01	0.329	S	3	134
ECCN. REDUCER SCH40	2 X 11/4"	12	YK062 9923	284	498	26	0.23	0.24	0.55	0.0230	0.0020	0.03	0.04	0.02	0.02	0.01	0.340	S	3	135
ECCN. REDUCER SCH40	2 X 11/2"	10	YK062 9923	285	497	29	0.24		0.52	0.0210	0.0030	0.02	0.01	0.01	0.02	0.01	0.336	S	3	132
ECCN. REDUCER SCH40	4 X 3"	22	YK062 1355	283	493	28	0.23	0.23	0.54	0.0220	0.0010	0.02	0.03	0.03	0.03	0.01	0.336	S	3	135
ECCN. REDUCER SCH40	12 X 8"	5	YK062 1567	284	495	27	0.24	0.24	0.53	0.0210	0.0030	0.04	0.04	0.04	0.04	0.01	0.351	S	3	136
ECCN. REDUCER SCH40	16 X 12"	2	YK062 3221	286	496	25	0.22	0.26	0.54	0.0230	0.0020	0.03	0.03	0.01	0.02	0.01	0.325	S	3	134
ECCN. REDUCER STD	20 X 16"	2	YK062 5680	285	494	28	0.21	0.25	0.56	0.0240	0.0020	0.01	0.04	0.03	0.02	0.01	0.318	S	3	133
CAP, SCH40	3/4"	330	YK062 2231	287	492	29	0.23	0.26	0.53	0.0250	0.0010	0.02	0.03	0.01	0.03	0.01	0.332	S	3	135
CAP, SCH40	11/4"	70	YK062 9012	286	497	26	0.25	0.24	0.54	0.0210	0.0030	0.03	0.03	0.02	0.04	0.01	0.357	S	3	137
CAP, SCH40	21/2"	100	YK062 1220	284	492	26	0.22	0.23	0.55	0.0220	0.0020	0.01	0.01	0.03	0.02	0.01	0.320	S	3	137
TEE, SCH40	1/2"	500	YK062 8012	286	495	29	0.23	0.26	0.53	0.0210	0.0030	0.03	0.04	0.02	0.01	0.01	0.336	S	3	132
TEE, SCH40	1"	330	YK062 1209	288	496	28	0.23	0.25	0.54	0.0210	0.0020	0.02	0.03	0.03	0.04	0.01	0.336	S	3	136
TEE, SCH40	2"	750	YK062 9923	287	493	27	0.24	0.26	0.56	0.0210	0.0020	0.02	0.01	0.04	0.01	0.01	0.344	S	3	132
TEE, SCH40	21/2"	120	YK062 1220	282	492	28	0.22	0.25	0.56	0.0220	0.0030	0.02	0.01	0.03	0.04	0.01	0.326	S	3	134
TEE, SCH40	3"	700	YK062 1001	286	495	26	0.21	0.24	0.57	0.0230	0.0020	0.01	0.04	0.03	0.02	0.01	0.320	S	3	135
TEE, SCH40	4"	600	YK062 1355	284	494	29	0.23	0.24	0.55	0.0210	0.0030	0.04	0.04	0.01	0.03	0.01	0.342	S	3	136
TEE, SCH40	6"	200	YK062 3212	287	496	27	0.23	0.24	0.55	0.0230	0.0020	0.03	0.04	0.02	0.02	0.01	0.340	S	3	133
REDUCING TEE, SCH40	1 X 1/2"	6	YK062 1209	286	493	28	0.24	0.25	0.52	0.0210	0.0030	0.02	0.01	0.01	0.02	0.01	0.333	S	3	132
REDUCING TEE, SCH40	11/4 X 1"	10	YK062 9012	284	491	29	0.23	0.23	0.54	0.0220	0.0010	0.02	0.03	0.03	0.03	0.01	0.333	S	3	135
REDUCING TEE, SCH40	2 X 11/2"	15	YK062 9923	286	492	28	0.24	0.24	0.53	0.0210	0.0030	0.04	0.04	0.02	0.01	0.01	0.348	S	3	134
REDUCING TEE, SCH40	21/2 X 2"	35	YK062 1220	284	495	28	0.21	0.25	0.56	0.0240	0.0020	0.01	0.04	0.03	0.02	0.01	0.318	S	3	135
REDUCING TEE, SCH40	4 X 3"	6	YK062 1355	286	496	26	0.23	0.26	0.53	0.0250	0.0010	0.02	0.03	0.01	0.03	0.01	0.332	S	3	132
REDUCING TEE, SCH40	14 X 8"	2	YK062 3467	285	497	27	0.25	0.24	0.54	0.0210	0.0030	0.03	0.03	0.02	0.04	0.01	0.357	S	3	134
																	MANAGER			
																	IMPORT & EXPORT			

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MADE IN ACCORDANCE WITH THE ABOVE SPECIFICATION AND WITH THE REQUIREMENT CALLED FOR BY THE ABOVE ORDER AND HAS BEEN TESTED TO THE SATISFACTION OF THE MANUFACTURER'S Q.C.INSPECTOR.



MAG GENERAL BUSINESS

QUALITY CERTIFICATE

ORIGINAL

Purchase: **IORELLA REPRESENTACIONES S.A.C.**

Date: **NOV.25, 2024**

Order No: **FR24-121-1**

Invoice No.: **HS24127M1**

Material Specification

Specification for inspection

Certificate to: EN10204-3.1

Visual and Dimensional

Hardness

Cr+Ni+Cr+Mn Cr+Mo

ASTM/ASME A234 WPB ED. 2019

ASME B16.9

Inspection GOOD

Max 197HB

<or=1 <or=0.32%

BUTT WELDING PIPE FITTINGS BRAND FR

RT:(5)GOOD

ICC:(5)GOOD

PMI(5): GOOD

Product Description/Size		Quantity (Pcs)	Heat I.D.	Tension Test(1)			Chemical Composition %										Heat Treat- ment (3)	Raw Material		
				YS Mpa	TS Mpa	E %	C	Si	Mn	P	S	Cr	Mo	Ni	Cu	V		CE	Type (4)	HB
				240	415	25	<0.35	0.10-0.35	0.60-1.05	<0.035	<0.040	<0.30	<0.12	<0.40	<0.40	<0.08				
					585															
ELBOW 45°, SCH40	45 X 1"	1200	9021	285	496	28	0.25	0.26	0.53	0.0240	0.0030	0.01	0.04	0.020	0.010	0.007	0.352	S	3	132
ELBOW 45°, SCH40	45 X 1 1/4"	2200	3921	287	494	29	0.23	0.25	0.54	0.0220	0.0010	0.04	0.03	0.020	0.030	0.006	0.339	S	3	134
ELBOW 45°, SCH40	45 X 3"	800	7734	286	495	27	0.24	0.22	0.54	0.0230	0.0010	0.02	0.04	0.030	0.010	0.005	0.346	S	3	133
ELBOW 45°, SCH40	45 X 4"	30	9901	284	498	26	0.23	0.23	0.52	0.0230	0.0020	0.03	0.03	0.010	0.010	0.006	0.331	S	3	136
ELBOW 45°, SCH40	45 X 6"	80	1291	285	497	29	0.24	0.23	0.52	0.0220	0.0010	0.01	0.03	0.040	0.010	0.005	0.339	S	3	135
ELBOW 45°, SCH40	45 X 8"	70	3491	283	493	28	0.23	0.24	0.52	0.0240	0.0030	0.01	0.03	0.030	0.020	0.007	0.329	S	3	134
ELBOW 45°, SCH40	45 X 12"	12	4402	284	495	27	0.25	0.23	0.52	0.0220	0.0020	0.02	0.04	0.020	0.030	0.006	0.353	S	3	135
ELBOW 45°, STD	45 X 14"	40	2200	286	496	25	0.23	0.25	0.53	0.0230	0.0010	0.04	0.03	0.030	0.020	0.007	0.337	S	3	133
ELBOW 45°, SCH40	45 X 24"	5	3399	285	494	28	0.22	0.24	0.54	0.0250	0.0020	0.03	0.02	0.040	0.010	0.006	0.325	S	3	132
ELBOW 90°, SCH40	90 X 3/4"	4000	3301	287	492	29	0.21	0.25	0.55	0.0240	0.0030	0.02	0.04	0.010	0.030	0.007	0.318	S	3	136
ELBOW 90°, SCH40	90 X 1"	10000	9021	286	497	26	0.23	0.26	0.56	0.0230	0.0010	0.01	0.03	0.020	0.020	0.007	0.335	S	3	134
ELBOW 90°, SCH40	90 X 1 1/2"	18000	2983	282	492	28	0.22	0.25	0.56	0.0240	0.0030	0.03	0.02	0.030	0.010	0.009	0.328	S	3	134
ELBOW 90°, SCH40	90 X 2"	12000	6009	286	495	26	0.21	0.23	0.54	0.0230	0.0010	0.02	0.02	0.010	0.020	0.005	0.311	S	3	133
ELBOW 90°, SCH40	90 X 2 1/2"	1000	5561	284	494	29	0.23	0.26	0.53	0.0240	0.0010	0.01	0.03	0.030	0.010	0.006	0.330	S	3	136
ELBOW 90°, SCH40	90 X 3"	6000	7734	287	496	27	0.24	0.22	0.55	0.0240	0.0010	0.01	0.03	0.040	0.020	0.006	0.345	S	3	132
ELBOW 90°, SCH40	90 X 4"	3000	9901	286	493	28	0.23	0.24	0.57	0.0230	0.0030	0.03	0.04	0.030	0.010	0.007	0.343	S	3	134
ELBOW 90°, SCH40	90 X 5"	1200	5544	284	491	29	0.22	0.26	0.53	0.0240	0.0010	0.01	0.03	0.010	0.030	0.006	0.320	S	3	135
ELBOW 90°, SCH40	90 X 6"	1200	1291	286	492	28	0.23	0.27	0.56	0.0230	0.0020	0.03	0.02	0.020	0.030	0.007	0.338	S	3	133
ELBOW 90°, SCH40	90 X 8"	400	3491	285	494	27	0.22	0.24	0.56	0.0230	0.0030	0.02	0.01	0.030	0.010	0.005	0.323	S	3	136
ELBOW 90°, SCH40	90 X 10"	100	3091	287	496	29	0.25	0.25	0.57	0.0260	0.0010	0.03	0.02	0.040	0.020	0.005	0.360	S	3	132
ELBOW 90°, STD	90 X 12"	70	8821	283	495	28	0.26	0.26	0.55	0.0250	0.0010	0.01	0.04	0.030	0.010	0.006	0.368	S	3	134
ELBOW 90°, SCH40	90 X 12"	100	4402	284	496	26	0.23	0.27	0.56	0.0230	0.0030	0.03	0.02	0.020	0.030	0.006	0.338	S	3	135
ELBOW 90°, SCH40	90 X 16"	70	3490	284	492	25	0.23	0.26	0.58	0.0240	0.0010	0.01	0.04	0.040	0.030	0.007	0.348	S	3	133
ELBOW 90°, SCH40	90 X 18"	35	3303	286	495	26	0.24	0.28	0.56	0.0260	0.0030	0.02	0.04	0.010	0.020	0.005	0.348	S	3	135
ELBOW 90°, SCH40	90 X 24"	4	3399	285	494	27	0.26	0.27	0.57	0.0230	0.0020	0.01	0.03	0.010	0.030	0.005	0.367	S	3	134

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MADE IN ACCORDANCE WITH THE ABOVE SPECIFICATION AND WITH THE REQUIREMENT CALLED FOR BY THE ABOVE ORDER AND HAS BEEN TESTED TO THE SATISFACTION OF THE MANUFACTURER'S Q.C.INSPECTOR.



MAG GENERAL BUSINESS

ORIGINAL

QUALITY CERTIFICATE

Purchase: FIORELLA REPRESENTACIONES S.A.C.

Date: NOV.25, 2024

Order No: FR24-121-1

Invoice No.: HS24127M1

Material Specification

ASTM/ASME A234 WPB ED. 2019

Specification for inspection

ASME B16.9

Certificate to: EN10204-3.1

Visual and Dimensional

Inspection GOOD

RT:(5)GOOD

Hardness

Max 197HB

ICC:(5)GOOD

Cr+Ni+Cr+Mo

<or=1 <or=0.32%

PMI(5): GOOD

BUTT WELDING PIPE FITTINGS BRAND FR

Product Description/Size		Quantity (Pcs)	Heat I.D.	Tension Test(1)			Chemical Composition %											Heat Treat- ment (3)	Raw Material	
				YS Mpa	TS Mpa	E %	C	Si	Mn	P	S	Cr	Mo	Ni	Cu	V	CE		Type (4)	HB
ELBOW 180°,SCH40	180 X 3"	20	7734	287	496	28	0.23	0.24	0.56	0.0220	0.0010	0.03	0.01	0.030	0.020	0.005	0.336	S	3	136
ELBOW 180°,SCH40	180 X 4"	15	9901	285	493	29	0.22	0.25	0.55	0.0230	0.0030	0.04	0.02	0.010	0.030	0.006	0.328	S	3	137
ELBOW 180°,SCH40	180 X 6"	15	1291	284	497	27	0.24	0.23	0.56	0.0230	0.0010	0.01	0.01	0.040	0.020	0.009	0.343	S	3	132
CON. REDUCER SCH40	1 X 1 1/2"	30	9021	286	495	26	0.24	0.24	0.55	0.0210	0.0030	0.01	0.02	0.010	0.030	0.007	0.342	S	3	134
CON. REDUCER SCH40	1 X 3/4"	40	9021	284	497	28	0.23	0.23	0.54	0.0210	0.0020	0.04	0.03	0.010	0.020	0.006	0.337	S	3	136
CON. REDUCER SCH40	1 1/2 X 1"	130	2983	285	495	26	0.22	0.24	0.55	0.0220	0.0020	0.03	0.03	0.040	0.020	0.009	0.329	S	3	136
CON. REDUCER SCH40	1 1/2 X 1 1/4"	250	2983	285	496	27	0.24	0.23	0.54	0.0230	0.0030	0.03	0.01	0.010	0.030	0.007	0.342	S	3	135
CON. REDUCER SCH40	2 X 1 1/2"	700	6009	286	491	29	0.23	0.24	0.56	0.0210	0.0010	0.04	0.02	0.010	0.010	0.005	0.338	S	3	132
CON. REDUCER SCH40	2 1/2 X 1 1/2"	300	5561	286	492	28	0.25	0.23	0.53	0.0210	0.0030	0.02	0.04	0.010	0.030	0.005	0.354	S	3	134
CON. REDUCER SCH40	3 X 1 1/4"	50	7734	284	496	26	0.24	0.25	0.51	0.0240	0.0010	0.01	0.03	0.020	0.020	0.007	0.337	S	3	133
CON. REDUCER SCH40	3 X 1 1/2"	30	7734	283	497	29	0.26	0.27	0.54	0.0230	0.0030	0.04	0.03	0.040	0.010	0.006	0.369	S	3	132
CON. REDUCER SCH40	3 X 2"	800	7734	285	498	27	0.24	0.24	0.52	0.0210	0.0010	0.03	0.04	0.030	0.020	0.007	0.345	S	3	136
CON. REDUCER SCH40	3 X 2 1/2"	130	7734	287	493	25	0.24	0.25	0.54	0.0240	0.0010	0.02	0.01	0.030	0.030	0.005	0.341	S	3	134
CON. REDUCER SCH40	4 X 2 1/2"	90	9901	285	491	26	0.24	0.26	0.53	0.0210	0.0010	0.04	0.02	0.010	0.010	0.005	0.343	S	3	135
CON. REDUCER SCH40	4 X 3"	140	9901	286	495	28	0.23	0.23	0.52	0.0250	0.0030	0.03	0.04	0.040	0.010	0.007	0.335	S	3	137
CON. REDUCER SCH40	5 X 2 1/2"	12	5544	284	496	29	0.26	0.24	0.56	0.0220	0.0010	0.01	0.03	0.010	0.020	0.009	0.365	S	3	136
CON. REDUCER SCH40	5 X 3"	12	5544	283	494	26	0.25	0.27	0.55	0.0240	0.0020	0.04	0.02	0.020	0.010	0.008	0.357	S	3	138
CON. REDUCER SCH40	5 X 4"	40	5544	285	493	27	0.26	0.25	0.53	0.0210	0.0030	0.01	0.02	0.040	0.040	0.009	0.361	S	3	135
CON. REDUCER SCH40	6 X 2"	20	1291	286	495	29	0.24	0.26	0.57	0.0230	0.0010	0.03	0.02	0.010	0.030	0.007	0.349	S	3	134
CON. REDUCER SCH40	6 X 3"	70	1291	283	495	26	0.21	0.26	0.52	0.0240	0.0020	0.04	0.01	0.030	0.030	0.008	0.312	S	3	136
CON. REDUCER SCH40	6 X 4"	250	1291	284	493	28	0.26	0.24	0.53	0.0230	0.0010	0.03	0.01	0.040	0.020	0.007	0.362	S	3	135
CON. REDUCER SCH40	6 X 5"	80	1291	285	494	29	0.24	0.22	0.55	0.0210	0.0030	0.01	0.03	0.020	0.010	0.009	0.343	S	3	135
CON. REDUCER SCH40	8 X 3"	8	3491	286	496	26	0.22	0.25	0.51	0.0230	0.0020	0.01	0.02	0.010	0.020	0.006	0.314	S	3	134
CON. REDUCER SCH40	8 X 4"	130	3491	287	497	27	0.21	0.26	0.53	0.0220	0.0010	0.03	0.01	0.020	0.030	0.005	0.311	S	3	136
CON. REDUCER SCH40	8 X 5"	80	3491	285	496	25	0.26	0.23	0.56	0.0250	0.0030	0.02	0.02	0.030	0.040	0.009	0.368	S	3	133


WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MADE IN ACCORDANCE WITH THE ABOVE SPECIFICATION AND WITH THE REQUIREMENT CALLED FOR BY THE ABOVE ORDER AND HAS BEEN TESTED TO THE SATISFACTION OF THE MANUFACTURER'S Q.C.INSPECTOR.



MAG GENERAL BUSINESS

ORIGINAL

QUALITY CERTIFICATE



Purchase: **FIGORELLA REPRESENTACIONES S.A.C.**

Order No: **FR24-121-2**

Invoice No.: **HS24127M2**

Material Specification

ASTM/ASME(S)A105 ED.2021

CARBON STEEL FLANGES BRAND FR

Specification for inspection

ASME B16.5

Certificate to: EN10204-3.1

Visual and Dimensional

Inspection GOOD

RT:(5)GOOD

Hardness

Max 197HB

ICC:(5)GOOD

Date: **NOV.25, 2024**

Cr+Ni+Cr+M Cr+Mo

<or=1.00% <or=0.32%

PMI(5): GOOD

Product Description/Size		Quantity (Pcs)	Heat I.D.	Tension Test(1)			Chemical Composition %											Heat Treat- ment (3)	Raw Material	
				YS Mpa	TS Mpa	E %	C	Si	Mn	P	S	Cr	Mo	Ni	Cu	V	CE		Type (4)	HB
THREADING, CLASS150	1"	50	88912	382	555	36	0.20	0.26	0.88	0.0160	0.0030	0.03	0.04	0.030	0.010	0.046	0.374	S	3	153
THREADING, CLASS150	2"	300	88912	381	555	32	0.22	0.24	0.83	0.0190	0.0020	0.01	0.03	0.010	0.030	0.043	0.321	S	3	152
THREADING, CLASS150	4"	50	88912	385	556	32	0.23	0.23	0.86	0.0160	0.0020	0.03	0.02	0.020	0.030	0.046	0.401	S	3	156
SLIP ON, RF CLASS150	2"	1850	88912	385	555	34	0.23	0.25	0.84	0.0190	0.0030	0.02	0.03	0.020	0.010	0.046	0.348	S	3	156
SLIP ON, RF CLASS150	3"	5000	88912	387	551	35	0.19	0.24	0.88	0.0180	0.0020	0.04	0.02	0.010	0.030	0.043	0.317	S	3	152
SLIP ON, RF CLASS150	4"	5000	88912	385	555	36	0.22	0.25	0.84	0.0170	0.0020	0.02	0.01	0.030	0.040	0.046	0.351	S	3	154
SLIP ON, RF CLASS150	6"	2659	88912	384	553	30	0.19	0.23	0.87	0.0170	0.0020	0.01	0.02	0.030	0.020	0.046	0.325	S	3	156
SLIP ON, RF CLASS150	10"	999	88912	385	552	36	0.22	0.22	0.83	0.0190	0.0020	0.01	0.03	0.010	0.010	0.043	0.311	S	3	153
WELDING NECK, CLASS150	3"	200	88912	382	550	34	0.22	0.22	0.86	0.0180	0.0030	0.02	0.01	0.030	0.010	0.046	0.384	S	3	152
WELDING NECK, CLASS150	4"	250	88912	386	551	35	0.20	0.21	0.87	0.0160	0.0030	0.02	0.02	0.020	0.020	0.046	0.325	S	3	156
WELDING NECK, CLASS150	16"	5	88912	388	556	32	0.19	0.23	0.84	0.0170	0.0020	0.03	0.02	0.040	0.020	0.043	0.398	S	3	153
BLIND, CLASS150	4"	300	88912	383	553	33	0.21	0.25	0.83	0.0160	0.0030	0.01	0.03	0.030	0.010	0.043	0.351	S	3	152
BLIND, CLASS150	8"	50	88912	384	552	35	0.18	0.26	0.85	0.0170	0.0010	0.03	0.04	0.040	0.030	0.046	0.344	S	3	156
BLIND, CLASS150	10"	2	88912	385	555	34	0.21	0.26	0.85	0.0190	0.0010	0.02	0.03	0.040	0.030	0.046	0.378	S	3	152
BLIND, CLASS150	14"	45	88912	386	553	33	0.19	0.25	0.86	0.0150	0.0030	0.03	0.01	0.020	0.010	0.043	0.318	S	3	154
BLIND, CLASS150	24"	20	88912	388	554	34	0.19	0.23	0.83	0.0170	0.0020	0.03	0.02	0.040	0.030	0.046	0.387	S	3	156
SLIP ON, RF CLASS300	1"	50	88912	386	556	32	0.18	0.23	0.87	0.0140	0.0030	0.04	0.02	0.010	0.010	0.046	0.348	S	3	155
SLIP ON, RF CLASS300	11/2"	15	88912	384	555	35	0.19	0.24	0.83	0.0150	0.0010	0.03	0.04	0.040	0.010	0.046	0.355	S	3	154
SLIP ON, RF CLASS300	16"	25	88912	385	554	35	0.17	0.23	0.82	0.0180	0.0010	0.03	0.01	0.020	0.040	0.043	0.327	S	3	152
WELDING NECK, CLASS300	1"	50	88912	386	556	32	0.20	0.25	0.85	0.0140	0.0030	0.01	0.04	0.030	0.040	0.043	0.351	S	3	154
BLIND, CLASS300	11/2"	60	88912	386	557	34	0.19	0.25	0.84	0.0160	0.0010	0.01	0.02	0.020	0.010	0.046	0.344	S	3	156
BLIND, CLASS300	3"	50	88912	385	556	36	0.22	0.26	0.83	0.0190	0.0030	0.01	0.03	0.010	0.010	0.046	0.378	S	3	155
BLIND, CLASS300	6"	15	88912	385	552	30	0.22	0.24	0.86	0.0160	0.0020	0.01	0.04	0.040	0.020	0.046	0.412	S	3	153
WELDING NECK, CLASS600	2"	100	88912	388	554	34	0.16	0.24	0.82	0.0160	0.0030	0.02	0.01	0.030	0.030	0.046	0.446	S	3	154

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MADE IN ACCORDANCE WITH THE ABOVE SPECIFICATION AND WITH THE REQUIREMENT CALLED FOR BY THE ABOVE ORDER AND HAS BEEN TESTED TO THE SATISFACTION OF THE MANUFACTURER'S Q.C.INSPECTOR.