

Rajalakshmi Engineering College

Name: Yadhu Nandhana R
Email: 241801321@rajalakshmi.edu.in
Roll no: 241801321
Phone: 7448879488
Branch: REC
Department: I AI & DS FD
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are tasked with implementing basic operations on a queue data structure using a linked list.

You need to write a program that performs the following operations on a queue:

Enqueue Operation: Implement a function that inserts an integer element at the rear end of the queue. Print Front and Rear: Implement a function that prints the front and rear elements of the queue. Dequeue Operation: Implement a function that removes the front element from the queue.

Input Format

The first line of input consists of an integer N, representing the number of elements to be inserted into the queue.

The second line consists of N space-separated integers, representing the queue elements.

Output Format

The first line prints "Front: X, Rear: Y" where X is the front and Y is the rear elements of the queue.

The second line prints the message indicating that the dequeue operation (front element removed) is performed: "Performing Dequeue Operation:".

The last line prints "Front: M, Rear: N" where M is the front and N is the rear elements after the dequeue operation.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

12 56 87 23 45

Output: Front: 12, Rear: 45

Performing Dequeue Operation:

Front: 56, Rear: 45

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
};
```

```
struct Node* front = NULL;
```

```
struct Node* rear = NULL;
```

```
struct Queue {  
    struct Node* front;  
    struct Node* rear;  
};
```

```
struct Queue q = {NULL, NULL};
```

```
void enqueue(int data) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = data;  
    newNode->next = NULL;
```

```
    if (q.rear == NULL) {  
        q.front = q.rear = newNode;  
        return;
```

```
    }  
    q.rear->next = newNode;  
    q.rear = newNode;
```

```
}  
  
void dequeue() {  
    if (q.front == NULL) {  
        // Queue is empty  
        return;  
    }  
    struct Node* temp = q.front;  
    q.front = q.front->next;  
    if (q.front == NULL) {  
        q.rear = NULL;  
    }  
    free(temp);  
}
```

```
void printFrontRear() {  
    int front = -1, rear = -1;  
    if (q.front != NULL) front = q.front->data;  
    if (q.rear != NULL) rear = q.rear->data;  
    printf("Front: %d, Rear: %d\n", front, rear);  
}
```

```
int main() {  
    int n, data;  
    scanf("%d", &n);  
    for (int i = 0; i < n; i++) {  
        scanf("%d", &data);  
        enqueue(data);
```

```
}  
printFrontRear();  
printf("Performing Dequeue Operation:\n");  
dequeue();  
printFrontRear();  
return 0;  
}
```

Status : Correct

Marks : 10/10