

HYPERTEXT MARKUP LANGUAGE

What is an HTML Element?

HTML elements are the core webpage units used to organize and display content in a browser. An element is usually formed with an opening tag, content, and a closing tag.

Structure of an HTML Element

```
<tagname>content</tagname>
```

Parts of an HTML Element

- ❑ **Opening Tag** – Marks the beginning of the element.
- ❑ **Content** – Information displayed on the webpage.
- ❑ **Closing Tag** – Marks the end of the element.

Example

```
<p>This is a paragraph.</p>
```

Here,

- ❑ `<p>` is the opening tag
- ❑ This is a paragraph. is the content
- ❑ `</p>` is the closing tag

Common HTML Elements

```
<h1>Main Heading</h1>
<p>Paragraph Text</p>
<div>Section Content</div>
```

Nested Elements

HTML elements can contain other elements inside them.

```
<p>This is <b>bold</b> text.</p>
```

Empty Elements

Some elements do not require closing tags because they contain no content.

Examples:

```
<br>
<hr>

```

Attributes in Elements

Attributes provide extra information inside the opening tag.

```

```

What Are HTML Attributes?

HTML attributes are extra settings added inside an HTML tag to control an element's behavior, appearance, identification, or functionality. They provide additional instructions to the browser about how an element should work or display.

Attributes are always written inside the opening tag of an HTML element.



Structure of an HTML Attribute

```
<tagname attributename="value">Content</tagname>
```

Example

```
<a href="https://example.com">Visit Website</a>
```

Here,

- `<a>` → Anchor element
- `href` → Attribute name
- `"https://example.com"` → Attribute value

The href attribute tells the browser where the link should open.

Parts of an Attribute

1. Attribute Name

The attribute name identifies the property added to the element.

Example:

```
href  
src  
title  
id
```

2. Attribute Value

The value defines the information assigned to the attribute.

Example:

```
href="home.html"
```

Here, "home.html" is the value.

Why HTML Attributes Are Used

Attributes are used to:

- Add links to elements
- Insert images
- Apply styles
- Identify elements uniquely
- Create tooltips
- Control form behavior
- Set dimensions and alignment
- Improve accessibility

Common HTML Attributes

Id Attribute

The id attribute uniquely identifies an element on a webpage.

Example

```
<p id="intro" >Welcome to HTML</p>
```

- Each id value should be unique.
- Used in CSS and JavaScript.

Class Attribute

The class attribute groups elements together for styling or scripting.

Example

```
<p class="text">Paragraph One</p>
```

```
<p class="text">Paragraph Two</p>
```

- Multiple elements can share the same class.

title Attribute

The title attribute displays extra information as a tooltip when the mouse pointer moves over the element.

Example

```
<h2 title="HTML Heading">Move mouse here</h2>
```

style Attribute

The style attribute applies inline CSS styles directly to an element.

Example

```
<p style="color:blue;">Blue Text</p>
```



ElevateMe



href Attribute

The href attribute specifies the destination URL of a link.

Example

```
<a href="about.html">About Page</a>
```

src Attribute

The src attribute defines the source path of media files such as images, audio, or videos.

Example

```

```

alt Attribute

The alt attribute provides alternative text for images if the image cannot load.

Example

```

```

Multiple Attributes

An element can contain multiple attributes separated by spaces.

Example

```

```

Here,

- src → Image path
- alt → Alternative text
- width → Image width

Global Attributes

Some attributes can be used with almost all HTML elements.

Examples

Attribute	Purpose
id	Unique identification
class	Group elements
style	Apply inline CSS
title	Add tooltip text



<https://elevatme.netlify.app>



<https://yaganti-spandana.netlify.app/>

