

R version 4.2.2 (2022-10-31 ucrt) -- "Innocent and Trusting"
Copyright (C) 2022 The R Foundation for Statistical Computing
Platform: x86_64-w64-mingw32/x64 (64-bit)

R is free software and comes with ABSOLUTELY NO WARRANTY.
You are welcome to redistribute it under certain conditions.
Type 'license()' or 'licence()' for distribution details.

Natural language support but running in an English locale

R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.

```
> #probability of random point in square is inside the circle using nsim
> #pi is given by draws and multiplying it by four
> pi.fun <- function(nsim){
+ x <- runif(nsim)
+ y <- runif(nsim)
+ prob <- mean(sqrt((x-0.5)^2 + (y-0.5)^2) <= 0.5)
+ pi <- 4*prob
+ return(c(prob = prob, pi = pi))
+ }
> # get the value of estimated value of pi
> set.seed(123)
> # > pi.fun(10000)
> # prob pi
> #pi is given by draws and multiplying it by four
>
>
>
```

```
> > #probability of random point in square is inside the circle using nsim
> #pi is given by draws and multiplying it by four
> pi.fun <- function(nsim){
+ x <- runif(nsim)
+ y <- runif(nsim)
+ prob <- mean(sqrt((x-0.5)^2 + (y-0.5)^2) <= 0.5)
+ pi <- 4*prob
+ return(c(prob = prob, pi = pi))
+ }
> # approximations of pi
> set.seed(123)
> pi.fun(10000)
      prob      pi
0.7894 3.1576
>
```