

R version 4.2.2 (2022-10-31 ucrt) -- "Innocent and Trusting"
 Copyright (C) 2022 The R Foundation for Statistical Computing
 Platform: x86_64-w64-mingw32/x64 (64-bit)

R is free software and comes with ABSOLUTELY NO WARRANTY.
 You are welcome to redistribute it under certain conditions.
 Type 'license()' or 'licence()' for distribution details.

Natural language support but running in an English locale

R is a collaborative project with many contributors.
 Type 'contributors()' for more information and
 'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
 'help.start()' for an HTML browser interface to help.
 Type 'q()' to quit R.

[Previously saved workspace restored]

```
> #####
>
> R code for Exercise 2
Error: unexpected symbol in "R code"
> #####
>
> #Load the data from CSV file
> volt <- read.csv("C://Users//yxa210024//Desktop//Masters//spring2023//Stats for DS//mini_project4//voltage.csv")
>
> #Attach the data for easy access to variables
> attach(volt)
>
> #Generate boxplots
> boxplot(voltage ~ location, main="BOXPLOT")
>
> #Define a custom function to calculate summary statistics
> new.summary <- function(x){
+ result <- summary(x)
+ result_summary<- c(result[-6], IQR = IQR(x), result[6], SD = sd(x))
+ return(result_summary)
+ }
>
>
> #Calculate summary statistics by location using the custom function
> by(voltage, location, new.summary)
location: 0
      Min.      1st Qu.      Median      Mean      3rd Qu.      IQR      Max.
 8.0500000  9.8000000  9.9750000  9.8036667 10.0500000  0.2500000 10.5500000
      SD
0.5409155
-----
location: 1
      Min.      1st Qu.      Median      Mean      3rd Qu.      IQR      Max.
 8.5100000  9.1525000  9.4550000  9.4223333  9.7375000  0.5850000 10.1200000
      SD
0.4788757
>
> #Subset the data for remote and local locations
> remote <- volt[which(location == 0), "voltage"]
> local <- volt[which(location == 1), "voltage"]
> #Generate normal QQ-plots for remote and local locations
> par(mfrow=c(2, 1))
> qqnorm(remote, main = "remote")
> qqline(remote)
> qqnorm(local, main = "local")
> qqline(local)
>
```

```
> #Calculate confidence interval using t-test
> T_test <- t.test(remote, local)
> Confidence_Interval <- T_test$conf.int
> Confidence_Interval
[1] 0.1172284 0.6454382
attr(,"conf.level")
[1] 0.95
>
```