```
R version 4.2.2 (2022-10-31 ucrt) -- "Innocent and Trusting"
Copyright (C) 2022 The R Foundation for Statistical Computing
Platform: x86 64-w64-mingw32/x64 (64-bit)
R is free software and comes with ABSOLUTELY NO WARRANTY.
You are welcome to redistribute it under certain conditions.
Type 'license()' or 'licence()' for distribution details.
 Natural language support but running in an English locale
R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.
Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.
[Previously saved workspace restored]
> #Load the necessary libraries
> library(boot)
Attaching package: 'boot'
The following object is masked by '.GlobalEnv':
   motor
> #Load the data from CSV file
> gpa <- read.csv("C://Users//yxa210024//Desktop//Masters//spring2023//Stats for DS//mini project
4//gpa.csv")
> #Attach the data for easy access to variables
> attach(qpa)
The following object is masked by .GlobalEnv:
    gpa
> #Generate scatter plots
> plot(gpa ~ act, data = gpa, pch = 20, main = "Scatterplot")
> #Calculate the Pearson correlation coefficient between gpa and act
> Cor relation <- cor(gpa, act)</pre>
> #Define a function for bootstrap resampling
> Correlation_Resampling function <- function(corr, indices) {</pre>
+ cor(corr[indices, 1], corr[indices, 2])
> #Define a function to get the bootstrapped samples
> Corr boots samp <- function(corr, i = c(1:n))</pre>
+ c <- corr[i,]
+ return(c)
> #Set the number of bootstrap replicates
> Boot replicates <- 1000
> set.seed(1000)
> #Perform bootstrap resampling for correlation between gpa and act
> Cor boot resample <- boot(gpa, Correlation Resampling function, R = Boot replicates)
> #Display the results of bootstrap resampling
> Cor boot resample
ORDINARY NONPARAMETRIC BOOTSTRAP
Call:
boot(data = gpa, statistic = Correlation Resampling function,
   R = Boot replicates)
```

```
Bootstrap Statistics:
original bias std. error t1* 0.2694818 0.008486976 0.1092285
     original bias
                           std. error
> #Calculate the 95% percentile confidence interval for correlation between gpa and act
> Boot cofidence interval(Cor boot resample, conf = 0.95, type = "perc")
Error in Boot cofidence interval (\overline{Cor} boot resample, conf = 0.95, type = "perc") :
  could not find function "Boot cofidence interval"
> boot.ci(Cor boot resample, conf = 0.95, type = "perc")
BOOTSTRAP CONFIDENCE INTERVAL CALCULATIONS
Based on 1000 bootstrap replicates
CALL :
boot.ci(boot.out = Cor boot resample, conf = 0.95, type = "perc")
Intervals:
Level Percentile
95% (0.0575, 0.4966)
Calculations and Intervals on Original Scale
> > Boot replicates <- 10000
Error: unexpected '>' in ">"
> > set.seed(1000)
Error: unexpected '>' in ">"
> > #Perform bootstrap resampling for correlation between gpa and act
Error: unexpected '>' in ">"
> > Cor boot resample <- boot(gpa, Correlation Resampling function, R = Boot replicates)
Error: unexpected '>' in ">"
> > #Display the results of bootstrap resampling
Error: unexpected '>' in ">"
> > Cor boot resample
Error: unexpected '>' in ">"
> Boot replicates <- 10000
> set.seed(1000)
> Cor boot resample <- boot(gpa, Correlation Resampling function, R = Boot replicates)
> Cor boot resample
ORDINARY NONPARAMETRIC BOOTSTRAP
Call:
boot(data = gpa, statistic = Correlation Resampling function,
    R = Boot replicates)
Bootstrap Statistics:
     original bias
                         std. error
t1* 0.2694818 0.004057848 0.1049293
> boot.ci(Cor boot resample, conf = 0.95, type = "perc")
BOOTSTRAP CONFIDENCE INTERVAL CALCULATIONS
Based on 10000 bootstrap replicates
CALL :
boot.ci(boot.out = Cor boot resample, conf = 0.95, type = "perc")
Intervals:
Level
         Percentile
95% (0.0701, 0.4791)
Calculations and Intervals on Original Scale
```