


Lesson1 of Building:bit Tower crane--"Infrared remote control"





Note:

- 1. When performing infrared remote control, the remote controller should face the infrared receiver on the expansion board.
- 2. There is a plastic piece on the bottom of the infrared remote controller that needs to be taken down for normal use.
- 3. The infrared light emitted by the infrared remote controller and the infrared receiver is invisible to the human eye. It can be seen under the camera without filtering infrared light.



infrared receiver

1.Experimental phenomena





2. Preparation before class

We needs to be ready:

Building Block Tower crane *1

micro:bit handle *1

USB data cable *1

2-1.Two programming methods:

Online programming:

First,we need to connect the micro:bit to the computer by USB data cable, the computer will pop up a USB flash drive. Then, click on the URL in the USB flash drive: http://microbit.org/ to enter the edit process interface, click to 【Extensions】, and copy the package URL:

https://github.com/lzty634158/yahboom_mbit_en and https://github.com/lzty634158/YB_IR to the input field, and you can use the building blocks of the Yahboom software package.

Offilne programming:

Open the offline programming software Makecode, click to 【Extension】 and copy the package URL: https://github.com/lzty634158/yahboom_mbit_en and https://github.com/lzty634158/YB_IR to the input field, and you can use the building blocks of the Yahboom software package.

For detailed programming, please read the documentation before class [1. Preparation before class] ---- [Introduction of programming method]. We use micro:bit official website for online programming in here.


3.Studying blocks

Blocks	Instruction









4.Programming

Next, we started to write the program for the infrared remote control of the building block Tower crane, as shown below:



```
on IR received message
 set | ir ▼ | to | message ▼
 if
                          IR_KeyValue value Up ▼
                                                      then
         message 🔻
   set ir ▼ to 1
                              IR_KeyValue value Down ▼
 else if <
                                                                     Θ
            message ▼
                                                           then
        ir ▼ to 2
   set
 else if <
                                                                    \Theta
            message 🔻
                              IR_KeyValue value Left ▼
                                                           then
   set ir ▼ to 3
 else if <
            message 🔻
                              IR_KeyValue value Right ▼
                                                            then
                                                                     Θ
   set ir ▼ to 4
 else if <
            message ▼
                              IR KeyValue value SpinLeft ▼
                                                               then 🛑
   set ir ▼ to 5
 else if
                                                                then 🖃
                              IR_KeyValue value SpinRight ▼
            message 🔻
   set ir ▼ to 6
                                                                    \Theta
 else if
            message 🔻
                              IR KeyValue value Beep ▼
                                                           then
        ir ▼ to 7
 else if <
                                                                    Θ
                              IR_KeyValue value Power ▼
                                                            then
            message ▼
   set ir ▼ to 8
                                                                    \Theta
 else if <
                             IR_KeyValue value Add ▼
            message 🔻
                                                          then
```








```
Θ
else if <
          message ▼ | = ▼ | IR_KeyValue value | Eight ▼ |
                                                            then
 set ir ▼ to 19
else if <
                                                                    \Theta
           message ▼
                             IR_KeyValue value Nine ▼
                                                           then
 set ir ▼ to 20
                                                                    Θ
else if <
                             IR_KeyValue value Light ▼
                                                            then
          message ▼
 set ir ▼ to 21
\oplus
```



```
forever
        ir ▼ = ▼ 1
 if
                          then
  set ir ▼ to 0
  CarCtrlSpeed2 back ▼ speed1 0 speed2 70
  pause (ms) 50 ♥
  CarCtrl stop ▼
 else if (
          ir ▼ = ▼ 2
                           then 🕣
  set ir ▼ to 0
  CarCtrlSpeed2 forward ▼ speed1 0 speed2 71
  pause (ms) 50 ▼
  CarCtrl stop ▼
 else if <
          ir ▼ = ▼ (3)
                           🗦 then 🕣
  set ir ▼ to 0
  CarCtrlSpeed2 back ▼ speed1 35 speed2 0
  pause (ms) 300 ▼
  CarCtrl stop ▼
          ir ▼ | = ▼ (4
 else if <
                             then 🖃
  set ir ▼ to 0
  CarCtrlSpeed2 forward ▼ speed1 33 speed2
  pause (ms) 50 ▼
  CarCtrl stop ▼
```














The above is the program for this Tower crane. After writing, we need to download it to the micro:bit board.