

Moveit scenario design

1. Usage environment

Motherboard: Jetson Orin Nano/Nx

ROS2: Humble

2. Driving the real machine

Driving the real machine is to convert the joint state information of the robot arm into the control of the real robot arm by subscribing to the `/joint_states` topic of Moveit2.

Note: Since the real robot arm does not have an obstacle avoidance function, some positions may encounter obstacles; so the planned robot arm movements should be as reasonable as possible and avoid positions with obstacles

(It is recommended to use preset positions to demonstrate driving the real machine)

2.1. Start the real machine

If you do not drive the real machine, simulate the robot arm movements in Moveit:

```
ros2 run jetcobot_driver sync_plan
```

2.2. Start Moveit2


```
ros2 launch jetcobot_moveit demo.launch.py
```

```
jetson@yahboom:~/jetcobot_colcon_ws$ source install/setup.bash
jetson@yahboom:~/jetcobot_colcon_ws$ ros2 run jetcobot_driver sync_plan
[INFO] [1746523618.089714205] [mycobot_receiver]: Connected to MyCobot at /dev/ttyUSB0, baud: 1000000
```


```
jetson@yahboom:~$ ros2 launch jetcobot_moveit demo.launch.py
[INFO] [launch]: All log files can be found below /home/jetson/.ros/log/2025-05-06-18-22-35-906299-yahboom-5757
[INFO] [launch]: Default logging verbosity is set to INFO
[INFO] [static_transform_publisher-1]: process started with pid [5758]
[INFO] [robot_state_publisher-2]: process started with pid [5760]
[INFO] [move_group-3]: process started with pid [5762]
[INFO] [rviz2-4]: process started with pid [5764]
[INFO] [ros2_control_node-5]: process started with pid [5766]
[INFO] [spawner-6]: process started with pid [5768]
[INFO] [spawner-7]: process started with pid [5770]
[static_transform_publisher-1] [INFO] [1746526957.078854709] [static_transform_publisher0]: Spinning until stopped - publishing transform
[static_transform_publisher-1] translation: ('0.000000', '0.000000', '0.000000')
[static_transform_publisher-1] rotation: ('0.000000', '0.000000', '0.000000', '1.000000')
[static_transform_publisher-1] from 'world' to 'base_link'
[ros2_control_node-5] [WARN] [1746526957.111454920] [controller_manager]: [Deprecated] Passing the robot description parameter directly to the control_manager n
```

3. Scene design


Import scene:



Select the scene corresponding to the path



After the scene appears, click publish



Start command

The robot needs to be successfully loaded in MoveIt and `You can start planning now!` appears. Run the following command: The robot will plan the Cartesian path by itself

```
ros2 run jetbot_moveit set_scene
```

