

3.AI large model voice interaction

3.AI large model voice interaction

1. Concept Introduction
 - 1.1 What is "AI Large Model Voice Interaction"?
 - 1.2 Implementation Principle
2. Code Analysis
 - Key Code
 1. Voice Input Node (`1argemodel/1argemodel/asr.py`)
 2. AI service and voice output node (`1argemodel/1argemodel/model_service.py`)
 - Code Analysis
3. Practical Operations
 - 3.1 Configuring Offline Voice Interaction
 - 3.2 Starting and Testing the Function

1. Concept Introduction

1.1 What is "AI Large Model Voice Interaction"?

In the `1argemodel` project, **AI Large Model Voice Interaction** combines the **offline ASR** and **offline TTS** described above with the **large language model (LLM)** core to form a complete conversational system that listens, speaks, and thinks.

This is no longer an isolated function, but rather the prototype of a true **voice assistant**. Users can engage in natural language conversations with the robot through voice, and the robot can understand questions, think about answers, and respond with voice. This entire process is completed locally, without the need for a network.

The core of this function is the **model_service` ROS2 node**. It acts as the brain and neural center, subscribing to ASR recognition results, invoking the LLM for thinking, and then publishing the LLM's text responses to the TTS node for speech synthesis.

1.2 Implementation Principle

This feature is implemented using a classic data flow pipeline:

1. **Audio -> Text (ASR)**: The `asr` node continuously listens to ambient sound. Once it detects a user speaking a sentence, it converts it into text and publishes it to the `/asr_text` topic.
2. **Text -> Thought -> Text (LLM)**: The `model_service` node subscribes to the `/asr_text` topic. Upon receiving the text from the ASR, it passes it as a prompt to a locally deployed large language model (such as `qwen` running through `ollama`). The LLM generates a text response based on the context.
3. **Text -> Audio (TTS)**: After receiving the LLM's response, the `model_service` node publishes it to the `/tts_text` topic.
4. **Audio Playback**: The `tts_on1y` node subscribes to the `/tts_text` topic. Upon receiving text, it immediately invokes the offline TTS model to synthesize it into audio and plays it through the speaker.

This process forms a complete closed loop: `speech input -> text processing -> text output -> speech output`.

2. Code Analysis

Key Code

1. Voice Input Node (largemodel/largemodel/asr.py)

```
# From largemodel/largemodel/asr.py
class ASRNode(Node):
    def __init__(self):
        # ...
        self.asr_pub = self.create_publisher(String, "asr", 5)
        # ...

    def kws_handler(self)->None:
        if self.listen_for_speech(self.mic_index):
            asr_text = self.ASR_conversion(self.user_speechdir)
            if asr_text != 'error':
                self.asr_pub_result(asr_text)

    def asr_pub_result(self, asr_result: str)->None:
        msg=String(data=asr_result)
        self.asr_pub.publish(msg)
```

2. AI service and voice output node

(largemodel/largemodel/model_service.py)

```
# From largemodel/largemodel/model_service.py
class LargeModelService(Node):
    def __init__(self):
        # ...
        self.asrsub = self.create_subscription(String, 'asr',
self.asr_callback,1)
        # ...

    def asr_callback(self, msg):
        """Callback function for handling ASR messages. / 处理ASR消息的回调函数。"""
        # ...
        result = self.model_client.infer_with_text(msg.data,
message=messages_to_use)
        self.process_model_result(result)

    def process_model_result(self, result, from_seewhat=False):
        """Process the result returned by the model. / 处理模型返回的结果。"""
        # ...
        user_friendly_response = response_json.get("response", "我正在处理...")
        # ...
        self._safe_play_audio(user_friendly_response)
        # ...
        self.execute_tools(tools_list)

    def _safe_play_audio(self, text_to_speak: str):
        """
        Synthesizes and plays all non-empty messages only in non-text chat mode.
        """
```

```

        if not self.text_chat_mode and text_to_speak:
            try:
                self.model_client.voice_synthesis(text_to_speak,
self.tts_out_path)
                self.play_audio_async(self.tts_out_path)
            except Exception as e:
                self.get_logger().error(f"Safe audio playback failed: {e}")

```

Code Analysis

The voice interaction functionality of the large AI model is implemented by two independent ROS nodes, `asr.py` and `model_service.py`, which communicate via the ROS topic `/asr`, forming a complete processing loop.

1. Voice Input and Publishing (`asr.py`):

- The `ASRNode` node processes voice input. In the `kws_handler` function, it performs audio recording and text conversion.
- After successful conversion, the `asr_pub_result` function is called. This function places the resulting text string into a `std_msgs.msg.String` message and then publishes it to the `/asr` topic via the `self.asr_pub` publisher.

2. Subscription and Response (`model_service.py`):

- During initialization, the `LargeModelService` node subscribes to the `/asr` topic using the `create_subscription` method and specifies `asr_callback` as its callback function.
- When `ASRNode` publishes a message on the `/asr` topic, the ROS system automatically calls the `asr_callback` function of `LargeModelService`, passing the message as the `msg` parameter.

3. Interaction Loop:

- After receiving the message, the `asr_callback` function extracts the text data (`msg.data`) and passes it to the large model for inference (`self.model_client.infer_with_text`).
- After inference is complete, the `process_model_result` function is called. This function extracts the reply text from the model result.
- Next, the `_safe_play_audio` function is called, which uses the TTS function (`self.model_client.voice_synthesis`) to synthesize the reply text into audio and play it back.
- At this point, a complete interaction loop from "receiving user voice" to "responding to the user with voice" is completed. The two nodes are decoupled using the ROS publish-subscribe model. `asr.py` handles input, while `model_service.py` handles processing and output.

3. Practical Operations

3.1 Configuring Offline Voice Interaction

To implement a fully offline voice interaction system, you need to ensure that all three components, ASR, TTS, and LLM, are configured for offline mode.

1. Open the main configuration file `yahboom.yaml`:

```
gedit ~/yahboom_ws/src/largemodel/config/yahboom.yaml
```

2. Modify/confirm the following key configurations:

```

asr:
  ros__parameters:
    use_offline_asr: False          # Key: Set to False to enable
    offline ASR
    regional_setting : "international"

model_service:
  ros__parameters:
    use_offline_tts: False          # Key: Set to False to enable
    offline TTS
    llm_platform: 'ollama'         # Key: Set to 'ollama' to enable
    offline LLM
    regional_setting : "international"

```

3. Open the model interface configuration file `large_model_interface.yaml`:

```
gedit ~/yahboom_ws/src/largemodel/config/large_model_interface.yaml
```

4. Confirm that all offline model paths are correct:

```

# large_model_interface.yaml

## Offline large model
ollama_model: "qwen2.5:7b" # Make sure the model has been downloaded via
ollama pull

## Offline speech recognition
local_asr_model: "/path/to/your/SenseVoiceSmall" # Make sure the ASR model
path is correct

## Offline speech synthesis
zh_tts_model: "/path/to/your/zh_CN-huayan-medium.onnx" # Make sure the TTS
model path is correct
# ...

```

3.2 Starting and Testing the Function

Note: Due to performance limitations, this example cannot be run on the Jetson Orin Nano 4GB. To experience this function, please refer to the corresponding section in <Online Large Model (Voice Interaction)>

1. Start `largemodel` main program:

Run the following command to enable voice interaction:

```
ros2 launch largemodel largemodel_control.launch.py
```

2. Test:

- **Wake up:** Say "Hi, yahboom" into the microphone.
- **Dialogue:** After the speaker responds, you can speak your questions.
- **Observe the log:** In the terminal running the `launch` file, you should see the following:
 1. The ASR node recognizes your question and prints it.
 2. The `model_service` node receives the text, calls the LLM, and prints the LLM's response.

- **Listen to the answer:** After a while, you should hear the robot's synthesized voice answer your question through the speaker.