

6.TensorRT on-board camera real-time image recognition tutorial

1. Preparation

Before we start this step, we need to make sure that we have completed all the steps in Tutorials 4 and 5 and can test simple examples.

2. Enter the executable directory

If you are in the **jetson-inference** directory, please execute the following directory.

cd build/aarch64/bin/

```
-desktop:~/yahboom/jetson-inference/build/aarch64/bin$ ls
                   detectnet-console.py imagenet-console
                                                            segnet-batch.py
 amera-viewer
camera-viewer.py
                   gl-display-test
                                         imagenet-console.py segnet-batch.sh
                                                                                 trt-console
cuda-from-numpy.py gl-display-test.py images
                                                                                 v412-console
                                                              segnet-camera
cuda-to-numpy.py
detectnet-camera
                   homography-camera
                                         my-detection.py
                                                              segnet-camera.py
                                                                                 v412-display
                                       my-recognition.py
                   homography-console
                                                              segnet-console
detectnet-camera.py imagenet-camera
                                                              segnet-console.py
                                         networks
                                                              superres-console
                    imagenet-camera.py
detectnet-console
```

3. Execute image recognition command

At this point we are better able to execute by the remote desktop, otherwise you may not see the camera interface, or connect by VNC remote desktop.

Enter the bin directory:

The live image recognition demo is located in /aarch64/bin and call imagenet-camera. It runs on the live camera stream and loads googlenet or alexnet using TensorRT based on user parameters.


```
$ ./imagenet-camera googlenet # Run with googlenet $ ./imagenet-camera alexnet # Run with alexnet
```

Frames per second (FPS), the classification object name from the video and the confidence of the classification object are printed to the OpenGL window title bar. By default, the application can recognize up to 1000 different types of objects, name mappings for 1000 types of objects, which can be found under repo:

data/networks/ilsvrc12_synset_words.txt



```
nano@nano-desktop: ~/jetson-inference/build/aarch64/bin
File Edit View Search Terminal Help
class 0894 - 0.011559
                       (wardrobe, closet, press)
class 0905 - 0.148682 (window shade)
imagenet-camera: 17.79785% class #519 (crate)
class 0421 - 0.029892 (bannister, banister, balustrade, balusters, handrail)
class 0453 - 0.022903
                       (bookcase)
class 0478 - 0.015747
                      (carton)
class 0498 - 0.052887
                      (cinema, movie theater, movie theatre, movie house, pictu
re palace)
class 0519 - 0.102295 (crate)
class 0526 - 0.026581
                       (desk)
class 0527 - 0.013321 (desktop computer)
                      (file, file cabinet, filing cabinet) (home theater, home theatre)
class 0553 - 0.043823
class 0598 - 0.030716
class 0664 - 0.016571 (monitor)
class 0713 - 0.014450
                       (photocopier)
                       (prison, prison house)
class 0743 - 0.021194
class 0745 - 0.036469
                       (projector)
          - 0.010567
class 0789
                       (shoji)
class 0799 - 0.016373 (sliding door)
class 0818 - 0.133911 (spotlight, spot)
class 0894 - 0.010864 (wardrobe, closet, press)
class 0905 - 0.132935 (window shade)
imagenet-camera: 13.39111% class #818 (spotlight, spot)
```



When an object is recognized, the English name of the object is displayed on the interface, and the percentage is the matching percentage.

! Note:

After the camera mount is installed, if the video picture is upside down, you can use the following methods to set and modify:

\$ cd ~/jetson-inference/utils/camera/ \$ gedit gstCamera.cpp



```
- Change the folloing code:
```bash
#if NV TENSORRT_MAJOR > 1 && NV_TENSORRT_MAJOR < 5 // if JetPack 3.1-3.3
(different flip-method)
const int flipMethod = 0; // Xavier (w/TRT5) camera is mounted inverted
#else
const int flipMethod = 2;
#endif
We need to change the above code to the code shown below:
#if NV TENSORRT MAJOR > 1 && NV TENSORRT MAJOR < 5 // if JetPack 3.1-3.3
(different flip-method)
const int flipMethod = 0; // Xavier (w/TRT5) camera is mounted inverted
#else
const int flipMethod = 0; // 2 change 0
#endif
Build the Code:
```bash
$ cd ~/jetson-inference/build/
$ make
$sudo make install
```