

4. Hardware interaction data processing

4. Hardware interaction data processing

- 4.1、 Hardware mounting (port binding)
- 4.2、 GUI display in docker
- 4.3、 docker containers and hosts transfer files to each other
 - 4.3.1、 use cp command
 - 4.3.1.1、 Copy files from the container to the host
 - 4.3.1.2、 Copy files from the host to the container
 - 4.3.2、 Using Data Volumes
 - 4.3.2.1、 Data Volume Overview
 - 4.3.2.2、 Data volume use

4.1、 Hardware mounting (port binding)

1、 Connect the device you need to mount to the board, Create udev rules in the host (/etc/udev/rules.d/)

The following is the ROS control board and Radar equipment mounting as an example, the actual situation according to their own equipment mounting

2、 Then, when opening the container, mount the devices with rules set on the rules into the docker container through parameters such as --device=/dev/myserial --device=/dev/rplidar

```
docker run -it --device=/dev/myserial --device=/dev/rplidar ubuntu:latest /bin/bash
```

3、 The device can be found in the docker container

```
jetson@ubuntu:~$ docker images
REPOSITORY          TAG          IMAGE ID          CREATED          SIZE
ubuntu              1.0         78ca7be949b6     About an hour ago 69.2MB
pengan88/ubuntu     1.0         78ca7be949b6     About an hour ago 69.2MB
hello-world         latest      46331d942d63     13 months ago   9.14kB

jetson@ubuntu:~$ ll /dev | grep ttyUSB*
lrwxrwxrwx    1 root    root          7 Apr 23 18:07 myserial -> ttyUSB0
lrwxrwxrwx    1 root    root          7 Apr 23 18:07 rplidar -> ttyUSB1
crwxrwxrwx    1 root    dialout 188,  0 Apr 23 18:07 ttyUSB0
crwxrwxrwx    1 root    dialout 188,  1 Apr 23 18:07 ttyUSB1

jetson@ubuntu:~$ docker run -it --device=/dev/myserial --device=/dev/rplidar
ubuntu:latest /bin/bash

root@03522257ba30:/# ls /dev #There are myserial and rplidar device in docker
```

```
console fd full mqueue myserial null ptmx pts random rplidar shm
stderr stdin stdout tty urandom zero
```


4.2、 GUI display in docker

1、 Install in the host (Factory image has been installed by default):

```
sudo apt-get install tigervnc-standalone-server tigervnc-viewer
sudo apt-get install x11-xserver-utils
```

2、 Execute in the host: xhost +

After the following image is displayed, perform 3 steps:

A terminal window titled 'jetson@jetson-desktop: ~' with a red title bar. The terminal shows the command 'xhost +' being executed, resulting in the output 'access control disabled, clients can connect from any host'. The prompt is 'jetson@jetson-desktop:~\$'.

3、 Execute the command in the host to enter the container:

```
docker run -it \                                # Run docker images interactively
--env="DISPLAY" \                               # Open the display GUI interface
--env="QT_X11_NO_MITSHM=1" \                   # Port 1 of X11 is used for display
-v /tmp/.X11-unix:/tmp/.X11-unix \            # map shows the service node directory
yahboomtechnology/ros-foxy:1.0.0              # The name of the image to start
/bin/bash                                     # Executes the /bin/bash command in the container
```

4、 Test

```
Execute in container: rviz2
```

4.3、 docker containers and hosts transfer files to each other

4.3.1、 use cp command

4.3.1.1、 Copy files from the container to the host

```
# command
docker cp [container id:Intra-container path] [Destination host path]

# test
# Execute inside the container, create a file test
jetson@ubuntu:~$ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS
c54bf9efae47	ubuntu:latest	"/bin/bash"	2 hours ago	Up 9 minutes
3b9c01839579	hello-world	"/hello"	3 hours ago	Exited (0) 3 hours ago

```

jetson@ubuntu:~$ docker attach c5
root@c54bf9efae47:/# cd
root@c54bf9efae47:~# ls
root@c54bf9efae47:~# touch test.txt
root@c54bf9efae47:~# ls
test.txt
root@c54bf9efae47:~# pwd
/root
root@c54bf9efae47:/# (read escape sequence) #ctrl+P+Q The container does not
stop exiting
jetson@ubuntu:~$ docker cp c54bf9efae47:/root/test.txt ~/
jetson@ubuntu:~$ ls # The test .txt file has been copied in
Desktop Documents Downloads fishros Music openvino Pictures Public
rootOnNVMe run_docker.sh sensors snap temp Templates test.txt Videos

```

example:

```

root@ebdc5cc1469f:/# cd
root@ebdc5cc1469f:~# ls
root@ebdc5cc1469f:~# touch test.txt
root@ebdc5cc1469f:~# ls
test.txt
root@ebdc5cc1469f:~# pwd
/root
root@ebdc5cc1469f:~# read escape sequence
jetson@unbutu:~$ docker cp ebdc5cc1469f:/root/test.txt ~/test/
jetson@unbutu:~$ cd ~/test/
jetson@unbutu:~/test$ ls
test.txt
jetson@unbutu:~/test$ █

```

4.3.1.2、 Copy files from the host to the container

```

# command
docker cp [host_file_path] [container id:the path within the docker]

# test
jetson@ubuntu:~$ docker ps -a
CONTAINER ID   IMAGE          COMMAND          CREATED        STATUS
PORTS         NAMES
c54bf9efae47   ubuntu:latest  "/bin/bash"     2 hours ago   Up 5 minutes
              funny_hugle
3b9c01839579   hello-world    "/hello"        3 hours ago   Exited (0) 3 hours ago
              jovial_brown
jetson@ubuntu:~$ ls
Desktop Documents Downloads fishros Music openvino Pictures Public
rootOnNVMe run_docker.sh sensors snap temp Templates test.txt Videos
jetson@ubuntu:~$ touch 11.txt
jetson@ubuntu:~$ ls

```

```

11.txt Desktop Documents Downloads fishros Music openvino Pictures Public
root@ubuntu:~$ docker cp 11.txt c54bf9efae47:/root/
jetson@ubuntu:~$ docker exec -it c54b /bin/bash
root@c54bf9efae47:/# ls
bin boot dev etc home lib media mnt opt proc root run sbin srv sys
tmp usr var
root@c54bf9efae47:/# cd /root/
root@c54bf9efae47:~# ls      # 11.txt The file has been copied in
11.txt test.txt

```

example:

```

jetson@unbutu:~/test$ ls
test.txt
jetson@unbutu:~/test$ touch 11.txt
jetson@unbutu:~/test$ ls
11.txt test.txt
jetson@unbutu:~/test$ docker cp 11.txt ebdc5cc1469f:/root/
jetson@unbutu:~/test$ docker exec -it ebdc5cc1469f /bin/bash
root@ebdc5cc1469f:/# cd
root@ebdc5cc1469f:~# ls
11.txt test.txt
root@ebdc5cc1469f:~#

```

4.3.2、 Using Data Volumes

4.3.2.1、 Data Volume Overview

Package the application and the running environment to form a container to run, and the run can be accompanied by the container, but our data requirements are expected to be persistent! For example, if you install a mysql and you delete the container, it is equivalent to deleting the library and running away, which is definitely not okay! So we hope that it is possible to share data between containers, and the data generated by docker containers, if a new image is not generated through docker commit, so that the data is saved as part of the image, then when the container is deleted, the data will naturally be gone! This will not work!

In order to save data, we can use volumes in Docker! Let the data be mounted locally to us! So that the data is not lost due to container deletion!

Peculiarity:

1. Data volumes can share or reuse data between containers
2. Changes in the volume can take effect directly
3. Changes in the data volume will not be included in the update of the image
4. The lifecycle of a data volume lasts until no container uses it

4.3.2.2、 Data volume use

command

`docker run -it -v host absolute path directory: directory inside the container
image name`

Test

`docker run -it -v /home/jetson/temp:/root/temp yahboomtechnology/ros-foxy:3.4.0
/bin/bash`

The `/home/jetson/temp` directory in the host and the `/root/temp` directory in the container can share data