

yolov8n segmentation

yolov8n segmentation

[Routine Experiment Effect](#)

[Code Explanation](#)

[Code structure](#)


[Part of the code](#)

[flow chart](#)

Routine Experiment Effect

In this section, we will learn how to use K230 to implement object segmentation based on yolov8n.

After connecting to the IDE, run the sample code in this section and use K230 to focus on the surroundings. You can see that based on the object detection, the detected object area will be rendered with different colors.



Code Explanation

Code structure

Since segmentation is based on detection, here we mainly list the differences in code structure from the detection in the previous section.

1. Added segmentation model-specific initialization phase, including mask array initialization
2. Modified the detection process to detection and segmentation process, added mask generation step

3. Added segmentation mask drawing step to display pipeline
4. Adjusted the order and relationship of each sub-process in the main loop

Part of the code

For the complete code, please refer to the file [Source Code/09.Scene/04.segment_yolov8n.py]

```
def postprocess(self, results):
    """
    自定义当前任务的后处理
    Custom post-processing for the current task

    参数:
    Parameters:
        results: 模型推理结果 / Model inference results

    返回:
    Returns:
        seg_res: 分割结果 / Segmentation results
    """
    with ScopedTiming("postprocess", self.debug_mode > 0):
        # 这里使用了aidemo的segment_postprocess接口进行后处理
        # Using aidemo's segment_postprocess interface for post-processing
        seg_res = aidemo.segment_postprocess(
            results,
            [self.rgb888p_size[1], self.rgb888p_size[0]],
            self.model_input_size,
            [self.display_size[1], self.display_size[0]],
            self.confidence_threshold,
            self.nms_threshold,
            self.mask_threshold,
            self.masks
        )
        return seg_res


def draw_result(self, pl, seg_res):
    """
    绘制分割结果到显示层
    Draw segmentation results to display layer


    参数:
    Parameters:
        pl: Pipeline对象 / Pipeline object
        seg_res: 分割结果 / Segmentation results
    """
    with ScopedTiming("display_draw", self.debug_mode > 0):
        if seg_res[0]: # 如果有检测到物体 / If objects are detected
            pl.osd_img.clear() # 清除OSD图层 / Clear OSD layer
            # 创建引用mask数据的图像对象 / Create image object referencing mask
            data
            mask_img = image.Image(self.display_size[0],
            self.display_size[1], image.ARGB8888, alloc=image.ALLOC_REF, data=self.masks)
            pl.osd_img.copy_from(mask_img) # 复制mask图像到OSD层 / Copy mask
            image to OSD layer

            # 提取检测结果 / Extract detection results
            dets, ids, scores = seg_res[0], seg_res[1], seg_res[2]
```

```
        for i, det in enumerate(dets):
            # 绘制标签和置信度 / Draw label and confidence
            x1, y1, w, h = map(lambda x: int(round(x, 0)), det)
            pl.osd_img.draw_string_advanced(
                x1, y1-50, 32,
                " " + self.labels[int(ids[i])] + " " +
str(round(scores[i], 2)),
                color=self.get_color(int(ids[i]))
            )
        else:
            pl.osd_img.clear() # 没有检测结果时清除OSD / Clear OSD when no
detection
```

flow chart





结束/End