

Control car and read encoder-USART

1.1 Explanation

Please read 《0. Motor introduction and usage》 first to understand the motor parameters, wiring method, and power supply voltage you are currently using. To avoid improper operation and damage to the driver board or motor.

I2C and serial communication cannot be shared, only one can be selected.

The 4 motor interfaces on the module correspond to motors on robot car, as shown below


M1 -> Upper left motor (left front wheel of the car)

M2 -> Lower left motor (left rear wheel of the car)

M3 -> Upper right motor (right front wheel of the car)

M4 -> Lower right motor (right rear wheel of the car)

Hardware wiring:



4-channel motor drive board	MSPM0G3507
RX2	PB6

4-channel motor drive board	MSPM0G3507
TX2	PB7
GND	GND
5V	5V

Motor	4-channel motor drive board(Motor)
M2	M-
V	3V3
A	H1B
B	H1A
G	GND
M1	M+

USB to TTL serial port module needs to be connected to print the processed encoder data.

If you are using Yahboom MSPM0G3507, you can directly connect the TYPE-C interface on the MSPM0G3507 development board to the computer USB port, and you can also achieve serial port printing, so you don't need to connect a USB to TTL serial port module.

USB TO TTL	MSPM0G3507
VCC	3V3
GND	GND
RXD	PA10
TXD	PA11

Serial port configuration: **Baud rate 115200, no parity check, no hardware flow control, 1 stop bit**

Note: The serial port here is used to print data on the serial port assistant, not for communication with the driver board

1.2 Code analysis

```
#define UPLOAD_DATA 2 // 1:接收总的编码器数据 2:接收实时的编码器 1: Receive total encoder data
2: Receive real-time encoder data

#define MOTOR_TYPE 1 //1:520电机 2:310电机 3:测速码盘TT电机 4:TT直流减速电机 5:L型520电机
//1:520 motor 2:310 motor 3:speed code disc TT motor 4:TT DC
reduction motor 5:L type 520 motor
```

- UPLOAD_DATA: used to set the data of the motor encoder. Set 1 to the total number of encoder pulses

and 2 to the real-time pulse data of 10ms.

- MOTOR_TYPE: used to set the type of motor used. Just modify the corresponding numbers according to the comments according to the motor you are currently using. You don't need to modify the rest of the code.

If you need to drive the motor and observe the data, just modify the two numbers at the beginning of the program. No changes are required to the rest of the code.

```
#if MOTOR_TYPE == 1
send_motor_type(1); //配置电机类型 Configure motor type
delay_ms(100);
send_pulse_phase(30); //配置减速比 查电机手册得出 Configure the reduction ratio. Check the
motor manual to find out
delay_ms(100);
send_pulse_line(11); //配置磁环线 查电机手册得出 Configure the magnetic ring wire. Check the
motor manual to get the result.
delay_ms(100);
send_wheel_diameter(67.00); //配置轮子直径,测量得出 Configure the wheel diameter and
measure it
delay_ms(100);
send_motor_deadzone(1900); //配置电机死区,实验得出 Configure the motor dead zone, and the
experiment shows
delay_ms(100);

#elif MOTOR_TYPE == 2
send_motor_type(2);
delay_ms(100);
send_pulse_phase(20);
delay_ms(100);
send_pulse_line(13);
delay_ms(100);
send_wheel_diameter(48.00);
delay_ms(100);
send_motor_deadzone(1600);
delay_ms(100);

#elif MOTOR_TYPE == 3
send_motor_type(3);
delay_ms(100);
send_pulse_phase(45);
delay_ms(100);
send_pulse_line(13);
delay_ms(100);
send_wheel_diameter(68.00);
delay_ms(100);
send_motor_deadzone(1250);
delay_ms(100);

#elif MOTOR_TYPE == 4
send_motor_type(4);
delay_ms(100);
send_pulse_phase(48);
delay_ms(100);
```

```

send_motor_deadzone(1000);
delay_ms(100);

#elif MOTOR_TYPE == 5
send_motor_type(1);
delay_ms(100);
send_pulse_phase(40);
delay_ms(100);
send_pulse_line(11);
delay_ms(100);
send_wheel_diameter(67.00);
delay_ms(100);
send_motor_deadzone(1900);
delay_ms(100);
#endif

```

This is used to store the parameters of the Yahboom motor. By modifying the MOTOR_TYPE parameter above, one-click configuration can be achieved.

In normally, do not modify the code here when using the Yahboom motor.

If you are using your own motor, or if a certain data needs to be modified according to your needs, you can check the course 《1.2 Control command》 to understand the specific meaning of each command.

```

while(1)
{
    if(times>=25)//定时器每100ms累加一次，当达到25次，即2.5秒的时候转换一次小车的状态    The timer
    accumulates every 100ms, and when it reaches 25 times, that is, every 2.5 seconds, the state
    of the car is changed.
    {
        #if MOTOR_TYPE == 4
        Car_Move_PWM();
        #else
        Car_Move();
        #endif
        times = 0;
    }
    if(g_recv_flag == 1)
    {
        g_recv_flag = 0;

        #if UPLOAD_DATA == 1
        Deal_data_real();

        printf("M1:%d,M2:%d,M3:%d,M4:%d\r\n",Encoder_Now[0],Encoder_Now[1],Encoder_Now[2],Encoder_No
w[3]);
        #elif UPLOAD_DATA == 2
        Deal_data_real();

        printf("M1:%d,M2:%d,M3:%d,M4:%d\r\n",Encoder_Offset[0],Encoder_Offset[1],Encoder_Offset[2],E
ncoder_Offset[3]);
        #elif UPLOAD_DATA == 3
        Deal_data_real();

```

```

printf("M1:%.2f,M2:%.2f,M3:%.2f,M4:%.2f\r\n",g_Speed[0],g_Speed[1],g_Speed[2],g_Speed[3]);
    #endif
    }
}

}

//定时器的中断服务函数,每100ms读取数据并打印
//The timer interrupt service function reads and prints data every 100ms
void TIMER_0_INST_IRQHandler(void)
{
    //如果产生了定时器中断    If a timer interrupt occurs
    switch( DL_TimerG_getPendingInterrupt(TIMER_0_INST) )
    {
        case DL_TIMER_IIDX_ZERO://如果是0溢出中断    If it is 0 overflow interrupt
            times++;
            break;

        default:
            break;
    }
}

```

A 100ms timer is set in the program. Each time the timer interrupt is triggered, the times variable will be incremented by one. When it reaches 25 times, that is, 2.5 seconds, the motion state of the car will be changed.

If the motor type is 4, that is, the motor without encoder, then the pwm version of the car state switching function is used. At the same time, read the data sent by the driver board and print the data out at the same time.

```

//检验从驱动板发送过来的数据,符合通讯协议的数据则保存下来
//Check the data sent from the driver board, and save the data that meets the communication protocol
void Deal_Control_Rxtemp(uint8_t rxtemp)
{
    static u16 step = 0;
    static u8 start_flag = 0;

    if(rxtemp == '$' && start_flag == 0)
    {
        start_flag = 1;
        memset(g_recv_buff,0,RXBUFF_LEN);//清空数据    clear data
    }

    else if(start_flag == 1)
    {
        if(rxtemp == '#')
        {
            start_flag = 0;
        }
    }
}

```

```

        step = 0;
        g_recv_flag = 1;
        memcpy(g_recv_buff_deal,g_recv_buff,RXBUFF_LEN); //只有正确才会赋值 Only
correct ones will be assigned
    }
    else
    {
        if(step > RXBUFF_LEN)
        {
            start_flag = 0;
            step = 0;
            memset(g_recv_buff,0,RXBUFF_LEN); //清空接收数据 Clear received data
        }
        else
        {
            g_recv_buff[step] = rxtemp;
            step++;
        }
    }
}
}
}

```

//将从驱动板保存到的数据进行格式处理，然后准备打印

//Format the data saved from the driver board and prepare it for printing

void Deal_data_real(void)

```

{
    static uint8_t data[RXBUFF_LEN];
    uint8_t length = 0;

    //总体的编码器 Overall encoder
    if ((strcmp("MAll",(char*)g_recv_buff_deal,4)==0))
    {
        length = strlen((char*)g_recv_buff_deal)-5;
        for (uint8_t i = 0; i < length; i++)
        {
            data[i] = g_recv_buff_deal[i+5]; //去掉冒号 Remove the colon
        }

        data[length] = '\0';

        char* strArray[10]; //指针数组 长度根据分割号定义 char 1字节 char* 4字节
Pointer array The length is defined by the split number char 1 byte char* 4 bytes
        char mystr_temp[4][10] = {'\0'};
        splitString(strArray,(char*)data, ", "); //以逗号切割 Split by comma
        for (int i = 0; i < 4; i++)
        {
            strcpy(mystr_temp[i],strArray[i]);
            Encoder_Now[i] = atoi(mystr_temp[i]);
        }
    }

    //10ms的实时编码器数据 10ms real-time encoder data
}

```

```

else if ((strcmp("MTEP", (char*)g_rcv_buff_deal, 4) == 0))
{
    length = strlen((char*)g_rcv_buff_deal) - 5;
    for (uint8_t i = 0; i < length; i++)
    {
        data[i] = g_rcv_buff_deal[i + 5]; //去掉冒号 Remove the colon
    }

    data[length] = '\0';

    char* strArray[10]; //指针数组 长度根据分割号定义 char 1字节 char* 4字节
    Pointer array The length is defined by the split number char 1 byte char* 4 bytes
    char mystr_temp[4][10] = {'\0'};
    splitString(strArray, (char*)data, ", "); //以逗号切割 Split by comma
    for (int i = 0; i < 4; i++)
    {
        strcpy(mystr_temp[i], strArray[i]);
        Encoder_Offset[i] = atoi(mystr_temp[i]);
    }
}
//速度 Speed
else if ((strcmp("MSPD", (char*)g_rcv_buff_deal, 4) == 0))
{
    length = strlen((char*)g_rcv_buff_deal) - 5;
    for (uint8_t i = 0; i < length; i++)
    {
        data[i] = g_rcv_buff_deal[i + 5]; //去掉冒号 Remove the colon
    }

    data[length] = '\0';

    char* strArray[10]; //指针数组 长度根据分割号定义 char 1字节 char* 4字节
    Pointer array The length is defined by the split number char 1 byte char* 4 bytes
    char mystr_temp[4][10] = {'\0'};
    splitString(strArray, (char*)data, ", "); //以逗号切割 Split by comma
    for (int i = 0; i < 4; i++)
    {
        strcpy(mystr_temp[i], strArray[i]);
        g_Speed[i] = atof(mystr_temp[i]);
    }
}
}

```

- Deal_Control_Rxtemp: Filter the received data and save those that meet the communication protocol.
- Deal_data_real: Extract the saved original data and reconstruct a new print format.

1.3 Experimental phenomenon

After the wiring is correct, write the program into the mainboard. After resetting, you can see that the car will move forward for 2.5S, move backward for 2.5S, rotate right for 2.5S, rotate left for 2.5S, then stop for 2.5S, and continue the above state switching actions.

At the same time, you can see that the printed motor values are constantly changing in the serial port assistant.

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118,M2:1127,M3:1136,M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119

M1:1118, M2:1127, M3:1136, M4:1119