

9. Intent Inference + Multimodal Visual Understanding + SLAM Navigation

1. Course Content

Note: This chapter requires completing the map mapping file configuration according to the **【Multimodal Visual Understanding + SLAM Navigation】** chapter.

1. Learn to use the RAG knowledge base to train personal intent understanding.

Course review:

If you need to enhance or reduce the diversity of the large model's replies, refer to **【AI Large Model Development】** - **【RAG Knowledge Base Deployment】** to modify the knowledge base and sample library.

Using the RAG knowledge base can expand the knowledge scope of the large model. This chapter explains how to extend the RAG knowledge base so that the large model can understand personal intents.

Special note!!!:

1. The personal intent understanding function varies by user, and large model replies are divergent, so the actual debugging results are not exactly the same.
2. Extending the personal intent understanding function must comply with social morality, public order, and laws and regulations. The technical service is not responsible for the final debugging results of this chapter or their impact.

2. Preparation

2.1 Content Description

Add a custom intent inference knowledge base. Since personal intents are divergent, there is no unified content, and the actual debugging results are not exactly the same.

The virtual machine used by default with this product starts the Dify Docker environment automatically at boot, so no additional startup is usually needed.


Open the virtual machine terminal, start the Dify environment:

```
sh ~/bringup_dify.sh
```



3.2 Uploading to the RAG Knowledge Base

Some intent inference is already configured at the factory. The following steps are for adding your own new intents.


1. Access the IP of the vehicle and enter the Dify backend.



2. Click 【Knowledge】 and click 【Sample Library】.



3. Click "Add File".



4. Upload your intent inference knowledge base.

Import from file

Sync from Notion

Sync from website

Upload file

📁

Drag and drop file or folder, or [Browse](#)

Supports DOCX, MDX, TXT, MARKDOWN, XLS, XLSX, PDF, VTT, HTML, PROPERTIES, MD, CSV, HTM. Max 5 in a batch and 15 MB each.

Next →

I want to create an empty Knowledge

5. Click 【Next】 , then click 【Save and Process】 .

Import from file

Sync from Notion

Sync from website

Upload file

📁

Drag and drop file or folder, or [Browse](#)

Supports DOCX, MDX, TXT, MARKDOWN, XLS, XLSX, PDF, VTT, HTML, PROPERTIES, MD, CSV, HTM. Max 5 in a batch and 15 MB each.

📄

decision-layer-training-examples-en.xlsx

XLSX · 5.84 KB

Next →

I want to create an empty Knowledge

KNOWLEDGE

1 DATA SOURCE

STEP 2 DOCUMENT PROCESSING

3 EXECUTE & FINISH

Once finishing embedding in High Quality mode, reverting to Economical mode is not available.

Embedding Model

multimodal-embedding-v1

Retrieval Setting

Learn more about retrieval method, you can change this at any time in the Knowledge settings.

Vector Search

Generate query embeddings and search for the text chunk most similar to its vector representation.

Rerank Model

qwen3-rerank

When embedding model supports multi-modal, please select a multi-modal rerank model for better performance.

Top K

3

Score Threshold

0.5

Full-Text Search

Index all terms in the document, allowing users to search any term and retrieve relevant text chunk containing those terms.

Hybrid Search

RECOMMEND

Execute full-text search and vector searches simultaneously, re-rank to select the best match for the user's query. Users can choose to set weights or configure a Rerank model.

Previous step

Save & Process

PREVIEW

decision-layer-training-ex... 0 ESTIMATED CHUNKS

Click the 'Preview Chunk' button on the left to load the preview

6. Wait for the processing to succeed, refresh the knowledge base, and you can see that the intent mapping file has been added.

Knowledge created

We automatically named the Knowledge, you can modify it at any time.



Knowledge name

decision-layer-tra...

EMBEDDING PROCESSING...

decision-layer-training-examples-en.xlsx 0%

Chunking Setting	Custom
Maximum Chunk Length	1024
Text Preprocessing Rules	Replace consecutive spaces, newlines and tabs
Index Method	High Quality
Retrieval Setting	Vector Search

Access the API

Go to document →



What's next

After finishing docume
manage and edit docu
and modify knowledge
then be integrated into
context, so make sure
Setting to ensure opti

[Learn more](#)

Dify | yahboom's Workspace

Explore Studio Knowledge / decision-layer-tra... Tools

Documents

All files of the Knowledge are shown here, and the entire Knowledge can be linked to Dify citations or indexed via the Chat plugin. [Learn more](#)

1 documents indexed failed

#	NAME	CHUNKING MODE	WORDS	RETRIEVAL COUNT	UPLOAD TIME
1	decision-layer-training-examples-en.xlsx	GENERAL	2.7k	0	08/17/2026 05:42 PM


Documents

Pipeline


Retrieval Testing

Settings


7. Return to the **Studio** interface and select the application corresponding to your camera model. Here, **microros-v2-zh** is used as an example.



8. Select **Task Routing**, and add your own defined intent expressions in the complex task category, for example, "I'm hungry", "I'm thirsty", and "I'm a little sleepy".



9. Select the 【Decision-Layer Sample Library】 knowledge retrieval node, and confirm that the newly added intent mapping knowledge base has been selected. If it has not been selected, click the Add button on the right to add the just-uploaded intent mapping knowledge base to this node.



Select reference Knowledge

decision-layer-tra...
ECO - INVERTED

fake_author.txt...
HQ - VECTOR

decision-layer-tra...
HQ - VECTOR

决策层训练样例.xlsx...
HQ - VECTOR

1 Knowledge selected

Cancel

Add

10. You can click "Preview" in the upper-right corner, for example, send "I'm hungry" and observe whether it enters the complex task branch, and confirm whether the decision layer can output high-level steps consistent with the intent mapping.

Finally, click **【Publish】** in the upper-right corner to re-publish the corresponding application.

4. Running the Case

4.1 Starting the Program

Open the virtual machine terminal, start the Dify environment (if it is already started, no need to start it again):

```
sh ~/bringup_dify.sh
```

```
yahboom@yahboom:~$ sh ~/bringup_dify.sh
[+] up 13/13
✓ Container docker-sandbox-1      Running      0.0s
✓ Container docker-web-1          Running      0.0s
✓ Container docker-db_postgres-1  Healthy     22.5s
✓ Container docker-ssrf_proxy-1    Running      0.0s
✓ Container docker-redis-1        Running      0.0s
✓ Container docker-weaviate-1      Running      0.0s
✓ Container docker-worker-1       Running      0.0s
✓ Container docker-api_websocket-1 Running      0.0s
✓ Container docker-plugin_daemon-1 Running      0.0s
✓ Container docker-worker_beat-1   Running      0.0s
✓ Container docker-api-1          Running      0.0s
✓ Container docker-nginx-1        Running      0.0s
✓ Container docker-init_permissions-1 Exited       28.4s
yahboom@yahboom:~$
```

Open the virtual machine terminal and enter the command to start the underlying proxy, camera topic, and Nav2 navigation:


```
ros2 launch microros_v2_bringup nav2.launch.py
```

```
yahboom@yahboom:~$ ros2 launch microros_v2_bringup nav2.launch.py
[INFO] [launch]: All log files can be found below /home/yahboom/.ros/log/2026-07-24-11-57-50-009345-yahboom-219629
[INFO] [launch]: Default logging verbosity is set to INFO
[INFO] [rviz2-1]: process started with pid [219604]
[INFO] [micro_ros_agent-2]: process started with pid [219606]
[INFO] [camera_driver-3]: process started with pid [219608]
[INFO] [robot_state_publisher-4]: process started with pid [219670]
[INFO] [joint_state_publisher-5]: process started with pid [219672]
[INFO] [ekf_node-6]: process started with pid [219674]
[INFO] [component_container_isolated-7]: process started with pid [219682]
[micro_ros_agent-2] [1784865471.046289] info | UDPv4AgentLinux.cpp | Init | running... | port: 8090
[robot_state_publisher-4] [INFO] [1784865471.195985237] [robot_state_publisher]: got segment base_footprint
[robot_state_publisher-4] [INFO] [1784865471.196067136] [robot_state_publisher]: got segment base_link
[robot_state_publisher-4] [INFO] [1784865471.196074446] [robot_state_publisher]: got segment bwheel_link
[robot_state_publisher-4] [INFO] [1784865471.196079846] [robot_state_publisher]: got segment can1_link
[robot_state_publisher-4] [INFO] [1784865471.196084086] [robot_state_publisher]: got segment can2_link
[robot_state_publisher-4] [INFO] [1784865471.196088634] [robot_state_publisher]: got segment can3_link
[robot_state_publisher-4] [INFO] [1784865471.196092897] [robot_state_publisher]: got segment imu_frame
[robot_state_publisher-4] [INFO] [1784865471.196097021] [robot_state_publisher]: got segment laser_frame
[robot_state_publisher-4] [INFO] [1784865471.196101332] [robot_state_publisher]: got segment lfwheel_link
[robot_state_publisher-4] [INFO] [1784865471.196105518] [robot_state_publisher]: got segment rfwheel_link
[joint_state_publisher-5] [INFO] [1784865471.581793865] [joint_state_publisher]: Waiting for robot_description to be published on the robot_description topic...
[camera_driver-3] [INFO] [1784865471.61683871] [esp32_ip_camera_publisher]: camera node started, camera_url: http://192.168.12.37:81/stream
[component_container_isolated-7] [INFO] [1784865471.621621536] [nav2_container]: Load Library: /opt/ros/humble/lib/libmap_server_core.so
[component_container_isolated-7] [INFO] [1784865472.588657350] [nav2_container]: Found class: rclcpp_components::NodeFactoryTemplate<nav2_map_server::CostmapFilterInfoServer>
[component_container_isolated-7] [INFO] [1784865472.588723330] [nav2_container]: Found class: rclcpp_components::NodeFactoryTemplate<nav2_map_server::MapSaver>
[component_container_isolated-7] [INFO] [1784865472.588736433] [nav2_container]: Found class: rclcpp_components::NodeFactoryTemplate<nav2_map_server::MapServer>
[component_container_isolated-7] [INFO] [1784865472.588735478] [nav2_container]: Instantiate class: rclcpp_components::NodeFactoryTemplate<nav2_map_server::MapServer>
```

Open another virtual machine terminal and enter the command to start the large model agent node:

```
ros2 launch multi_brains llm_agent_control.launch.py
```

After initialization is complete, the following content will be displayed:

A terminal window titled 'yahboom@VM: ~' with standard window controls. It displays the output of the 'ros2 launch multi_brains llm_agent_control.launch.py' command. The logs show the initialization of the 'llm_agent_node', including configuration of command velocity, image cache path, PTZ startup parameters, scan topic, obstacle guard, buzzer, and client initialization. The process concludes with a successful connection and PTZ servo initialization.

```
G_MODE=False, LANGUAGE=en, CAR_TYPE=ptz
[llm_agent_node-1] [INFO] [1787128762.059479166] [llm_agent_node]: Initializing
LLM Agent Node...
[llm_agent_node-1] [INFO] [1787128762.070369334] [llm_agent_node]: [CONFIG] cmd_
vel_topic=/cmd_vel
[llm_agent_node-1] [INFO] [1787128762.077274270] [llm_agent_node]: [CONFIG] imag
e_cache_path=/home/yahboom/microros_ws/cache/llm_camera.jpg
[llm_agent_node-1] [INFO] [1787128762.078819208] [llm_agent_node]: [PTZ] startup
initialization enabled: x=0.0°, y=-45.0°, count=20, interval=0.10s
[llm_agent_node-1] [INFO] [1787128762.106861388] [llm_agent_node]: [FOLLOW] scan
_topic=/scan, obstacle_guard=True, buzzer_topic=/beep, buzzer=True
[llm_agent_node-1] [INFO] [1787128762.107460365] [llm_agent_node]: [DIFY] Initia
lize client: base_url=http://localhost/v1, api_key=app-SAnX****Zt2E
[llm_agent_node-1] [INFO] [1787128762.109741022] [llm_agent_node]: [DIFY] Testin
g connection....
[llm_agent_node-1] [INFO] [1787128762.130633809] [llm_agent_node]: [TRACK_KCF] S
ubscribed /tracking_bbox, type=smart_tracker/msg/TrackBox
[llm_agent_node-1] [INFO] [1787128762.131212772] [llm_agent_node]: LLM Agent Nod
e initialized successfully
[llm_agent_node-1] [INFO] [1787128762.133300019] [llm_agent_node]: [DIFY] Connec
tion successful ✓
[llm_agent_node-1] [INFO] [1787128764.080740503] [llm_agent_node]: [PTZ] Servo i
nitialization complete: x=0.0°, y=-45.0°
```

Then follow the process of starting the navigation function for initial localization. After opening the RViz2 visualization interface, click **2D Pose Estimate** in the toolbar at the top, roughly mark the robot's position and orientation on the map. After initial localization, the preparation is complete.



Then open another terminal and start the text dialogue client:

```
ros2 run multi_brains terminal_client
```


```

yahboom@VM: ~
> =====
> MicroROS LLM Agent Terminal Client
> =====
> Enter natural-language commands to control the robot
>
> Examples:
>   > Go to point A
>   > Follow the red line
>   > Look at what is ahead
>   > Move forward 2 meters
>
> Commands:
>   reset - Reset conversation context
>   clear - Clear screen
>   help  - Show this help
>   exit  - Exit program
> =====

```

Use the Chinese input method:

- Click the input method icon in the upper-right corner of the virtual machine to switch to Chinese pinyin. You can also press the `Shift` shortcut key in the terminal to switch.



4.2 Test Cases

Reference test cases are given here. Users can write their own dialogue commands:

- I feel a little thirsty.

4.2.1 Case 1

Enter "I feel a little thirsty." in the terminal. If the intent mapping knowledge base has a high-level task configured for "thirsty", for example, "go to the tea room/kitchen to get water or observe the drink location",

```
> [Sending] I'm feeling a little thirsty
> [Sent] New commands can be accepted. The latest command will take
priority.
>
> [Progress] [Decision] Thinking...
>
> [Progress] [Decision] Okay, navigating to the pantry now.
>
> [Progress] Decision-making plan: 1. Navigate to Point A
>
> [Progress] [Preparation] Adjusting the camera to look straight
ahead...
> [Progress] [Action 1/1] navigation(A)
>
> [Progress] [Navigation] Heading to Point A...
>
```

Then the execution-layer large model will execute according to the decision-layer steps:

```

[llm_agent_node-1] [INFO] [1704882023.33863308] [llm_agent_node]: [PROGRESS] Decision layer plan: 1. Navigate to Point A
[llm_agent_node-1] [INFO] [1704882023.339025700] [llm_agent_node]: [PROGRESS] [Preparation] Adjusting camera to face straight ahead...
[llm_agent_node-1] [INFO] [1704882023.841612436] [llm_agent_node]: [PROGRESS] [Action 1/1] navigation(A)
[llm_agent_node-1] [INFO] [1704882023.842859551] [llm_agent_node]: [NAVIGATION] Start common navigation: A
[llm_agent_node-1] [INFO] [1704882023.842935262] [llm_agent_node]: [NAV] Target coordinate: pos=(-1.058, 0.621, 0.000), ori=(0.000, 0.000, -0.470, 0.882)
[llm_agent_node-1] [INFO] [1704882023.849662594] [llm_agent_node]: [NAV] Waiting to arrive at 'A' (Timeout 300.0s)...
[llm_agent_node-1] [INFO] [1704882023.849803047] [llm_agent_node]: [NAV] Navigation goal accepted: 'A'
[llm_agent_node-1] [INFO] [1704882023.850200810] [llm_agent_node]: [PROGRESS] [Navigation] Moving towards Point A...
[llm_agent_node-1] [INFO] [1704882040.446977929] [llm_agent_node]: [NAV] result_callback: status=4, result_type=NavigateToPose_Result
[llm_agent_node-1] [INFO] [1704882040.447795513] [llm_agent_node]: [NAV] Navigation completed: status=4
[llm_agent_node-1] [INFO] [1704882040.448157631] [llm_agent_node]: [NAV] Successfully arrived at 'A' ✓
[llm_agent_node-1] [INFO] [1704882040.448602719] [llm_agent_node]: [PROGRESS] [Navigation] Arrived at Point A ✓
[llm_agent_node-1] [INFO] [1704882040.449061419] [llm_agent_node]: [PROGRESS] [Action 1/1] navigation(A) Success ✓
[llm_agent_node-1] [INFO] [1704882044.457743491] [llm_agent_node]: [PROGRESS] [Feedback Decision] Arrived at the pantry, now observing the surrounding environment
[llm_agent_node-1] [INFO] [1704882044.458463476] [llm_agent_node]: [PROGRESS] Decision layer plan: 1. Take photos of surroundings from multiple directions and give feedback
[llm_agent_node-1] [INFO] [1704882044.460985978] [llm_agent_node]: [PROGRESS] [Action 1/1] observe_surroundings()
[llm_agent_node-1] [INFO] [1704882044.467778903] [llm_agent_node]: [OBSERVE] Start observing surrounding environment
[llm_agent_node-1] [INFO] [1704882044.469268840] [llm_agent_node]: [PROGRESS] [Observe 1/3] Observing front...
[llm_agent_node-1] [INFO] [1704882047.682917428] [llm_agent_node]: [PROGRESS] [Observe] Front: Waiting for new image timeout
[llm_agent_node-1] [INFO] [1704882047.683351278] [llm_agent_node]: [PROGRESS] [Observe 2/3] Observing front-right...
[llm_agent_node-1] [INFO] [1704882050.295290533] [llm_agent_node]: [PROGRESS] [Observe] Front-right: Acquired image from the corresponding orientation
[llm_agent_node-1] [INFO] [1704882050.295751209] [llm_agent_node]: [PROGRESS] [Observe 3/3] Observing front-left...
[llm_agent_node-1] [INFO] [1704882053.509204200] [llm_agent_node]: [PROGRESS] [Observe] Front-left: Waiting for new image timeout
[llm_agent_node-1] [INFO] [1704882053.509706287] [llm_agent_node]: [OBSERVE] Surrounding image collection complete, total 1 direction
[llm_agent_node-1] [INFO] [1704882053.510011258] [llm_agent_node]: [OBSERVE] Observation finished, gmbal returns to initial position
[llm_agent_node-1] [INFO] [1704882054.013116417] [llm_agent_node]: [SERVO] Gmbal homing complete: x=0.0°, y=-45.0°
[llm_agent_node-1] [INFO] [1704882054.013657825] [llm_agent_node]: [PROGRESS] [Action 1/1] observe_surroundings() Success ✓
[llm_agent_node-1] [INFO] [1704882055.277632754] [llm_agent_node]: [DIFY] Feedback image 1/1 upload complete: file_id=37142c48-949c-4695-aecd-9aabf272fcc5, HTTP 201
[llm_agent_node-1] [INFO] [1704882066.731691282] [llm_agent_node]: [Action] finishtask: Task cycle ended
[llm_agent_node-1] [INFO] [1704882066.732467436] [llm_agent_node]: [RESULT] Arrived at the pantry and observed the surrounding environment, but did not find pantry facilities
[llm_agent_node-1] [INFO] [1704882066.732764635] [llm_agent_node]: [INPUT] == Command #8 processing complete, feedback rounds ≤12, total time: 50.67s ==

```

After the robot completes the task, it enters a waiting state, and the conversation history will continue to be retained. You can input `reset` in the terminal to reset the conversation context, or input a new natural language instruction to let the latest instruction take over the current task.

```

[llm_agent_node-1] [INFO] [1784867518.113324588] [llm_agent_node]: [INPUT] — Received user input #3: '/'
'reset'
[llm_agent_node-1] [INFO] [1784867518.114754858] [llm_agent_node]: [PROGRESS] [DECISION] Thinking...
[llm_agent_node-1] [INFO] [1784867522.880420933] [llm_agent_node]: [ACTION] finishtask: Task cycle ended
[llm_agent_node-1] [INFO] [1784867522.881048600] [llm_agent_node]: [RESULT] System reset, awaiting new
instructions
[llm_agent_node-1] [INFO] [1784867522.881456002] [llm_agent_node]: [INPUT] --- Instruction #3 processed,
feedback turn <12, total time: 4.77s ---

```

5. Source Code Analysis

The key new point in this chapter is not in the new ROS action source code, but in the **Dify intent mapping knowledge base and task routing**. The ROS side still reuses the navigation, visual understanding, and feedback loop capabilities covered in Chapter 6.

Current relevant source code and configuration paths:

```

~/microros_ws/src/multi_brains/multi_brains/llm_agent_node.py
~/microros_ws/src/multi_brains/multi_brains/services/dify_coordinator.py
~/microros_ws/src/multi_brains/multi_brains/controllers/navigation_controller.py
~/microros_ws/src/multi_brains/config/llm_agent_config.yaml
~/microros_ws/src/multi_brains/config/map_mapping.yaml

```

5.1 Where the New Capability Is

"Intent inference" does not add new action functions such as `hunger()` or `thirsty()`, but adds a layer of personal semantic mapping to Dify. For example, when the user says "I'm a little thirsty", the knowledge base supplements it as "need to go to the tea room/kitchen to observe whether there is water or a drink", and then the decision layer decomposes this goal into steps such as navigation, observation, and return.

Three Dify configuration points need attention in the workflow:

- **Task routing:** classifies personal expressions such as "I'm hungry", "I'm thirsty", and "I'm a little sleepy" into the complex task branch.

- **Decision-layer sample library/knowledge retrieval node:** selects the uploaded intent mapping knowledge base so that the decision layer can retrieve the task description corresponding to personal intents.
- **Conversation variable** `map_mapping`: maps location names such as "tea room" and "office" to navigation target IDs such as `A` and `B`.

If any of these three is missing, the robot will not be able to reliably derive executable actions from "implicit intents".

5.2 Core Flow

```
User inputs "I'm currently in the office area, and I feel a little thirsty"
-> Dify task routing determines it as a complex task/intent inference
-> Knowledge retrieval node recalls the "thirsty"-related task description from
the intent mapping knowledge base
-> Decision layer generates high-level steps combined with map_mapping
-> Execution layer outputs only one action JSON per round
-> llm_agent_node.py parses the action field and distributes it through
action_registry
-> NavigationController executes get_current_pose() / navigation(target)
-> seewhat() uploads the current frame to Dify as robot feedback
-> Dify continues to the next step based on navigation or image feedback
-> finishtask() ends the current task cycle
```

The feedback loop of `llm_agent_node.py` reads the execution result and then uses "robot feedback: executing {actions} completed/failed" to continue requesting Dify. Complex tasks do not execute multiple actions at once, but instead follow "decide one round, execute one action, and after feedback, decide the next round".