

# Control Robot Forward and Backward

---

## Control Robot Forward and Backward

- 1 Experiment Objective
- 2 Experiment Preparation
- 3 Experiment Procedure
- 4 Experiment Summary

## 1 Experiment Objective

This course focuses on learning how to control the robot's forward, backward, and stop functions.

## 2 Experiment Preparation

This course involves the following functions from the Muto hexapod robot's Python library:

**forward(step):** Walk forward. `step` is the stride width. A larger effective value results in a wider stride. The value range for `step` is [10, 25].

**back(step):** Walk backward. `step` is the stride width. A larger effective value results in a wider stride. The value range for `step` is [10, 25].

**stop():** Stop movement.

**reset():** Reset the robot. The robot will stand in its initial posture.

**speed(level):** Control the robot's movement speed. The value range for `level` is [1-5]. A larger value results in a higher movement frequency.

## 3 Experiment Procedure

Open the JupyterLab client and navigate to the code path:


```
muto/Samples/Control/4.forward_back.ipynb
```

By default, `g_ENABLE_CHINESE` is `False`. If you need to display Chinese, please set `g_ENABLE_CHINESE=True`.

```
# Chinese switch. The default value is English
g_ENABLE_CHINESE = False

Name_widgets = {
    'Stop': ("Stop", "Stop"),
    'Forward': ("Forward", "Forward"),
    'Backward': ("Backward", "Backward"),
    'End': ("End", "Finish")
}
```

Click 'Run All Cells', then scroll to the bottom to see the generated controls.



Click the different buttons to perform their corresponding functions.



Each time a button is clicked, the corresponding function is executed. The button event handling is as follows:

```
# Key press event processing
def on_button_clicked(b):
    ALL_Uncheck()
    b.icon = 'check'
    with output:
        print("Button clicked:", b.description)
    if b.description == Name_widgets['Stop'][g_ENABLE_CHINESE]:
        g_bot.stop()
        b.icon = 'uncheck'
    elif b.description == Name_widgets['Forward'][g_ENABLE_CHINESE]:
        g_bot.forward(g_step)
    elif b.description == Name_widgets['Backward'][g_ENABLE_CHINESE]:
        g_bot.back(g_step)
```

The `g_step` variable is controlled by the Step slider. When the slider's value changes, it detects which button has been pressed and immediately updates the `g_step` value for the robot.

```
def on_slider_step(value):
    global g_step
    g_step = value
    if button_forward.icon == 'check':
        g_bot.forward(g_step)
    elif button_backward.icon == 'check':
        g_bot.back(g_step)
    print("step:", value)
```

The robot's movement speed is controlled by the Speed slider. When the slider's value changes, the robot's movement speed is updated immediately.

```
def on_slider_speed(value):
    global g_bot
    g_bot.speed(value)
    print("speed:", value)
```

## 4 Experiment Summary

In this experiment, JupyterLab controls are used to manage the hexapod robot's forward, backward, and stop functions. For example, set Step to 20 and Speed to 2, then click the Forward button. The hexapod robot will move forward, the Forward button will be checked, and the command pressed will be displayed below the controls. At this point, changing the values of the Step or Speed sliders will change the robot's stride width and speed.

When you need to stop, click the Stop button.



Step:  25

step: 25

Speed:  3

Forward Backward Stop End

To exit the program, press the 'End' button.