3. Remote control

3. Remote control

- 3.1. Remote Login
- 3.2. VSCode
- 3.3. Transfer files
 - 3.3.1 VM and RDK X3 board
 - 3.3.2 Windows and the RDK X3 board

[Note]

- The RDK X3 board does not provide a graphical interface (you can install it yourself if necessary), and this tutorial uses SSH to connect the car remotely.
- Because the running of some codes requires root permission, log in as the root user directly.
- The IP of the robot can be displayed via OLED.

3.1. Remote Login

Turn on the car power supply, and the car IP will be displayed on the OLED screen. For example, if the IP address of my car is 192.168.2.67, open the terminal in the virtual machine and type

ssh root@192.168.2.67

```
yahboom@yahboom-virtual-machine: ~ □  

yahboom@yahboom-virtual-machine: ~ 80x24


yahboom@yahboom-virtual-machine: ~$ ssh root@192.168.2.67

root@192.168.2.67's password:
```

The following may occur during the initial connection: Enter yes and press Enter.

```
yahboom@yahboom-virtual-machine:~$ ssh root@192.168.2.67
The authenticity of host '192.168.2.67 (192.168.2.67)' can't be established.
ECDSA key fingerprint is SHA256:3zWGqxpxy70rVY8Nt0JNL4brHK+N9W8Fxh7BQ7fPJh0.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
```


Enter the password [yahboom], press Enter, you can remotely connect to the car.




3.2. VSCode

The above operations realize the development of SSH remote connection car, and then build a visual development environment on the PC side.

Open VSCode on the VM, click "Extend" plug-in on the left, search for "ssh", and install the "Remote-SSH" plug-in.



After the installation, a Remote Explorer appears on the left.



Click the "+" Add button to the right of SSH and type

```
ssh root@192.168.2.67

Enter SSH Connection Command

ssh root@192.168.2.67

按 "Enter" 以确认或按 "Esc" 以取消
```

Then select the default profile for the first item,

```
| Select SSH configuration file to update


/home/yahboom/.ssh/config

/etc/ssh/ssh_config

Settings specify a custom configuration file

Help about SSH configuration files
```


The ssh command information you just entered will be saved, and you do not need to fill in the information the next time you log in remotely. The IP address of the new remote target is displayed in the list on the left.




If it does not appear, you can click Refresh.



Click the arrow button to connect the RDK X3 board in the current window,




Enter your password [yahboom], press Enter,



Indicates that you are connected to the remote. Click [Open folder],



Enter the working space of the car and click [OK]



That gives you remote access to the code on the car. After modification, it will be synchronized to the car end, and can be compiled and run by itself.


```
Mcnamu_driver.py - yahboomcar_ws [SSH: 192.168.2.67] - Visual Studio Code
文件 编辑 选择 杳看 转到 运行 终端 帮助
                          资源管理器
                                                                                                                    Mcnamu_driver.py ×
                     > 幊 build
                         > 🖷 config
                                                                                                                                       #public lib
from math import pi
from SunriseRobotLib import SunriseRobot
                           > ii robot_localization
                           œ
   yehboomcar_bringup

init__py
calibrate_angular.py
calibrate_linear.py

Monamu_driver.gv

init__py
calibrate_linear.py
calibrat
                                > 📹 resource
                                > 🧖 test
                                ∨ = yahboomcar_bringup
                                                                                                                                               def __init__(self, name):
    super().__init__(name)
    self.RA2DE = 180 / pi
    self.car = SunriseRobot()
                                                                                                                                                                   self.car.set_car_type(6)
self.car.create_receive_threading()
                                     🌏 patrol.py
                                      setup.cfg
                                                                                                                                                                                                                                                                                                                                                                            Remote - SSH
                                     🌏 setup.py
                              > ii yahboomcar_colortrack
                             > ii yahboomcar_ctrl
                               > 📹 vahboomcar deeplearning
                                                                                                                      [14:16:29.356] [Forwarding server 43281] Got connecti( [14:16:29.405] [Forwarding server 43281] Got connecti( (1) ROS Extension Initializing...
                    > 大纲
   £55
                     > 时间线
                                    58.2.67 ⊗ 0 △ 0 № 0
                                                                                                                                                                                                                                                                                                               行 137,列 1 制表符长度: 4 UTF-8 LF ( Python 3.8.10 64-bit
```

In addition, you can start multiple terminals to run relevant commands in VSCode with a successful connection.



3.3. Transfer files

3.3.1 VM and RDK X3 board

Suppose the RDK X3 board IP [192.168.2.67], user name [root], password [yahboom];

Virtual machine user name [yahboom].


```
scp root@192.168.2.67:/userdata/xx.py /home/yahboom # 从旭日派复制文件到虚拟机# Copy files from RDK X3 board to virtual machine scp /home/yahboom/xx.py root@192.168.2.67:/userdata # 从虚拟机复制文件到旭日派# Copy files from the virtual machine to the RDK X3 board scp -r root@192.168.2.67:/userdata/test /home/yahboom # 从旭日派复制文件夹到虚拟机# Copy the folder from the RDK X3 board to the virtual machine scp -r /home/yahboom/test root@192.168.2.67:/userdata # 从虚拟机复制文件夹到旭日派# Copy folder from virtual machine to RDK X3 board
```

3.3.2 Windows and the RDK X3 board


Open the link https://winscp.net/eng/download.php in Windows, download WinSCP and then double-click the [.exe] file to install. Double-click the icon below to open the WinSCP software



If the login dialog box does not pop up, click [New session] in the upper left, enter the host name, user name, password, and click login.



For example, the robot IP address [192.168.2.67], user name [root], and password [yahboom]. The following is an example of a successful login



- Windows->the RDK X3 board: Select the file (folder) you want to transfer and click "Upload".
- the RDK X3 board ->Windows: Select the file (folder) you want to transfer and click "Download".