

# Plugins

## Quick Start

A plugin is just a **small code module** that extends OpenClaw with additional functionality (commands, tools, and Gateway RPC). Most of the time, you'll use a plugin when you want a feature that isn't built into core OpenClaw (or you want to exclude optional features from the main installation). Quick path:

1. See what's loaded:

```
openclaw plugins list
```

2. Install an official plugin (e.g., Voice Call):

```
openclaw plugins install @openclaw/voice-call
```

3. Restart the Gateway, then configure under `plugins.entries.<id>.config`.

## Available Plugins (Official)

- As of 2026.1.15, Microsoft Teams is only available as a plugin; if using Teams, install `@openclaw/msteams`.
- Memory (Core) — Bundled memory search plugin (enabled by default via `plugins.slots.memory`)
- Memory (LanceDB) — Bundled long-term memory plugin (auto-recall/capture; set `plugins.slots.memory = "memory-lancedb"`)
- [Voice Call](#) — `@openclaw/voice-call`
- [Zalo Personal](#) — `@openclaw/zalouser`
- [Matrix](#) — `@openclaw/matrix`
- [Nostr](#) — `@openclaw/nostr`
- [Zalo](#) — `@openclaw/zalo`
- [Microsoft Teams](#) — `@openclaw/msteams`
- Google Antigravity OAuth (provider auth) — Bundled as `google-antigravity-auth` (disabled by default)
- Gemini CLI OAuth (provider auth) — Bundled as `google-gemini-cli-auth` (disabled by default)
- Qwen OAuth (provider auth) — Bundled as `qwen-portal-auth` (disabled by default)
- Copilot Proxy (provider auth) — Local VS Code Copilot Proxy bridge; different from built-in `github-copilot` device login (bundled, disabled by default)

OpenClaw plugins are **TypeScript modules** loaded at runtime via jiti. **Config validation does not execute plugin code**; it uses the plugin manifest and JSON Schema. See [Plugin Manifest](#). Plugins can register:

- Gateway RPC methods
- Gateway HTTP handlers
- Agent tools
- CLI commands
- Background services

- Optional config validation
- **Skills** (by listing `skills` directory in the plugin manifest)
- **Auto-reply commands** (execute without invoking an AI agent)

Plugins run in the **same process as the Gateway**, so treat them as trusted code. Tool writing guide: [Plugin Agent Tools](#).

## Runtime Helpers

Plugins can access selected core helpers via `api.runtime`. For phone TTS:

```
const result = await api.runtime.tts.textToSpeechTelephony({
  text: "Hello from OpenClaw",
  cfg: api.config,
});
```

Notes:

- Uses core `messages.tts` config (OpenAI or ElevenLabs).
- Returns PCM audio buffer + sample rate. Plugins must resample/encode for their provider.
- Edge TTS does not support phone.

## Discovery and Priority

OpenClaw scans in order:

1. Config path
  - `plugins.load.paths` (file or directory)
2. Workspace extensions
  - `<workspace>/openclaw/extensions/*.ts`
  - `<workspace>/openclaw/extensions/*/index.ts`
3. Global extensions
  - `~/openclaw/extensions/*.ts`
  - `~/openclaw/extensions/*/index.ts`
4. Bundled extensions (shipped with OpenClaw, **disabled by default**)
  - `<openclaw>/extensions/*`

Bundled plugins must be explicitly enabled via `plugins.entries.<id>.enabled` or `openclaw plugins enable <id>`. Installed plugins are enabled by default but can be disabled the same way. Each plugin must contain an `openclaw.plugin.json` file in its root directory. If the path points to a file, the plugin root is that file's directory, which must contain the manifest. If multiple plugins resolve to the same id, the first match in the order above wins, and lower-priority copies are ignored.

## Package Collections

A plugin directory can contain a `package.json` with `openclaw.extensions`:

```
{
  "name": "my-pack",
  "openclaw": {
    "extensions": [".src/safety.ts", ".src/tools.ts"]
  }
}
```

Each entry becomes a plugin. If the package lists multiple extensions, the plugin id becomes `name/<fileBase>`. If your plugin imports npm dependencies, install them in that directory so `node_modules` is available (`npm install` / `pnpm install`).

## Channel Directory Metadata

Channel plugins can broadcast onboarding metadata via `openclaw.channel` and install hints via `openclaw.install`. This keeps the core directory data-free. Example:

```
{
  "name": "@openclaw/nextcloud-talk",
  "openclaw": {
    "extensions": [".index.ts"],
    "channel": {
      "id": "nextcloud-talk",
      "label": "Nextcloud Talk",
      "selectionLabel": "Nextcloud Talk (self-hosted)",
      "docsPath": "/channels/nextcloud-talk",
      "docsLabel": "nextcloud-talk",
      "blurb": "Self-hosted chat via Nextcloud Talk webhook bots.",
      "order": 65,
      "aliases": ["nc-talk", "nc"]
    },
    "install": {
      "npmSpec": "@openclaw/nextcloud-talk",
      "localPath": "extensions/nextcloud-talk",
      "defaultChoice": "npm"
    }
  }
}
```

OpenClaw can also merge **external channel directories** (e.g., MPM registry exports). Place JSON files in one of:

- `~/.openclaw/mpm/plugins.json`
- `~/.openclaw/mpm/catalog.json`
- `~/.openclaw/plugins/catalog.json`

Or point `OPENCLAW_PLUGIN_CATALOG_PATHS` (or `OPENCLAW_MPM_CATALOG_PATHS`) to one or more JSON files (comma/semicolon/ `PATH` separated). Each file should contain `{ "entries": [ { "name": "@scope/pkg", "openclaw": { "channel": {...}, "install": {...} } } ] }`.

## Plugin ID

Default plugin ids:

- Package collections: `package.json` `name`
- Standalone files: file base name (`~/.../voice-call.ts` → `voice-call`)

If a plugin exports `id`, OpenClaw uses it but warns when it doesn't match the configured id.

## Configuration

```
{
  plugins: {
    enabled: true,
    allow: ["voice-call"],
    deny: ["untrusted-plugin"],
    load: { paths: ["~/Projects/oss/voice-call-extension"] },
    entries: {
      "voice-call": { enabled: true, config: { provider: "twilio" } },
    },
  },
}
```

Fields:

- `enabled`: Master switch (default: true)
- `allow`: Allow list (optional)
- `deny`: Deny list (optional; deny takes precedence)
- `load.paths`: Additional plugin files/directories
- `entries.<id>`: Per-plugin switch + config

Config changes **require a Gateway restart**. Validation rules (strict):

- Unknown plugin ids in `entries`, `allow`, `deny`, or `slots` are **errors**.
- Unknown `channels.<id>` keys are **errors** unless the plugin manifest declares the channel id.
- Plugin config is validated using JSON Schema embedded in `openclaw.plugin.json` (`configsSchema`).
- If a plugin is disabled, its config is preserved and a **warning** is issued.

## Plugin Slots (Exclusive Categories)

Some plugin categories are **exclusive** (only one active at a time). Use `plugins.slots` to select which plugin owns a slot:

```
{
  plugins: {
    slots: {
      memory: "memory-core", // or "none" to disable memory plugins
    },
  },
}
```

If multiple plugins declare `kind: "memory"`, only the selected one loads. Others are disabled with diagnostics.

## Control UI (Schema + Labels)

The control UI uses `config.schema` (JSON Schema + `uiHints`) to render better forms. OpenClaw augments `uiHints` at runtime based on discovered plugins:

- Add per-plugin labels for `plugins.entries.<id>` / `.enabled` / `.config`

- Merge optional plugin-provided config field hints at: `plugins.entries.<id>.config.<field>`

If you want plugin config fields to show good labels/placeholders (and mark keys as sensitive), provide `uiHints` and JSON Schema in the plugin manifest. Example:

```
{
  "id": "my-plugin",
  "configSchema": {
    "type": "object",
    "additionalProperties": false,
    "properties": {
      "apiKey": { "type": "string" },
      "region": { "type": "string" }
    }
  },
  "uiHints": {
    "apiKey": { "label": "API Key", "sensitive": true },
    "region": { "label": "Region", "placeholder": "us-east-1" }
  }
}
```

## CLI

```
openclaw plugins list
openclaw plugins info <id>
openclaw plugins install <path> # copy a local file/dir into
~/.openclaw/extensions/<id>
openclaw plugins install ./extensions/voice-call # relative path ok
openclaw plugins install ./plugin.tgz # install from a local tarball
openclaw plugins install ./plugin.zip # install from a local zip
openclaw plugins install -l ./extensions/voice-call # link (no copy) for dev
openclaw plugins install @openclaw/voice-call # install from npm
openclaw plugins update <id>
openclaw plugins update --all
openclaw plugins enable <id>
openclaw plugins disable <id>
openclaw plugins doctor
```

`plugins update` only works for npm installations tracked under `plugins.installs`. Plugins can also register their own top-level commands (e.g., `openclaw voicecall`).

## Plugin API (Overview)

Plugins export one of:

- Function: `(api) => { ... }`
- Object: `{ id, name, configSchema, register(api) { ... } }`

## Plugin Hooks

Plugins can bundle hooks and register them at runtime. This lets plugins bundle event-driven automation without a separate hook package.

## Example

```
import { registerPluginHooksFromDir } from "openclaw/plugin-sdk";

export default function register(api) {
  registerPluginHooksFromDir(api, "./hooks");
}
```

Notes:

- Hooks directory follows normal hook structure (`HOOK.md` + `handler.ts`).
- Hook eligibility rules still apply (OS/binary/env/config requirements).
- Plugin-managed hooks show as `plugin:<id>` in `openclaw hooks list`.
- You cannot enable/disable plugin-managed hooks via `openclaw hooks`; enable/disable the plugin instead.

## Provider Plugins (Model Auth)

Plugins can register **model provider auth flows** so users can run OAuth or API key setup inside OpenClaw (no external scripts). Register providers via `api.registerProvider(...)`. Each provider exposes one or more auth methods (OAuth, API key, device code, etc.). These methods drive:

- `openclaw models auth login --provider <id> [--method <id>]`

Example:

```
api.registerProvider({
  id: "acme",
  label: "AcmeAI",
  auth: [
    {
      id: "oauth",
      label: "OAuth",
      kind: "oauth",
      run: async (ctx) => {
        // Run OAuth flow and return auth profiles.
        return {
          profiles: [
            {
              profileId: "acme:default",
              credential: {
                type: "oauth",
                provider: "acme",
                access: "...",
                refresh: "...",
                expires: Date.now() + 3600 * 1000,
              },
            },
          ],
          defaultModel: "acme/opus-1",
        };
      },
    },
  ],
});
```

Notes:

- `run` receives a `ProviderAuthContext` with `prompter`, `runtime`, `openUrl`, and `oauth.createVpsAwareHandlers` helpers.
- Return `configPatch` when you need to add default models or provider config.
- Return `defaultModel` so `--set-default` can update agent defaults.

## Registering Messaging Channels

Plugins can register **channel plugins**, which behave like built-in channels (WhatsApp, Telegram, etc.). Channel config lives under `channels.<id>`, validated by your channel plugin code.

```
const myChannel = {
  id: "acmechat",
  meta: {
    id: "acmechat",
    label: "AcmeChat",
    selectionLabel: "AcmeChat (API)",
    docsPath: "/channels/acmechat",
    blurb: "demo channel plugin.",
    aliases: ["acme"],
  },
  capabilities: { chatTypes: ["direct"] },
  config: {
    listAccountIds: (cfg) => Object.keys(cfg.channels?.acmechat?.accounts ?? {}),
    resolveAccount: (cfg, accountId) =>
      cfg.channels?.acmechat?.accounts?.[accountId ?? "default"] ?? {
        accountId,
      },
  },
  outbound: {
    deliveryMode: "direct",
    sendText: async () => ({ ok: true }),
  },
};

export default function (api) {
  api.registerChannel({ plugin: myChannel });
}
```

Notes:

- Put config under `channels.<id>` (not `plugins.entries`).
- `meta.label` is used for labels in CLI/UI lists.
- `meta.aliases` adds alternate ids for normalization and CLI input.
- `meta.preferOver` lists channel ids to skip when both are configured for auto-enable.
- `meta.detailLabel` and `meta.systemImage` let the UI show richer channel labels/icons.

# Writing a New Messaging Channel (Step-by-Step)

Use this when you want a **new chat interface** ("messaging channel") rather than a model provider. Model provider docs are under `/providers/*`.

## 1. Choose id + config structure

- All channel config lives under `channels.<id>`.
- For multi-account setups, prefer `channels.<id>.accounts.<accountId>`.

## 2. Define channel metadata

- `meta.label`, `meta.selectionLabel`, `meta.docsPath`, `meta.blurb` control CLI/UI lists.
- `meta.docsPath` should point to a docs page like `/channels/<id>`.
- `meta.preferOver` lets the plugin replace another channel (auto-enable prefers it).
- `meta.detailLabel` and `meta.systemImage` are used by the UI for detail text/icons.

## 3. Implement required adapters

- `config.listAccountIds` + `config.resolveAccount`
- `capabilities` (chat types, media, threads, etc.)
- `outbound.deliveryMode` + `outbound.sendText` (for basic send)

## 4. Add optional adapters as needed

- `setup` (wizard), `security` (DM policy), `status` (health/diagnostics)
- `gateway` (start/stop/login), `mentions`, `threading`, `streaming`
- `actions` (message operations), `commands` (native command behavior)

## 5. Register the channel in the plugin

- `api.registerChannel({ plugin })`

Minimal config example:

```
{
  channels: {
    acmechat: {
      accounts: {
        default: { token: "ACME_TOKEN", enabled: true },
      },
    },
  },
}
```

Minimal channel plugin (outbound only):

```
const plugin = {
  id: "acmechat",
  meta: {
    id: "acmechat",
    label: "AcmeChat",
    selectionLabel: "AcmeChat (API)",
    docsPath: "/channels/acmechat",
    blurb: "AcmeChat messaging channel.",
    aliases: ["acme"],
  },
  capabilities: { chatTypes: ["direct"] },
}
```



```

config: {
  listAccountIds: (cfg) => Object.keys(cfg.channels?.acmechat?.accounts ?? {}),
  resolveAccount: (cfg, accountId) =>
    cfg.channels?.acmechat?.accounts?.[accountId ?? "default"] ?? {
      accountId,
    },
},
outbound: {
  deliveryMode: "direct",
  sendText: async ({ text }) => {
    // deliver `text` to your channel here
    return { ok: true };
  },
},
};

export default function (api) {
  api.registerChannel({ plugin });
}

```

Load the plugin (extension directory or `plugins.load.paths`), restart the Gateway, then configure `channels.<id>` in your config.

## Agent Tools

See the dedicated guide: [Plugin Agent Tools](#).

## Register Gateway RPC Methods

```

export default function (api) {
  api.registerGatewayMethod("myplugin.status", ({ respond }) => {
    respond(true, { ok: true });
  });
}

```

## Register CLI Commands

```

export default function (api) {
  api.registerCli(
    ({ program }) => {
      program.command("mycmd").action(() => {
        console.log("Hello");
      });
    },
    { commands: ["mycmd"] },
  );
}

```

# Register Auto-Reply Commands

Plugins can register custom slash commands that **execute without invoking an AI agent**. This is useful for toggle commands, status checks, or quick operations that don't need LLM processing.

```
export default function (api) {
  api.registerCommand({
    name: "mystatus",
    description: "Show plugin status",
    handler: (ctx) => ({
      text: `Plugin is running! Channel: ${ctx.channel}`,
    }),
  });
}
```

Command handler context:

- `senderId`: Sender's ID (if available)
- `channel`: Channel the command was sent on
- `isAuthorizedSender`: Whether the sender is an authorized user
- `args`: Arguments passed after the command (if `acceptsArgs: true`)
- `commandBody`: Full command text
- `config`: Current OpenClaw config

Command options:

- `name`: Command name (without leading `/`)
- `description`: Help text shown in command list
- `acceptsArgs`: Whether the command accepts arguments (default: false). If false and arguments are provided, the command won't match and the message goes to other handlers
- `requireAuth`: Whether authorized sender is required (default: true)
- `handler`: Function that returns `{ text: string }` (can be async)

Example with auth and args:

```
api.registerCommand({
  name: "setmode",
  description: "Set plugin mode",
  acceptsArgs: true,
  requireAuth: true,
  handler: async (ctx) => {
    const mode = ctx.args?.trim() || "default";
    await saveMode(mode);
    return { text: `Mode set to: ${mode}` };
  },
});
```

Notes:

- Plugin commands are processed before built-in commands and AI agents
- Commands are registered globally, applying to all channels
- Command names are case-insensitive (`/MyStatus` matches `/mystatus`)
- Command names must start with a letter and can only contain letters, numbers, hyphens, and underscores

- Reserved command names (like `help`, `status`, `reset`, etc.) cannot be overridden by plugins
- Duplicate command registration across plugins fails with diagnostic error

## Register Background Services

```
export default function (api) {
  api.registerService({
    id: "my-service",
    start: () => api.logger.info("ready"),
    stop: () => api.logger.info("bye"),
  });
}
```

## Naming Conventions

- Gateway methods: `pluginId.action` (e.g., `voicecall.status`)
- Tools: `snake_case` (e.g., `voice_call`)
- CLI commands: kebab or camel, but avoid conflicts with core commands

## Skills

Plugins can bundle Skills in the repo ( `skills/<name>/SKILL.md` ). Enable via `plugins.entries.<id>.enabled` (or other config gating), and ensure it exists in your workspace/hosted Skills location.

## Distribution (npm)

Recommended packaging:

- Main package: `openclaw` (this repo)
- Plugins: Standalone npm packages under `@openclaw/*` (e.g., `@openclaw/voice-call`)

Publish contract:

- Plugin `package.json` must contain `openclaw.extensions` with one or more entry files.
- Entry files can be `.js` or `.ts` (jiti loads TS at runtime).
- `openclaw plugins install <npm-spec>` uses `npm pack`, extracts to `~/~/.openclaw/extensions/<id>/`, and enables it in config.
- Config key stability: Scoped packages are normalized to **unscoped** ids in `plugins.entries.*`.

## Example Plugin: Voice Call

This repo includes a voice call plugin (Twilio or log fallback):

- Source: `extensions/voice-call`
- Skills: `skills/voice-call`
- CLI: `openclaw voicecall start|status`
- Tools: `voice_call`
- RPC: `voicecall.start`, `voicecall.status`
- Config (twilio): `provider: "twilio"` + `twilio.accountsId/authToken/from` (optional `statusCallbackUrl`, `twimlUrl`)
- Config (dev): `provider: "log"` (no network)

See [Voice Call](#) and `extensions/voice-call/README.md` for setup and usage.

## Security Notes

---

Plugins run in the same process as the Gateway. Treat them as trusted code:

- Only install plugins you trust.
- Prefer allow lists via `plugins.allow`.
- Restart the Gateway after changes.

## Testing Plugins

---

Plugins can (and should) bundle tests:

- In-repo plugins can keep Vitest tests under `src/**` (e.g., `src/plugins/voice-call/plugin.test.ts`).
- Individually released plugins should run their own CI (lint/build/test) and verify `openclaw.extensions` points to the built entry point (`dist/index.js`).

For more about plugins, see: [Plugins - OpenClaw](#)