Scene Design and Attached Object Obstacle Avoidance

Preface: On the Raspberry Pi 5 and Jetson-nano, ROS runs in Docker, so the MoveIt2 experience is limited; it is recommended that Raspberry Pi 5 and Jetson-nano users run MoveIt2-related cases on a virtual machine. On the Orin board, ROS runs directly on the board, so Orin board users can run MoveIt2-related cases directly on the board, using the same commands as running on a virtual machine. This section will use running on a virtual machine as the example for demonstration.

1. Content Description

In industrial automated assembly and warehouse sorting scenarios, after the robot arm grasps a workpiece, the workpiece becomes part of the robot arm itself (Attached Collision Object). If the planner does not consider the volume of the workpiece itself, the workpiece is very likely to collide with and damage the shelf layers when the robot arm feeds it into a narrow shelf or workstation.

This course introduces how to import a complex 3D static shelf scene in MoveIt2, and dynamically attach a cylindrical workpiece to the robot arm's gripper in the program. MoveIt2 will bind this workpiece to the end link in real time, and in the subsequent multi-layer shelf shuttling motion planning, incorporate the workpiece's collision geometry into the global obstacle avoidance computation, safely and smoothly completing the simulated workpiece placement task.

---


2. Launch and Operation Steps

2.1 Launching the MoveIt2 Simulation Environment

Enter the following command in the terminal to launch the MoveIt2 simulation environment:

```
ros2 launch dofbot_pro_moveit demo_3d.launch.py
```

Once the program starts, when **You can start planning now!** is output in the terminal, it means the MoveIt2 simulation environment was launched successfully, as shown in the figure below:



2.2 Starting Real-Machine Linkage (Optional)

If you want the simulation actions to synchronously control the real physical robot arm, open another terminal and run the hardware control conversion node:

```
ros2 run movelt_demo SimulationToMachine
```

(It is recommended not to start this node during the initial test. First verify that the obstacle-avoidance trajectory is correct in the pure RViz simulation environment before connecting to the real machine).


2.3 Running the Workpiece Attachment and Shuttling Planning Program

In another terminal, enter the following command to run the scene planning program:

```
ros2 run movelt_demo set_scene
```

After the program runs:

1. The node first dynamically generates and attaches a purple cylindrical workpiece (`cylinder1`) at the position of the robot arm's end-effector gripper (`Gripping`);
2. Carrying the cylindrical workpiece, the robot arm first smoothly plans and moves to the `init` preparation pose;
3. Then tilts downward to the `down` pose;
4. Next, MoveIt computes a fine trajectory that avoids colliding with the shelf partitions, guiding the robot arm's end effector to precisely feed the cylinder into the middle layer of the shelf, simulating a smooth placement action, as shown in the figure below:



3. Core Code Analysis

Program source code path:
`~/yahboomcar_ros2_ws/dofbot_pro_ws/src/moveIt_demo/moveIt_demo/set_scene.py`

3.1 Node Initialization and Interface Definition

The program is natively written in ROS 2 Python. The class `SetScene` initializes the action execution client, the scene publisher, and the motion planning service client:

```
import time
import rclpy
from rclpy.node import Node
from rclpy.action import ActionClient
from control_msgs.action import FollowJointTrajectory
from geometry_msgs.msg import Pose
from moveit_msgs.msg import (
    PlanningScene,
    CollisionObject,
    AttachedCollisionObject,
    Constraints,
    JointConstraint,
)
from moveit_msgs.srv import GetMotionPlan
from shape_msgs.msg import SolidPrimitive

class SetScene(Node):
    def __init__(self):
        super().__init__('set_scene_node')
```

```
        self.get_logger().info("Initializing SetScene node...")

        # 1. Trajectory execution Action client
        self._action_client = ActionClient(
            self,
            FollowJointTrajectory,
            '/arm_group_controller/follow_joint_trajectory'
        )

        # 2. Planning scene publisher (used to inject/attach obstacles into the
environment)
        self._planning_scene_pub = self.create_publisher(PlanningScene,
'/planning_scene', 10)

        # 3. Motion planning service client
        self._plan_client = self.create_client(GetMotionPlan,
'/plan_kinematic_path')

        # 4. The 5 joint names of the robot arm
        self.joint_names = [
            "arm1_Joint", "arm2_Joint", "arm3_Joint",
            "arm4_Joint", "arm5_Joint"
        ]

        # 5. Preset named target poses (in radians)
        self.named_states = {
            "up":   [0.0,  0.0,      0.0,     0.0,     0.0],
            "down": [0.0, -1.5708,   0.0,     0.0,     0.0],
            "init": [0.0,  1.5708,  -1.5708, -1.5708,  0.0],
        }
```

3.2 Dynamic Workpiece Creation and Attachment (add_and_attach_cylinder)

How does MoveIt know that the robot arm is "holding an object"?
The program achieves this through `AttachedCollisionObject`:

- Creates a `CollisionObject` cylinder 3 cm high with a radius of 2 cm;
- Specifies its attachment carrier as the end link `link_name = "Gripping"`;
- Configures `touch_links = ["llink2", "rlink2"]`, telling the collision detection engine that physical contact between the left and right gripper fingers and the workpiece is allowed without reporting errors;
- Adds it to `scene.robot_state.attached_collision_objects` and publishes it to `/planning_scene`.

```
    def add_and_attach_cylinder(self):
        """Create a cylindrical obstacle and attach it to the Gripping link at
the end of the robot arm"""
        scene = PlanningScene()
        scene.is_diff = True

        # 1. Define the workpiece geometric collision body (a cylinder 0.03m
high with a radius of 0.02m)
        collision_object = CollisionObject()
        collision_object.header.frame_id = "Gripping"
        collision_object.header.stamp = self.get_clock().now().to_msg()
```

```
        collision_object.id = "cylinder1"

        cylinder = SolidPrimitive()
        cylinder.type = SolidPrimitive.CYLINDER
        cylinder.dimensions = [0.03, 0.02]  # [height, radius]

        grab_pose = Pose()
        grab_pose.orientation.w = 1.0
        grab_pose.position.z = 0.00
        grab_pose.position.x = 0.00

        collision_object.primitives.append(cylinder)
        collision_object.primitive_poses.append(grab_pose)
        collision_object.operation = CollisionObject.ADD

        # 2. Construct an AttachedCollisionObject bound to the Gripping link
        attached_object = AttachedCollisionObject()
        attached_object.link_name = "Gripping"
        attached_object.object = collision_object
        attached_object.touch_links = ["llink2", "rlink2"]  # Two gripper links
allowed to make contact

        scene.robot_state.attached_collision_objects.append(attached_object)
        scene.robot_state.is_diff = True

        # Publish the scene change
        self._planning_scene_pub.publish(scene)
        time.sleep(1.0)
        self.get_logger().info("The cylindrical workpiece has been successfully
attached to the end of the robot arm!")
```

3.3 Collision-Free Planning Considering the Workpiece Geometry (plan_to_joints)

After attaching the workpiece, when `/plan_kinematic_path` is called, MoveIt automatically treats `cylinder1` as a rigid extension at the frontmost part of the robot arm for collision detection, ensuring that the workpiece does not scrape against the upper and lower partitions when entering the shelf layers:

```
    def plan_to_joints(self, target_joints, current_joints):
        """Send a joint-space trajectory planning request with attached-object
obstacle avoidance to MoveIt"""
        request = GetMotionPlan.Request()
        req = request.motion_plan_request
        req.group_name = "arm_group"

        req.start_state.joint_state.name = self.joint_names
        req.start_state.joint_state.position = list(current_joints)

        constraints = Constraints()
        for i, name in enumerate(self.joint_names):
            jc = JointConstraint()
            jc.joint_name = name
            jc.position = target_joints[i]
            jc.tolerance_above = 0.01
            jc.tolerance_below = 0.01
```

```
            jc.weight = 1.0
            constraints.joint_constraints.append(jc)
        req.goal_constraints.append(constraints)

        req.num_planning_attempts = 10
        req.allowed_planning_time = 5.0

        future = self._plan_client.call_async(request)
        rclpy.spin_until_future_complete(self, future)
        response = future.result()

        if response.motion_plan_response.error_code.val == 1:
            return response.motion_plan_response.trajectory
        return None
```

3.4 Continuous Multi-Station Pick-and-Place Simulation (run Method)

In the main execution logic, first attach the workpiece, then sequentially execute the preparation pose, the head-down transition pose, and the precise target pose inside the shelf, implementing the full-flow collision-free trajectory planning and action playback:

```
    def run(self):
        # 1. Attach the cylindrical workpiece
        self.add_and_attach_cylinder()

        current_joints = self.named_states["up"]

        # 2. Move to the init preparation pose
        target = self.named_states["init"]
        if self.plan_and_execute(target, current_joints, name="init"):
            current_joints = target

        # 3. Move to the down transition pose
        target = self.named_states["down"]
        if self.plan_and_execute(target, current_joints, name="down"):
            current_joints = target

        # 4. Move to the target placement angle inside the shelf layer
        target = [0.0, -1.57, -0.875, 0.60, 0.0]
        if self.plan_and_execute(target, current_joints, name="custom"):
            current_joints = target

        self.get_logger().info("All attached-object obstacle-avoidance placement
actions in the multi-layer shelf are complete!")
```