OpenClaw API-KEY Configuration

OpenClaw API-KEY Configuration

1. Course Content
2. API-KEY Application
    2.1 Recommended Model Service Providers
3. Configure OpenClaw API-KEY
    3.1 Configuration Methods
    3.2 Quick Configuration
        3.2.1 Configure baseurl
        3.2.2 Fill in apiKey and baseUrl
4. View Connected Model Status
    4.1 View Configured Model List
    4.2 Verify Configuration Success
5. Other Connection Methods
    5.1 CLI Command Configuration (Suitable for Beginners)
    5.2 Modify Configuration File (Recommended Method)
        Configuration File Location
        Edit Configuration File
6. Common Problems and Solutions

1. Course Content

This course will provide a detailed introduction to configuring AI model API-KEYs for OpenClaw, including the API-KEY application process, two configuration methods (CLI command configuration and configuration file modification), and how to verify successful configuration. After completing this course, you will be able to successfully connect and use various AI model service providers.

Course Objectives

- Understand the types of model service providers supported by OpenClaw
- Master the method for applying for API-KEY
- Learn how to view and verify the status of connected models

2. API-KEY Application

2.1 Recommended Model Service Providers

- Refer to the accompanying tutorial [AI Large Model Development] — [Register Model Service Account] for API-KEY application reference
- OpenClaw supports many model service providers, for example:
    - **OpenAI**
    - **Alibaba Cloud** - Tongyi Qianwen
    - **DeepSeek**
    - **Zhipu AI**
    - **Moonshot**

- You can freely choose a model service provider based on the network policies of your country and region, and register and apply for an API-KEY on the corresponding official website

3. Configure OpenClaw API-KEY

3.1 Configuration Methods

OpenClaw provides two methods for configuring API-KEY:

1. **Desktop App Configuration (Recommended)**
2. **Direct Configuration File Modification** (Suitable for developers)
3. Configuration file path: `$HOME/.openclaw/openclaw.json`

3.2 Quick Configuration


> **Note**
>
> - The factory-preset **openclaw.json** configuration file has built-in Alibaba Cloud Bailian platform's baseurl and commonly used models for quick configuration


- Suitable for quick hands-on experience, first register for an Alibaba Cloud Bailian large model account and create an API-KEY (refer to the accompanying tutorial [AI Large Model Development] — [Register Model Service Account])
- The factory preset configuration file has already configured Bailian model parameters, just fill in the API-KEY and baseUrl to use directly
- Open the OpenClaw configuration file:

```
nano $HOME/.openclaw/openclaw.json
```

3.2.1 Configure baseurl

- Users need to configure the baseUrl corresponding to their own account. Go to the Alibaba Cloud Model Studio Console, apply for API key, copy the API key and OpenAI-compatible address (Base URL), and fill in the corresponding positions.


Alibaba Cloud Model Studio
Model
Documentation
CLI
Default Workspace
China North 2 (Beijing)
English
API Management
API Key
API Key
1. API Key Encrypted Storage:A new API Key is only displayed once after creation for copying or downloading. The platform uses irreversible encryption for storage, and the plaintext cannot be viewed again in the console. Existing API Keys will continue to work normally without any impact.
2. workspace Dedicated Domain:The platform provides each workspace with an independent inference API domain, offering higher concurrency capacity and network isolation to ensure stable, low-latency access in high-traffic scenarios.
3. Token Plan: A dedicated Base URL + API Key is required to take effect. Get it now >
OpenAI compatible
Anthropic
/apps/anthropic
No API Key
To call foundation models or applications, please apply for an API Key
1 Create API Key
Click the Create API Key button to create one immediately, then copy it (please be careful not to leak it)
2 View Documentation
Click API Reference at the top of the page to view detailed API documentation
3 Get Started
Use models and applications on the Model Studio platform with your API Key based on the documentation
Create API Key


API Quick Access
Once you leave this dialog, you will not be able to retrieve the key.
Copy or download your API key immediately. Keep it safe. Anyone who obtains this key can make service requests on your behalf and incur charges. If lost, you can reset or create a new key.
API Key
Copy
Base Url
API Host
OpenAI Compatible Endpoint
DashScope
Download
Close


3.2.2 Fill in apiKey and baseUrl

- **Method 1: Open Desktop App Configuration**


Double-click the desktop icon:




Find AI Large Models and Agents, fill in apiKey and baseUrl. The two positions can be the same. Visual large models can also separately fill in other OpenAI protocol-compatible visual models.



Click Save and Sync Configuration, then exit.



- **Method 2: Find the corresponding field and replace baseurl and apiKey fields**
  - Path: $HOME/.openclaw/openclaw.json



After filling in, press `Ctrl+X`, then press `Y` to confirm saving, and press Enter to exit.

4. View Connected Model Status

4.1 View Configured Model List

After configuration, you can use the following command to view the connected models:

```
openclaw models list
```

```
jetson@yahboom:~/yahboomcar_ros2_ws/dofbot_pro_ws$ openclaw models list

🦞 OpenClaw 2026.3.13 (61d171a) — Ah, the fruit tree company! 🍑

20:16:21 [plugins] reply-bridge: Plugin registered (hooks: before_message_write, message_sending)
20:16:21 [plugins] robot_control: Registered all robot control tools
20:16:26 [plugins] feishu_chat: Registered feishu_chat, feishu_chat_members
20:16:26 [plugins] feishu_im: Registered feishu_im_user_message, feishu_im_user_fetch_resource, feishu_im_user_get_messages, feishu_im_user_get_thread_messages, feishu
im_user_search_messages
20:16:26 [plugins] feishu_search: Registered feishu_search_doc_wiki
20:16:26 [plugins] feishu_drive: Registered feishu_drive_file, feishu_doc_comments, feishu_doc_media
20:16:26 [plugins] feishu_wiki: Registered feishu_wiki_space, feishu_wiki_space_node
20:16:26 [plugins] feishu_sheets: Registered feishu_sheet
20:16:26 [plugins] feishu_im: Registered feishu_im_bot_image
20:16:26 [plugins] Registered all OAPI tools (calendar, task, bitable, search, drive, wiki, sheets, im)
20:16:26 [plugins] feishu_doc: Registered feishu_fetch_doc, feishu_create_doc, feishu_update_doc
20:16:26 [plugins] feishu_oauth: Registered feishu_oauth tool
20:16:26 [plugins] feishu_oauth_batch_auth: Registered feishu_oauth_batch_auth tool
20:16:26 [plugins] robot-control: SeeWhat channels loaded: [feishu]
Model                                      Input      Ctx      Local Auth  Tags
bailian/qwen3.8-max                        text+image 977k     no    yes   default,configured
bailian/qwen3.7-plus                       text+image 256k     no    yes   configured
bailian/MiniMax-M2.5                       text       192k     no    yes   configured
bailian/glm-5.2                            text       198k     no    yes   configured
bailian/glm-5.1                            text       198k     no    yes   configured
bailian/kimi-k2.6                          text+image 256k     no    yes   configured
jetson@yahboom:~/yahboomcar_ros2_ws/dofbot_pro_ws$
```

4.2 Verify Configuration Success

1. **Test Conversation**

   ```
   openclaw tui
   ```

   Start the TUI interface, send a test message (such as "Hello"), and confirm the model can respond normally.

```
hello


<tts>Hello! Xiaoya here, ready to help.</tts>

Hello! 🤖 Xiaoya here, fully charged and ready to go. What would you like me to do today?
connected | idle
agent main | session main (openclaw-tui) | bailian/qwen3.8-max | tokens 16k/1.0m (2%)

```

5. Other Connection Methods


- If you have your own model provider or need to connect to other model providers later, refer to the following tutorials

5.1 CLI Command Configuration (Suitable for Beginners)


1. **Start Configuration Wizard**

   ```
   openclaw onboard
   ```


- Select [Yes] and press Enter



- Select configuration mode as QuickStart and press Enter



2. **Select Model Service Provider**
    - Use up and down arrows to select the service provider for which you have applied for an API-KEY, press Enter to confirm. Here we take Alibaba Cloud Bailian model provider as an example. The configuration method for other model providers is the same.
    - Here select custom provider **[Custom Provider]**




- Fill in the base_url of the model service provider




3. Enter API-KEY


- After selecting a service provider, the system will prompt you to enter the corresponding API-KEY




- Paste or enter your applied API-KEY and press Enter to confirm




- Select interface protocol as **OpenAI-compatible**




4. Fill in the model name. Here we take MiniMax as an example.



- **Endpoint ID** is the model provider identifier, you can fill in freely




- Model alias (optional) can be left empty




5. **Other Configuration**


- For other configuration items, press as shown in the figure below to select all Skip, no configuration needed








- Press space to select **Skip for now** for Enable Hooks



- Select Restart to restart the gateway and apply the configuration



5.2 Modify Configuration File (Recommended Method)

Configuration File Location

- The configuration file is located at: `$HOME/.openclaw/openclaw.json`

Edit Configuration File

```
nano $HOME/.openclaw/openclaw.json
# Or use your favorite editor, such as vim, code, etc. It is recommended to modify through IDEs like vscode for easier operation
```

1. **Add Model Provider Configuration**

Add or modify the `models.providers` section in the configuration file. Refer to the format below. You can refer to the factory default **bailian** provider's configuration format:

```
{
  "models": {
    "providers": {
      "openai": {
        "apiKey": "OPENAI_API_KEY"
      },
      "anthropic": {
        "apiKey": "ANTHROPIC_API_KEY"
      },
      "google": {
        "apiKey": "GOOGLE_API_KEY"
      }
    }
  },
  "agents": {
    "defaults": {
      "model": {
        "primary": "openai/gpt-4"
      }
    }
  }
}
```

3. **Save and Exit**
    - Press `Ctrl+O` to save, `Ctrl+X` to exit (nano editor)
4. **Factory Default Bailian Configuration (Can be directly modified or referenced)**

```
"bailian": {
  "baseUrl": "https://dashscope.aliyuncs.com/compatible-mode/v1",
  "apiKey": "sk-a87e1137b17b4a35af13aaxxxxxxx",
  "api": "openai-completions",
  "models": [
    {
      "id": "qwen3.5-plus",
      "name": "qwen3.5-plus",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text",
        "image"
      ],
      "cost": {
        "input": 0,
        "output": 0,
        "cacheRead": 0,
        "cacheWrite": 0
      },
```

```
      "contextWindow": 1000000,
      "maxTokens": 65536
    },
    {
      "id": "qwen3.6-plus",
      "name": "qwen3.6-plus",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text",
        "image"
      ],
      "cost": {
        "input": 0,
        "output": 0,
        "cacheRead": 0,
        "cacheWrite": 0
      },
      "contextWindow": 1000000,
      "maxTokens": 65536
    },
    {
      "id": "qwen3-coder-next",
      "name": "qwen3-coder-next",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text"
      ],
      "cost": {
        "input": 0,
        "output": 0,
        "cacheRead": 0,
        "cacheWrite": 0
      },
      "contextWindow": 262144,
      "maxTokens": 65536
    },
    {
      "id": "MiniMax-M2.5",
      "name": "MiniMax-M2.5",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text"
      ],
      "cost": {
        "input": 0,
        "output": 0,
        "cacheRead": 0,
        "cacheWrite": 0
      },
      "contextWindow": 196608,
```

```
      "maxTokens": 32768
    },
    {
      "id": "glm-5",
      "name": "glm-5",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text"
      ],
      "cost": {
        "input": 0,
        "output": 0,
        "cacheRead": 0,
        "cacheWrite": 0
      },
      "contextWindow": 202752,
      "maxTokens": 16384,
      "compat": {
        "thinkingFormat": "qwen"
      }
    },
    {
      "id": "glm-4.7",
      "name": "glm-4.7",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text"
      ],
      "cost": {
        "input": 0,
        "output": 0,
        "cacheRead": 0,
        "cacheWrite": 0
      },
      "contextWindow": 202752,
      "maxTokens": 16384,
      "compat": {
        "thinkingFormat": "qwen"
      }
    },
    {
      "id": "kimi-k2.5",
      "name": "kimi-k2.5",
      "api": "openai-completions",
      "reasoning": false,
      "input": [
        "text",
        "image"
      ],
      "cost": {
        "input": 0,
```

```
          "output": 0,
          "cacheRead": 0,
          "cacheWrite": 0
        },
        "contextWindow": 262144,
        "maxTokens": 32768,
        "compat": {
          "thinkingFormat": "qwen"
        }
      }
    ]
  }
```

6. Common Problems and Solutions

Problem: After configuration, it prompts API-KEY is invalid or authentication failed

1. Confirm the API-KEY is correct (note there should be no extra spaces)
2. Check if the API-KEY has expired or been disabled
3. Confirm if the account balance is sufficient (some service providers require prepaid balance)

Problem: Configuration is correct but cannot connect to the model service

1. Check if the network connection is normal
2. Confirm if the network in your country/region can access the service
3. Try switching to another model service provider for testing