Fingertip Trajectory Recognition

Fingertip Trajectory Recognition
1. Course Content
2. Preparation
3. Case Demonstration
4. Core Source Code Analysis

1. Course Content


This lesson implements acquiring the color image and using the mediapipe framework to detect fingertips, starting and stopping the recording of the fingertip's trajectory in the image through gestures. After recording ends, a trajectory image of the fingertip is generated and the trajectory is recognized.

2. Preparation


```
ros2 launch yahboomcar_bringup mediapipe_demo.launch.py demo:=FingerTrajectory
```

3. Case Demonstration


After the program runs, as shown in the figure below, place the palm flat in the camera view with the fingers spread and the palm facing the camera, similar to the number 5 gesture. The image will draw the joints of the entire palm. Adjust the position of the palm so that it is as close as possible to the upper-middle part of the screen.




At this point, keep the index finger still and retract the other fingers, similar to the number 1 gesture.




While keeping the gesture 1 pose unchanged, move the position of the finger. A red line appears on the screen, drawing the path of the index finger's movement.



After the figure is drawn, open all fingers, similar to the number 5 gesture, and the drawn figure will be generated below.





Note: The drawn figure needs to be closed, otherwise part of the content may be missing.

There are currently four recognizable trajectory figures: triangle, rectangle, circle, and five-pointed star.

4. Core Source Code Analysis

Program code path:

```
~/yahboomcar_ros2_ws/yahboomcar_ws/src/common_demo/common_demo/mediapipe/11_FingerTrajectory.py
```

Import the required library files,

```
import math
import time
import cv2 as cv
import numpy as np
import mediapipe as mp
import rclpy
```

```
from rclpy.node import Node
from cv_bridge import CvBridge
from sensor_msgs.msg import Image
from arm_msgs.msg import ArmJoints,ArmJoint
import cv2
import gc
import threading
import enum
```

Initialize the data and define the Publisher and Subscriber,

```
def __init__(self,name):
    super().__init__(name)
    self.drawing = mp.solutions.drawing_utils
    self.timer = time.time()
    self.move_state = False
    self.state = State.NULL
    self.points = []
    self.start_count = 0
    self.no_finger_timestamp = time.time()
    self.gc_stamp = time.time()
    self.hand_detector = mp.solutions.hands.Hands(
        static_image_mode=False,
        max_num_hands=1,
        min_tracking_confidence=0.05,
        min_detection_confidence=0.6
    )
    self.rgb_bridge = CvBridge()
    #Define the topic for controlling the 6 servos and publish the detected pose
    self.TargetAngle_pub = self.create_publisher(ArmJoints, "arm6_joints", 10)
    self.init_joints = [90, 164, 18, 0, 90, 30]
    self.pubSix_Arm(self.init_joints)
    #Define the Subscriber for the color image topic
    self.sub_rgb =
self.create_subscription(Image,"/camera/color/image_raw",self.get_RGBImageCallBac
k,100)
```

Color image callback function,

```
def get_RGBImageCallBack(self,msg):
    rgb_image = self.rgb_bridge.imgmsg_to_cv2(msg, "bgr8")
    rgb_image = cv2.flip(rgb_image, 1) # Horizontal flip
    result_image = np.copy(rgb_image)
    if self.timer <= time.time() and self.state == State.RUNNING:
        self.state = State.NULL
    try:
        #Call the process function to detect the palm
        results = self.hand_detector.process(rgb_image) if self.state !=
State.RUNNING else None
        #Determine whether a palm is detected; if results is not 0, it means a
palm has been detected
        if results is not None and results.multi_hand_landmarks:
            gesture = "none"
            index_finger_tip = [0, 0]
```

```
            # Record the current time for timeout handling
            self.no_finger_timestamp = time.time()
            #Iterate through the detection results
            for hand_landmarks in results.multi_hand_landmarks:
                self.drawing.draw_landmarks(
                    result_image,
                    hand_landmarks,
                    mp.solutions.hands.HAND_CONNECTIONS)
                landmarks = get_hand_landmarks(rgb_image,
hand_landmarks.landmark)
                #Call hand_angle to calculate the bending angle of each finger
                angle_list = (hand_angle(landmarks))
                #Call the h_gesture function to determine the gesture made by the
fingers
                gesture = (h_gesture(angle_list))
                index_finger_tip = landmarks[8].tolist()

            if self.state == State.NULL:
                 # Detect the index finger extended alone with the other fingers
in a fist
                if gesture == "one":
                    self.start_count += 1
                    if self.start_count > 20:
                        self.state = State.TRACKING
                        self.points = []
                else:
                    self.start_count = 0

            elif self.state == State.TRACKING:
                # Spread the five fingers to end drawing
                if gesture == "five":
                    self.state = State.NULL

                    # Generate a black-and-white trajectory image
                    track_img = get_track_img(self.points)

                    contours = cv2.findContours(track_img, cv2.RETR_EXTERNAL,
cv2.CHAIN_APPROX_NONE)[-2]

                    contour = get_area_max_contour(contours, 300)

                    contour = contour[0]
                    # Recognize the drawn figure based on the trajectory image
                    # cv2.fillPoly draws and fills a polygon on the image
                    track_img = cv2.fillPoly(track_img, [contour,], (255, 255,
255))

                    for _ in range(3):
                        # Erosion function
                        track_img = cv2.erode(track_img,
cv2.getStructuringElement(cv2.MORPH_RECT, (5, 5)))

                        # Dilation function
                        track_img = cv2.dilate(track_img,
cv2.getStructuringElement(cv2.MORPH_RECT, (5, 5)))
```

```
                    contours = cv2.findContours(track_img, cv2.RETR_EXTERNAL,
cv2.CHAIN_APPROX_NONE)[-2]

                    contour = get_area_max_contour(contours, 300)

                    contour = contour[0]
                    h, w = track_img.shape[:2]

                    track_img = np.full([h, w, 3], 0, dtype=np.uint8)
                    track_img = cv2.drawContours(track_img, [contour, ], -1, (0,
255, 0), 2)

                    # Perform polygon approximation on the image contour points
                    approx = cv2.approxPolyDP(contour, 0.026 *
cv2.arcLength(contour, True), True)

                    track_img = cv2.drawContours(track_img, [approx, ], -1, (0,
0, 255), 2)

                    graph_name = 'unknown'

                    # Determine the figure based on the number of vertices of the
contour envelope
                    if len(approx) == 3:
                        graph_name = 'Triangle'
                    if len(approx) == 4 or len(approx) == 5:
                        graph_name = 'Square'
                    if 5 < len(approx) < 10:
                        graph_name = 'Circle'
                    if len(approx) == 10:
                        graph_name = 'Star'
                    cv2.putText(track_img, graph_name, (10,
40),cv2.FONT_HERSHEY_SIMPLEX, 1.2, (255, 255, 0), 2)
                    cv2.imshow('track', track_img)

                else:
                    if len(self.points) > 0:
                        if distance(self.points[-1], index_finger_tip) > 5:
                            self.points.append(index_finger_tip)
                    else:
                        self.points.append(index_finger_tip)

                draw_points(result_image, self.points)
            else:
                pass
        else:
            if self.state == State.TRACKING:
                if time.time() - self.no_finger_timestamp > 2:
                    self.state = State.NULL
                    self.points = []

    except BaseException as e:
        print(e)

    #result_image = cv2.cvtColor(result_image, cv2.COLOR_RGB2BGR)
    cv2.imshow('image', result_image)
```

```
    key = cv2.waitKey(1)
     # Press the spacebar to clear the recorded trajectory
    if key == ord(' '):
        self.points = []
    if time.time() > self.gc_stamp:
        self.gc_stamp = time.time() + 1
        gc.collect()
```

hand_angle function, calculates the bending angle of each finger

```
def hand_angle(landmarks):
    angle_list = []
    # thumb
    angle_ = vector_2d_angle(landmarks[3] - landmarks[4], landmarks[0] -
landmarks[2])
    angle_list.append(angle_)
    # index
    angle_ = vector_2d_angle(landmarks[0] - landmarks[6], landmarks[7] -
landmarks[8])
    angle_list.append(angle_)
    # middle
    angle_ = vector_2d_angle(landmarks[0] - landmarks[10], landmarks[11] -
landmarks[12])
    angle_list.append(angle_)
    # ring
    angle_ = vector_2d_angle(landmarks[0] - landmarks[14], landmarks[15] -
landmarks[16])
    angle_list.append(angle_)
    # pink
    angle_ = vector_2d_angle(landmarks[0] - landmarks[18], landmarks[19] -
landmarks[20])
    angle_list.append(angle_)
    angle_list = [abs(a) for a in angle_list]
    return angle_list
```

h_gesture function, determines the gesture made by the fingers through 2D features

```
def h_gesture(angle_list):
    thr_angle, thr_angle_thumb, thr_angle_s = 65.0, 53.0, 49.0
    if (angle_list[0] < thr_angle_s) and (angle_list[1] < thr_angle_s) and
(angle_list[2] < thr_angle_s) and (
            angle_list[3] < thr_angle_s) and (angle_list[4] < thr_angle_s):
        gesture_str = "five"
    elif (angle_list[0] > 5) and (angle_list[1] < thr_angle_s) and (angle_list[2]
> thr_angle) and (
            angle_list[3] > thr_angle) and (angle_list[4] > thr_angle):
        gesture_str = "one"
    else:
        gesture_str = "none"
    return gesture_str
```

get_track_img function, generates the trajectory image,

```
def get_track_img(points):
    points = np.array(points).astype(dtype=np.int32)
    x_min, y_min = np.min(points, axis=0).tolist()
    x_max, y_max = np.max(points, axis=0).tolist()
    track_img = np.full([y_max - y_min + 100, x_max - x_min + 100, 1], 0,
dtype=np.uint8)
    points = points - [x_min, y_min]
    points = points + [50, 50]
    draw_points(track_img, points, 1, (255, 255, 255))
    return track_img
```