

Understand and publish images

Understand and publish images

- 3.1, Understanding of images
- 3.2, UnionFS (Union File System)
- 3.3, Image layering
 - 3.3.1, Layered Understanding
 - 3.3.2, The benefits of using layered docker images
- 3.4, Create and publish images
 - 3.4.1, Create images
 - 3.4.2, Publish images

3.1, Understanding of images

1. An image is a lightweight, executable, independent software package that contains all the content needed to run a certain software. We package applications and configurations into a complete, deliverable, and deployable operating environment, including code, libraries required for runtime, environment variables, and configuration files. This packaged operating environment is the image file.
2. Only through image files can docker container instances be generated.

3.2, UnionFS (Union File System)

1. Union File System (UnionFS) is a layered, lightweight, high-performance file system. It is the basis of docker images, and supports file system modifications as a single submission to be superimposed layer by layer, and different directories can be mounted under the same virtual file system.
2. Images can be inherited through layering, and various specific application images can be made based on the basic image.

Characteristics of Union File System: Multiple file systems can be loaded at the same time, but from the outside, only one file system can be seen; Union loading will superimpose each layer of file system, so that the final file system will contain files and directories of all layers.

3.3, Image layering

When downloading an image, pay attention to the download log output, you can see that it is downloaded layer by layer:

```

pi@yahboom:~$ docker pull mysql
Using default tag: latest
latest: Pulling from library/mysql
6425367b44c9: Pull complete
7cef374d113a: Pull complete
1751ddbc0d77: Pull complete
f41e9e3c6d9a: Pull complete
c26e9c11cd2d: Pull complete
949ad8819238: Pull complete
3028a5ad3fd0: Pull complete
a41584bf2c82: Pull complete
f413abbd4b9d: Pull complete
da7c55c30cf5: Pull complete
038fc84e09b5: Pull complete
Digest: sha256:a43f6e7e7f3a5e5b90f857fbed4e3103ece771b19f0f75880f767cf66bbb6577
Status: Downloaded newer image for mysql:latest
docker.io/library/mysql:latest
pi@yahboom:~$

```

To view the image layer, you can use the command: `docker image inspect image name`

```
pi@yahboom:~$ docker image inspect mysql:latest
```

```

[
  {
    "Id":
      "sha256:5371f8c3b63eec64a33b35530be5212d6148e0940111b57b689b5ba1ffe808c8",
    "RootFS": {
      "Type": "layers",
      "Layers": [
        "sha256:d6d4fc6aef875958d6186f85f03d88e6bb6484ab2dd56b30a79163baceff2f6d",
        "sha256:05c3b0b311a02bc56ca23105a76d16bc9b8c1d3e6eac808f4efb1a2e8350224b",
        "sha256:7b80f7f05642477ebc7d93de9539af27caab7c41a768db250fe3fe2b5506ca2c",
        "sha256:50e037faefab22cb1c75e60abb388b823e96a845650f3abd6d0a27e07a5a1d5e",
        "sha256:66040abb3f7201d2cc64531349a8225412db1029447a9431d59d999c941d56f6",
        "sha256:857162425652837a362aa5f1c3d4974cc83702728793de52ba48176d5367a89b",
        "sha256:7eebed3016f6b6ab68aa8e6be35f0689a3c18d331b7b542984a0050b859eaf26",
        "sha256:2fc4c142633d57d795edc0f3fd457f99a35fa611eab8b8c5d75c66e6eb729bc2",
        "sha256:7fde2d12d484f0c14dabd9ca845da0bcdaf60bd773a58ca2d73687473950e7fe",
        "sha256:9319848a00d38e15b754fa9dcd3b6e77ac8506850d32d8af493283131b9745a3",
        "sha256:5ff94d41f068ea5b52244393771471edb6a9a10f7a4ebafda9ef6629874a899b"
      ]
    },
    "Metadata": {
      "LastTagTime": "0001-01-01T00:00:00Z"
    }
  }
]

```

3.3.1, Layered Understanding

- All docker images start with a base image layer. When modifications or new content is added, a new image layer will be created on top of the current image layer.
- For a simple example, if a new image is created based on ubuntu 20.04, this is the first layer of the new image; if a python package is added to the image, a second image layer will be created on top of the base image layer; if a security patch is added, a third image layer will be created.
- Docker images are read-only. When the container is started, a new writable layer is loaded on top of the image! This layer is what we usually call the container layer, and everything below the container is called the image layer!

3.3.2, The benefits of using layered docker images

Resource sharing, for example, if multiple images are built from the same base image, then the host only needs to keep a base image on the disk, and only needs to load a base image in the memory, so that it can serve all containers, and each layer of the image can be shared.

3.4, Create and publish images

3.4.1, Create images

Method 1, submit an image from the container:

```
# command
docker commit -m="committed description" -a="author" container id target image
name to be created: [label name] [-m -a parameters can also be omitted]

# test
pi@yahboom:~$ docker ps -a
CONTAINER ID   IMAGE                COMMAND              CREATED        STATUS
PORTS         NAMES
c54bf9efae47   ubuntu:latest        "/bin/bash"         3 hours ago    Up 24 minutes
              funny_hugle
3b9c01839579   hello-world          "/hello"            3 hours ago    Exited (0) 3 hours ago
              jovial_brown
pi@yahboom:~$ docker commit c54bf9efae47 ubuntu:1.0
sha256:78ca7be949b6412f74ba12e8d16bd548aaa7c3fa25134326db3a67784f848f8f
pi@yahboom:~$ docker images # Generated ubuntu:1.0 image
REPOSITORY          TAG                 IMAGE ID            CREATED            SIZE
ubuntu              1.0                78ca7be949b6       5 seconds ago     69.2MB
yahboomtechnology/ros-foxy  3.4.0             49581aa78b6b       5 hours ago       24.3GB
yahboomtechnology/ros-foxy  3.3.9             cefb5ac2ca02       4 days ago        20.5GB
yahboomtechnology/ros-foxy  3.3.8             49996806c64a       4 days ago        20.5GB
yahboomtechnology/ros-foxy  3.3.7             8989b8860d17       5 days ago        17.1GB
yahboomtechnology/ros-foxy  3.3.6             326531363d6e       5 days ago        16.1GB
ubuntu              latest             bab8ce5c00ca       6 weeks ago       69.2MB
hello-world         latest            46331d942d63       13 months ago     9.14kB
```

Method 2: Dockerfile to create an image:

```
# command
docker build -f dockerfile file path -t new image name: TAG . # The docker build
command ends with a . to indicate the current directory
# test
docker build -f dockerfile-ros2 -t yahboomtechnology/ros-foxy:1.2 .
```


For more information about writing Dockerfile, please refer to:
https://docs.docker.com/develop/develop-images/dockerfile_best-practices/

3.4.2. Publish images

A docker repository is a place where image files are stored. The largest public repository is dockerhub (<https://hub.docker.com/>), which stores a large number of images for users to download.

Steps to publish images to docker hub:

1. Address: <https://hub.docker.com/>, register an account first
2. Ensure that the account can be logged in normally



3. Use the tag command to modify the image name

The specification for publishing an image to docker hub is:

```
docker push registered username/image name
```

For example, my registered username is: pengan88, so I need to modify the image name first

```
# command:
docker tag image ID modified image name

# test
pi@yahboom:~$ docker images
REPOSITORY          TAG          IMAGE ID          CREATED           SIZE
ubuntu              1.0         78ca7be949b6     5 seconds ago    69.2MB
ubuntu              latest      bab8ce5c00ca     6 weeks ago      69.2MB
hello-world         latest      46331d942d63     13 months ago    9.14kB
pi@yahboom:~$ docker tag 78ca7be949b6 pengan88/ubuntu:1.0
pi@yahboom:~$ docker images
REPOSITORY          TAG          IMAGE ID          CREATED           SIZE
pengan88/ubuntu     1.0         78ca7be949b6     23 minutes ago    69.2MB
ubuntu              1.0         78ca7be949b6     23 minutes ago    69.2MB
ubuntu              latest      bab8ce5c00ca     6 weeks ago      69.2MB
hello-world         latest      46331d942d63     13 months ago    9.14kB
```

4. Log in to docker hub to publish the image:


```
pi@yahboom:~$ docker login -u pengan88
Password:      # Enter the account and password registered with Docker Hub here
WARNING! Your password will be stored unencrypted in
/home/jetson/.docker/config.json.
Configure a credential helper to remove this warning. See
https://docs.docker.com/engine/reference/commandline/login/#credentials-store
```

Login Succeeded

```
pi@yahboom:~$ docker push pengan88/ubuntu:1.0
The push refers to repository [docker.io/pengan88/ubuntu]
ca774712d11b: Pushed
874b048c963a: Mounted from library/ubuntu
1.0: digest:
sha256:6767d7949e1c2c2adffbc5d3c232499435b95080a25884657fae366ccb71394d size:
736
```


5. Visit docker hub to see that it has been successfully released

Want faster and simpler Kubernetes development? Test out [Telepresence for Docker](#) today.

 dockerhub

Search Docker Hub

Explore Repositories Organizations Help

Upgrade  pengan88

pengan88


Repositories

ubuntu

General

Using 0 of 1 private repositories. [Get more](#)


General Tags Builds Collaborators Webhooks Settings



Add a short description for this repository


The short description is used to index your content on Docker Hub and in search engines. It's visible to users in search results.

[Update](#)



pengan88 / ubuntu

Description

This repository does not have a description 

Last pushed: a few seconds ago

Docker commands


To push a new tag to this repository,

`docker push pengan88/ubuntu:tagname`

[Public View](#)

Tags

This repository contains 1 tag(s).

| Tag | OS | Type | Pulled | Pushed |
|-----|---|-------|--------|-------------------|
| 1.0 |  | Image | --- | a few seconds ago |

[See all](#) [Go to Advanced Image Management](#)

Automated Builds

Manually pushing images to Hub? Connect your account to GitHub or Bitbucket to automatically build and tag new images whenever your code is updated, so you can focus your time on creating.

Available with Pro, Team and Business subscriptions. [Read more about automated builds](#)

Upgrade