2.Basic communication

2.1. Node settings

Function package path: ~/transbot_ws/src/transbot_bringup

The functions that Transbot SE needs to implement: car speed control, speed information feedback, robotic arm control, robotic arm status feedback, battery voltage feedback, buzzer control, and pan/tilt control.

The contents of setting the underlying driver node of Transbot SE according to the requirements are as follows:

- Topics

  Publish odometer message【/transbot/get_vel】

  Publish imu message【/transbot/imu】

  Post battery voltage news【/voltage】

  Subscribe to car sports news【/cmd_vel】

  Subscribe to robotic arm control messages【/TargetAngle】

  Subscribe to gimbal servo control messages【/PWMServo】

- Service (client)

  Receive buzzer control message【/Buzzer】

  Receive and feedback the current angle message of the robotic arm【/CurrentAngle】

2.2. View node data

1) Start

jetson/Raspberry Pi 4B

```
roscore
rosrun transbot_bringup transbot_driver.py
```

Raspberry Pi 5

Before running, please confirm that the large program has been permanently closed

Enter docker

Note: If there is a terminal that automatically starts docker, or there is a docker terminal that has been opened, you can directly enter the docker terminal to run the command, and there is no need to manually start docker

Start docker manually

```
./run_docker.sh
```




```
roscore
```

Enter the same docker from multiple terminals

Keep the program of the previous docker terminal running and open a new terminal

Enter the following command

```
docker ps
```

Enter the same docker and use the following 18870bc3dc00 to modify the ID displayed on the actual terminal.

```
docker exec -it 18870bc3dc00 /bin/bash
```




```
rosrun transbot_bringup transbot_driver.py
```

2) View the node graph

jetson motherboard/Raspberry Pi 4B

```
rqt_graph
```

Raspberry Pi 5

Enter the same docker from multiple terminals

Keep the program of the previous docker terminal running and open a new terminal

Enter the following command

```
docker ps
```

Enter the same docker and use the following 18870bc3dc00 to modify the ID displayed on the actual terminal.

```
docker exec -it 18870bc3dc00 /bin/bash
```




```
rqt_graph
```



3) View services

jetson motherboard/Raspberry Pi 4B

```
rosservice list
```

Raspberry Pi 5

Enter the same docker from multiple terminals

Keep the program of the previous docker terminal running and open a new terminal

Enter the following command

```
docker ps
```

Enter the same docker and use the following 18870bc3dc00 to modify the ID displayed on the actual terminal.

```
docker exec -it 18870bc3dc00 /bin/bash
```




```
rosservice list
```

Print as follows (mainly used):

```
/Buzzer
/CurrentAngle
/PWMServo
/voltage
... ...
```

Command line publishing service

jetson/Raspberry Pi 4B

```
# buzzer
rosservice call /Buzzer "buzzer: 1" # Turn on the buzzer
rosservice call /Buzzer "buzzer: 0" # Turn off the buzzer
# Get the current angle of the robotic arm
rosservice call /CurrentAngle "apply: 'GetJoint'"
```

Raspberry Pi 5

Enter the same docker from multiple terminals

Keep the program of the previous docker terminal running and open a new terminal

Enter the following command

```
docker ps
```

Enter the same docker and use the following 18870bc3dc00 to modify the ID displayed on the actual terminal.

```
docker exec -it 18870bc3dc00 /bin/bash
```




```
# buzzer
rosservice call /Buzzer "buzzer: 1" # Turn on the buzzer
rosservice call /Buzzer "buzzer: 0" # Turn off the buzzer
# Get the current angle of the robotic arm
rosservice call /CurrentAngle "apply: 'GetJoint'"
```

- Robotic arm

```
```



id	corresponding servo	angle range	running time
7	Steering gear connected to the body	[0, 225]	[10, 2000]
8	Section 2 steering gear	[30, 270]	[10, 2000]
9	Gripper servo	[30, 180]	[10, 2000]

Do not copy when issuing control instructions; type by hand and double-click the [Tab] key to complete.

- PTZ control

Control commands, such as the picture below



id	corresponding servo	angle range	camera
1	Move left and right (X)	[0, 180]	High frame rate
2	Move up and down (Y)	[0, 180]	High frame rate

4) View topic messages

Publish topics from the command line and drive the car



Note: Do not copy and paste; type by hand and double-click the [Tab] key to complete.

Using the rqt_topic tool

jetson motherboard/Raspberry Pi 4B

```
rosrun rqt_topic rqt_topic
```

Raspberry Pi 5

Enter the same docker from multiple terminals

Keep the program of the previous docker terminal running and open a new terminal

Enter the following command

```
docker ps
```

Enter the same docker and use the following 18870bc3dc00 to modify the ID displayed on the actual terminal.

```
docker exec -it 18870bc3dc00 /bin/bash
```




```
rosrun rqt_topic rqt_topic
```



As can be seen from the picture, the data can be printed only by putting a √ mark in the previous box. At this time, the battery voltage is 11.6V; the car's linear velocity and angular velocity decibels are [0.2, 0.99]; and the car's imu information is also available.

5) Dynamic parameter configuration

No adjustments are needed at this time, just for reference.

jetson/Raspberry Pi 4B

```
rosrun rqt_reconfigure rqt_reconfigure
```

Raspberry Pi 5

Enter the same docker from multiple terminals

Keep the program of the previous docker terminal running and open a new terminal

Enter the following command

```
docker ps
```

Enter the same docker and use the following 18870bc3dc00 to modify the ID displayed on the actual terminal.

```
docker exec -it 18870bc3dc00 /bin/bash
```




```
rosrun rqt_reconfigure rqt_reconfigure
```



【linear_max】: Maximum limit of linear speed

【angular_max】： Maximum limit of angular velocity

【linear_min】: Minimum limit of linear speed

【angular_min】： Minimum limit of angular velocity