

APP control

APP control

1. Learning objectives
2. Building blocks
3. Motor wiring
4. Programming
5. Experimental phenomenon
 - 5.1 Download APP
 - 5.2 APP remote controlAPP interface function introduction:

1. Learning objectives

In this course, we mainly learn how to use MakeCode graphical programming to realize Bluetooth APP remote control of Airplane.


2. Building blocks

For the building blocks steps, please refer to the installation drawings of **[Assembly Course]--[Airplane]** in the materials or the building blocks installation book.

3. Motor wiring

Insert the motor wiring on the left side of the car into the M1 interface of the Super:bit expansion board, and the black line is close to the battery side;

As shown below:



4. Programming

Method 1 Online programming:

First, connect micro:bit to the computer via a USB data cable, and the computer will pop up a U disk. Click the URL in the U disk: <https://makecode.microbit.org/> to enter the programming interface. Then, add the Yahboom software package <https://github.com/YahboomTechnology/SuperBitLibV2>, and you can start programming.

Method 2 Offline programming:

Open the offline programming software MakeCode and enter the programming interface. Click [New] and add the Yahboom software package <https://github.com/YahboomTechnology/SuperBitLibV2> to start programming.

For the summary program of this course, please open the **microbit-Airplane-APP-control.hex** we provide in the MakeCode programming interface to view it.

5. Experimental phenomenon

5.1 Download APP

Android users, please use the mobile browser to scan the following QR code to download and install the APP;

Apple users, please use the hand camera to scan the QR code to download and install the APP.



IOS




Android


! Note: During the installation or use of the APP, if the phone prompts that any permissions need to be obtained, please select "Agree".

5.2 APP remote control


1) After the program is downloaded successfully, turn on the power switch of the car, and the micro:bit dot matrix will display an "S" pattern, as shown in the figure below. This is the state of Bluetooth disconnection.




2) Turn on the Bluetooth of the mobile phone, open our APP, you can see the interface as shown in the figure below, click **Allow APP to use positioning information**.




3) After the mobile phone is close to the car and waits for a while, the Bluetooth will automatically connect; if it does not automatically connect, we can click [Search Bluetooth devices] to search for the device to connect.



After the Bluetooth is successfully connected, a smiley face pattern will be displayed on the micro:bit dot matrix; if the Bluetooth is disconnected, a crying face pattern will be displayed on the dot matrix.



[Bluetooth successful connection status]




[Bluetooth disconnection status]


APP interface function introduction:

Main control interface:

- The forward button controls the Airplane propeller to rotate clockwise, and it stops when released;
- The backward button controls the Airplane propeller to rotate counterclockwise, and it stops when released;
- After the left turn button is pressed, the Airplane propeller will continue to rotate counterclockwise;
- After the right turn button is pressed, the Airplane propeller will continue to rotate clockwise;
- Piano key 1 controls the Airplane to stop;
- Press the piano key to hear the buzzer play different tones




Car light interface:



RGB light interface:

Due to the upgrade of micro:bit V2 motherboard, the Bluetooth code control has deleted the RGB light control and changed to dot matrix display.



The buttons under the mode option have not yet defined any functions.

