

Spiders sense human body

Spiders sense human body

1. Learning Objectives
2. Building Blocks
3. Sensor Wiring
4. Code Analysis
5. Write and download the program
6. Experimental Phenomenon

1. Learning Objectives

In this course, we mainly learn how to use Python programming to realize the spider's automatic sensing of the human body moving forward.

2. Building Blocks

For the building block steps, please refer to the installation drawings of [Assembly Course]-[Fleeing spider] in the materials or the building block installation album.

3. Sensor Wiring


The motor wiring on the left side of the car is inserted into the M1 interface of the Super:bit expansion board, and the black line is close to the battery side;

The motor wiring on the right side of the car is inserted into the M3 interface of the Super:bit expansion board, and the black line is close to the battery side;


The human infrared sensing module is connected to the P1P2 interface.

last line ends with a blank program.


2. Click the thumb 'Check' button to check whether there are any errors in our code. If a cursor or underline appears in a line, it means a syntax error. Please check and modify it. If there is no error, the lower left corner will prompt that there is no problem with the detection.



3. Click the 'REPL' button to check whether the Superbit library has been downloaded. If not, please refer to [Preparation before class] --> [2.4 Python Programming Guide].



4. After the program is written, connect the computer and microbit mainboard with a microUSB data cable, please click the 'Flash' button to download the program to the micro:bit mainboard. **(You need to click the 'REPL' button again to turn off the import library file function before you can download the program normally).**



5. If the download fails, please confirm whether the microbit is connected to the computer normally via the microUSB data cable and the Superbit Python library has been imported.

6. Experimental Phenomenon

After the spider is powered on, the microbit mainboard will display 0 after initialization. When the human infrared module detects an obstacle behind it, the dot matrix displays 1 and the spider moves forward for 2 seconds. Otherwise, the spider remains motionless and the microbit mainboard displays 0.