MSPM0_K210 barcode recognition

1. K210 communicates with MSPM0

1.1 Experimental prerequisites

This tutorial uses the MSPM0G3507 development board. K210 needs to run the program in **K210-AI(MSPM0G3507)** to start the experiment

MSPM0G *1

K210 visual module *1 (must have an SD card (with AI models), camera)

USB to TTL module *1

1.2 Experimental wiring

Method 1: Use USB to TTL module

MSPM0G	K210 visual module
RX	TXD
GND	GND
VCC	5V

MSPM0G	USB to TTL module
TX	RXD
GND	GND



Method 2: Use the onboard Type-C port



1.3 Main code explanation

This example sets the baud rate of the serial port printing to 115200 bps, and the baud rate of the k210 module connection to 115200 bps.






```
int main(void)
{
    SYSCFG_DL_init();

    NVIC_ClearPendingIRQ(MYUART_INST_INT_IRQN);//清除串口中断标志 Clear the serial port interrupt flag
    NVIC_EnableIRQ(MYUART_INST_INT_IRQN);//使能串口中断 Enable serial port interrupt



    while (1)
    {
         if (k210_msg.class_n != 0)//例程号不为空 Routine number is not empty
        {
            if(k210_msg.class_n == 2)
            {

sprintf(buff_com,"x=%d,y=%d,w=%d,h=%d\r\n",k210_msg.x,k210_msg.y,k210_msg.w,k210_msg.h);
                uart0_send_string(buff_com);

                sprintf(buff_com,"str = %s\r\n",k210_msg.msg_msg);
                uart0_send_string(buff_com);
                k210_msg.class_n = 0;
            }
```

```
        }
        delay_ms(500);

    }
}
```

After the above program, if this routine is run, the members of the k210_msg structure will have corresponding values and will be processed through the serial port printing

k210_msg: is the structure for receiving information, and its main members are

- x: is the horizontal coordinate of the upper left corner of the identified box (range: 0-240)
- y: is the vertical coordinate of the upper left corner of the identified box (range: 0-320)
- w: is the width of the identified box (range: 0-240)
- h: is the length of the identified box (range: 0-320)
- id: is the identified label
- class_n: routine number
- msg_msg[20]: valid data

After the data is received and processed by the function, each member of k210_msg will store valid information. If you want to perform secondary development, you can directly call the members of k210_msg

Note: The keil project source code must be compiled under the SDK path.

1.4 Experimental phenomenon

1. After connecting the cable, the K210 perspective module runs offline. Please check 【6.2 K210 as coprocessor】--【ReadMe】

   Link:http://www.yahboom.net/study/K210-AI-Camera

2. Set the serial port assistant to the interface shown in the figure



3. Then run the barcode recognition routine, and the serial port assistant will print out the important information transmitted from k210 to MSPM0G, as shown in the figure below



Barcode recognition only transmits the five member variables x, y, w, h, and msg of k210_msg.