

# Bayes Classifier and Naïve Bayes


# Probabilistic Classification

- Credit scoring:
  - Inputs are **income** and **savings**
  - Output is **low-risk** vs **high-risk**
- Input:  $\mathbf{x} = [x_1, x_2]^T$ , Output:  $C \in \{0, 1\}$
- Prediction:
$$\text{choose } \begin{cases} C = 1 & \text{if } P(C = 1 | \mathbf{x}_1, \mathbf{x}_2) > 0.5 \\ C = 0 & \text{otherwise} \end{cases}$$

or equivalently

$$\text{choose } \begin{cases} C = 1 & \text{if } P(C = 1 | \mathbf{x}_1, \mathbf{x}_2) > P(C = 0 | \mathbf{x}_1, \mathbf{x}_2) \\ C = 0 & \text{otherwise} \end{cases}$$

# A side note: probabilistic inference



H = "Have a headache"

F = "Coming down with Flu"

$$P(H) = 1/10$$


$$P(F) = 1/40$$

$$P(H|F) = 1/2$$

One day you wake up with a headache. You think: "Drat! 50% of flus are associated with headaches so I must have a 50-50 chance of coming down with flu"

Is this reasoning good?

# Probabilistic Inference



H = "Have a headache"

F = "Coming down with Flu"

$$P(H) = 1/10$$


$$P(F) = 1/40$$

$$P(H|F) = 1/2$$

$$P(F \wedge H) = P(F)P(H | F) = \frac{1}{40} * \frac{1}{2} = \frac{1}{80}$$

$$P(F|H) = \frac{P(F \wedge H)}{P(H)} = \frac{1}{8}$$

# Bayes classifier



A simple bayes net

*posterior* → 
$$P(y | \mathbf{x}) = \frac{P(y) p(\mathbf{x} | y)}{p(\mathbf{x})}$$

*prior* →  $P(y)$

Given a set of training examples, to build a Bayes classifier, we need to

1. Estimate  $P(y)$  from data
2. Estimate  $P(x|y)$  from data

Given a test data point  $x$ , to make prediction

1. Apply bayes rule:  $P(y | \mathbf{x}) \propto P(y)P(\mathbf{x} | y)$
2. Predict  $\arg \max_y P(y | \mathbf{x})$

# Bayes Classifiers in a nutshell

1. Estimate  $P(x_1, x_2, \dots, x_m \mid y=v_i)$  for each value  $v_i$
  3. Estimate  $P(y=v_i)$  as fraction of records with  $y=v_i$ .
- } *learning*
4. For a new prediction:

$$y^{\text{predict}} = \underset{v}{\operatorname{argmax}} P(y = v \mid x_1 = u_1 \cdots x_m = u_m)$$
$$= \underset{v}{\operatorname{argmax}} P(x_1 = u_1 \cdots x_m = u_m \mid y = v) P(y = v)$$

Estimating the joint distribution of  $x_1, x_2, \dots, x_m$  given  $y$  can be problematic!

# Joint Density Estimator Overfits


- Typically we don't have enough data to estimate the joint distribution accurately
- It is common to encounter the following situation:
  - If no training examples have the exact  $\mathbf{x}=(u_1, u_2, \dots, u_m)$ , then  $P(\mathbf{x}/y=v_i) = 0$  for all values of  $Y$ .
- In that case, what can we do?
  - we might as well guess a random  $y$  based on the prior, i.e.,  $p(y)$

$$P(y | \mathbf{x}) = \frac{P(y) p(\mathbf{x} | y)}{p(\mathbf{x})}$$

# The Naïve Bayes Assumption

- Assume that each attribute is independent of any other attributes given the class label

$$\begin{aligned} &P(x_1 = u_1 \cdots x_m = u_m \mid y = v_i) \\ &= P(x_1 = u_1 \mid y = v_i) \cdots P(x_m = u_m \mid y = v_i) \end{aligned}$$





# Conditional Independence

- $P(x_1 | x_2, y) = P(x_1 | y)$ 
  - $X_1$  is independent of  $x_2$  given  $y$
  - $x_1$  and  $x_2$  are conditionally independent given  $y$
- If  $X_1$  and  $X_2$  are conditionally independent given  $y$ , then we have
  - $P(X_1, X_2 | y) = P(X_1 | y) P(X_2 | y)$

# Naïve Bayes Classifier

- By assuming that each attribute is independent of any other attributes given the class label, we now have a *Naïve* Bayes Classifier
- Instead of learning a joint distribution of all features, we learn  $p(x_i | y)$  separately for each feature  $x_i$
- Everything else remains the same

# Naïve Bayes Classifier

- Assume you want to predict output  $y$  which has  $n_y$  values  $v_1, v_2, \dots, v_{n_y}$ .
- Assume there are  $m$  input attributes called  $\mathbf{x}=(x_1, x_2, \dots, x_m)$
- Learn a conditional distribution of  $p(\mathbf{x}|y)$  for each possible  $y$  value,  $y = v_1, v_2, \dots, v_{n_y}$ , we do this by:
  - Break training set into  $n_y$  subsets called  $S_1, S_2, \dots, S_{n_y}$  based on the  $y$  values, i.e.,  $S_i$  contains examples in which  $y=v_i$
  - For each  $S_i$ , learn  $p(y=v_i) = |S_i| / |S|$
  - For each  $S_i$ , learn the conditional distribution each input features, e.g.:

$$P(x_1 = u_1 \mid y = v_i), \dots, P(x_m = u_m \mid y = v_i)$$

$$y^{\text{predict}} = \underset{v}{\operatorname{argmax}} P(x_1 = u_1 \mid y = v) \cdots P(x_m = u_m \mid y = v) P(y = v)$$

# Example

$X_1$	$X_2$	$X_3$	Y
1	1	1	0
1	1	0	0
0	0	0	0
0	1	0	1
0	0	1	1
0	1	1	1

Apply Naïve Bayes, and make prediction for (1,0,1)?

1. Learn the prior distribution of y.  
 $\mathbf{P}(y=0)=1/2$ ,  $\mathbf{P}(y=1)=1/2$
2. Learn the conditional distribution of  $x_i$  given y for each possible y values  
 $\mathbf{p}(X_1|y=0)$ ,  $\mathbf{p}(X_1|y=1)$   
 $\mathbf{p}(X_2|y=0)$ ,  $\mathbf{p}(X_2|y=1)$   
 $\mathbf{p}(X_3|y=0)$ ,  $\mathbf{p}(X_3|y=1)$

For example,  $\mathbf{p}(X_1|y=0)$ :

$\mathbf{P}(X_1=1|y=0)=2/3$ ,  $\mathbf{P}(X_1=1|y=1)=0$

...

To predict for (1,0,1):

$$P(y=0|(1,0,1)) = \frac{P((1,0,1)|y=0)P(y=0)}{P((1,0,1))}$$

$$P(y=1|(1,0,1)) = \frac{P((1,0,1)|y=1)P(y=1)}{P((1,0,1))}$$

# Laplace Smoothing

- With the Naïve Bayes Assumption, we can still end up with zero probabilities
- E.g., if we receive an email that contains a word that has never appeared in the training emails
  - $P(\mathbf{x}|\mathbf{y})$  will be 0 for all  $\mathbf{y}$  values
  - We can only make prediction based on  $p(\mathbf{y})$
- This is bad because we ignored all the other words in the email because of this single rare word
- Laplace smoothing can help

$$P(X_1=1 | y=0)$$



$$= (\mathbf{1} + \text{\# of examples with } y=0, X_1=1) / (\mathbf{k} + \text{\# of examples with } y=0)$$

$k$  = the total number of possible values of  $x$

- For a binary feature like above,  $p(x|\mathbf{y})$  will not be 0

# Bayes Classifier is a **Generative Approach**

- Generative approach:
  - Learn  $p(y)$ ,  $p(\mathbf{x} | y)$ , and then apply bayes rule to compute  $p(y | \mathbf{x})$  for making predictions
  - This is equivalent to assuming that each data point is generated following a **generative process** governed by  $p(y)$  and  $p(X | y)$



- Generative approach is just one type of learning approaches used in machine learning
  - Learning a correct generative model is difficult
  - And sometimes unnecessary
- KNN and DT are both what we call discriminative methods
  - They are not concerned about any generative models
  - They only care about finding a good discriminative function
  - For KNN and DT, these functions are deterministic, not probabilistic
- One can also take a probabilistic approach to learning discriminative functions
  - i.e., Learn  $p(y|X)$  directly without assuming  $X$  is generated based on some particular distribution given  $y$  (i.e.,  $p(X|y)$ )
  - Logistic regression is one such approach