

Preparing Flight Delay Data



PARALLEL PROGRAMMING WITH DASK IN PYTHON



Dhavide Aruliah

Director of Training, Anaconda

Case study: Analyzing flight delays



Limitations of Dask DataFrames

- Reading data into Dask DataFrames:
 - A single file
 - Using `glob` on many files
- Limitations:
 - Unsupported file formats
 - Cleaning files independently
 - Nested subdirectories tricky with `glob`

Sample account data

`accounts/Alice.csv` :

```
date,amount
2016-01-31,103.15
2016-02-25,114.17
2016-03-06,4.03
2016-05-20,150.48
```

`accounts/Bob.csv` :

```
date,amount
2016-01-04,99.68
2016-02-09,146.41
2016-02-21,-42.94
2016-03-14,0.26
```

Reading/cleaning in a function

```
import pandas as pd
from dask import delayed
@delayed
def pipeline(filename, account_name):
    df = pd.read_csv(filename)
    df['account_name'] = account_name
    return df
```

Using dd.from_delayed()

```
delayed_dfs = []  
for account in ['Bob', 'Alice', 'Dave']:  
    fname = 'accounts/{}.csv'.format(account)  
    delayed_dfs.append(pipeline(fname, account))  
import dask.dataframe as dd  
dask_df = dd.from_delayed(delayed_dfs)  
dask_df['amount'].mean().compute()
```

```
10.56476
```

Flight delays and weather

- Cleaning flight delays
 - Use `.replace() : 0` → `NaN`
- Cleaning weather data
 - `'PrecipitationIn'` : text → numeric
 - Add column for airport code

Flight delays data

```
df = pd.read_csv('flightdelays-2016-1.csv')  
df.columns
```

```
Index(['FL_DATE', 'UNIQUE_CARRIER', 'FL_NUM', 'ORIGIN',  
      'ORIGIN_CITY_NAME', 'ORIGIN_STATE_ABR', 'ORIGIN_STATE_NM',  
      'DEST', 'DEST_CITY_NAME', 'DEST_STATE_ABR',  
      'DEST_STATE_NM', 'CRS_DEP_TIME', 'DEP_DELAY',  
      'CRS_ARR_TIME', 'ARR_DELAY', 'CANCELLED', 'DIVERTED',  
      'CARRIER_DELAY', 'WEATHER_DELAY', 'NAS_DELAY',  
      'SECURITY_DELAY', 'LATE_AIRCRAFT_DELAY',  
      'Unnamed: 22'],  
      dtype='object')
```


Flight delays data

```
df['WEATHER_DELAY'].tail()
```

```
89160    NaN
89161    0.0
89162    NaN
89163    NaN
89164    NaN
Name: WEATHER_DELAY, dtype: float64
```

Replacing values

series

```
0    6
1    0
2    6
3    5
4    7
dtype: int64
```

```
new_series = series.replace(
    6, np.nan)
new_series
```

```
0    NaN
1    0.0
2    NaN
3    5.0
4    7.0
dtype: float64
```

Let's practice!

PARALLEL PROGRAMMING WITH DASK IN PYTHON

Preparing Weather Data

PARALLEL PROGRAMMING WITH DASK IN PYTHON



Dhavide Aruliah

Director of Training, Anaconda

Daily weather data

```
import pandas as pd
df = pd.read_csv('DEN.csv', parse_dates=True, index_col='Date')
df.columns
```

```
Index(['Max TemperatureF', 'Mean TemperatureF', 'Min TemperatureF',
      'Max Dew PointF', 'MeanDew PointF', 'Min DewpointF', 'Max Humidity',
      'Mean Humidity', 'Min Humidity', 'Max Sea Level PressureIn',
      'Mean Sea Level PressureIn', 'Min Sea Level PressureIn',
      'Max VisibilityMiles', 'Mean VisibilityMiles',
      'Min VisibilityMiles',
      'Max Wind SpeedMPH', 'Mean Wind SpeedMPH', 'Max Gust SpeedMPH',
      'PrecipitationIn', 'CloudCover', 'Events', 'WindDirDegrees'],
      dtype='object')
```

Daily weather data

```
df.loc['March 2016', ['PrecipitationIn', 'Events']].tail()
```

Date	PrecipitationIn	Events
2016-03-27	0.00	NaN
2016-03-28	0.00	NaN
2016-03-29	0.04	Rain-Thunderstorm
2016-03-30	0.04	Rain-Snow
2016-03-31	0.01	Snow

Examining PrecipitationIn & Events columns

```
df['PrecipitationIn'][0]  
type(df['PrecipitationIn'][0])
```

```
'0.00'  
str
```

```
df[['PrecipitationIn', 'Events']].info()
```

```
<class 'pandas.core.frame.DataFrame'>  
RangeIndex: 366 entries, 0 to 365  
Data columns (total 2 columns):  
PrecipitationIn    366 non-null object  
Events             115 non-null object  
dtypes: object(2)  
memory usage: 5.8+ KB
```

Converting to numeric values

series

```
0      0
1      M
2      2
3    1.5
4      E
dtype: object
```

```
new_series = pd.to_numeric(series,
                             errors='coerce')
```

new_series

```
0    0.0
1    NaN
2    2.0
3    1.5
4    NaN
dtype: float64
```


Let's practice!

PARALLEL PROGRAMMING WITH DASK IN PYTHON

Merging & Persisting DataFrames

PARALLEL PROGRAMMING WITH DASK IN PYTHON



Dhavide Aruliah

Director of Training, Anaconda

Merging DataFrames

- Pandas: `pd.merge()`
- Pandas: `pd.DataFrame.merge()`
- Dask: `dask.dataframe.merge()`

Merging example

left_df

	cat_left	value_left
0	d	4
1	d	9
2	b	1
3	d	7
4	c	3

right_df

	cat_right	value_right
0	b	9
1	c	2
2	f	0
3	d	8
4	a	8

Merging example

```
left_df.merge(right_df,  
               left_on=['cat_left'],  
               right_on=['cat_right'],  
               how='inner')
```

	cat_left	value_left	cat_right	value_right
0	d	4	d	8
1	d	9	d	8
2	d	7	d	8
3	b	1	b	9
4	c	3	c	2

Dask DataFrame pipelines

- Flight delays & weather set up
 1. Read & clean 12 months of flight delay data
 2. Make `flight_delay` dataframe with `dd.from_delayed`
 3. Read & clean weather daily data from 5 airports
 4. Make `weather` dataframe with `dd.from_delayed`
 5. Merge the two dataframes

Dask DataFrame pipelines

- Flight delays & weather set up
 1. Read & clean 12 months of flight delay data
 2. Make `flight_delay` dataframe with `dd.from_delayed`
 3. Read & clean weather daily data from 5 airports
 4. Make `weather` dataframe with `dd.from_delayed`
 5. Merge the two dataframes

Repeated reads & performance

```
import dask.dataframe as dd  
df = dd.read_csv('flightdelays-2016-*.csv')  
%time print(df.WEATHER_DELAY.mean().compute())
```

```
2.701183508773752  
CPU times: user 3.35 s, sys: 719 ms, total: 4.07 s  
Wall time: 1.64 s
```

```
%time print(df.WEATHER_DELAY.std().compute())
```

```
21.230502105  
CPU times: user 3.33 s, sys: 706 ms, total: 4.04 s  
Wall time: 1.61 s
```


Repeated reads & performance

```
%time print(df.WEATHER_DELAY.count().compute())
```

```
192563
```

```
CPU times: user 3.36 s, sys: 695 ms, total: 4.06 s
```

```
Wall time: 1.66 s
```

Using persistence

```
%time persisted_df = df.persist()
```

```
CPU times: user 3.32 s, sys: 688 ms, total: 4.01 s  
Wall time: 1.59 s
```

```
%time print(persisted_df.WEATHER_DELAY.mean().compute())
```

```
2.701183508773752  
CPU times: user 15.1 ms, sys: 9.24 ms, total: 24.3 ms  
Wall time: 18.5 ms
```

Using persistence

```
%time print(persisted_df.WEATHER_DELAY.std().compute())
```

```
21.230502105
```

```
CPU times: user 29.6 ms, sys: 12.5 ms, total: 42.1 ms
```

```
Wall time: 29.5 ms
```

```
%time print(persisted_df.WEATHER_DELAY.count().compute())
```

```
192563
```

```
CPU times: user 9.88 ms, sys: 2.98 ms, total: 12.9 ms
```

```
Wall time: 9.43 ms
```

Let's practice!

PARALLEL PROGRAMMING WITH DASK IN PYTHON

Final thoughts

PARALLEL PROGRAMMING WITH DASK IN PYTHON



Matthew Rocklin & Dhavide Aruli...

Instructors, Anaconda

What you've learned

- How to:
 - Use Dask data structures and delayed functions
 - Set up data analysis pipelines with deferred computation
 - ... while working with real-world data!

Next steps

- Deploying Dask on your own cluster
- Integrating with other Python libraries
- Dynamic task scheduling and data management
- <https://dask.org/>

Congratulations!

PARALLEL PROGRAMMING WITH DASK IN PYTHON