
Fog computing task scheduling

a multi-objective AI-based approach

Théo FIGINI
M2 Computer Science
Academic year 2023-2024

Hosting organization: *LAAS-CNRS*

February, 1st 2024 - June, 25th 2024

Referring teacher:
Andrei DONCESCU

Tutor:
Tom GUÉROUT

June, 18th 2024

Abstract

Introduction

As the number of devices grows exponentially, the demand for computing resources increases. The traditional cloud computing model is not sufficient to handle the massive amount of data generated by these devices. Fog computing is an alternative model that extends the computing resources to the edge of the network, closer to the devices. This model reduces the latency and bandwidth usage, and improves the overall performance of the system. However, the increasing demand for computing resources also raises concerns about the energy consumption and the environmental impact of fog computing systems.

In this paper, we will propose an AI-based task scheduling algorithm that integrate the use of green energy sources while satisfying the Quality of Service (QoS) requirements of the users.

The rest of this paper is organized as follows. In Chapter 2, we present an overview of the existing research on task scheduling, energy efficiency and AI in the context of fog computing. In Chapter 3, we describe the proposed task scheduling algorithm and the integration of green energy sources. In Chapter 4, we present the experimental results and the performance evaluation of the algorithm. Finally, in Chapter 5, we conclude the paper and discuss the future work.

Related Work

There are many existing studies and researches on the topics task scheduling, energy efficiency and AI in the context of fog computing. The concept of fog computing was introduced by Cisco in 2012 [1], and since then, many researches have been conducted to improve the performance of fog computing systems and reduce their environmental impact.

Fog computing

Fog computing is a paradigm that extends cloud computing and services to the edge of the network. [2] and [3] respectively investigate the concepts surrounding fog and its applications in the context of IoT. [4] offers an extensive review of the existing work on fog computing.

Task Scheduling in Fog Computing

Genetic Algorithms

The task scheduling problem in fog computing has been widely studied in the literature. Many researchers have proposed different algorithms and techniques to optimize the task scheduling process in fog computing systems. [5] offers an analysis of the existing algorithms while identifying the challenges and research gaps. In [6], the authors propose a task scheduling algorithm based on Swarm Intelligence and Machine Learning. This hybrid approach minimizes the execution time and the makespan and improves the performance of the load balancing scheduling. In [7], an optimization model is proposed for the problem of mapping data stream over fog nodes while considering the load of those nodes and the latency between the sensors and the nodes. A heuristic based on genetic algorithms is then presented to address the complexity of the problem. In [8], the authors propose a task clustering and scheduling mechanism based on Differential Evolution to find the optimal execution time for the tasks. The mechanism is compared to the Firefly Algorithm and Particle Swarm Optimization, and the results show that the proposed mechanism outperforms the other two algorithms in terms of execution time, system efficiency and stability.

Fuzzy Logic

[9] proposes a ranking-based task scheduling method that combines fuzzy logic and user preferences. In [10], the authors propose an approach based on Fuzzy Logic for real-time task scheduling in IoT applications.

Energy Efficiency in Fog Computing

The energy efficiency of fog computing systems has been a major concern for researchers. [11] introduces a mathematical framework to evaluate the trade-off of fog computing systems, especially in terms of power consumption and energy efficiency. In [12], the authors propose two Integer Linear Programming models, where the second one aims at minimizing the energy consumption while maximizing successfully provisioned tasks. The authors of [13] provides an overview of the energy efficiency challenges in fog computing and presents a comprehensive survey of the existing energy-efficient techniques and algorithms. An energy-aware Metaheuristic algorithm based on the Harris Hawks Optimization algorithm, itself based on a local search strategy for task scheduling in fog computing, is proposed in [14]. [15] proposes an energy efficient algorithm through an integrated computation model.

AI in Fog Computing

The use of AI in fog computing has been a growing trend in the literature. An efficient binary CNN with numerous skip connections is proposed by the authors of [16]. In [17], the authors designed an intelligent energy-saving model based on CNN and a task scheduling model is designed based on the policy gradient algorithm. [18] present an improved convolutional neural network so solve the value function of a Continuous Markov Decision Process model, so it can be applied to a multi-user system.

Offloading using Fuzzy logic

Introduction

Introduced in 1965 by Lotfi Zadeh[19], fuzzy logic is based on a "degree of truth" instead of a finite value, usually 0 or 1, it aims to represent the vagueness of human language and thought. Fuzzy systems are the means to implement fuzzy logic, they are two types of fuzzy systems: Mamdani and Sugeno, both are similar but differ in the way the output is determined. The most common one Mamdani and it's the one we will be using in this project. The Mamdani fuzzy system follows three steps:

- the inputs are fuzzified into fuzzy membership functions,
- a set of rules are applied to the fuzzy inputs to determine the fuzzy output,
- the fuzzy output is defuzzified to get a crisp value.

Fuzzification

Fuzzification is the process of converting a crisp value into a fuzzy value, this is done by assigning a membership function to the input value. The membership function is a curve that defines how much the input value belongs to a certain fuzzy set. The most common membership functions are the triangular and trapezoidal functions, they are defined by three or four parameters respectively. The triangular function is defined by the parameters a , b and c and is given by:

$$\mu(x) = \begin{cases} 0 & \text{if } x \leq a, \\ \frac{x-a}{b-a} & \text{if } a \leq x \leq b, \\ \frac{c-x}{c-b} & \text{if } b \leq x \leq c, \\ 0 & \text{if } x \geq c. \end{cases} \quad (1)$$

The trapezoidal function is defined by the parameters a , b , c and d and is given by:

$$\mu(x) = \begin{cases} 0 & \text{if } x \leq a, \\ \frac{x-a}{b-a} & \text{if } a \leq x \leq b, \\ 1 & \text{if } b \leq x \leq c, \\ \frac{d-x}{d-c} & \text{if } c \leq x \leq d, \\ 0 & \text{if } x \geq d. \end{cases} \quad (2)$$

Rule evaluation

The rule evaluation is the process of determining the fuzzy output based on the fuzzy inputs and a set of rules. The rules are defined by two parts: the "if" or antecedent part and the "then" or consequent part. The antecedent part deals with inputs, it can either be a single input or a combination of inputs, the combination can be done using the logical operators "and" and "or". The consequent part deals with the output. In the context of this project, the rules are usually of the form "if Bandwidth is low then processing is local". The rules are generally defined by the user and are based on their knowledge of the system.

Defuzzification

Defuzzification is the process of converting a fuzzy output into a crisp value, there are several methods to do this, the most common one is the centroid method. The centroid method calculates the center of mass of the fuzzy output, this is done by taking the weighted average of the output values. The weighted average is calculated by taking the sum of the product of the output value and its membership value divided by the sum of the membership values. The formula for the centroid method is given by:

$$y = \frac{\sum_i \mu_i \cdot y_i}{\sum_i \mu_i}. \quad (3)$$

Where y is the crisp output, μ_i is the membership value of the output value y_i .

Conclusion

Conclusion

Bibliography

- [1] Flavio Bonomi et al. “Fog computing and its role in the internet of things”. In: *Proceedings of the First Edition of the MCC Workshop on Mobile Cloud Computing*. MCC '12. used. Helsinki, Finland: Association for Computing Machinery, 2012, pp. 13–16. ISBN: 9781450315197. DOI: [10.1145/2342509.2342513](https://doi.org/10.1145/2342509.2342513). URL: <https://doi.org/10.1145/2342509.2342513>.
- [2] Muhammad Ehsan Rana and Nirase Abubacker. “Fog Computing Foundations”. In: used. June 2023, pp. 1–20. ISBN: 9781668444665. DOI: [10.4018/978-1-6684-4466-5.ch001](https://doi.org/10.4018/978-1-6684-4466-5.ch001).
- [3] Nirase Abubacker, Muhammad Ehsan Rana, and Mafas Raheem. “Fog Computing Applications”. In: used. June 2023, pp. 30–58. ISBN: 9781668444665. DOI: [10.4018/978-1-6684-4466-5.ch003](https://doi.org/10.4018/978-1-6684-4466-5.ch003).
- [4] Mohammed Al-Musawi, Dunya Alrseetmiwe, and Zahraa Saad. “Fog computing system for internet of things: Survey”. In: 16 (Nov. 2023). used, 1_10.
- [5] Javid Misirli and Emiliano Casalicchio. “An Analysis of Methods and Metrics for Task Scheduling in Fog Computing”. In: *Future Internet* 16.1 (2024). used. ISSN: 1999-5903. DOI: [10.3390/fi16010016](https://doi.org/10.3390/fi16010016). URL: <https://www.mdpi.com/1999-5903/16/1/16>.
- [6] Gaith Rjoub and Jamal Bentahar. “Cloud Task Scheduling Based on Swarm Intelligence and Machine Learning”. In: *2017 IEEE 5th International Conference on Future Internet of Things and Cloud (FiCloud)*. used. 2017, pp. 272–279. DOI: [10.1109/FiCloud.2017.52](https://doi.org/10.1109/FiCloud.2017.52).
- [7] Claudia Canali and Riccardo Lancellotti. “GASP: Genetic Algorithms for Service Placement in Fog Computing Systems”. In: *Algorithms* 12.10 (2019). used. ISSN: 1999-4893. DOI: [10.3390/a12100201](https://doi.org/10.3390/a12100201). URL: <https://www.mdpi.com/1999-4893/12/10/201>.
- [8] Adil Yousif, Mohammed Bakri Bashir, and Awad Ali. “An Evolutionary Algorithm for Task Clustering and Scheduling in IoT Edge Computing”. In: *Mathematics* 12.2 (2024). used. ISSN: 2227-7390. DOI: [10.3390/math12020281](https://doi.org/10.3390/math12020281). URL: <https://www.mdpi.com/2227-7390/12/2/281>.
- [9] Mohammed Anis Benblidia et al. “Ranking Fog nodes for Tasks Scheduling in Fog-Cloud Environments: A Fuzzy Logic Approach”. In: *2019 15th International Wireless Communications & Mobile Computing Conference (IWCMC)*. used. 2019, pp. 1451–1457. DOI: [10.1109/IWCMC.2019.8766437](https://doi.org/10.1109/IWCMC.2019.8766437).
- [10] Hala S. Ali et al. “Real-Time Task Scheduling in Fog-Cloud Computing Framework for IoT Applications: A Fuzzy Logic based Approach”. In: *2021 International Conference on COMMunication Systems & NETWORKS (COMSNETS)*. used. 2021, pp. 556–564. DOI: [10.1109/COMSNETS51098.2021.9352931](https://doi.org/10.1109/COMSNETS51098.2021.9352931).
- [11] Raad S. Alhumaima. “Energy efficiency and latency analysis of fog networks”. In: *China Communications* 17.4 (2020). used, pp. 66–77. DOI: [10.23919/JCC.2020.04.007](https://doi.org/10.23919/JCC.2020.04.007).
- [12] Zhiming He et al. “Green Fog Planning for Optimal Internet-of-Thing Task Scheduling”. In: *IEEE Access* 8 (2020). used, pp. 1224–1234. DOI: [10.1109/ACCESS.2019.2961952](https://doi.org/10.1109/ACCESS.2019.2961952).
- [13] Usman Mahmood Malik et al. “Energy-Efficient Fog Computing for 6G-Enabled Massive IoT: Recent Trends and Future Opportunities”. In: *IEEE Internet of Things Journal* 9.16 (2022). used, pp. 14572–14594. DOI: [10.1109/JIOT.2021.3068056](https://doi.org/10.1109/JIOT.2021.3068056).
- [14] Mohamed Abdel-Basset et al. “Energy-Aware Metaheuristic Algorithm for Industrial-Internet-of-Things Task Scheduling Problems in Fog Computing Applications”. In: *IEEE Internet of Things Journal* 8.16 (2021). used, pp. 12638–12649. DOI: [10.1109/JIOT.2020.3012617](https://doi.org/10.1109/JIOT.2020.3012617).

- [15] Yan Wang et al. “Service delay and optimization of the energy efficiency of a system in fog-enabled smart cities”. In: *Alexandria Engineering Journal* 84 (2023). used, pp. 112–125. ISSN: 1110-0168. DOI: <https://doi.org/10.1016/j.aej.2023.10.034>. URL: <https://www.sciencedirect.com/science/article/pii/S1110016823009365>.
- [16] Lijun Wu et al. “An Efficient Binary Convolutional Neural Network With Numerous Skip Connections for Fog Computing”. In: *IEEE Internet of Things Journal* 8.14 (2021). used, pp. 11357–11367. DOI: [10.1109/JIOT.2021.3052105](https://doi.org/10.1109/JIOT.2021.3052105).
- [17] Dexian Yang et al. “Energy saving strategy of cloud data computing based on convolutional neural network and policy gradient algorithm”. In: *PLOS ONE* 17.12 (Dec. 2022). used, pp. 1–18. DOI: [10.1371/journal.pone.0279649](https://doi.org/10.1371/journal.pone.0279649). URL: <https://doi.org/10.1371/journal.pone.0279649>.
- [18] Bing Jing and Huimin Xue. “IoT Fog Computing Optimization Method Based on Improved Convolutional Neural Network”. In: *IEEE Access* 12 (2024). used, pp. 2398–2408. DOI: [10.1109/ACCESS.2023.3348133](https://doi.org/10.1109/ACCESS.2023.3348133).
- [19] L.A. Zadeh. “Fuzzy sets”. In: *Information and Control* 8.3 (1965). used, pp. 338–353. ISSN: 0019-9958. DOI: [https://doi.org/10.1016/S0019-9958\(65\)90241-X](https://doi.org/10.1016/S0019-9958(65)90241-X). URL: <https://www.sciencedirect.com/science/article/pii/S001999586590241X>.