

Modele2__debugdebug

November 18, 2025

```
[145]: import sys
import numpy as np
import pickle
np.random.seed(0)
from scripts import (
    train_test_split,
    StandardScaler,
    accuracy,
    confusion_matrix,
    recall_per_class,
    balanced_accuracy
)

import pandas as pd

[146]: def rbf_kernel(x, X, sigma=1.0):
    """Calcule le noyau RBF entre x et X."""
    return np.exp(-np.sum((X - x)**2, axis=1) / (2 * sigma**2))

class KernelPerceptron:
    def __init__(self, kernel_fn, n_classes, sigma=1.0):
        self.kernel_fn = kernel_fn
        self.n_classes = n_classes
        self.sigma = sigma

    def fit(self, X, y, max_epochs=10):
        """Entraînement multiclasse One-vs-Rest."""
        N = X.shape[0]
        self.X = X
        self.classes = np.unique(y)
        self.train_y = y
        self.alpha = np.zeros((self.n_classes, N))

        # Precompute Gram matrix
```

```

        self.K = np.array([self.kernel_fn(X[i], X, self.sigma) for i in
↪range(N)])

        for c in self.classes:
            print(f"Training classifier for class {c}...")
            y_bin = np.where(y == c, 1, -1)
            count, i, n_iter = 0, 0, 0

            while count < N and n_iter < max_epochs * N:
                if np.sign(np.sum(self.alpha[c] * y_bin * self.K[i])) !=
↪y_bin[i]:
                    self.alpha[c][i] += 1
                    count = 0
                else:
                    count += 1
                    i = (i + 1) % N
                    n_iter += 1
            print("Training done.")

        def predict(self, X_test):
            """Retourne la classe prédite pour chaque x_test."""
            scores = np.zeros((len(X_test), self.n_classes))
            for i, x in enumerate(X_test):
                k = self.kernel_fn(x, self.X, self.sigma)
                for c in self.classes:
                    y_bin = np.where(self.train_y == c, 1, -1)
                    scores[i, c] = np.sum(self.alpha[c] * y_bin * k)
            return np.argmax(scores, axis=1)

```

```

[147]: def rbf_kernel_svm(X,Y, sigma):
        dists = np.sum(X**2, axis=1)[:,None] + np.sum(Y**2, axis=1)[None, :] - 2 *
↪X @ Y.T
        return np.exp(-dists / (2*sigma**2))

class SVM:
    def __init__(self, sigma=1.0, max_iter=5, sample_weights=None):
        self.sigma = sigma
        self.max_iter = max_iter
        self.sample_weights = sample_weights

    def fit(self, X, y):
        self.X = X
        self.y = y
        self.classes = np.unique(y)
        self.K = rbf_kernel_svm(X,X,self.sigma)

        N = X.shape[0]

```

```

self.alpha = {}

for c in self.classes:
    print(f"train class {c} vs rest")
    y_bin = np.where(y == c, 1, -1)
    alpha_c = np.zeros(N)

    for it in range(self.max_iter):
        for i in range(N):
            f = np.sum(alpha_c * y_bin * self.K[:, i])
            if y_bin[i] * f <= 0:
                alpha_c[i] += self.sample_weights[i]

        self.alpha[c] = alpha_c

def decision_function(self, X_test):
    K_test = rbf_kernel_svm(X_test, self.X, self.sigma)

    scores = []
    for c in self.classes:
        y_bin = np.where(self.y == c, 1, -1)
        s = K_test @ (self.alpha[c] * y_bin)
        scores.append(s)

    return np.vstack(scores).T

def predict(self, X_test):
    scores = self.decision_function(X_test)
    return self.classes[np.argmax(scores, axis=1)]

```

```

[148]: # --- Load training data ---
path_to_data = 'ift-3395-6390-kaggle-2-competition-fall-2025/train_data.pkl'
with open(path_to_data, "rb") as f:
    train_data = pickle.load(f)

X_imgs = train_data["images"].astype(np.float32)

y = train_data["labels"].reshape(-1)
X_imgs = (X_imgs - X_imgs.min()) / (X_imgs.max() - X_imgs.min() + 1e-6)
X_imgs = (X_imgs - X_imgs.mean()) / (X_imgs.std() + 1e-6)

```

```

[149]: def radial_profile(img):
    """Calcule le profil radial moyen d'une image."""
    h, w = img.shape
    y, x = np.ogrid[:h, :w]
    r = np.sqrt((x - w//2)**2 + (y - h//2)**2).astype(int)

```

```
return np.bincount(r.ravel(), img.ravel()) / np.bincount(r.ravel())
```

```
[150]: def extract_simple_stats(img):
        gray = img.mean(axis=2)
        return np.array([gray.mean(), gray.std(), gray.min(), gray.max()], dtype=np.
        ↪float32)
```

```
[151]: def simple_augment(images):
        flips = images[:, :, ::-1, :] # inversion horizontale
        noise = images + 0.01*np.random.randn(*images.shape)
        return np.concatenate([images, flips,
                               noise
                               ],
                               axis=0)
```

```
[152]: def fft_features(images):
        """Extrait les caractéristiques FFT d'images."""
        gray = images.mean(axis=3)
        F = np.fft.fft2(gray, axes=(1, 2))
        return np.abs(np.fft.fftshift(F, axes=(1, 2)))
```

```
[153]: X_imgs = simple_augment(X_imgs)
        y = np.concatenate([y, y, y])

        fft_mag = fft_features(X_imgs)
        X_fft = np.array([radial_profile(img) for img in fft_mag], dtype=np.float32)

        X_stats = np.array([extract_simple_stats(img) for img in X_imgs], dtype=np.
        ↪float32)
        X = np.hstack([X_fft, X_stats])

        scaler = StandardScaler()
        X = scaler.fit_transform(X)
```

```
[154]: X_train, X_test, y_train, y_test = train_test_split(
        X, y, test_size=0.2, random_state=0
    )
```

```
[155]: """
        model = SVM(sigma=5, max_iter=5, sample_weights=sample_weights)
        model.fit(X_train, y_train)
        """
```

```
[155]: '\nmodel = SVM(sigma=5, max_iter=5,
        sample_weights=sample_weights)\nmodel.fit(X_train, y_train)\n'
```

```
[156]: model = KernelPerceptron(kernel_fn=rbf_kernel, n_classes=5, sigma=2)
model.fit(X_train, y_train, max_epochs=5)
```

```
Training classifier for class 0...
Training classifier for class 1...
Training classifier for class 2...
Training classifier for class 3...
Training classifier for class 4...
Training done.
```

```
[157]: """
model = SoftmaxClassifier(input_dim=X.shape[1], num_classes=num_classes, reg=0.
    ↪0.05, seed=0)
model.fit(X_train, y_train, lr=2, n_steps=5000, sample_weights=sample_weights)
"""
```

```
[157]: '\nmodel = SoftmaxClassifier(input_dim=X.shape[1], num_classes=num_classes,
reg=0.05, seed=0)\nmodel.fit(X_train, y_train, lr=2, n_steps=5000,
sample_weights=sample_weights)\n'
```

Understanding Deep Learning Requires Rethinking Generalization (Zhang et al., ICLR 2017) → importance de la fréquence dans image classification. Fourier Transform in Image Processing — Gonzalez & Woods (exemples de séparation de classes via magnitude spectrale) FOURIER CNNs (Rippel et al., 2015) → montre qu'une représentation FFT est plus stable et expressive que pixels bruts. Spectral Representations for Image Classification (several IEEE papers) → radial power spectra suffisent à classifier des textures complexes. Why Do Deep Neural Networks Learn High-Frequency Patterns? (Xu et al., NeurIPS 2019)

```
[158]: y_pred = model.predict(X_test)
acc = (y_pred == y_test).mean()
print("Test accuracy =", acc)

cm = confusion_matrix(y_test, y_pred)
bal_acc = balanced_accuracy(y_test, y_pred)
rec = recall_per_class(cm)

print("Balanced acc :", bal_acc)
print("Recall par classe :", rec)
print("Recall moyen :", rec.mean())
print(cm)
```

```
Test accuracy = 0.6851851851851852
Balanced acc : 0.6602831089211119
Recall par classe : [0.7366548  0.88059701 0.61068702 0.62903226 0.44444444]
Recall moyen : 0.6602831089211119
[[207  38  19  10   7]
 [  6  59   2   0   0]
 [  7  22  80  11  11]
 [  7  19  17  78   3]
```

```
[ 1 11  7  6 20]
```

```
[159]: pickle.dump((model, scaler), open("model_test1.pkl", "wb"))
```

```
[ ]: # -----
# 1. Charger le modèle entraîné
# -----
model, scaler = pickle.load(open("model_test1.pkl", "rb"))

# -----
# 2. Charger le test_data.pkl
# -----
with open("ift-3395-6390-kaggle-2-competition-fall-2025/test_data.pkl", "rb") as f:
    test_data = pickle.load(f)

X_test_imgs = test_data["images"]

X_test_imgs = test_data["images"].astype(np.float32)

X_test_imgs = (X_test_imgs - X_test_imgs.min()) / (X_test_imgs.max() -
    X_test_imgs.min() + 1e-6)
X_test_imgs = (X_test_imgs - X_test_imgs.mean()) / (X_test_imgs.std() + 1e-6)

# -----
# 4. Normaliser avec les stats du train
# -----
fft_mag_test = fft_features(X_test_imgs)
X_fft_test = np.array([radial_profile(img) for img in fft_mag_test], dtype=np.
    float32)

X_stats_test = np.array([extract_simple_stats(img) for img in X_test_imgs],
    dtype=np.float32)

X_test_feats = np.hstack([X_fft_test, X_stats_test])

X_test_norm = scaler.transform(X_test_feats)

# -----
# 5. Prédire
# -----

y_pred = model.predict(X_test_norm).astype(int)

# -----
# 6. Générer le CSV Kaggle
# -----
```

```

df = pd.DataFrame({
    "ID": np.arange(1, len(y_pred)+1),
    "Label": y_pred
})

df.to_csv("ift3395_YAPS_MCS_V13.csv", index=False)

print("Fichier 'submission.csv' généré !")

#print(df.head())

df1 = pd.read_csv("ift3395_YAPS_MCS_V13.csv")
df2 = pd.read_csv("ift3395_YamirPoldoSilvaV9_debug.csv")

comparison = df1.compare(df2)
print(comparison)
print("Nombre de différences :", len(comparison))

```

Fichier 'submission.csv' généré !

	Label	
	self	other
1	3.0	2.0
2	0.0	1.0
6	1.0	0.0
7	2.0	0.0
9	1.0	2.0
..
393	1.0	4.0
394	1.0	3.0
395	1.0	2.0
396	2.0	0.0
397	3.0	4.0

[240 rows x 2 columns]

Nombre de différences : 240