

# Ruby on Rails 5.x

*Do início ao fim!*

# **Consumindo uma API (View/Controller)**

# Consumindo uma API (View/Controller)

- API do CEP
  - `https://viacep.com.br/`

# Consumindo uma API (View/Controller)

- Migration

```
rails g migration AddZipCodeToUserProfiles
```

```
zip_code:string
```

```
rails db:migrate
```

# Consumindo uma API (View/Controller)

- Profile Controller

```
# app/controllers/users_backoffice/profile_controller.rb

def params_user
  params.require(:user).permit(:first_name, :last_name, :email,
    :password, :password_confirmation,
    user_profile_attributes: [:id, :zip_code, :address, :gender,
    :birthdate, :avatar])
end
```

# Consumindo uma API (View/Controller)

- Controller Zip Code

```
rails g controller users_backoffice/zip_code
```

```
#####
```

```
class UsersBackoffice::ZipCodeController < UsersBackofficeController
  def show
    @cep = CEP.new(params[:zip_code])
  end
end
```

# Consumindo uma API (View/Controller)

- Route

```
namespace :users_backoffice do
  get 'welcome/index'
  get 'profile', to: 'profile#edit'
  patch 'profile', to: 'profile#update'
  get 'zip_code', to: 'zip_code#show'
end
```

# Consumindo uma API (View/Controller)

- `link_to, remote: true`

```
https://api.rubyonrails.org/v5.2.3/classes/ActionView/Helpers/UrlHelper.html#method-i-link_to
```



# Consumindo uma API (View/Controller)

```
# app/views/users_backoffice/profile/edit.html.erb

<div class="form-group">
  <%= profile_form.label :address, class:"control-label col-md-3 col-sm-3
col-xs-12" %>
  <div class="col-md-6 col-sm-6 col-xs-12">
    <div class="input-group">
      <%= profile_form.text_field :zip_code, class:"form-control col-md-7
col-xs-12"%>
      <span class="input-group-btn">
        <%= link_to "Buscar CEP", users_backoffice_zip_code_path, remote:
true, class:"btn btn-primary", id: 'zip-code-link' %>
      </span>
    </div>
  </div>
</div>

...
```

# Consumindo uma API (View/Controller)

```
# app/views/users_backoffice/profile/edit.html.erb

...

<script>
  var zip_code_link = document.getElementById("zip-code-link");
  let zip_code_input =
document.getElementById("user_user_profile_attributes_zip_code");

  zip_code_input.addEventListener("change", function () {
    zip_code_link.href = '<%= users_backoffice_zip_code_path
%>/?zip_code=' + zip_code_input.value;
  });
</script>
</span>
</div>
</div>
</div>
```

# Consumindo uma API (View/Controller)

- Show.JS

```
# app/views/users_backoffice/zip_code/show.js.erb

var address =
document.getElementById("user_user_profile_attributes_address");

address.value = '<%= @cep.endereco %>';
```