

Ruby on Rails 5.x

Do início ao fim!

Full-text Search / Instalando o Elasticsearch

Full-text Search / Instalando o Elasticsearch

- **Elasticsearch**

`https://www.elastic.co/products/elasticsearch`

Full-text Search / Instalando o Elasticsearch

- **Bonsai**

`https://bonsai.io/`

Full-text Search / Instalando o Elasticsearch

- **Instalando**

`https://www.elastic.co/guide/en/elasticsearch/reference/current/deb.html`

Full-text Search / Instalando o Elasticsearch

● Instalando

- `sudo apt-get update`
- `sudo apt-get install default-jdk`
- `wget`
`https://artifacts.elastic.co/downloads/elasticsearch/elasticsearch-7.3.0-amd64.deb`
- `wget`
`https://artifacts.elastic.co/downloads/elasticsearch/elasticsearch-7.3.0-amd64.deb.sha512`
- `shasum -a 512 -c elasticsearch-7.3.0-amd64.deb.sha512`
- `sudo dpkg -i elasticsearch-7.3.0-amd64.deb`

Full-text Search / Instalando o Elasticsearch

- **Ajuste o Vagrantfile e reinicie o vagrant**

```
# Vagrantfile
config.vm.provider "virtualbox" do |v|
  v.memory = 2048
end

config.vm.network :forwarded_port, guest: 9200, host:
9200 # Elasticsearch

vagrant reload
```

Full-text Search / Instalando o Elasticsearch

- **Iniciando**

```
ps -p 1
```

systemd

```
sudo systemctl start elasticsearch.service
```

init

```
sudo -i service elasticsearch start
```


Full-text Search / Instalando o Elasticsearch

- **Testando**

```
curl 'http://localhost:9200'
```

Full-text Search / Instalando o Elasticsearch

- **Ajustando o Elasticsearch**

```
sudo vim /etc/elasticsearch/elasticsearch.yml
```

```
# alterar
```

```
network.host: 0.0.0.0
```

```
cluster.initial_master_nodes: ["node-1"]
```

Full-text Search / Instalando o Elasticsearch

- Reinicie o Elasticsearch

```
sudo systemctl restart elasticsearch.service
```

Full-text Search / Instalando o Elasticsearch

- **Teste pelo navegador**

`http://localhost:9200`