

Лабораторная работа №2

Управление пользователями и группами

Руслан Алиев

16 декабря 2025

Российский университет дружбы народов, Москва, Россия

Цель работы

Получение практических навыков управления учётными записями пользователей и групп в операционной системе Linux.

Ход выполнения работы

Определение текущего пользователя

```
raliev@raliev:~$ whoami
raliev
raliev@raliev:~$ id
uid=1000(raliev) gid=1000(raliev) groups=1000(raliev),10(wheel) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
raliev@raliev:~$ su
Password:
root@raliev:/home/raliev# id
uid=0(root) gid=0(root) groups=0(root) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
root@raliev:/home/raliev#
exit
raliev@raliev:~$ █
```

Рис. 1: Определение текущего пользователя

```
raliev@raliev:~$ whoami
raliev
raliev@raliev:~$ id
uid=1000(raliev) gid=1000(raliev) groups=1000(raliev),10(wheel) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
raliev@raliev:~$ su
Password:
root@raliev:/home/raliev# id
uid=0(root) gid=0(root) groups=0(root) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
root@raliev:/home/raliev#
exit
raliev@raliev:~$ █
```

Рис. 2: Работа под пользователем root

Просмотр конфигурации sudo

```
raliev@raliev:~ -- sudo -i visudo
#
# Defaults    env_keep += "HOME"

Defaults     secure_path = /sbin:/bin:/usr/sbin:/usr/bin

## Next comes the main part: which users can run what software on
## which machines (the sudoers file can be shared between multiple
## systems).
## Syntax:
##
##      user    MACHINE=COMMANDS
##
## The COMMANDS section may have other options added to it.
##
## Allow root to run any commands anywhere
root    ALL=(ALL)        ALL

## Allows members of the 'sys' group to run networking, software,
## service management apps and more.
## %sys ALL = NETWORKING, SOFTWARE, SERVICES, STORAGE, DELEGATING, PROCESSES, LOCATE, DRIVERS

## Allows people in group wheel to run all commands
%wheel  ALL=(ALL)        ALL

## Same thing without a password
%wheel  ALL=(ALL)        NOPASSWD: ALL

## Allows members of the users group to mount and unmount the
## cdrom as root
%users  ALL=/sbin/mount /mnt/cdrom, /sbin/umount /mnt/cdrom

## Allows members of the users group to shutdown this system
%users  localhost=/sbin/shutdown -h now

## Read drop-in files from /etc/sudoers.d (the # here does not mean a comment)
#include_dir /etc/sudoers.d
```

```
-----  
raliev@raliev:~$ sudo -i visudo  
[sudo] password for raliev:  
raliev@raliev:~$  
raliev@raliev:~$ sudo -i useradd -G wheel alice  
raliev@raliev:~$ id alice  
uid=1001(alice) gid=1001(alice) groups=1001(alice),10(wheel)  
raliev@raliev:~$ sudo -i passwd alice  
New password:  
BAD PASSWORD: The password is shorter than 8 characters  
Retype new password:  
passwd: password updated successfully  
-----
```

Рис. 4: Создание пользователя alice


```
raliev@raliev:~$ su alice
```

```
Password:
```

```
alice@raliev:/home/raliev$ sudo useradd bob
```

We trust you have received the usual lecture from the local System Administrator. It usually boils down to these three things:

- #1) Respect the privacy of others.
- #2) Think before you type.
- #3) With great power comes great responsibility.

For security reasons, the password you type will not be visible.

```
[sudo] password for alice:
```

```
alice@raliev:/home/raliev$ sudo passwd bob
```

```
New password:
```

```
BAD PASSWORD: The password is shorter than 8 characters
```

```
Retype new password:
```

```
passwd: password updated successfully
```

```
alice@raliev:/home/raliev$ id bob
```

```
uid=1002(bob) gid=1002(bob) groups=1002(bob)
```

Рис. 5: Создание пользователя bob



alice@raliev:/home/raliev – vim /etc/login.defs

```
# the user to be removed (passed as the first argument).
#
#USERDEL_CMD    /usr/sbin/userdel_local

#
# Enables userdel(8) to remove user groups if no members exist.
#
USERGROUPS_ENAB no

#
# If set to a non-zero number, the shadow utilities will make sure that
# groups never have more than this number of users on one line.
# This permits to support split groups (groups split into multiple lines,
# with the same group ID, to avoid limitation of the line length in the
# group file).
#
# 0 is the default value and disables this feature.
#
#MAX_MEMBERS_PER_GROUP 0

#
# If useradd(8) should create home directories for users by default (non
# system users only).
# This option is overridden with the -M or -m flags on the useradd(8)
# command-line.
#
CREATE_HOME      yes

#
# Force use shadow, even if shadow passwd & shadow group files are
# missing.
#
#FORCE_SHADOW    yes

#
# Select the HMAC cryptography algorithm
```



alice@raliev:/etc/skel – vim .bashrc

/etc/skel

```
# .bashrc

# Source global definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
fi

# User specific environment
if ! [[ "$PATH" =~ "$HOME/.local/bin:$HOME/bin:" ]]; then
    PATH="$HOME/.local/bin:$HOME/bin:$PATH"
fi
export PATH

# Uncomment the following line if you don't like systemctl's auto-paging feature:
# export SYSTEMD_PAGER=

# User specific aliases and functions
if [ -d ~/.bashrc.d ]; then
    for rc in ~/.bashrc.d/*; do
        if [ -f "$rc" ]; then
            . "$rc"
        fi
    done
fi
unset rc
export EDITOR=/usr/bin/vim
```

```
root@raliev:/etc/skel# su alice
alice@raliev:/etc/skel$ sudo -i useradd carol
alice@raliev:/etc/skel$ sudo passwd carol
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: password updated successfully
alice@raliev:/etc/skel$ su carol
Password:
carol@raliev:/etc/skel$ id
uid=1003(carol) gid=100(users) groups=100(users) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
carol@raliev:/etc/skel$ cd
carol@raliev:~$ ls -Al
total 12
-rw-r--r--. 1 carol users 18 Oct 29 2024 .bash_logout
-rw-r--r--. 1 carol users 144 Oct 29 2024 .bash_profile
-rw-r--r--. 1 carol users 549 Dec 14 11:27 .bashrc
drwxr-xr-x. 2 carol users 6 Dec 14 11:26 Documents
drwxr-xr-x. 4 carol users 39 Oct 2 18:52 .mozilla
drwxr-xr-x. 2 carol users 6 Dec 14 11:26 Pictures
carol@raliev:~$ █
```

Рис. 8: Домашний каталог carol

```
alice@raliev:/etc/skel$ sudo cat /etc/shadow | grep carol
carol:$y$j9T$kf0eKV3Hk0WSPLRDUSvL.$EhupcKWkTMDT8r6BDRQGdT/CKKsRm5Q059KPHB3zPLA:20436:0:99999:7:::
alice@raliev:/etc/skel$ sudo passwd -n 30 -w 3 -x 90 carol
passwd: password changed.
alice@raliev:/etc/skel$ sudo cat /etc/shadow | grep carol
carol:$y$j9T$kf0eKV3Hk0WSPLRDUSvL.$EhupcKWkTMDT8r6BDRQGdT/CKKsRm5Q059KPHB3zPLA:20436:30:90:3:::
alice@raliev:/etc/skel$
alice@raliev:/etc/skel$ sudo grep alice /etc/passwd /etc/shadow /etc/group
/etc/passwd:alice:x:1001:1001::/home/alice:/bin/bash
/etc/shadow:alice:$y$j9T$NN0VCQbu/maUVuIzdia.w/$MA2tWxe/2g8JiCEcWkgqRs8RkeybY.mb1fDX8DCwh4:20436:0:99999:7:::
/etc/group:wheel:x:10:raliev,alice
/etc/group:alice:x:1001:
alice@raliev:/etc/skel$ sudo grep carol /etc/passwd /etc/shadow /etc/group
/etc/passwd:carol:x:1003:100::/home/carol:/bin/bash
/etc/shadow:carol:$y$j9T$kf0eKV3Hk0WSPLRDUSvL.$EhupcKWkTMDT8r6BDRQGdT/CKKsRm5Q059KPHB3zPLA:20436:30:90:3:::
alice@raliev:/etc/skel$
```

Рис. 9: Параметры пароля carol

```
alice@raliev:/etc/skel$  
alice@raliev:/etc/skel$ sudo groupadd main  
alice@raliev:/etc/skel$ sudo groupadd third  
alice@raliev:/etc/skel$ sudo usermod -aG main alice  
alice@raliev:/etc/skel$ sudo usermod -aG main bob  
alice@raliev:/etc/skel$ sudo usermod -aG third carol  
alice@raliev:/etc/skel$ id carol  
uid=1003(carol) gid=100(users) groups=100(users),1004(third)  
alice@raliev:/etc/skel$ id bob  
uid=1002(bob) gid=1002(bob) groups=1002(bob),1003(main)  
alice@raliev:/etc/skel$ id alice  
uid=1001(alice) gid=1001(alice) groups=1001(alice),10(wheel),1003(main)  
alice@raliev:/etc/skel$
```

Рис. 10: Проверка групп

Заключение

В ходе лабораторной работы были получены практические навыки администрирования пользователей и групп в Linux.

Освоены механизмы разграничения прав доступа, настройки sudo, управления паролями и группами, что является основой администрирования многопользовательских систем.