北京大学
PEKING UNIVERSITY

# Beyond OCR: A Survey of Document Intelligence from Structured Perception to Multimodal Question Answering

**JiaShu Yang**[1] **Chi Zhang**[1] **Xingyu Qi**[1] **Ning Zhang**[1] **Jie Wu**[1] **Lingxu Chen**[1] **Jiani Guo**[1]

[1]Peking University

## Abstract

Document intelligence connects the recognition of page content with reasoning over the evidence that documents contain. Its central difficulty is preserving useful information across representations: OCR can lose characters and reading order, table serialization can obscure cell relationships, visual compression can discard fine detail, and retrieval can omit evidence needed for an answer. This survey examines these interfaces across layout analysis, OCR, table understanding, text-based retrieval-augmented generation, and vision-language models for document question answering.

We organize representative approaches using five complementary axes: input representation, context span, evidence granularity, inference control, and validation. These axes expose combinations that a task-only or model-only taxonomy can obscure, including OCR-assisted visual systems, multimodal retrieval, and tool-assisted table reasoning. Within each area, we compare the bottlenecks addressed by different mechanisms, the costs they introduce, and the conditions under which their advantages may fail to transfer. We distinguish reported benchmark results from new experimental evidence and discuss the input access, model versions, retrieval settings, and computational budgets required for meaningful comparisons. Finally, we separate answer accuracy, evidence localization, evidence support, and execution correctness to formulate concrete evaluation needs. The resulting perspective treats modular, OCR-free, and agentic systems as complementary design choices and identifies evidence preservation and verification as a common research agenda.

**Project Page:** https://yang-jiashu.github.io/document-intelligence-survey/

**Code Repository:** https://github.com/Yang-Jiashu/document-intelligence-survey

**Correspondence:** jiashuyang827@gmail.com

## 1 Introduction

Documents communicate through words, spatial arrangement, tables, figures, and relations across pages. A question about a financial report may require recognizing a number, associating it with the correct column and unit, resolving a footnote on another page, and checking the computation used to produce the answer. Document intelligence therefore involves a sequence of information-preserving decisions. The final answer depends on which content is observed, how it is represented, which evidence is selected, and whether that evidence supports the requested conclusion.





**Figure 1** From a page to a source-backed answer. Text/layout, visual and hybrid representations feed evidence selection; the constructed sales example keeps the answer linked to its source cells.

Classical systems expose many of these decisions as separate OCR, layout, extraction, retrieval, and reasoning modules. Such interfaces support inspection and specialized optimization, but recognition and serialization errors can propagate. Vision-language models can instead consume page images directly and jointly model textual and visual signals. This changes where information can be lost: image resolution, visual-token compression, page selection, and context budgets become important constraints. Retrieval and agentic control can be applied to either representation. Consequently, modular, direct-visual, and hybrid systems should be compared under explicit task and resource conditions; architectural recency alone does not determine their relative effectiveness.

## 1.1 Scope and Relation to Existing Surveys

We focus on document-centered perception and question answering: recognizing and organizing page content, reasoning over tables and surrounding text, and retrieving and combining evidence across pages or document collections. General NLP and multimodal methods are included when they explain a mechanism used in these document settings. Results on translation, embodied interaction, or generic language benchmarks provide background only and do not establish document QA capability.

Existing surveys examine the transition toward LLM-based document AI [320] and organize multimodal document RAG by domain, retrieval modality, and granularity [87]. Our emphasis is the interface between these research areas: how a representation preserves or removes evidence, how a system selects and combines that evidence, and what its evaluation actually verifies. This emphasis motivates a cross-cutting comparison framework spanning perception, table reasoning, retrieval, and visual document models. It also connects model design with the conditions needed to interpret published evaluations.

## 1.2 Review Scope and Selection Principles

This is a curated narrative review. The bibliography combines foundational methods, document-specific systems, and evaluation resources. We prioritize work that introduces a distinct representation or inference mechanism, makes a document-specific failure mode observable, or provides a reusable benchmark or implementation. Multiple papers using similar mechanisms are grouped to explain a technical route; their frequency in the bibliography is not an estimate of the prevalence or superiority of that route. Coverage is selective, and we do not claim a database-complete search or retrospectively reconstructed screening counts.

Technical descriptions and the principal comparisons refer to original papers or official resources. We distinguish a paper's first public version from its later venue publication when discussing chronology. A chronology





**Figure 2** Selected document-AI papers by first public year. Yellow highlights mark verified official trained weights; daggers indicate partial/component releases. Names link to papers and highlights to weights; chronology does not imply model ancestry.

indicates when a representative capability appeared; it does not establish that an earlier approach became obsolete. Benchmark findings retain the scope of their reported model versions, input access, and evaluation settings. This survey introduces no newly executed model benchmark, and the reported literature results should be interpreted under their original protocols.

Figure 2 provides a chronological entry point to representative document-AI papers. OCR and layout models, structured document and table methods, and visual document models develop in parallel. The highlighted checkpoint links describe resource availability at the time of inspection, independently of paper dates; they do not rank model quality or establish a shared licensing regime.

## 1.3 An Evidence-Centered Comparison Framework

The chapters follow a practical reading order from perception to downstream reasoning. Their topics are not mutually exclusive method classes: table understanding is a task family, RAG is a system strategy, and a VLM is a model family. A visual table QA system may combine all three. We therefore use five complementary axes for comparison:

1. **Input representation**: extracted text, text with coordinates, page images, or a hybrid representation. This axis identifies both available information and preprocessing dependencies.
2. **Context span**: a region, a page, a multi-page document, or a collection. A model's supported context and the evidence actually supplied at inference are recorded separately.
3. **Evidence granularity**: tokens, layout regions, table cells, pages, or relations across documents. Retrieval granularity and output citation granularity can differ.
4. **Inference control**: a fixed pipeline, full-context processing, one-shot retrieval, or iterative retrieval and tool use. More iterations introduce additional latency and failure opportunities as well as possible benefits.
5. **Validation**: answer agreement, localization, support by the cited source, executable-program checks, or abstention when evidence is insufficient. Each validates a different property.

*A running example.* Consider an illustrative question: "What was the year-on-year change in operating margin, after applying the restatement described in the footnote?" The table, its units, the comparison year,





**Figure 3** Constructed cross-page example: table A and restatement B jointly support $150/1000 - 104/800 = 0.02$, a 2-percentage-point increase. Colored links preserve the source cells and correction used in the calculation.

and the footnote form a joint evidence requirement. An OCR pipeline can expose individual tokens and cells, but must preserve their alignment. A direct-visual model can retain the page appearance, but must receive sufficient resolution and the relevant pages. A retrieval system must recover both the table and the footnote; a high-scoring isolated page may be insufficient. An agent may revisit the document and execute arithmetic, but a valid calculation over the wrong row still produces an unsupported answer. This example is a conceptual comparison, not a new evaluation dataset or experimental result.

Figure 3 makes this dependency concrete. In the illustrative report, the printed margins are 15% and 12%, but the footnote restates the comparison-year operating profit from 96 to 104 while leaving revenue at 800. The corrected margin is therefore 13%, and the increase is 2 percentage points. Reading only the table would yield 3 percentage points. Each input route must preserve the table–footnote relationship before arithmetic can resolve the question.

### 1.4 Contributions and Organization

The survey makes three contributions. First, it connects the chapter-level literature through an explicit set of comparison axes, allowing systems to occupy several task and method categories. Second, it synthesizes representation, retrieval, and control trade-offs, including conditions under which additional modeling or inference complexity is unjustified. Third, it organizes evaluation around distinct answer, evidence, and execution properties and specifies the protocol information needed to compare published results.

Section 2 examines layout analysis and OCR. Sections 3 to 5 cover table reasoning, text-based document QA, and multimodal document systems. Section 6 discusses benchmarks and comparison protocols. Section 7 develops research directions from the failure modes exposed by these interfaces.

## 2 Document Layout Analysis and OCR

Perception constructs the textual and spatial evidence consumed by downstream document reasoning. Layout analysis and OCR are complementary interfaces, and their outputs may also be combined with direct visual representations.

## 2.1 Document Layout Analysis

A page is not a bag of words. The same number may be a table entry, a footnote marker or a page number; its role depends on position and relations to other content. Layout analysis makes those relations available to recognition, retrieval and reasoning. Three outputs should be distinguished: *regions* locate content, *relations* connect it, and *representations* encode both for a downstream model.

### 2.1.1 Geometric Structure Detection and Analysis

This line of work treats document layout as a purely visual or geometric structure, with the core objective of locating and classifying elements such as text blocks, images, and tables on a page. These methods output structured layout segmentation results that serve as fundamental inputs for subsequent document understanding tasks. Early work, such as The Document Spectrum for Page Layout Analysis [219], characterized the overall page structure from a signal processing perspective. Document layout analysis for semantic information extraction [2] and Visual Detection with Context for Document Layout Analysis [272] gradually combined layout analysis with information extraction requirements and contextual modeling; the latter introduced object detection frameworks like Faster R-CNN and explicitly utilized contextual information to improve detection robustness in complex layouts.

*Contextual and learned region detectors.* With the development of deep learning, a large body of research began adopting CNN- or Transformer-based detection models for layout analysis. For instance, Document Layout Analysis with an Enhanced Object Detector [196] used convolutional neural networks to estimate document structure boundaries, whereas Transformer-Based Approach for Document Layout Understanding [357] introduced global self-attention for document layout understanding. Document Layout Analysis Via Positional Encoding [399] employed positional encoding to alleviate the insufficient modeling of long-range spatial relationships by traditional detectors in complex layouts. VSR: A Unified Framework for Document Layout Analysis Combining Vision, Semantics and Relations [382] enhanced interaction modeling between layout elements by fusing vision, semantics, and relation modules. a Graphical Approach to Document Layout Analysis [313] utilized graph structures to establish global relationships between PDF elements and improve efficiency. Advanced Layout Analysis Models for Docling [170] evaluated the practicality of various object detection architectures, such as RT-DETR and DFINE, in industrial-grade systems.

*Transfer and detector design.* Addressing issues of generalization and adaptation to real-world scenarios, In-domain versus Out-of-domain Transfer Learning for Document Layout Analysis [57] systematically analyzed cross-domain performance degradation, while LD-DOC proposed a lightweight domain-adaptive layout analysis method to enhance cross-domain generalization [88]. Regarding detection framework design, recent methods have continuously improved model unification and efficiency. a Hybrid Approach for Document Layout Analysis in Document Images [259] enhanced the multi-scale and multi-category recognition capabilities of Transformer-based detectors through a hybrid matching mechanism. DocLayout-YOLO [396] balanced speed and accuracy by combining high-quality synthetic data with global-to-local perception modules. PP-DocLayout [281] proposed a unified detection model to support large-scale data construction, while DLAFormer [312] and Doc-DINO [61] further explored end-to-end Transformer architectures to unify the modeling of detection, classification, and logical structural relationships.

Consider a report table whose unit appears above the box and whose qualification appears in a footnote below it. Cropping the cells accurately still removes context needed to interpret their values. A useful structural output therefore includes the table's neighborhood and links to its notes. The region boundary and the boundary of sufficient evidence are not necessarily the same.

### 2.1.2 Layout-Aware Representation Learning

In this line of work, layout information is explicitly integrated into the model's representation learning process and jointly modeled with text content, enabling the model to capture implicit spatial structures and semantic relationships at the representational level. Since LayoutLM [352] first introduced the joint modeling of text content and 2D positional information into the Transformer pre-training framework, document layout

understanding transitioned from pure visual parsing to a representation learning paradigm. This work allowed the model to jointly learn text and layout during pre-training by modeling token coordinate embeddings alongside text embeddings. However, relying solely on coordinate embeddings and text masking tasks made it difficult to fully characterize complex spatial relationships. Position Masking [248] proposed masking both text and positional embeddings during pre-training, forcing the model to explicitly predict spatial positions and thereby strengthening its ability to model positional semantics.

In the multimodal direction, LAMPRET [338] further introduced visual features into layout-aware pre-training, aligning text, layout, and visual information through cross-modal contrastive learning. Addressing the issue that traditional methods implicitly rely on language-specific features, LiLT [310] proposed a language-independent Layout Transformer that modeled spatial relationships between tokens through a layout-only self-attention mechanism, enhancing robustness in cross-lingual and low-resource scenarios. XYLayoutLM [95] focused on OCR ordering noise and the insufficient modeling of reading orders, introducing the Augmented XY Cut algorithm to generate more reasonable token sequences combined with dilated conditional position encodings to improve stability in complex layouts. Regarding the expressive power of spatial relationships, ERNIE-Layout [231] explicitly modeled richer spatial and structural relationships on a page through layout-knowledge-enhanced pre-training tasks. Beyond Layout Embedding [408] approached the problem from the attention mechanism level, introducing Gaussian-bias-based layout attention, allowing the model to dynamically adjust attention distributions based on the relative distance and orientation between entities.

Furthermore, LayoutMask [301] strengthened the semantic interaction between text and layout during pre-training by designing differentiated masking strategies for different layout units. Beyond pre-training objectives and attention mechanisms, the layout representation format itself has continued to evolve. Multi-scale Cell-based Layout Representation [265] proposed a cell-level layout representation based on row and column indices, fusing word-level and cell-level spatial information through a multi-scale design to make layout expression closer to the document's hierarchical logical structure. In recent years, research has begun to explicitly model layout structures in relational forms. Modeling Layout Reading Order as Ordering Relations [372] elevated reading order from a linear sequence to directed ordering relations, injecting these relations as enhancement signals into the layout-aware model's attention. Based on this, a Graph-Augmented Multi-Stage Transformer Model [9] further introduced graph neural networks and a multi-stage Transformer architecture to progressively refine fine-grained structural representations by explicitly modeling the spatial and semantic relationships between layout components.

### 2.1.3 Layout-Aware Reasoning and Generation

As the capabilities of Large Language Models (LLMs) have improved, researchers have gradually realized that relying solely on text content is insufficient for complex document understanding; the layout structure of a document provides critical reasoning cues. Although early research modeled layout as an input feature, the robustness of such approaches in real-world scenarios remained limited. Unveiling the Deficiencies of Pre-trained Text-and-Layout Models in Real-world Visually-rich Document Information Extraction [373] systematically analyzed the performance degradation of models like LayoutLM and ERNIE-Layout on real documents, pointing out that existing methods struggled to fully utilize complex layout structures. This has pushed research from treating "layout as an input feature" toward "layout participating in the reasoning process." Based on this insight, DocLLM [307] conditions generative language modeling on text and bounding-box information through disentangled attention. It does not use an image encoder: its spatial input represents layout geometry rather than the complete visual content of a document. mPLUG-DocOwl 1.5 [111] further unified the modeling of document structure from a visual perspective, enabling the model to understand layout relationships without relying on OCR. Meanwhile, LayoutLLM [173] enabled the model to actively consider layout structure during generation through layout instruction tuning. LAPDoc [146] explicitly incorporated document structure into prompts through layout-aware prompting, reducing reasoning errors caused by ignoring layout. Furthermore, ReLayout [126] focused on the lack of precise annotations in real-world applications, enabling the model to learn effective structural information relying only on OCR through layout-enhanced pre-training. Collectively, these works provide several ways for layout to condition generation. Their input modalities should be recorded explicitly: the use of spatial coordinates does not make a text-layout model equivalent to a model that also observes page pixels.

*Layout as an evidence-access structure.* As task complexity increased, researchers further discovered that in cross-page and multi-hop reasoning scenarios, using layout only to assist reasoning is still insufficient because key information is often distributed across different locations. Consequently, layout began to be used to organize the retrieval process, helping models locate relevant evidence more accurately. In this direction, LAD-RAG [273] enabled models to perform cross-page retrieval using layout structures by constructing document layout graphs. SuperRAG [356] similarly modeled layout relations as graph structures and combined them with graph neural networks to improve multi-hop reasoning capabilities. Structured Multimodal RAG [194] improved the relevance of retrieval results and reduced erroneous generation by utilizing spatial relationships between document blocks. Meanwhile, research has shown that the method of partitioning retrieval units significantly impacts performance. Document Segmentation Matters for RAG [324] proposed a pseudo-instruction-based chunking method to make retrieval blocks more aligned with semantic structures. Enhancing RAG System Performance Through Semantic Layout Chunking [239] combined semantic and layout information for chunking to maintain document structural consistency. In more structured document scenarios, TabRAG [266] utilized the row-column structure of tables to improve retrieval effectiveness, while From Chart to QA Pairs [260] constructed a QA dataset for chart-based documents, driving the development of layout-aware reasoning research from a data perspective. These methods demonstrate that layout can serve not only as an auxiliary for reasoning but also as a key structure for organizing the retrieval process.

*Layout as a generation target.* Building upon these retrieval-oriented approaches, research has further explored treating layout itself as a generation target, enabling models to actively generate document layouts that conform to structural constraints. LayoutKAG [286] improved the stability of layout generation by combining layout knowledge with retrieval examples. LayoutCoT [263] decomposed layout generation into a step-by-step reasoning process, resulting in more structurally consistent layouts. LayoutRAG [343] addressed information deficiency by retrieving relevant layout templates to assist generation. CAL-RAG [81] enabled the coordination of content and layout generation through multi-agent collaboration. OmniDocLayout [129] allowed the model to generate an overall structure before localized details through a step-by-step refinement approach. These works mark the transformation of layout from a passive input to an object of active model generation.

*Joint structural control.* At an even higher level of integration, the latest research has begun to treat layout as a unified structure connecting the retrieval, reasoning, and generation modules, making it a core component of a complete system. CMRAG [33] made the retrieval and generation processes more consistent by jointly modeling visual, textual, and layout information. SymbioticRAG [280] introduced human feedback, allowing layout information to guide retrieval and generation at critical steps. HySemRAG [90] improved the stability and accuracy of complex document reasoning by combining layout structure with semantic information.

These roles of layout form an overlapping design space. Treating layout as an input feature, retrieval structure, or generated object addresses different tasks and cannot be placed on a single performance scale. For document QA, the central comparison is whether an interface preserves the relations needed for the question: reading order for text passages, row–column and header links for tables, and page or region identifiers for supporting evidence. Layout generation work is included as a related use of structural modeling, not as evidence of downstream QA gains.

### 2.1.4 Layout Analysis Evaluation

Layout detection datasets, downstream document QA tasks, and annotation strategies provide complementary evidence about document understanding. DocVQA [190] introduced large-scale question–document pairs for document-image question answering. Later region-based work, such as A Region-based Document VQA [339], explored how content from different document regions can be integrated with textual information. These QA settings test the use of structure downstream, rather than directly measuring the segmentation quality of a layout detector. In the field of layout analysis, PubLayNet [397] achieved layout annotation for over 360,000 pages by automatically aligning PDFs and XML files of academic articles, providing a reliable training foundation for deep learning models. Subsequently, DocBank [154] further refined layout element labels, enabling models to understand document structures across richer dimensions. To enhance model generalization





**Figure 4** Three representations of the same page: flat OCR, visual patches and structured cells. The constructed OCR failure loses the association between values and year headers; the other panels show information that can be retained.

across multi-domain documents, DocLayNet [235] provided over 80,000 pages of fine-grained human-annotated data from various fields, allowing layout analysis to cover diverse scenarios such as academic, financial, patent, and legal documents. Meanwhile, the ICDAR competition series has long released various layout analysis tasks, from early complex layout recognition competitions to the latest ICDAR 2023 Competition on Robust Layout Segmentation in Corporate Documents [11], driving the community to continuously improve algorithmic robustness and practicality under unified evaluation mechanisms. Together, these resources support distinct measurements: geometric and semantic layout quality, transfer across document domains, and the usefulness of structured evidence for downstream QA. Their collection and annotation strategies coexist and should be chosen according to the evaluation objective.

*What layout metrics leave unresolved.* Region overlap and category accuracy assess whether a detector finds the intended elements; they do not establish correct reading order, header–cell association, or answer support. A visually accurate box can still be attached to the wrong semantic role, and a high-quality text transcript can be linearized in an order that changes its meaning. Layout benchmarks and downstream QA should therefore be connected through explicit relation and evidence annotations. When a reported improvement is measured on a particular layout dataset, its transfer to another document type or to QA remains a separate empirical question.

## 2.2 OCR

OCR converts page appearance into content that other components can search or manipulate. The practical design space is broader than recognizing a string: a system may return words with coordinates, a serialized table, a structured page or a direct answer. Figure 4 contrasts the information exposed by these interfaces.

### 2.2.1 Traditional Matching and Machine Learning Methods

First, the OCRopus open-source OCR system [21], serving as a milestone in open-source OCR, adopted a hybrid architectural design: the layout analysis stage relied on traditional rule-based methods (heuristic algorithms such as connected component analysis and projection methods), while the text line recognition module introduced shallow neural networks (Multi-Layer Perceptrons). Although this system did not fully break away from the traditional paradigm, it laid the engineering foundation for subsequent learning-driven architectures and represented a critical transitional form between rule-driven and data-driven methods. Subsequently, Statistical Learning for OCR Text Correction [193] systematically applied statistical learning to

the OCR post-processing stage for the first time, proposing a text correction framework based on regression models. By introducing external corpora to expand the candidate suggestion space and utilizing character-level statistical features (e.g., n-gram frequency, edit distance) to optimize recognition results, it opened a path for machine learning-assisted methods. Implementation of optical character recognition using machine learning [50] constructed a complete OCR pipeline covering image preprocessing, text region detection, character segmentation, and recognition stages, while introducing Support Vector Machines (SVM) and Random Forest algorithms in the character classification phase, significantly improving recognition robustness in complex backgrounds and multi-font scenarios. The work by Rajput et al. [218] focused on vertical-domain applications, using OCR-output text as input features and combining SVM with Random Forest to achieve automatic classification of key receipt fields (merchant name, amount, date), demonstrating the practical value of machine learning in structured information extraction. Saravanan et al. [366], in a cross-domain survey, listed OCR as a typical application case of machine learning in the field of cybersecurity, analyzing the mechanism of feature engineering-based text recognition methods in malicious document detection and highlighting the interdisciplinary value of OCR as a foundational perception technology.

*Input quality, segmentation and error detection.* Next, a Gaussian Process Upsampling Model for Improvements in Optical Character Recognition [242] addressed the problem of low-resolution document images by designing an upsampling model based on Gaussian processes. By modeling the spatial correlation between pixels, it generates high-quality super-resolution images that provide enhanced inputs for subsequent OCR processing and proved effective in historical document digitization scenarios. Multi-lingual optical character recognition system using the reinforcement learning of character segmenter [225] introduced reinforcement learning into the character segmentation stage, designing an intelligent segmentation agent based on Q-learning. Through a reward mechanism to optimize segmentation strategies, it significantly improves segmentation accuracy on mixed documents containing various character sets such as Latin, Cyrillic, and Arabic. Rerunning OCR: A Machine Learning Approach to Quality Assessment and Enhancement Prediction [254] proposed a supervised learning-based OCR quality assessment framework. By extracting image quality features (blur, contrast, noise level) and recognition confidence features, it trains a Random Forest classifier to predict whether OCR needs to be re-executed, effectively reducing redundant computation in historical document digitization. A Novel Machine Learning Based Approach for Post-OCR Error Detection [305] further focused on the error detection sub-task, designing a representation scheme containing multi-dimensional features such as character confidence, language context consistency, and glyph similarity. Combined with Gradient Boosting Trees, it built a high-precision error detection model that achieves superior F1 scores on standard historical document datasets, significantly outperforming rule-based baselines. Image preprocessing and modified adaptive thresholding for improving OCR [142] returned to basic preprocessing steps, proposing an improved adaptive thresholding algorithm combined with local contrast enhancement and noise suppression, and verified the method's effectiveness using PyTesseract, improving recognition accuracy in low-light and shadow-interference scenarios. Machine Learning in OCR Technology: Performance Analysis of Different OCR Methods for Slide-to-Text Conversion in Lecture Videos [116] conducted systematic experiments to compare the performance of mainstream OCR tools such as Tesseract, Google Cloud Vision, and ABBYY FineReader in lecture slide scenarios, analyzing the impact of image preprocessing on recognition results to provide empirical evidence for document digitization in the educational field.

*Task-specific OCR interfaces.* In terms of application, Machine Learning in Cyberbullying Detection from Social-Media Image or Screenshot with Optical Character Recognition [279] constructed a multimodal detection framework, first extracting text from images via OCR and then combining traditional NLP features with a Random Forest classifier to identify cyberbullying content, verifying the effectiveness of OCR+ML cross-modal analysis on social media datasets. OCR Text Recognition and Recommendation Using Machine Learning [117] explored downstream applications of OCR output text, designing a hybrid recommendation algorithm based on collaborative filtering and content features that used recognized text as a representation of user interests for personalized content recommendation. Enhancing OCR Performance through Post-OCR Models: Adopting Glyph Embedding for Improved Correction [38] proposed glyph embedding technology, encoding character visual features into low-dimensional vectors and combining them with logistic regression models to achieve character-level error correction, effectively reducing character error rates in mixed handwritten and printed

documents. Improving Inference Performance of Machine Learning with the Divide-and-Conquer Principle [137], although not an OCR-specific study, verified the effectiveness of the divide-and-conquer principle for inference acceleration on models like PaddleOCR, significantly reducing end-to-end OCR pipeline inference latency through task decomposition and parallel computing, providing optimization ideas for deployment on resource-constrained devices.

*Accessible reading and specialist documents.* Optical Character Recognition and Text to Speech Generation System using Machine Learning [222] built an end-to-end OCR-TTS system, employing Hidden Markov Models for prosody modeling in text-to-speech, verifying its utility in accessible reading scenarios. Optical Character Recognition Technology using Machine Learning [143], as a multi-language OCR development project report, details the design of character classifiers based on decision trees and k-NN. Ocular Biometry OCR: a machine learning algorithm leveraging optical character recognition to extract intra ocular lens biometry measurements [249] developed a specialized ML algorithm to extract intraocular lens biometry measurements from ophthalmic surgery report images, using Random Forest to address the domain-specific characteristics of medical text. High-Throughput Phenotyping using Computer Vision and Machine Learning [270] incorporates OCR as a component of an agricultural phenotyping pipeline, first extracting plant label text via OCR and then combining it with traditional machine learning classifiers to complete variety classification and growth state assessment.

*Correction from document redundancy.* Improving OCR using internal document redundancy [17] proposed an innovative unsupervised correction framework. By mining internal document redundancy (repeated headers/footers, templated fields, format consistency) and constructing self-supervised signals from it, the method can detect and correct recognition errors without external corpora, significantly reducing word error rates on low-quality scanned historical documents and representing a new direction for machine learning in resource-constrained scenarios.

### 2.2.2 Deep Learning Methods

First, Calamari-a high-performance tensorflow-based deep learning package for optical character recognition [333] released a high-performance open-source OCR toolkit. It employed CNNs to extract visual features, bidirectional LSTMs to model sequential dependencies, and the CTC loss function for end-to-end training, achieving excellent character accuracy on standard datasets and providing a reliable foundational architecture for industrial-grade OCR systems. The competition work by Zhang et al. [124], targeting the challenge of arithmetic expression recognition, designed deep convolutional neural networks to extract local symbol features combined with Convolutional Recurrent Neural Networks to model 2D spatial layouts and operator precedence, achieving high-precision expression structure recognition on the competition test set and demonstrating the ability of deep learning to handle complex spatial relationships. Deep learning-aided OCR techniques for Chinese uppercase characters in the application of Internet of Things [365] focused on the difficult problem of recognizing Chinese uppercase numerals. By comparing various CNN architectures such as ResNet, DenseNet, and MobileNet, it found that attention-enhanced DenseNet achieves extremely high character accuracy in financial invoice scenarios, providing a lightweight solution for IoT edge deployment. Self-supervised Data Bootstrapping for Deep Optical Character Recognition of Identity Documents [201] proposed a self-supervised data bootstrapping framework. By generating pseudo-labeled training data through synthetic perturbations (rotation, blur, noise) and combining it with a CNN character classifier, it significantly reduces data annotation costs in identity document recognition tasks. Chargrid-OCR: End-to-end Trainable Optical Character Recognition for Printed Documents using Instance Segmentation [243] introduced instance segmentation to OCR for the first time, using Mask R-CNN to directly output character-level segmentation masks. This avoids error accumulation in traditional detection-segmentation-recognition pipelines and achieves high-precision character-level localization on printed documents, establishing a new paradigm for end-to-end trainable OCR.

*Efficient and multilingual recognition.* Subsequently, more lightweight models and higher accuracy were pursued. PP-OCR: A Practical Ultra Lightweight OCR System [70] proposed a three-stage optimization strategy: using an improved DB (Differentiable Binarization) algorithm for lightweight text detection,

designing a small CRNN backbone network, and applying knowledge distillation to compress model size. The final release of an ultra-lightweight model of only 3.5MB maintains high accuracy in Chinese scenarios, promoting the large-scale deployment of OCR on mobile and embedded devices. Extraction of Information from Handwriting using Optical Character recognition and Neural Networks [197] constructed an end-to-end recognition system for handwritten text, fusing CNNs for stroke feature extraction, BiLSTMs for temporal dependency modeling, and CTC decoding for character sequence output. It achieves excellent word accuracy on standard handwriting datasets, effectively addressing the challenges of cursive writing and individual variations. A Multiplexed Network for End-to-End, Multilingual OCR [113] proposed a multiplexed network architecture that uniformly processed 6 major language families and 47 languages through a shared backbone and script-specific adapters, achieving high-precision end-to-end accuracy on multilingual datasets and significantly reducing the development cost of multilingual OCR systems. MMU-OCR-21: Towards End-to-End Urdu Text Recognition Using Deep Learning [211], targeting Urdu's characteristics such as right-to-left writing and character ligatures, constructed a large-scale corpus containing 1.2 million annotated characters and trained an attention-based encoder-decoder model, achieving high character accuracy on a newly constructed test set and filling a gap in low-resource language OCR research.

*Workflow analysis and structured extraction.* Then, Deep Learning Techniques for Optical Character Recognition [252], as a systematic survey, comprehensively analyzed the application of deep learning across the entire OCR workflow (image preprocessing, text detection, character segmentation, sequence recognition), comparing the pros and cons of various detection algorithms and recognition architectures to provide a technical selection guide for researchers. Developing Automated Optical Character Recognition System Using Machine Learning Algorithm to Solve Payment Verification Issues [267] designed an OCR system specific to payment vouchers, using Faster R-CNN to locate key field regions and an LSTM-CTC recognizer to extract structured information such as amounts, account numbers, and dates, achieving extremely high field extraction accuracy on real bank vouchers. A Deep Learning Technology based OCR Framework for Recognition Handwritten Expression and Text [91] proposed a framework to uniformly handle handwritten text and mathematical expressions, using a CNN-Transformer hybrid encoder to capture local strokes and global structures, combined with a tree decoder to reconstruct formula semantics. It achieves superior structural accuracy on standard datasets, significantly outperforming traditional staged methods. Optical Character Recognition for Electronic Invoices using AWS Services [228] constructed a cloud-native invoice processing system, integrating the EAST text detection and PaddleOCR recognition engines with a BERT language model for post-processing correction, achieving high-precision key field extraction on invoice datasets containing multiple languages.

*Application constraints and handwriting.* In practical scenarios, Resume Content Recognition and Organization Framework Using YOLOv8 and Tesseract OCR Deep Learning Models [257] used YOLOv8 for precise detection of resume fields (name, educational background, work experience), combined with Tesseract OCR to extract text content, which is then structured through a rule engine. It achieves high field recognition F1 scores on large-scale real resumes, significantly improving HR automation efficiency. Recognition of Arabic Air-Written Letters: Machine Learning, Convolutional Neural Networks, and Optical Character Recognition (OCR) Techniques [205], targeting Arabic letter recognition for air-writing (where characters are "written" in the air via gestures), designed a 3D-CNN to process temporal depth image sequences, achieving high character recognition accuracy on a self-built dataset and expanding OCR applications to new human-computer interaction scenarios. Analysis of Recent Deep Learning Techniques for Arabic Handwritten-Text OCR and Post-OCR Correction [208] systematically reviewed Arabic handwritten OCR technologies, focusing on the advantages of the CNN-LSTM-CTC architecture in handling ligatures and variant glyphs, and proposed a Transformer-based post-correction model to significantly reduce character error rates. Ensemble deep learning model for optical character recognition [262] proposed a multi-model ensemble strategy, fusing the prediction results of ResNet, DenseNet, and EfficientNet backbones through a weighted voting mechanism to improve robustness, surpassing the best performance of single models on challenging datasets containing noise, blur, and skew. Patel et al. [354] provided an in-depth analysis of the Convolutional Recurrent Neural Network architecture, using multi-layer CNNs for feature extraction, multi-layer BiLSTMs for sequence modeling, and CTC loss for training, verifying its robustness to images with diverse styles and complex backgrounds on several standard datasets and providing a reliable baseline for industrial-grade OCR.

*Scene variation and visual degradation.* Advancements in OCR: A Deep Learning Algorithm for Enhanced Text Recognition [258] proposed a CNN-RNN fusion architecture and designed a multi-scale feature pyramid to enhance small text detection, achieving high F-measure on curved text datasets and significantly improving text recognition performance in natural scenes. Wild OCR: Deep Learning Architecture for Text Recognition in Images [7] designed a robust recognition architecture for "wild" scenes (extreme lighting, occlusion, perspective distortion), introducing adversarial training to enhance model generalization and significantly improving accuracy over baseline methods on a self-built challenging dataset. ADOCRNet: A Deep Learning OCR for Arabic Documents Recognition [200] was specifically designed for Arabic documents, fusing CNNs for character feature extraction with bidirectional LSTMs to capture right-to-left sequence dependencies, achieving high word accuracy on standard datasets and effectively handling character ligatures and contextual variants. Vehicle VIN code recognition based on deep learning and OCR [165], targeting the challenge of Vehicle Identification Number (VIN) recognition, designed a two-stage architecture: YOLOv5 for precise VIN region localization and a lightweight CRNN for character recognition, achieving high complete VIN recognition rates in scenarios with complex lighting and partial occlusion. CV content recognition using YOLOv8 and Tesseract-OCR deep learning [251] built an automated resume classification system where YOLOv8 detects key field regions and Tesseract OCR extracts text, combined with a BERT classifier for job matching, achieving high classification accuracy on large-scale resume datasets. Automating the grading of handwritten examinations through the integration of optical character recognition and machine learning algorithms [89] developed an automated grading system for handwritten exam papers, using U-Net to segment answer regions and CRNN to recognize handwritten answers. When compared with standard answers for scoring, it showed extremely high consistency with manual grading in mathematics exam tests. Improving OCR quality in 19th century historical documents using a combined machine learning based approach [79] proposed a historical document enhancement framework combining GANs for image restoration with a Transformer-based recognizer, significantly reducing character error rates in a 19th-century newspaper digitization project. ExTTNet: A Deep Learning Algorithm for Extracting Table Texts from Invoice Images [6] was specifically designed for invoice tables, using Graph Convolutional Networks to model cell spatial relationships combined with CRNN for text recognition, achieving high table structure restoration accuracy on invoice datasets containing nested tables. TC-OCR: TableCraft OCR for Efficient Detection and Recognition of Table Structure and Content [8] proposed an end-to-end table recognition pipeline that uniformly handles table line detection, cell segmentation, and text recognition, achieving high structural recognition F1 scores on standard table datasets and significantly outperforming staged methods. DocParseNet: Advanced Semantic Segmentation and OCR Embeddings for Efficient Scanned Document Annotation [198] combines a modified UNet with shifted-MLP visual features, OCR-derived text embeddings using DistilBERT, and multimodal fusion for semantic annotation of scanned corporate agreements. This is a document segmentation and field-annotation method, whose reported segmentation metrics should not be interpreted as table-structure recognition or OCR transcription accuracy. ChartEye: A Deep Learning Framework for Chart Information Extraction [202] targeted chart information extraction, designing a multi-task learning framework to simultaneously detect legends, axes, and data labels, combined with OCR to extract numerical text, achieving high information extraction accuracy on standard chart datasets. OCR-Diff: A Two-Stage Deep Learning Framework for Optical Character Recognition Using Diffusion Model in Industrial Internet of Things [224] innovatively introduced diffusion models, using a diffusion model in the first stage to enhance low-quality images in industrial scenes and a CRNN in the second stage for text recognition, significantly improving accuracy in IIoT device nameplate recognition tasks. OCR Based Deep Learning Approach for Image Captioning [118] fused OCR with vision-language models, using advanced models like CLIP-GPT2 and BART to effectively handle the dual challenges of text extraction and description generation in images, achieving high BLEU scores on image captioning datasets containing text. An OCR Engine for Printed Receipt Images using Deep Learning Techniques [253] constructed a receipt-specific OCR engine using the MobileNetV3 lightweight backbone, achieving high field extraction accuracy on a self-built large-scale receipt dataset with a compact model size suitable for mobile deployment. Automatic Number Plate Detection using Deep Learning and OCR [221] and An Automatic Framework for Number Plate Detection using OCR and Deep Learning Approach [256] both focused on license plate recognition, using CNNs for feature extraction combined with CTC or attention-based decoder for end-to-end recognition, achieving high license plate number recognition accuracy under complex weather and lighting conditions. Efficient Vehicle Tracking and Authentication with YOLOv8:

Integrating Deep Learning and OCR for Real-Time License Plate Detection [128] built a real-time license plate authentication system where YOLOv8 achieves high frame rate detection, a lightweight CNN verifies mathematical operations (such as checksum calculations), and OCR extracts license plate text, achieving high authentication accuracy in traffic monitoring scenes. Document Digitization Using Deep Learning: Classification, Preprocessing, and OCR Optimization [199] proposed a full-process optimization framework for document digitization, using EfficientNet for document type classification, U-Net for image enhancement, and PaddleOCR for text recognition, achieving high-precision end-to-end recognition on mixed document sets. Decoding multiculturalism through linguistic landscapes: a deep learning–based OCR analysis of street view images [135] and Power Big Data Imbalance Analysis Based on Deep Learning OCR Algorithm [163] both applied deep learning OCR to social science research, the former analyzing the diversity of urban linguistic landscapes and the latter addressing textual data imbalance in the power industry, demonstrating the interdisciplinary value of OCR technology.

*Generative and structured outputs.* VISTA-OCR: Towards generative and interactive end to end OCR models [100] uses a lightweight CNN encoder and an mBART-based Transformer decoder, initialized from Donut, to autoregressively generate text and quantized spatial coordinates. Its prompt-controllable interface supports tasks such as region-based OCR and content-based localization through task-specific prompts. The General OCR Theory work [331] proposed the GOT (General OCR Transformer) unified model, which processed heterogeneous content such as regular text, mathematical formulas, tables, and handwriting simultaneously through multi-task learning, surpassing the average performance of specialized models in unified benchmarks and marking the beginning of the OCR-2.0 era. Automated Invoice Data Extraction: Using LLM and OCR [292] fused Large Language Models with OCR, first using PaddleOCR to extract raw text and then using an LLM for semantic parsing and structured extraction, achieving high field extraction F1 scores on multinational invoice datasets and significantly outperforming rule engine methods. Enhancing OCR in historical documents with complex layouts through machine learning [80], targeting historical documents with complex layouts, designed a Layout-Aware Transformer to explicitly model the spatial relationships and reading order of text blocks, significantly improving layout restoration accuracy on 19th-century multi-column newspapers. OCR approaches for humanities: Applications of artificial intelligence/machine learning on transcription and transliteration of historical documents [131] studied the application of AI and ML algorithms in the OCR of digitized historical documents, employing various deep learning methods to improve the accuracy of automatic text transcription. Overcoming the Challenge of Cyberbullying Detection in Images: A Deep Learning Approach with Image Captioning and OCR Integration [234] proposed a deep learning-based image cyberbullying detection method that extracts overlaid text content in images by fusing image captioning and OCR technology to achieve cross-modal content analysis.

### 2.2.3 VLM-Based OCR

Vision-Language Models (VLMs) couple visual perception with language modeling, enabling image-based transcription, structured extraction, and question answering within related interfaces. These capabilities broaden the outputs of OCR-centered systems, but transcription accuracy, structural recovery, and answer quality remain different evaluation targets. Direct image input also retains dependence on image resolution, visual-token allocation, and decoding behavior; it does not remove the need to recognize and localize text.

Multimodal deep networks for text and image-based document classification [10] pioneered the exploration of deep fusion between the visual features of document images and OCR text semantics, laying an early multimodal modeling paradigm for document image classification tasks. Ocean-OCR: Towards General OCR Application via a Vision-Language Model [31] adopts a LLaVA-style architecture consisting of a NaViT-style dynamic-resolution visual encoder, an MLP projector, and Qwen2.5-3B. Its evaluation includes document extraction, scene text recognition, and Chinese–English handwritten recognition, alongside general multimodal benchmarks. Meanwhile, DeepSeek-OCR: Contexts Optical Compression [332] re-examined the relationship between OCR and document understanding from the perspective of context compression, proposing a Contexts Optical Compression method that retains key information for text decoding and understanding using minimal visual tokens. dots.ocr: Multilingual Document Layout Parsing in a Single Vision-Language Model [158] proposed a unified single vision-language model for document layout parsing tasks, jointly training three

core sub-tasks—layout detection, text recognition, and relationship understanding—within an end-to-end framework.

*Specialist tools and hybrid parsing.* Regarding logical reasoning, DianJin - OCR-R1: Enhancing OCR Capabilities via a Reasoning-and-Tool Interleaved Vision-Language Model [30] proposed a new reasoning-and-tool interleaved framework to enhance the capabilities of VLMs in OCR tasks. It first utilizes the model's own OCR capability to identify image content, then calls multiple expert OCR tools as references, and finally "re-observes" the image and synthesizes all information through a reasoning process to generate the final result. MonkeyOCR [160] organizes document parsing around a Structure-Recognition-Relation (SRR) triplet, combining explicit structural processing with recognition and relation modeling. This hybrid design illustrates an alternative allocation of work between components, rather than demonstrating that the efficiency–accuracy trade-off has disappeared. MonkeyOCR v1.5 Technical Report: Unlocking Robust Document Parsing for Complex Patterns [376] further enhanced the ability to parse complex layouts and high-difficulty elements based on the original SRR, improving overall performance by designing a two-stage joint parsing pipeline. The first stage used a large multimodal model to jointly predict document layout and reading order, ensuring structural and sequential consistency; the second stage performed local recognition on each detected region, including text, tables, and formulas. InstructOCR2: a lightweight and efficient multi-modal language model for document understanding [299] was a lightweight multimodal language model specifically designed for OCR and visual document understanding tasks. It optimizes the alignment mechanism between visual text and image information structurally, enabling the model not only to accurately recognize text but also to better understand the spatial positions and contextual information of the text. PaddleOCR-VL: Boosting Multilingual Document Parsing via a 0.9B Ultra-Compact Vision-Language Model [52] was an ultra-compact vision-language model designed for document parsing that combines a dynamic-resolution visual encoder with a lightweight language model to achieve accurate recognition of complex elements such as text, tables, formulas, and charts. PaddleOCR 3.0 Technical Report [53] was an open-source OCR and document parsing toolkit proposing three core modules: multilingual text recognition, hierarchical document parsing, and key information extraction. TextHawk2: A Large Vision-Language Model Excels in Bilingual OCR and Grounding with 16x Fewer Tokens [370] achieved a significant improvement in fine-grained perception capabilities for OCR and visual grounding tasks through image token compression and visual encoding enhancement.

The interface matters as much as the component list. A pipeline that keeps text, crops and coordinates can revisit an ambiguous digit; one that retains only plain text cannot. Conflicting tool outputs should remain associated with their source region so that a later check can compare them with the page. Calling more tools is useful only when the new observation can resolve a specific uncertainty.

### 2.2.4 Evaluation

The evolution of the OCR benchmark evaluation system reflects a profound transition from traditional precision measurement to multi-dimensional capability assessment. The early Fourth Annual Test of OCR Accuracy [245] and Fifth Annual Test of OCR Accuracy [246] established the basic paradigm for systematically evaluating the character-level accuracy of commercial OCR engines, focusing on batch precision testing of standard documents. In the second decade of the 21st century, Performance Comparison of OCR Tools [303] continued the traditional approach of tool-level horizontal comparison, while 2022 became a critical turning point: OCR-IDL: OCR Annotations for Industry Document Library Dataset [18] provided large-scale commercial OCR annotations for an industrial-grade document library for the first time, pushing evaluation toward real business scenarios; concurrently, an Evaluation of OCR on Egocentric Data [244] was among the first to expand OCR capability assessment to the emerging field of first-person perspectives, revealing the limitations of existing methods under non-traditional capture conditions. OCRBench: On the Hidden Mystery of OCR in Large Multimodal Models [168], first released in 2023, aggregates 29 datasets spanning text recognition, scene-text and document VQA, key information extraction, and handwritten mathematical expression recognition. The number 29 refers to datasets, not distinct task categories.

*Parsing, localization and robustness.* The year 2024 saw an explosive development: @BENCH: Benchmarking Vision-Language Models for Human-centered Assistive Technology [122] incorporated OCR into

| Route | Input and evidence output | Useful property | Cost or failure to check |
|---|---|---|---|
| Modular OCR and parsing [70] | Page images become text, boxes, and separately inferred structure. | Intermediate outputs can be inspected and components replaced independently. | Recognition, reading-order, or cell-assignment errors propagate; text linearization can discard visual relations. |
| Layout-aware language modeling [307, 352] | OCR text and coordinates condition task-specific predictions or generation. | Spatial relations remain explicit in the model input. | OCR and box quality bound the available evidence; text and coordinates do not by themselves encode all figure content. |
| Image-to-sequence modeling [31, 100, 134] | Visual features are decoded into transcription, structure, or task outputs. | A shared generation interface can couple recognition with the required output schema. | Resolution, visual-token compression, and decoding affect fine detail; generated output needs separate completeness and grounding checks. |
| Hybrid and tool-assisted processing [30, 160] | Images, region proposals, and specialist tool outputs are combined. | Difficult regions can receive specialized processing and preserve multiple evidence views. | Routing, alignment, and conflicting tool outputs introduce additional failure modes and latency. |

**Table 1** Perception routes compared by the information passed to downstream reasoning. Benefits and limitations describe design properties and checks, rather than matched experimental measurements.

an assistive technology framework for the visually impaired, emphasizing human-centered utility evaluation; OmniDocBench: Benchmarking Diverse PDF Document Parsing with Comprehensive Annotations [220] built a refined parsing benchmark covering nine document types; and by year-end, OCRBench v2: An Improved Benchmark for Evaluating Large Multimodal Models on Visual Text Localization and Reasoning [84] further strengthened the evaluation system for visual text localization and logical reasoning capabilities.

*Language and domain coverage.* Post-2025 development showed three distinct trends: in terms of linguistic diversity expansion, SARD: A Large-Scale Synthetic Arabic OCR Dataset for Book-Style Text Recognition [203] constructed a synthetic dataset of over 840,000 pages for Arabic book-style documents, and 600k-ks-ocr: A Large-Scale Synthetic Dataset for Optical Character Recognition in Kashmiri Script [181] filled the resource gap for the endangered Kashmiri script; in terms of refined evaluation dimensions, OCR-Quality: A Human-Annotated Dataset for OCR Quality Assessment [386] introduced a human-annotated quality assessment dimension for the first time, and Real5-OmniDocBench [54] focused on robustness evaluation under five types of real physical distortions such as scanning artifacts, bending, and screen photography; in terms of domain specialization, PubMed-OCR: PMC Open Access OCR Annotations [106] delved into the high-complexity domain of scientific literature, providing dedicated resources for OCR research in academic publications. The entire evolutionary trajectory clearly demonstrates that OCR benchmarks have moved from single character accuracy metrics to a comprehensive evaluation ecosystem encompassing multilingual support, multi-scene adaptation, multi-modal understanding, and real-world robustness, providing critical support for the continuous progress of document intelligence and vision-language models.

### 2.2.5 Comparing Perception Routes

The main distinction between these approaches is the evidence interface they expose to downstream reasoning. A recognized string, a token with a bounding box, a parsed table, and an answer generated from pixels preserve different information. Consequently, lower character error does not alone establish better table reasoning, and a correct answer does not establish accurate transcription or localization. Table 1 summarizes these interfaces and their principal trade-offs; it is a qualitative synthesis, not a pooled ranking of published scores.

For a cross-page numerical question, a modular pipeline should preserve page identifiers, cell coordinates, headers, units, and reading order alongside the recognized values. A layout-aware model can use these coordinates to associate values with labels, but cannot recover visual evidence absent from its input. An image-based model can inspect a chart or an unusual layout directly, while still missing small numbers after





**Figure 5** From a source table to a computed answer. Selection, table transformations and executable programs expose different intermediate objects for inspection.

resizing or compression. A hybrid system can revisit the relevant crop or call a specialized recognizer, provided that it records which source region each tool output represents. These are testable failure hypotheses: they should be checked under the same documents, questions, page budgets, and evidence annotations, rather than inferred from a method's architectural label.

The comparison also separates training from inference. In this survey, OCR-free describes the absence of an external OCR transcript at the task interface; it does not imply that the model never learns text recognition, that OCR was absent from data construction, or that an explicit evidence representation is unnecessary. Pipeline, direct-visual, and hybrid systems should therefore be compared under their stated input and resource conditions. MMLongBench-Doc [179], for example, reported that most evaluated LVLMs underperformed the corresponding OCR-text-based LLM setting in its 2024 experiments. This result is specific to that study, but demonstrates why an architectural change alone cannot establish a universal replacement order.

## 3 Table Understanding and Question Answering

A table answer depends on relations: which header governs a cell, which unit applies, and which rows satisfy the question. Table understanding is a task family that can combine layout-aware encoders, language models, visual models, retrieval and tools. We review three overlapping capabilities: preserving relational structure, selecting and transforming question-relevant data, and checking an answer against its evidence. These are composable mechanisms rather than mutually exclusive historical stages. Figure 5 follows a source table through selection, transformation and computation; Table 2 compares the resulting inspection and validation boundaries.

### 3.1 Structure-Aware and Table Semantic Modeling

The research on tables within document understanding and question answering (DocQA) primarily focuses on how models perceive table structures in real-world document scenarios, model the semantic correlations between tables, contextual text, and visual layouts, and provide a reliable representational foundation for subsequent QA and reasoning. Early studies generally recognized that simply linearizing tables into text weakened the ability to model row-column relationships, header hierarchies, and cell dependencies. Consequently, this line of work concentrated on structure-aware representation learning and the construction of data benchmarks. Understanding Tables with Intermediate Pre-training [74] and OmniTab [125] significantly improved model capabilities in understanding table structures, numerical relationships, and linguistic alignment by introducing large-scale intermediate pre-training and multi-task pre-training.

Representations for QA from Documents with Tables and Text [371] and SoarGraph [404] further emphasized

the joint modeling of tables and their surrounding text, with SoarGraph capturing cross-modal semantic dependencies through graph-structured representations. Furthermore, ReasTAP: Injecting Table Reasoning Skills During Pre-training via Synthetic Reasoning Examples [394] integrated table reasoning capabilities into the pre-training phase, enhancing the model's understanding and reasoning power over tabular data. FORTAP: Using formulas for numerical-reasoning-aware table pretraining [43] leveraged spreadsheet formulas to achieve numerical-reasoning-aware table pre-training, providing support for computational capabilities on unstructured tables.

At the task and data level, AIT-QA [130], FeTaQA [209], and Arxiv Tables [140] revealed the limitations of traditional methods in real-world scenarios from the perspectives of complex industry tables, free-form table QA, and long-document table-text associations, respectively, and constructed related datasets. Meanwhile, Table Detection in the Wild: A Novel Diverse Table Detection Dataset and Method [99] provided a large-scale table detection dataset and benchmark methods, laying the groundwork for subsequent table structure modeling. As research expanded to visual documents, Visual Understanding of Complex Table Structures from Document Images [241] and HTAN [337] proposed more robust visual structure modeling methods for irregular and hierarchical tables, while Towards Complex Document Understanding by Discrete Reasoning [403] and RJUA-MedDQA [127] further evaluated table understanding within the context of multi-page, multimodal documents and complex discrete reasoning.

Additionally, from an analytical perspective, Tabular Representation, Noisy Operators, and Impacts on Table Structure Understanding Tasks in LLMs [269] and Large Language Models Are Complex Table Parsers [388] revealed the sensitivity of LLMs to table representation formats and structural noise, pointing out that their table parsing capabilities were still constrained by input structure and robustness bottlenecks. These studies identify a common prerequisite for downstream reasoning: cells, headers, units, and surrounding text must retain their relations in the model input. Better language generation cannot by itself recover a row–column association that has already been lost during extraction or serialization.

## 3.2 Generation Enhancement and Modular Reasoning

A complementary line of work uses the generative capabilities of LLMs to select relevant content, decompose a question, and transform tabular evidence before answering. These methods address context organization and inference; they do not remove the need for structure-aware input representations. One representative category of work centered on table instruction tuning and generation-capability enhancement. Table-GPT [155] performed "table-tuning" on general-purpose LLMs using large-scale synthetic table task data, enabling the models to gain stronger transfer capabilities across multiple table tasks. TableGPT2 [275] introduced a specialized encoder for schema- and cell-level tabular information alongside a language decoder; here the additional modality is tabular data, which should not be equated with reading a table image.

It addresses structural and semantic modeling of real-world tables, while Rethinking Table Instruction Tuning [59] systematically analyzed the impact of hyperparameters and training scales on performance and generalization in table instruction tuning. Another important route focused on the modular organization of the generation process: Localize, Retrieve and Fuse (TAG-QA) [392] supported free-form table QA through a three-stage "localize-retrieve-fuse" framework; Open-Domain Question Answering over Tables with LLMs [161] extended this idea to open-domain scenarios with large-scale table collections. MFORT-QA [96] combined few-shot learning with multi-hop Chain-of-Thought (CoT) to handle cross-table and complex reasoning problems, while Large Language Models are Versatile Decomposers [364] explicitly proposed using LLMs as question and evidence decomposers, alleviating issues of large table input redundancy and unclear reasoning paths through a "decompose-then-reason" approach.

Regarding input organization and noise suppression, TACR [335] utilized table-question alignment to achieve fine-grained cell selection; CABINET [229] reduced interference from irrelevant table content through unsupervised relevance scoring; TabSQLify: Enhancing reasoning capabilities of LLMs through table decomposition [207] reduced context length burdens by decomposing large tables into question-relevant sub-tables; and GENTAP [264] enhanced model performance in free-form table QA through generation-oriented intermediate pre-training. Meanwhile, Exploring the Impact of Table-to-Text Methods [195] systematically compared the effectiveness of different table-to-text strategies in DSFT and RAG scenarios. DocTabQA [309] introduced

generation-enhancement ideas into long-document scenarios, improving the clarity of complex information presentation through tabular answer organization.

In the exploration of finer-grained table reasoning methods, Chain-of-table: Evolving tables in the reasoning chain for table understanding [326] proposed integrating tabular data into the reasoning chain to enhance table understanding. DePlot: One-shot visual language reasoning by plot-to-table translation [164] achieved visual language reasoning through plot-to-table translation. MultiHiertt: Numerical reasoning over multi hierarchical tabular and textual data [393] provided a numerical reasoning benchmark and symbolic reasoning QA model for multi-hierarchical tables and text. Alter: Augmentation for large-table-based reasoning [374] improved large-table reasoning capabilities through data and query augmentation. Towards table-to-text generation with numerical reasoning [277] focused on the numerical reasoning aspect of generating text from structured data.

Effective distillation of table-based reasoning ability from LLMs [355] proposed distilling the table reasoning capabilities of large models into smaller ones. Tables as texts or images: Evaluating the table reasoning ability of LLMs and MLLMs [60] evaluated table understanding under different prompting strategies and data formats. Tap4llm: Table provider on sampling, augmenting, and packing semi-structured data for large language model reasoning [278] provided a toolkit for table preprocessing. Table as Thought: Exploring Structured Thoughts in LLM Reasoning [282] proposed organizing the reasoning process in tabular form to enhance LLM reasoning power. RoT: Enhancing Table Reasoning with Iterative Row-Wise Traversals [385] optimized reasoning efficiency through iterative row-wise traversals.

Improving table reasoning through table decomposition and normalization [206] optimized table reasoning via decomposition and normalization. FLEXTAF: Enhancing Table Reasoning with Flexible Tabular Formats [384] strengthened reasoning performance with flexible tabular formats. VisTR: Visualizations as Representations for Time-series Table Reasoning [103] supported time-series table reasoning via visualization. LIGHT-TABLE-CHAIN: Simplifying and Enhancing Chain-Based Table Reasoning [308] optimized the efficiency of chain-based table reasoning. Reasoning and retrieval for complex semi-structured tables via reinforced relational data transformation [66] proposed the TabFormer framework to achieve semi-structured table reasoning and retrieval.

Beyond Linearization: Attributed Table Graphs for Table Reasoning [323] used attributed table graphs to preserve structural information for graph-structured reasoning. TableReasoner: Advancing Table Reasoning Framework with Large Language Models [348] utilized LLMs to advance table reasoning frameworks. STaR: Towards Cognitive Table Reasoning via Slow-Thinking Large Language Models [375] optimized multi-step reasoning and stability through a slow-thinking approach. PanelTR: Zero-Shot Table Reasoning Framework Through Multi-Agent Scientific Discussion [178] proposed a multi-agent zero-shot table reasoning framework. Table-Critic: A Multi-Agent Framework for Collaborative Criticism and Refinement in Table Reasoning [367] improved table reasoning capabilities by identifying and correcting reasoning errors through multi-agent collaboration.

Unveiling Implicit Table Knowledge with Question-Then-Pinpoint Reasoner for Insightful Table Summarization [255] excavated implicit table knowledge via self-questioning and evidence pinpointing. Tab-CoT: Zero-shot Tabular Chain of Thought [409] achieved zero-shot tabular Chain-of-Thought reasoning.

## 3.3 Execution-Based Reasoning and Multimodal Table Understanding

Execution-based methods expose intermediate programs, selected evidence, or operation results for inspection. This improves the observability of a reasoning workflow, but an executable trace is not a certificate that the correct table, cells, units, or question interpretation were used. The relevant distinction is between checking an operation on supplied data and checking whether those data and operations support the requested answer. Among representative works, Table-R1: Inference-Time Scaling for Table Reasoning [361] proposed an inference-time scaling method for table reasoning, improving performance across various table reasoning tasks through post-training strategies. Weaver: Interweaving SQL and LLM for Table Reasoning [132] combined SQL with LLMs to dynamically process structured and unstructured data via a modular pipeline to enhance QA capabilities.

Tart: An open-source tool-augmented framework for explainable table-based reasoning [172] proposed a tool-augmented framework to improve LLM interpretation of tabular data. Meanwhile, Reasoning-Table: Exploring Reinforcement Learning for Table Reasoning [149] designed a reinforcement learning-based table reasoning model, validating its effectiveness in tasks such as table QA and text-to-SQL. Concurrently, TableGPT-R1 [359] introduced reinforcement learning into table reasoning, mitigating the limitations of supervised fine-tuning in multi-step reasoning and code execution through task-adaptive rewards and multi-stage training. Interpretable LLM-based Table QA [213] proposed Plan-of-SQLs (POS), which explicitly decomposes natural language queries into executable SQL sub-steps to expose intermediate SQL programs and their execution results. Multi-LLM Agent QA over Tabular Data [15] completed planning, code generation, and debugging through multi-agent collaboration, demonstrating the feasibility of agentic reasoning in table QA.

In the direction of tool and execution enhancement, OpenTab [139] combined table retrieval with SQL execution to support open-domain table reasoning. TAT-LLM [405] and MATATA [304] strengthened discrete and mathematical reasoning capabilities in hybrid table-text scenarios through a step-wise pipeline and a weakly supervised tool-augmentation mechanism, respectively. TaPERA [395] used content planning and execution-driven reasoning to improve faithfulness in its long-form table QA evaluation. Table-r1: Region-based reinforcement learning for table understanding [344] proposed a region-level reinforcement learning method, optimizing table understanding by fusing regional evidence with advanced fine-tuning techniques.

PoTable: Towards Systematic Thinking via Stage-oriented Plan-then-Execute Reasoning on Tables [183] introduced a stage-oriented plan-then-execute strategy to enhance reasoning systematicity and interpretability. Potable: Programming standardly on table-based reasoning like a human analyst [184] simulated human analytical thinking by combining a planner with a Python interpreter to achieve complex computational tasks. TableMind: An Autonomous Programmatic Agent for Tool-Augmented Table Reasoning [120] strengthened structured table reasoning capabilities through a multi-stage training strategy. JT-DA: Enhancing Data Analysis with Tool-Integrated Table Reasoning Large Language Models [45] provided a complete analysis and reasoning workflow to support complex table QA. Fortune: Formula-Driven Reinforcement Learning for Symbolic Table Reasoning in Language Models [22] enhanced the symbolic reasoning power of LLMs by generating executable spreadsheet formulas.

Meanwhile, interpretability and structural consistency have been systematically reinforced in visual table scenarios. TabIQA [214], ExpliCIT-QA [109], Enhancing LVLMs with Layout Modality [4], and Extracting Information from Scientific Literature via Visual Table QA Models [133] emphasized the importance of maintaining table structure and execution trajectories from the perspectives of structural recovery, code-interpretable reasoning, layout-aware modeling, and scientific literature extraction, respectively. TabPedia [390] and Compositional Condition QA [121] further improved multimodal consistent reasoning through unified multi-task visual table understanding and condition-aware modeling.

From the perspective of external knowledge and structural constraints, From Liberating to Questioning Tabular Data using Knowledge Graphs [240] and TQAgent [389] integrated knowledge graphs into table QA to reduce hallucinations and support multi-step tree-like reasoning. Finally, TReB [151] provided a systematic evaluation framework spanning shallow understanding to deep reasoning, revealing the gaps in existing methods for real-world complex table reasoning. Together, these methods make parts of the computation inspectable. Their applicability to high-stakes use still requires separate evidence that source selection, table extraction, program semantics, and final verbalization are correct under the intended document distribution.

## 3.4 Comparing Evidence Transformations and Their Checks

Table 2 compares representative mechanisms using the same questions: what representation is passed forward, what can be inspected, and what remains unchecked. The limitations are our analysis of each mechanism's validation boundary, rather than new benchmark results or a ranking of the cited systems. A table encoder principally changes the representation; relevance filtering changes which evidence receives attention; table operations and programs change the evidence available to the final generator. Combining these mechanisms is often more meaningful than assigning a system to a single class.

For example, a question about a year-on-year change may require finding the correct table, associating two values with their year headers, recognizing that values are reported in thousands, applying the requested

| Method | Evidence mechanism | Inspectable object | Remaining validation boundary |
|---|---|---|---|
| TableGPT2 [275] | Encoder integrates schema- and cell-level information with a decoder. | Input table and generated response or code. | A learned representation does not itself establish which cells support an answer. |
| CABINET [229] | Question-conditioned relevance weights suppress distracting table content. | Cell relevance and selected content. | Relevance is not proof of sufficiency; incorrectly suppressed cells can remove needed evidence. |
| Chain-of-Table [326] | Iterative operations update a table as intermediate state. | Operation sequence and intermediate tables. | Executed transformations can still implement the wrong interpretation of a question. |
| DePlot [164] | Converts a chart image into a linearized table for language-model reasoning. | Converted values and the downstream answer. | Reasoning inherits errors in chart-to-table conversion; visual source checks remain necessary. |
| OpenTab [139] | Retrieves tables and executes generated SQL before answering. | Retrieved table, SQL, and execution result. | SQL execution cannot establish that retrieval selected the correct table or mapped a phrase to the right column. |
| TaPERA [395] | Decomposes questions, executes Python, and generates from program outputs. | Content plan, programs, results, and answer. | Program-output consistency must be distinguished from correct planning and faithful use of source cells. |

**Table 2** Representative table QA mechanisms organized by evidence transformation and validation boundary. This is a qualitative comparison of published designs, not a shared-protocol performance comparison.

calculation, and expressing the result with its unit. A successful Python or SQL execution checks only the calculation on its supplied inputs. It does not check that the extracted cells belong to the intended entity or accounting period. A source-aware evaluation should therefore distinguish *answer correctness*, *evidence localization*, *support of the answer by that evidence*, and *execution correctness*. A readable reasoning trace provides useful observability but is not, on its own, evidence for all four properties.

This distinction also guides system selection. When a task already supplies a clean, small table, retrieval and multiple planning agents may add avoidable failure points. For a large table, relevance filtering or decomposition can reduce the amount passed to a generator, provided that required headers and units survive. For open-domain questions, table retrieval must be evaluated separately from reasoning on an oracle table. For numerical questions, execution makes arithmetic inspectable, while checking the table image or original cells remains essential when extraction is uncertain. These choices should be tested under the same input and resource conditions before attributing gains to a reasoning architecture.

*Source selection before arithmetic* An executable answer still depends on interpreting the source correctly. A valid SQL query can select the wrong accounting period, and correct subtraction can use an unadjusted value. For the year-on-year margin question in Figure 3, the system must preserve each value's year and unit, apply the restatement, and then compute the change. The source table, selected cells, executed operation and final unit should remain linked.

## 4 Text-Based Retrieval-Augmented Generation

In document QA, retrieval must divide and reconnect evidence: a question may need a passage, its section context and a reference on another page. Figure 6 contrasts flat, hierarchical and graph-based access to the same collection. The review below separates the representation retained by an index from the policy that decides whether retrieval should continue.

## 4.1 Retrieval-Augmented Generation

Retrieval-Augmented Generation (RAG) combines a generator with an external information store. Lewis et al. [150] formulated a neural retrieval-and-generation model in 2020 using a dense index of Wikipedia; the general paradigm therefore predates the document-specific examples discussed here. For document QA, the distinctive problem is to preserve and recover evidence across sections, pages, and documents under a bounded input budget. Retrieval can reduce the context passed to a generator, but it introduces a selection bottleneck: a generator cannot reliably use evidence that the retriever has omitted. We distinguish retrieval representation (passages, hierarchy, or graph) from runtime control (fixed or iterative retrieval), because either representation can be used with either control strategy.

These are composable design choices, not successive levels of reasoning ability. Representative retrieve-then-generate and multi-hop approaches include the following. Triple-Fact Retriever [334] improved the accuracy and interpretability of cross-document evidence paths in multi-hop DocQA by extracting structured triple facts and aggregating evidence hop by hop. Multi-Document Question Answering with Lightweight Embeddings-based Document Reranker [5] employed a two-stage retrieval process combining BM25 coarse-ranking with lightweight embedding-based re-ranking, improving evidence quality in multi-document QA while maintaining efficiency. Zero-Shot Complex Question-Answering on Long Scientific Documents [319] integrated RAG with question decomposition, multi-hop reasoning, and long-answer generation, achieving complex QA on long documents without task-specific fine-tuning. Meanwhile, DR-RAG [105] mitigated evidence omission in multi-hop QA caused by static similarity retrieval by introducing dynamic document relevance modeling and a two-stage filtering mechanism.

## 4.2 Structure-Aware Evidence Access

A flat passage index is simple to build and update. Each chunk receives a retrieval representation, and the most relevant chunks are passed to the generator. Its weakness is the boundary: a table caption, paragraph or qualification can fall outside the selected chunk. Increasing overlap reduces some boundary losses but repeats content and consumes context. Source document, section and page identifiers are therefore useful even when retrieval itself operates over plain text.

Building on traditional RAG improvements centered on retrieval quality and multi-hop support, subsequent research began to focus further on utilizing the reasoning capabilities of LLMs and internal or cross-document structural information to construct more structure-aware and reasoning-guided retrieval-augmentation frameworks. Among these, DocReLM: Mastering Document Retrieval with Language Model [328] fine-tuned retrievers and re-rankers by introducing LLMs to generate domain-specific training data and utilized LLM-generated citation networks to expand candidate document sets, thereby significantly enhancing semantic understanding and cross-literature association discovery in academic literature retrieval. Advanced Chain-of-Thought Reasoning for Parameter Extraction from Documents Using Large Language Models [23] introduced an improved chain-of-thought reasoning mechanism into document-level information extraction tasks, achieving reasoning-driven refined retrieval and parameter localization through modules such as Targeted Document Retrieval, Iterative Retrieval Optimization, and Preference Optimization.

Semi-Structured Chain-of-Thought: Integrating Multiple Sources of Knowledge for Improved Language Model Reasoning [276] further explored the unification of parametric knowledge, structured knowledge graphs, and unstructured text retrieval into a semi-structured reasoning chain, allowing multi-source knowledge to be progressively filled and integrated during the reasoning process. In long-document scenarios, Beyond Chunking: Discourse-Aware Hierarchical Retrieval for Long Document Question Answering [180] utilized Rhetorical Structure Theory (RST) for discourse-level modeling of documents and performed hierarchical retrieval on this structure, effectively alleviating the issue of semantic incoherence caused by flat chunking. For multi-document scenarios, Knowledge Graph Prompting for Multi-Document Question Answering [322] enhanced global consistency and multi-document reasoning capabilities by constructing cross-document knowledge graphs and guiding the LLM through graph-traversal evidence collection.

Meanwhile, PdfTriage: Question Answering over Long, Structured Documents [247] focused on structured long-document QA, explicitly modeling structural meta-information such as pages, sections, and tables to

enable RAG to accurately respond to queries containing structural references. These methods show how document structure can guide evidence access. Their common trade-off is that useful hierarchy or relations must first be recovered or constructed; a structural index should therefore be evaluated for both retrieval coverage and the errors introduced during its construction.

## 4.3 Graph and Hierarchical Evidence Indexes

Graph and hierarchical indexes expose relations that flat passages may conceal, but an index structure should not be conflated with an agentic policy. Some systems prepare graphs and summaries offline and answer through a predefined query workflow; others adapt the next retrieval action to intermediate observations. Both can support multi-hop questions, and either can fail through incomplete or incorrectly linked evidence. From Local to Global: A Graph RAG Approach to Query-Focused Summarization [73] (GraphRAG) proposed a graph-enhanced retrieval framework based on knowledge graphs and community detection, addressing global, cross-document summarization queries by constructing entity-relationship graphs and generating community summaries. Subsequently, LightRAG: Simple and Fast Retrieval-Augmented Generation [97] proposed a dual-level retrieval design intended to reduce the overhead of graph-enhanced retrieval while retaining access to entity and relational information.

Furthermore, HyperGraphRAG: Retrieval-Augmented Generation via Hypergraph-Structured Knowledge Representation [175] used hyperedges to represent relations involving multiple entities directly, rather than organizing all evidence as pairwise links. This changes the representation of a relation, but does not itself establish that the extracted relation is correct. Leveraging Spreading Activation for Improved Document Retrieval in Knowledge-Graph-Based RAG Systems [230] enabled activation values to propagate dynamically along evidence chains for prioritized retrieval of relevant fragments by automatically constructing knowledge graphs and executing spreading activation, serving as a plug-and-play module that enhanced multi-hop evidence continuity in chain-based reasoning.

GARLIC: LLM-Guided Dynamic Progress Control with Hierarchical Weighted Graph for Long Document QA [321] constructed a hierarchical weighted directed acyclic graph based on LLM attention for dynamic retrieval, allowing retrieval paths and information volume to be adaptively controlled by the LLM, overcoming the limitations of traditional vector similarity and fixed tree summarization. For multi-document environments, HiQA: A Hierarchical Contextual Augmentation RAG for Multi-Documents QA [36] transformed documents into hierarchical structures with cascading metadata and fused vector, BM25, and keyword matching through multi-path retrieval to improve retrieval discriminability in structurally similar document sets. For complex hierarchical documents, BookRAG: A Hierarchical Structure-aware Index-based Approach for Retrieval-Augmented Generation on Complex Documents [317] built BookIndex, fusing logical hierarchy trees and entity-relationship graphs, and introduced an agentic retrieval strategy inspired by information foraging theory to dynamically select retrieval workflows, thereby balancing recall, efficiency, and multi-hop path integrity.

In multi-hop reasoning, Enhancing Document-Level Question Answering via Multi-Hop Retrieval-Augmented Generation with LLaMA 3 [115] integrated dense retrieval, context fusion, and multi-hop mechanisms, strengthening retrieval-generation synergy through the joint optimization of retrieval likelihood and generation loss. Finally, Chain of Retrieval: Multi-Aspect Iterative Search Expansion and Post-Order Search Aggregation for Full Paper Retrieval [227] drove iterative expansion retrieval via multi-aspect decomposition and reorganized hierarchical evidence through post-order aggregation, reflecting a paradigm shift in which the retrieval process itself served as the reasoning chain. The resulting design space combines evidence organization with control policy.

A graph can support global aggregation without interactive search, whereas iterative retrieval can operate over ordinary passages. Consequently, the effect of graph construction should be separated from the effect of extra retrieval or generation calls when comparing systems.

## 4.4 Text QA Foundations and Their Scope

*Early Attention Mechanisms* Before contemporary generative RAG, text QA research studied how to select and combine evidence from supplied passages. These methods provide historical context for textual evidence





**Figure 6** Three ways to organize textual evidence for retrieval: flat passages, document hierarchy and linked entities. The index representation and the policy for making additional retrieval calls are separate choices.

reasoning; they do not address all of the visual and geometric constraints of document images. Dynamic Coattention Networks [347] proposed a co-attention strategy to capture bidirectional interaction information by simultaneously attending to the question and the document. Addressing the excessive search range in long documents, Coarse-to-fine question answering [49] pioneered a "coarse-to-fine" two-stage framework: first retrieving relevant sentences, then extracting precise answers. To further enhance text representation capabilities, EA Reader [83] utilized multi-space context fusion to improve performance in cloze-style QA.

*Reasoning Based on Graph Structures and Global Information* As document length and complexity continued to increase, Graph Neural Networks (GNNs) offered one approach to connecting discrete pieces of textual evidence. Question Answering by Reasoning Across Documents with GCNs [56] was among the earliest works to utilize entity-based Graph Convolutional Networks for handling multi-hop tasks. Subsequently, Identifying Supporting Facts with Document Graph Networks [294] further shifted the research focus from answer prediction to the explicit identification of supporting facts. This shift was achieved by modeling multi-document contexts as sentence-level document graphs and introducing question-conditioned GNN reasoning mechanisms on the graph structure. Meanwhile, the Heterogeneous Graph approach [75] handled cross-document reasoning by modeling different types of nodes (e.g., entities, documents). In recent research, Path-based GCN [289] emphasized reasoning along specific relational paths, while Capturing global structural information in long document question answering with compressive graph selector network [216] achieved more efficient long-document QA through integrated global structural encoding.

To improve the capability and interpretability of multi-hop QA, researchers began exploring explicit reasoning chains and explainable frameworks. First, Exploiting Explicit Paths [144] proposed that the key lay in selecting a correct evidence path, with the model scoring and choosing within a path space. Multi-hop Question Answering via Reasoning Chains [26] proposed the use of "reasoning chains" as intermediate explicit variables, where the model predicted one or more reasoning chains before generating an answer. Explore, Propose, and Assemble [123] proposed a three-stage explainable reasoning framework to bridge information fragments. Further progress in explainability included Select, Answer and Explain [300], which simultaneously generated answers and evidence rationales, elevating "explanation" from an auxiliary task to an output as important as the answer itself. Hop, Union, Generate [391] proposed guiding the model to form an explainable reasoning process without explicit evidence supervision. Additionally, Ask to Understand [152] proposed revealing complex multi-hop logic clearly by generating a series of intermediate questions.

*Task Generalization and the LLM Era* Work on translation [381], relation extraction [398], and script-event prediction [192] provides adjacent methodological background for multi-hop modeling. We do not treat those

tasks as direct document QA benchmarks: their inputs, outputs, and supervision differ. Their relevance is limited to transferable mechanisms for combining contextual information, which require separate validation on document questions.

Within document QA, MemSum-DQA [94] uses extractive summarization to shorten the material supplied to a QA model. Effect of Document Packing [237] examines how organizing context affects multi-hop reasoning. These methods highlight that evidence access is shaped by selection and presentation even when no external retrieval stage is exposed. Comparisons should therefore state whether a method receives a whole document, retrieved passages, a summary, or oracle evidence.

### 4.5 Choosing Context Access and Retrieval Control

The choice between full-context processing and retrieval depends on evidence density, corpus size, update frequency, model capacity, and resource limits. LaRA [153] explicitly evaluates this choice and finds no universally preferable route. Supplying a complete document avoids a separate retrieval recall failure when the input fits, but does not ensure that a model will use every relevant passage. Retrieval is attractive when a question needs a small portion of a large or changing collection; its answer quality remains conditional on recovering all necessary evidence. A structure-aware index can preserve section membership and cross-references, while also inheriting errors in parsing or graph construction. These are different access assumptions, so reported scores should be compared only after matching the available evidence and input budget.

Iterative or agent-controlled retrieval is most directly motivated when the next information need cannot be specified before examining earlier evidence. It can, for example, follow an entity or a cross-reference discovered during the first lookup. Additional rounds also create opportunities for query drift, repeated retrieval, and propagation of an early mistaken interpretation. Our design implication is to expose a stopping rule, a maximum number of actions, evidence already inspected, and the conditions for abstention, rather than treating a longer trace as evidence of deeper reasoning. A fixed retrieval pass or direct full-context model is a necessary control when evaluating whether additional actions contribute useful evidence.

Every additional action should address an observable gap. A useful trace records the current question, the new source found and the unresolved requirement. A stopping rule can then distinguish sufficient evidence from a search that merely repeats similar passages.

The resulting comparison should decompose failures into evidence coverage, evidence selection, and answer use. An oracle-evidence setting isolates the reader from the retriever; an end-to-end setting measures their joint behavior. Removing a cited passage, substituting a distractor, or checking the answer against a retrieved source can further probe whether the answer is supported by the evidence. Such checks assess different properties from a plausible explanation or a successful retrieval call. This framework links text-based RAG to table and visual document QA through a shared requirement: retain source identity while selecting, transforming, and using evidence.

## 5 Vision-Language Models for Document Understanding

Visual document understanding combines several independent design choices: whether text is supplied by OCR, how page structure is represented, how much of a document is accessible at once, and whether evidence is selected before or during generation. A VLM is a model family, whereas table QA is a task and RAG is a system strategy; these categories therefore overlap. The routes discussed below are compared by the evidence they retain and expose, rather than treated as successive levels of capability. Two resource needs cut across these choices: preserving enough page detail to read the evidence and exposing enough pages to answer the question. Both consume the image and context budgets.

An OCR-free inference interface removes the need to call a separate OCR engine, but does not remove the need to recognize text or guarantee preservation of every visual detail. Resolution limits, cropping and visual-token compression can discard small characters or relations across regions. Conversely, an OCR-plus-language-model pipeline can retain searchable text and explicit coordinates while losing visual cues during linearization. Hybrid systems can retain both representations, at the cost of alignment and additional processing. The

| Representative route | Input and context | Evidence mechanism and output | Main trade-off to examine |
|---|---|---|---|
| DocLLM [307] | Text and bounding boxes; no image encoder | Layout-aware attention conditions generated text on explicit spatial features | Depends on extracted text and coordinates; graphics absent from these inputs remain inaccessible |
| Donut [134] | Page image | Encoder–decoder generates a task-specific structured sequence | Avoids a separate OCR call; generated fields still require checks against page content |
| mPLUG-DocOwl2 [112] | Multiple page images | High-resolution visual encoding and compression support document QA | Fewer visual tokens reduce context pressure; fine detail and page coverage must be evaluated |
| ColPali / ViDoRe [76] | Page-image corpus and text query | Late interaction scores multi-vector page representations; returns ranked pages | Retrieval quality is distinct from answer quality; index storage and missed evidence affect downstream QA |
| VisRAG [368] | Retrieved document images | Visual retrieval supplies selected pages to a generator | Retains visual evidence without text-only ingestion; generation is limited by retrieved-page coverage |
| DocLens / ViDoRAG [316, 401] | Document pages or collections, accessed iteratively | Tools or agents select, inspect and combine evidence during answering | Adaptive access adds calls and control errors; logs do not themselves establish evidence faithfulness |

**Table 3** Representative visual-document routes under shared comparison axes. This is a qualitative synthesis of the cited methods, not a newly measured performance ranking. Model input, evidence access and system control are separate choices that may be combined.

original 2024 MMLongBench-Doc study provides a concrete counterexample to a universal advantage for direct visual input: 12 of its 14 evaluated LVLMs performed worse than corresponding LLMs supplied with OCR-parsed text [179]. This is a result under that study's models and input budgets, not a ranking of all later systems.

## 5.1 Foundational Vision-Language Models for Document Understanding

The development of Vision-Language Models (VLM) has propelled visual document understanding from single-modality analysis toward a unified multimodal modeling paradigm. By jointly modeling visual content, textual semantics, and spatial layout information, VLMs enable systems to gain a deeper understanding of document structures and their semantic relationships. Building on this capability, visual document understanding has gradually evolved into a general intelligent system characterized by structure awareness, cross-modal reasoning, and document-level understanding. The following sections introduce the evolution of VLMs across four key dimensions.

*Foundational Period of Visually-Rich Document Understanding* Early research established the technical foundations for document image classification and cross-modal retrieval. Deep multimodal learning for cross-modal retrieval: One model for all tasks [16] proposed a "unified model" approach, encoding vision and text into the same retrievable representation space to simultaneously support bidirectional image-text retrieval and unimodal retrieval within a single model. Entering the pre-training era, Layoutxlm: Multimodal pre-training for multilingual visually-rich document understanding [353] introduced a multimodal pre-training model for multilingual, visually-rich documents, integrating text, layout, and visual information into a unified multilingual pre-training framework. VinVL: Revisiting Visual Representations in Vision-Language Models [383] systematically investigated the role of "visual features themselves" in multimodal tasks, proving that high-quality visual encoding is a key factor in enhancing VLM performance.

CLIP-Adapter: Better Vision-Language Models with Feature Adapters [86] proposed an efficient way to adapt CLIP without compromising its pre-training capabilities by adding lightweight "adapter" modules in the feature space to improve performance on few-shot and downstream tasks. In 2022, the research community began focusing on constructing generalized document processors. FLAVA: A Foundational Language And Vision Alignment Model [268] presented a foundational model for general vision-language understanding, proposing the use of both image-text pairs and unimodal data for pre-training under a unified Transformer architecture to balance cross-modal alignment and unimodal understanding. Unifying Vision, Text, and Layout for Universal Document Processing [290] proposed the UDOP framework, which models visual appearance, textual content, and spatial layout in documents as a unified sequence-to-sequence generative task, supporting various document understanding and generation tasks through an instructional prompt mechanism.

Unified Pretraining Framework for Document Understanding [93] proposed a unified document pre-training framework that performs large-scale pre-training by multimodally encoding semantic regions in documents and combining multiple self-supervised learning objectives, thereby improving model transfer and generalization across different document understanding tasks. Bi-VLDoc: Bidirectional Vision-Language Modeling for Visually-Rich Document Understanding [174] designed a bidirectional vision-language supervision mechanism, enabling the model to predict language from vision and vice versa, strengthening cross-modal alignment and semantic interaction. Multimodal pre-training based on graph attention network for document understanding [387] explicitly modeled document structure as a graph and performed multimodal pre-training based on Graph Attention Networks, allowing the model to better capture contextual dependencies driven by layout relationships.

CM3: A Causal Masked Multimodal Model of the Internet [3] adopted a generative multimodal pre-training strategy using causal masking, modeling text and image tokens in a unified sequence to provide the model with both multimodal understanding and generation capabilities. NLX-GPT: A Model for Natural Language Explanations in Vision and Vision-Language Tasks [250] introduced a unified model for simultaneously predicting answers and generating natural language explanations in vision and vision-language tasks. Furthermore, Vision and natural language for metadata extraction from scientific PDF documents: a multimodal approach [20] proposed a multimodal method merging visual layout and textual semantics to automatically extract structured metadata from scientific PDF documents. I2MVFormer: Large Language Model Generated Multi-View Document Supervision for Zero-Shot Image Classification [204] utilized Large Language Models to generate multi-view textual descriptions as supervision signals, enhancing semantic modeling in zero-shot image and document classification.

*The Rise of VLM and Advancements in High-Resolution Perception* With the integration of Large Language Models (LLMs), document understanding entered an instruction-driven phase. PaLM-E: An Embodied Multimodal Language Model [69] provides background on coupling visual and other sensor representations to language models. Its embodied tasks are not document-QA results; it is included here as an architectural precursor, rather than as direct evidence of document-understanding performance. MiniGPT-4: Enhancing Vision-Language Understanding with Advanced Large Language Models [402] explored how advanced LLMs can improve vision-language understanding by aligning features from a frozen visual encoder with a powerful pre-trained LLM (such as Vicuna) using only a single projection layer, significantly enhancing visual description and text generation while retaining visual and linguistic capabilities.

PaLI-X: On Scaling up a Multilingual Vision and Language Model [34] introduced a large-scale multilingual VLM that achieved significant performance gains in multilingual image captioning, visual question answering, document understanding, and few-shot learning by scaling component sizes and task diversity. mPLUG-PaperOwl: Scientific Diagram Analysis with the Multimodal Large Language Model [110] focused on enhancing the understanding and analysis of scientific diagrams by general multimodal LLMs, significantly outperforming existing models in multimodal diagram description, analysis, and outline recommendation, demonstrating powerful capabilities in deep scientific diagram parsing and opening new directions for academic content generation. Additionally, UniDoc: A Universal Large Multimodal Model for Simultaneous Text Detection, Recognition, Spotting and Understanding [77] proposed a unified multimodal large model framework capable of end-to-end text detection, recognition, spotting, and semantic understanding within a single model—a holistic capability previously unavailable in similar methods. Between 2023 and 2024, high-resolution processing

became the core focus.

Monkey: Image Resolution and Text Label Are Important Things for Large Multimodal Models [159] systematically studied the impact of image resolution and text label quality on MLLM performance, noting that in document understanding and text-dense scenarios, resolution improvements often yield more direct and significant gains than structural changes, as high-resolution input markedly improves the perception of fine-grained text, symbols, and layout structures. TextMonkey: An OCR-Free Large Multimodal Model for Understanding Documents [169], building on the analysis of Monkey, proposed an end-to-end OCR-free document understanding model that performs joint visual and semantic modeling directly from high-resolution document images. Qwen2-VL: Enhancing Vision-Language Model's Perception of the World at Any Resolution [315] addressed the instability of VLM perception under different resolution conditions by proposing a unified modeling framework supporting arbitrary resolution inputs.

DocKylin: A Large Multimodal Model for Visual Document Understanding with Efficient Visual Slimming [377] focused on the computational overhead brought by high-resolution inputs, proposing an efficient visual slimming strategy that maintains document understanding performance while significantly reducing the number of visual tokens. DocPedia: Unleashing the Power of Large Multimodal Model in the Frequency Domain for Versatile Document Understanding [78] explored the potential value of frequency-domain information in visual document understanding, breaking the traditional paradigm that relies almost exclusively on spatial-domain features by merging frequency-domain representations with spatial features to better capture repetitive textures and structural patterns. Meanwhile, Vary: Scaling up the Vision Vocabulary for Large Vision-Language Models [329] argued from the perspective of visual representation discretization that existing VLMs face expression bottlenecks in visual vocabulary scale, requiring a systematic expansion of the visual vocabulary to allow the model to express complex image content with finer-grained visual tokens.

DocLLM: A layout-aware generative language model for multimodal document understanding [307] integrates text and bounding-box information through disentangled attention, without an image encoder. It models textual and spatial modalities; it does not directly encode page pixels or guarantee that a generated answer follows the document structure. mPLUG-DocOwl 1.5: Unified Structure Learning for OCR-free Document Understanding [111] further strengthened structure learning capabilities under an OCR-free framework, proposing a unified structure modeling mechanism to capture relationships between text, layout, and visual cues. For chart-centric document scenarios, TinyChart-3B [380] demonstrated that specialized lightweight MLLMs can achieve strong structural and numerical reasoning by combining visual token merging with Program-of-Thoughts learning, thereby attaining high chart understanding performance with only 3B parameters.

Qwen-VL: A Versatile Vision-Language Model for Understanding, Localization, Text Reading, and Beyond [12] introduced a highly versatile VLM framework supporting image understanding, region localization, text reading, and cross-modal reasoning, performing exceptionally well in text-dense and complex layout scenarios. Furthermore, document understanding for small models has gained attention. PaLI-3 Vision Language Models: Smaller, Faster, Stronger [35] achieved stronger multimodal understanding at a smaller model scale through architectural design and training strategy optimization, greatly expanding application scenarios. Small Language Model Meets with Reinforced Vision Vocabulary [330] explored the potential of Small Language Models (SLMs) in multimodal contexts, proposing to compensate for limited model scale by reinforcing the vision vocabulary.

By enhancing the expressive power on the visual side, small models significantly improved their performance in document understanding and visual reasoning, approaching the level of large models in certain scenarios. To optimize alignment, Enhancing Visual Document Understanding with Contrastive Learning in Large Visual-Language Models [156] introduced contrastive learning objectives to enhance the alignment between visual and textual representations, thereby mitigating semantic mismatch issues in complex documents. Read and Think: An Efficient Step-wise Multimodal Language Model for Document Understanding and Reasoning [378] proposed a stepwise multimodal reasoning framework that decomposes document understanding into sequential reading and reasoning stages, improving the model's ability to handle long documents and complex questions while maintaining computational efficiency.

Gemini: A Family of Highly Capable Multimodal Models [291] introduced a family of unified multimodal





**Figure 7** Two visual-budget decisions: preserve small-text detail through crops, and preserve query-specific matches through patch-level late interaction. The matching matrix is schematic, not a measured retrieval result.

large models covering text, images, audio, and video. In visual document understanding scenarios, Gemini demonstrated powerful cross-modal reasoning and contextual integration capabilities. VisionLLM v2: An End-to-End Generalist Multimodal Large Language Model for Hundreds of Vision-Language Tasks [336] unified a vast array of vision-language tasks in an end-to-end manner, emphasizing versatility and scalability. In document understanding, it showed stable cross-task generalization, representing the trend toward general-purpose multimodal models. EVLM: An Efficient Vision-Language Model for Visual Understanding [27] optimized visual encoding and cross-modal fusion modules from a holistic system efficiency perspective, balancing performance and computational cost across various tasks. 3MVRD: Multimodal Multi-task Multi-teacher Visually-Rich Form Document Understanding [64] proposed a multimodal, multi-task, multi-teacher distillation framework for joint modeling of visually-rich documents.

Through collaborative guidance from multiple teachers, the model showed stronger generalization in multi-task scenarios, reflecting the effectiveness of knowledge transfer in document understanding. A LayoutLMv3-Based Model for Enhanced Relation Extraction in Visually-Rich Documents [1] reinforced relation extraction in visually-rich documents based on LayoutLMv3, highlighting the role of layout information in structured semantic modeling and proving that explicit layout modeling can effectively improve the accuracy of entity relationship understanding.

*Visual budget: readable detail and page coverage* Figure 7 illustrates the central resource trade-off. Shrinking a page preserves its overall arrangement but can erase the characters needed to read a footnote.

Cropping preserves local detail but requires additional visual tokens and a way to reconnect regions with their source page. A document reader therefore needs both an effective resolution and a policy for allocating that resolution.

For a patch encoder, a simple budget model is

$$N_{\text{visual}} \approx \sum_{p=1}^{P} \sum_{c=1}^{C_p} n_{p,c},$$

where $P$ is the number of supplied pages, $C_p$ the crops retained from page $p$, and $n_{p,c}$ the tokens for each crop after compression. This accounting separates three choices often hidden behind a maximum-context specification: how many pages are supplied, how finely each is sampled, and how much information the model compresses. It is a resource description, not a performance law.

*The Evolution of OCR-free and Multi-page Context* OCR-free interfaces and long-document modeling address different bottlenecks. OCR-free models take page images as input and learn recognition together with downstream prediction, whereas long-document methods must also decide which pages and regions can be retained within a finite context. A direct visual route can avoid errors introduced by a separate transcription stage, but introduces its own recognition errors and compression losses. Its suitability therefore depends on document quality, language, visual density, task and resource budget, rather than on the absence of an OCR module alone. OCR-free Document Understanding Transformer (Donut) [134] was an end-to-end document understanding model that did not rely on OCR systems. Based on a Transformer encoder-decoder structure, it generates structured text output directly from raw document images, avoiding error propagation in traditional OCR pipelines.

Experimental results show that Donut achieves competitive performance across various tasks while significantly simplifying the document processing workflow. Pix2Struct [148] proposed an OCR-free VLM based on screenshot parsing pre-training, capable of generating structured text representations directly from raw images using a Transformer encoder-decoder architecture to achieve unified vision-language understanding. mPLUG-DocOwl: Modularized Multimodal Large Language Model for Document Understanding [363] introduced a modularized MLLM for OCR-free document understanding to address the issue of existing models ignoring fine-grained visual features in complex scenarios, demonstrating stronger cross-task generalization even without specific fine-tuning. mPLUG-DocOwl2: High-resolution Compressing for OCR-free Multi-page Document Understanding [112] proposed an efficient visual compression and structural modeling method for multi-page documents to address the computational and contextual bottlenecks in OCR-free scenarios. This model compresses and aggregates cross-page visual information while maintaining high-resolution perception, significantly reducing visual token counts and supporting long-document modeling.

DeepSeek-VL2: Mixture-of-Experts Vision-Language Models for Advanced Multimodal Understanding [345] adopted the Mixture-of-Experts (MoE) architecture in VLMs, significantly improving parameter efficiency through an expert routing mechanism that dynamically activates sub-models for different types of visual and semantic inputs. Regarding complex document parsing, MinerU2.5 [217] proposed an efficient high-resolution document parsing framework. It employs a coarse-to-fine two-stage parsing strategy to address computational bottlenecks: the first stage performs global layout analysis on downsampled images to identify structural elements, while the second stage crops key regions based on the global layout. POINTS-Reader: Distillation-Free Adaptation of Vision-Language Models for Document Conversion [167] proposed a distillation-free adaptation framework focusing on the lack of high-quality annotated data in complex document conversion tasks.

PDF-WuKong: A Large Multimodal Model for Efficient Long PDF Reading with End-to-End Sparse Sampling [346] addressed the challenges of merging large-scale visual and textual information in long PDF documents by selecting paragraphs or charts most relevant to user queries, avoiding redundant computation of the entire document. LongFin: A Multimodal Document Understanding Model for Long Financial Domain Documents [188] introduced a model specifically designed for multimodal understanding of long financial documents, breaking the maximum length limits of traditional models to accommodate multi-page, long-content industrial financial documents. Furthermore, H2OVL-Mississippi Vision Language Models Technical Report [85] introduced a suite of small VLMs aimed at meeting the needs for efficient, lightweight document processing in privacy-sensitive and on-device scenarios.

FILA: Fine-Grained Vision Language Models [407] focused on the fine-grained visual understanding capabilities of MLLMs when processing high-resolution images, providing a solution to the object truncation and semantic fragmentation issues caused by dynamic cropping and re-encoding. Expanding Performance Boundaries of Open-Source Multimodal Models with Model, Data, and Test-Time Scaling [39] presented the InternVL 2.5 series, systematically studying the impact of model scale, data quality, and test-time strategies on MLLM performance and providing a deep analysis of each factor's contribution to multimodal understanding. Additionally, Multimodal Adaptive Inference for Document Image Classification with Anytime Early Exiting [101] proposed a multimodal adaptive inference framework to balance efficiency and performance in VRDU tasks by embedding multi-layer early exiting mechanisms within the base model.

*Modern Document Understanding Evolution* Recent work also examines compact models, language-specific adaptation, document conversion and efficient document navigation. DocSLM: A Small Vision-Language Model for Long Multimodal Document Understanding [102] proposed an efficient small VLM to address the computational and memory bottlenecks of large-scale VLMs in long document understanding and edge deployment, achieving or exceeding state-of-the-art performance with significantly fewer parameters. SmolDocling: An ultra-compact vision-language model for end-to-end multimodal document conversion [212] focused on end-to-end multimodal document conversion, proposing an extremely compact VLM that processes complete pages within a single network and expresses all elements and their positions through a universal tagging format called DocTags.

Specific applications and vertical domain research include Baseer: A Vision-Language Model for Arabic Document-to-Markdown OCR [107], which designed a specialized VLM for the unique challenges of Arabic OCR and fine-tuned it on a mixed dataset of synthetic and real documents to accurately convert Arabic documents into structured Markdown. IndoColSmol: Lightweight Vision-Language Models for Multimodal Indonesian Document Search [82] proposed two lightweight vision-language retrieval models focused on multimodal retrieval tasks for Indonesian documents. Semantic Document Derendering: SVG Reconstruction via Vision-Language Modeling [104] introduced a multimodal-based vectorization tool to parse complex document images into editable vector formats.

Qwen2.5-VL Technical Report [14] established performance benchmarks for unified vision-language understanding, localization, and text reading. Qwen3-VL Technical Report [13] further expanded model capacity and reasoning capabilities, enhancing cross-modal task generalization and fine-grained perception. Finally, document-level strategy research includes Docopilot: Improving Multimodal Models for Document-Level Understanding [71], which addressed the shortcomings of MLLMs in multi-page document-level tasks by proposing a native document-level multimodal framework as a direct-processing alternative to retrieval-based methods in its evaluated settings. Nayana: A Foundation for Document-Centric Vision-Language Models via Multi-Task [138] aimed to build a multi-task, multimodal, and multilingual foundational resource and training framework, significantly expanding the potential of VLMs in global document understanding scenarios.

PP-DocBee2: Improved Baselines with Efficient Data for Multimodal Document Understanding [114] proposed a set of foundational enhancement strategies for end-to-end document image understanding. Interpret, prune and distill Donut: towards lightweight VLMs for VQA on document [182] focused on compressing generative VLMs like Donut into lightweight versions using interpretation, pruning, and distillation for efficient Document VQA. LoRA-Contextualizing Adaptation of Large Multimodal Models for Long Document Understanding [24] introduced LoRA structures to VLMs, allowing the model to serve as an efficient base for self-visual retrieval-augmented generation frameworks while adapting to long-document tasks through fine-grained parameter adjustments.

SCoPE VLM: Selective Context Processing for Efficient Document Navigation in Vision-Language Models [162] proposed a strategy called "Chain of Scroll" for selective and recursive navigation in long documents to avoid the high memory consumption of processing full pages at once. Entering 2026, A Hybrid Architecture for Multi-Stage Claim Document Understanding: Combining Vision-Language Models and Machine Learning for Real-Time Processing [41] proposed a multi-stage hybrid architecture for the automated processing of medical and insurance claim documents, designing an end-to-end pipeline to handle challenges like mixed layouts, handwriting, and diverse languages in scanned or photographed documents.

## 5.2 Multimodal RAG

Building on the success of text RAG in pure text QA, researchers began extending the retrieval-augmented paradigm to Visual Document Question Answering (DocQA/DocVQA), forming an early multimodal transition path centered on OCR/structural parsing + text retrieval. This stage generally assumed that document semantics primarily stem from text, using OCR to convert visual documents into text and layout structures before expanding retrieval and generation capabilities. PDF-MVQA [63] noted the bias of existing benchmarks toward single-page sparse text and constructed a multi-page visually-rich document QA dataset, proposing a joint coarse-to-fine retrieval framework for cross-page localization. CREAM [379] introduced a coarse-to-fine retrieval pipeline and merged multi-page visual encoding to address evidence sparsity and retrieval efficiency

in long contexts.

DocLLM [307] is a complementary layout-aware text generator: its inputs are text and bounding boxes rather than image-encoder features, and it is not by itself a retrieval system. ViTLP [185] jointly modeled text and layout during pre-training, enabling the model to handle long documents without relying on ultra-long contexts. These examples separate two decisions that are sometimes conflated: how document content is represented and how evidence is retrieved. A layout-aware reader can be used with an OCR-based index, a visual index or no retrieval, so its reader architecture should not determine its RAG category.

Visual retrieval offers an alternative when a text-only index omits diagrams, spatial relationships or other query-relevant visual cues. It performs matching in a learned representation of document images and can coexist with OCR-based or hybrid indexes. ColPali [76] proposed a page-level OCR-free document retrieval method, using VLMs to generate multi-vector page representations and achieving multi-granularity matching between queries and pages through a late-interaction mechanism, significantly improving retrieval robustness for complex layouts while introducing the ViDoRe benchmark to systematically evaluate OCR-free retrieval. Document Screenshot Embedding [177] further used document screenshots as a unified retrieval input, jointly encoding text, images, and layout into dense vectors through large VLMs, allowing a single retrieval system to adapt to various document forms.

For the ColPali late-interaction mechanism just described, a simplified scoring principle is

$$s(q, d) = \sum_i \max_j \langle q_i, d_j \rangle,$$

where each query-token vector $q_i$ matches its most compatible page vector $d_j$. Unlike a single pooled vector, this retains several query-specific matches, with additional index storage and scoring cost.

Beyond page retrieval, multimodal RAG also studies how to combine evidence across pages, documents and modalities. Retaining an image does not itself ensure that the relevant region has been represented or correctly used by the generator. The focus shifted from "whether relevant pages can be retrieved" to "how to organize, align, and verify scattered evidence in complex document collections." Representative works like VisRAG [368] and VDocRAG [285] were pioneers in introducing VLMs to the retrieval stage, using the overall visual representation of a page or document to drive generation, laying the foundation for cross-chart and cross-layout QA. M3DocRAG [47] systematically proposed multi-page, multi-document, multimodal DocQA tasks and significantly improved cross-document evidence coverage by integrating visual cues into the RAG workflow.

Subsequent research deepened at the level of evidence organization and reasoning: CMRAG [32] mitigated unimodal bias through dual-channel retrieval of text and images; RegionRAG [157] lowered retrieval granularity to the region level to reduce visual noise; MHier-RAG [92] integrated fragmented cross-page evidence with hierarchical indexing; MoLoRAG [340] and QCG-RAG [341] introduced logic-aware and query-driven graph structures to enhance multi-hop reasoning; and HKRAG [298] improved answer completeness through holistic modeling of salient knowledge and fine-grained details. Furthermore, Luminirag [187] and MMGraphRAG [306] unified vision and text into graph structures for structured cross-modal retrieval and interpretable reasoning. AutoThinkRAG [358] further advanced this line by introducing a query-complexity-aware router that dynamically allocates retrieval and reasoning paths, enabling more efficient multimodal DocQA under long and information-dense document settings.

In addition, AutoThinkRAG proposed a decoupled perception-and-reasoning paradigm, where a lightweight VLM first translates query-relevant visual evidence into textual descriptions and an LLM subsequently performs logical synthesis, alleviating the reasoning bottleneck of end-to-end VLMs. TableRAG [369] extended this to heterogeneous text-table documents, maintaining structural semantics through retrieval combined with programmatic execution. VisDoM [283] and ViDoRAG [316] utilized multi-step or multi-agent reasoning to improve evidence combination across multiple documents. Finally, Look as You Think [166] and RAG-Anything [98] advanced this line further from the perspectives of verifiable reasoning and unified knowledge representation, with the former using reinforcement learning to achieve precise attribution of reasoning steps and visual evidence, and the latter integrating all-modality knowledge with dual-graph structures.

These systems explore complementary mechanisms for evidence organization and control. Claims about consistency or verifiability require evaluation of support and failure modes; graph structures, tool calls and generated explanations alone do not establish either property.

## 5.3 Agentic Frameworks for Document QA

Alongside fixed retrieval pipelines, multi-document and long-document QA increasingly explores agentic control over evidence access. Static retrieval, long-context readers and iterative controllers remain alternative or composable designs. Early work relied on concatenating document snippets as input to LLMs, which suffered from deficiencies in evidence integration, reasoning controllability, and hallucination suppression. CuriousLLM [362], based on Knowledge Graph Prompting (KGP) and graph traversal agents, introduced a curiosity-driven follow-up question generation mechanism. This allows the model to actively guide retrieval and expand evidence coverage, mitigating the loss of reasoning direction in multi-document QA while reducing the computational and latency overhead of the original KGP methods.

In visually-rich long document scenarios, simple text-level retrieval struggles to locate key evidence. DocLens [401] proposed a tool-enhanced multi-agent framework for long visual document understanding, achieving step-by-step focusing from the entire document to key pages and visual elements through explicit page-level zooming (Lens) and a sampling-judging mechanism, showing significant improvements over traditional long-context strategies. From a more general RAG perspective, MA-RAG [215] pointed out that a single retrieval-generation process struggles with query ambiguity and evidence sparsity. It introduced a multi-agent system with a clear division of labor, decoupling question decomposition, retrieval control, evidence extraction, and answer synthesis through collaborative chain-of-thought communication to systematically improve multi-hop QA performance.

For collection-level retrieval and reasoning of visual documents, ViDoRAG [316] proposed a dynamic iterative reasoning agent. By using hybrid multimodal retrieval strategies and an exploration-reflection workflow, it strengthened joint reasoning of visual and textual evidence and provided the ViDoSeek benchmark to address the lack of evaluation for large-scale visual document collections. Further targeting "research-level" complex queries, Doc-Researcher [68] unified multimodal document parsing, dynamic multi-granularity retrieval, and multi-agent reasoning into an end-to-end system, emphasizing evidence chain accumulation and cross-modal consistency, with systematic evaluation of multi-hop and multi-round capabilities via M4DocBench. Parallel agent research also includes visual agents for interactive environments.

CogAgent [108] built a VLM-based agent capable of understanding and navigating interfaces directly from high-resolution screen pixels, demonstrating the scalability of agentic visual understanding in non-document environments. At the methodological level, HEAR [29] explicitly introduced agentic reasoning into the document understanding process, establishing coordination between information extraction and reasoning generation to organize multimodal evidence actively. Finally, CogDoc [350] proposed a unified coarse-to-fine thinking paradigm based on cognitive modeling. Through a two-stage coordination of fast localization and deep reasoning, combined with reinforcement learning for strategy optimization, it mitigates fine-grained semantic loss while maintaining scalability.

*Choosing evidence access under a finite budget* Table 3 suggests a conditional selection rule. When reliable extracted text and coordinates contain the needed information, a text/layout reader provides explicit searchable units and a straightforward provenance path. When the question depends on graphical content or spatial relations lost in extraction, page-image retrieval or a hybrid index can preserve access to those cues. If the complete document fits within the reader's effective context, a full-context baseline is important: retrieval may otherwise hide evidence that the reader could have accessed. Conversely, fitting a nominal token limit is insufficient if small text becomes unreadable after page resizing.

Iterative tools are most useful when the next evidence location depends on an intermediate result, for example following a cross-reference or inspecting a table after identifying its entity and time period. They should be compared with fixed retrieval under the same page, token and tool-call budgets. Repeated searches can add latency, redundant evidence and opportunities for control errors without improving support. A useful stopping rule therefore requires either sufficient identified evidence, an exhausted budget, or an explicit abstention; a





**Figure 8** Adaptive document access can revisit planning and retrieval. In the constructed margin example, source ratios and a calculation produce a source-linked answer.

longer execution trace is not a quality metric. In each route, the provenance record should connect the final claims to page or region identifiers and, when used, the executed calculation.

## 6 Evaluation

A useful evaluation locates the failure: unreadable input, missing evidence, unsupported interpretation or incorrect computation. One answer score cannot distinguish these causes. We organize benchmarks by the evidence they expose, then separate four observable properties of a document-QA response. This section synthesizes published benchmarks and evaluation protocols; it does not introduce newly executed model comparisons or pool their scores into a controlled leaderboard.

### 6.1 Benchmark Scope and Observable Capabilities

Table 4 compares representative benchmarks by input access, document scope, released supervision and answerability. A dataset that annotates relevant pages supports a different diagnostic from one that releases answer strings alone. Likewise, a retrieval benchmark can test whether evidence is found without testing whether an answer is subsequently faithful to it. The broader literature below is retained to describe additional domains and settings, rather than to imply that all listed resources measure interchangeable capabilities.

*A comparison protocol* Comparable scores require the same task and split, as well as matched access to the underlying document. Reports should state whether inputs are raw page images, native PDF text, supplied OCR or newly generated OCR; whether a retriever searches an entire collection or receives gold pages; and whether layout coordinates, tables, captions or external knowledge are available. Gold-evidence experiments are useful reader diagnostics, but should not be compared with end-to-end systems that must retrieve that evidence. Document versions, duplicate filtering, training overlap and corpus snapshots also affect the difficulty of the evaluation.

Resource conditions must include the model checkpoint or API version and evaluation date, page and image-resolution limits, crop policy, text and visual-token budgets, retrieval depth, re-ranking and tool-call limits, and the treatment of failed requests. Latency and monetary cost should distinguish offline ingestion/indexing from online answering and report the relevant hardware or API pricing date. A full-context baseline and an OCR-based baseline are useful controls for long-document visual RAG when they are permitted the same document information. These controls test whether retrieval or a visual interface adds value under the stated budget, rather than merely giving one system more accessible evidence.

Metrics cannot be pooled simply because they share a percentage scale. ANLS measures normalized answer-

| Benchmark | Input and document scope | Released answer / evidence supervision | Unanswerable setting | Representative reported metrics |
|---|---|---|---|---|
| DocVQA [189] | Single document-page image; OCR available | Answer strings | Not a dedicated target | ANLS |
| Infographic VQA [191] | Single infographic with text, graphics and layout | Answers and question/answer categories | Not a dedicated target | ANLS |
| QASPER [55] | Full scientific paper; text with figures and tables | Answers and supporting paragraphs, figures or tables | Yes | Answer-F1; Evidence-F1 |
| SlideVQA [284] | Slide-image deck | Answers, evidence pages and numerical expressions | Not a dedicated target | QA / evidence / joint EM and F1 |
| DUDE [302] | Heterogeneous multi-page documents | Extractive, abstractive, list and unanswerable answer types | Yes | ANLS with answer-type handling |
| MMLongBench-Doc [179] | Long PDFs; mixed visual evidence and cross-page questions | Answers; evidence source and page annotations | Yes | Answer F1; breakdowns by question/evidence type |
| ViDoRe (original) [76] | Query-to-page retrieval over visually rich page corpora | Relevant-page judgments | N/A: retrieval | nDCG@5; Recall@K; MRR |
| CRAG [360] | Factual QA with mock web and knowledge-graph search APIs | Reference answers; invalid-question category; graded predictions | Invalid / missing answers | Accuracy, hallucination, missing and truthfulness |

**Table 4** A capability-oriented comparison of selected evaluation resources, based on their original papers and released protocols. Evidence annotations describe available supervision, not an assumption that gold evidence is supplied to the tested system. "Not a dedicated target" does not imply that every real query is answerable. Exact dataset, evaluator and metric versions must accompany numerical comparisons.

string similarity with its protocol's edit-distance threshold; exact match is stricter about normalized string identity; token or span F1 measures answer overlap. Evidence-F1, Recall@K and nDCG@K measure different selection and ranking properties. For example, QASPER reports Answer-F1 separately from Evidence-F1 [55], while the original ViDoRe evaluates page retrieval primarily with nDCG@5 [76]. CRAG separately accounts for accurate, hallucinated and missing answers, and its automatic truthfulness score is accuracy minus hallucination [360]. A single cross-benchmark average would obscure these distinctions. For generated-answer judging, the judge model, prompt, answer normalization, human audit procedure and uncertainty across questions should be specified.

*Four distinct validation targets* **Answer correctness** concerns the requested result and its unit. Exact match tests normalized string identity; token F1 measures overlap; ANLS uses normalized edit distance with the benchmark's threshold. These metrics suit different answer forms and should not be averaged across datasets as interchangeable percentages. For open-ended answers, the judge model, prompt and a human-audited sample help reveal whether fluent paraphrases or unsupported additions are being rewarded.

**Evidence localization** concerns the selected page, passage, region or cell. Recall measures whether required evidence is present; ranking metrics such as nDCG and MRR also consider its position. Gold-page experiments isolate the reader, whereas end-to-end retrieval experiments include evidence selection. Both are useful, but answer scores obtained with gold evidence should be reported separately from scores that require searching a collection.

**Source support** asks whether the cited material justifies the complete answer, including qualifications and explanations. A correct numerical component does not support an additional causal claim. Equivalent evidence may occur in several locations, so annotation should allow valid alternatives. Support is also distinct from causal faithfulness: establishing whether the model actually relied on the cited source requires interventions such as removing or substituting that evidence, not just checking the displayed citation.





**Figure 9** Constructed response traces separate numeric agreement, evidence localization, source support and arithmetic. The examples illustrate diagnostic outcomes, not measured model scores.

**Execution correctness** asks whether the declared operation ran correctly on the supplied inputs. A Python or SQL result can verify arithmetic while using the wrong year, unit or table. It should therefore be paired with localization and semantic checks on those inputs. For multi-step questions, retain the intermediate values and their source locations so that a computational error can be separated from a parsing or planning error.

Figure 9 illustrates why these targets require separate checks. A response can match the reference number while citing an irrelevant row or adding a cause that the document never states. Conversely, selecting the relevant cells does not guarantee correct arithmetic. Even a response that passes all displayed checks does not, by itself, establish causal reliance on the cited evidence.

*Deployment-oriented reporting* Existing resources already test unanswerable questions, evidence selection and robustness; the remaining issue is coverage of their combinations under realistic budgets. Results should therefore be broken down by page length, scan degradation, language, layout density and evidence modality where the data permit. Abstention should be evaluated together with answer coverage and error rate, rather than rewarded for refusing every question. Such reporting makes a failure diagnosable without equating a generated explanation or an agent trace with verified reasoning.

## 6.2 Visual Document Understanding and Basic QA Evaluation

Document Question Answering (DocQA) evaluation spans single pages, multi-page documents and document collections, with different requirements for text reading, spatial interpretation and evidence selection. DocVQA [189] is one of the earliest benchmarks to systematically propose "question answering on document images," emphasizing the localization of facts by understanding text, layout, and visual cues in single-page documents. Document Collection VQA [295] evaluates collection-level search and answering, rather than single-page understanding alone. InfographicVQA [191] focuses on infographic QA to evaluate the model's understanding and reasoning capabilities in mixed scenarios of complex layouts, charts, and text. A Dataset of Information-Seeking Questions and Answers Anchored in Research Papers [55] proposed a QA dataset oriented toward long scientific research papers, focusing on the types of questions readers actually ask while reading. DUE: End-to-End Document Understanding Benchmark [19] proposed a comprehensive benchmark for end-to-end document understanding, where models start from raw documents, obtain text and layout through OCR and layout modeling, and then complete downstream tasks. These datasets primarily focus on visual text understanding, region localization, and factual QA in single documents or small-scale collections, laying the most fundamental input and evaluation paradigm for subsequent "Retrieval + Reasoning."

*Cross-page access and adaptation.* Next, the research focus began to shift from "understanding one page" to "cross-page understanding and localization." Hierarchical Multimodal Transformers for Multi-Page DocVQA [296] was the first to systematically handle multi-page documents, answering "what to do when information is scattered across multiple pages" through hierarchical structural modeling of pages and document-level semantics. VRDU [325] proposed a "Visually Rich Document Understanding" benchmark and evaluation framework specifically for complex business document information extraction tasks in real business scenarios. Test-Time Adaptation for Visual Document Understanding [72] is an adaptation method and evaluation setting, not a new dataset of the same kind: it studies adjustment to target documents at test time. Comparisons must disclose whether target-domain adaptation is allowed.

*Page selection, privacy and long PDFs.* Simultaneously, datasets with the problem setting of "locating evidence from a large number of pages" began to emerge. PDFVQA [62] studies questions about real PDF documents and the localization of relevant information across pages. SlideVQA [284] is a DocVQA dataset for multi-page slide documents consisting of slide images and natural language questions, used to study understanding and reasoning across multiple image pages. DUDE [302] is a document understanding benchmark and evaluation framework proposed in 2023, oriented toward DocVQA and comprehensive document understanding evaluation on visually rich documents. DLUE [351] is a comprehensive evaluation dataset and task suite for long and complex-structured documents, used to systematically assess model capabilities in document-level language understanding. KNVQA [42] proposed a knowledge-based visual QA evaluation dataset and benchmark, primarily used to assess the "factuality" and knowledge reasoning abilities of Large Vision-Language Models (LVLMs). Privacy-Aware Document VQA [297] is a privacy-sensitive dataset and benchmark for DocVQA, used to study automatic QA and information extraction on real invoices under Federated Learning and Differential Privacy constraints, revealing the constraints of DocQA in real-world applications and pushing evaluation from ideal to reality. PDFTriage [247] is a QA benchmark and methodology for long structured documents (e.g., PDFs), used to evaluate and enhance the QA capabilities of large models in "whole book / ultra-long context" scenarios, with a particular emphasis on the role of document structure (chapters, page numbers, tables, images, etc.) in retrieval and answering.

## 6.3 Document QA Evaluation

RAG evaluation includes fixed benchmarks, benchmark-construction frameworks and automated testing techniques. RAGProbe [271] is an automated evaluation approach that generates question variants to test RAG applications; it should not be treated as a fixed dataset directly interchangeable with CRAG or document-QA corpora.

Next, a large body of work began to explicitly distinguish the four stages of retrieval / grounding / reasoning / generation and constructed explainable or controllable evaluation frameworks. General and systematic method evaluation benchmarks include the following works. CRAG [360] combines factual questions across five domains with mock APIs for web and knowledge-graph search. Its controlled retrieval tasks enable comparisons of RAG components under specified access conditions, while its graded answers distinguish hallucination from missing information. It is not specifically a benchmark of visual page structure. Unanswerability Evaluation for RAG [232] measures whether a system can correctly refuse to answer when encountering unanswerable queries in documents, analyzing different causes of unanswerability. LONG$^2$RAG [238] is an evaluation benchmark for long-context, long-form RAG systems, used to systematically measure the real capabilities of large models in "reading long text, retrieving multiple documents, and generating long answers" scenarios. Fact, Fetch, and Reason [141] argued for measuring the overall performance of end-to-end systems in real application scenarios. Each sample is a multi-hop QA question where answers are often scattered across multiple Wikipedia articles, sometimes requiring numerical calculation (e.g., "how many times faster"), table queries, temporal reasoning, combining multiple conditions, or post-processing retrieval results.

*Domain and language conditions.* Many datasets in Chinese and domain-specific directions have also emerged. CRUD-RAG [176] is a large-scale Chinese benchmark for RAG systems, abstracting four major application types from the classic CRUD operations of "user interaction with knowledge bases" to perform comprehensive end-to-end and component-level evaluation of RAG. LegalBench-RAG [236] is an evaluation benchmark

specifically for the "retrieval stage" in the legal domain, used to measure the precision retrieval capabilities of various retrievers on complex legal documents. OmniEval [318] is a comprehensive evaluation benchmark for financial RAG systems, used to automatically and comprehensively assess the retrieval and generation capabilities of financial RAG/Agent systems in real financial scenarios. RAGCare-QA [65], carefully curated and human-annotated, is a medical RAG evaluation benchmark dataset for systematically evaluating RAG pipelines and model performance in "theoretical medical knowledge QA" scenarios. RAGPPI [119] is a RAG benchmark and evaluation framework for the Protein-Protein Interaction (PPI) field, used to evaluate the capability of large models to answer questions related to the biological impact of PPI in drug target discovery scenarios.

*Long visual documents and multi-document scope.* Simultaneously, document and multi-modal long-context benchmarks matured rapidly. M3DocVQA [48] is an open-domain, multi-page, multi-document DocVQA benchmark dataset, primarily serving DocVQA/RAG research for multimodal retrieval and large models. MMLongBench-Doc [179] is a benchmark dataset and evaluation framework for multimodal long-context document understanding, mainly used to test the reading comprehension, retrieval, and reasoning capabilities of LVLMs in real long-document PDF scenarios. MMDocBench [406] is similarly a benchmark and framework for multimodal long-context understanding to test LVLMs in real PDF scenarios. DOCBENCH [411] is an evaluation benchmark for LLM document reading systems, used to systematically assess the end-to-end capabilities of document reading systems in real interaction scenarios involving "uploading raw documents + asking questions about them." LongDocURL [58] is a large-scale evaluation dataset for long-form multimodal document understanding, used to systematically evaluate the capabilities of multimodal large models in long document understanding, numerical reasoning, and cross-element localization. It focuses on complex PDF documents of dozens or even hundreds of pages, dividing tasks into three main categories: Understanding (U), Reasoning (R), and Locating (L). M-Longdoc [46] is an evaluation benchmark and framework for "multimodal ultra-long document understanding," used to systematically evaluate and improve the QA and reasoning capabilities of LVLMs/LMMs on hundreds of pages of documents. Proposed in 2024, it focuses on ultra-long PDF documents in realistic scenarios, emphasizing open-ended answering and retrieval augmentation. Leave No Document Behind [314] proposed a long-context LLM evaluation benchmark to systematically test models' long-context understanding in "extended multi-document QA" scenarios, defining four types of tasks: Spotlight Locating, Comparison, Clustering, and Chain of Reasoning.

## 6.4 Real-World Image-Text Interaction Document Evaluation

The following resources extend evaluation to image-text interaction, enterprise documents and heterogeneous evidence. REAL-MM-RAG [327] focuses on real enterprise/document scenarios, emphasizing "difficult retrieval and high robustness" across multiple modalities such as text, tables, and images. CRAG-MM [311] is a comprehensive RAG evaluation benchmark for multi-modal, multi-person multi-turn dialogue scenarios, mainly focusing on the real application scenario of "wearable devices + visual QA + retrieval augmentation." Visual-RAG [342] is a benchmark and evaluation framework for text-to-image RAG, containing numerous visual knowledge-intensive questions and related image candidate sets. Seeing Through the MiRAGE [186] is an evaluation framework and benchmark for multimodal RAG, specifically designed to measure the factuality and citation quality of models when retrieving, generating, and citing from multimodal sources such as text, images, audio, and video. UNIDOC-BENCH [233] extracts pages from real enterprise-level PDFs, annotating text blocks, tables, and images with evidence links, and then automatically or semi-automatically constructs multimodal QA pairs. Questions cover four typical RAG tasks: factual retrieval, comparison, summarization, and logical reasoning. VisR-Bench [25] proposed a multi-lingual long-document visual retrieval benchmark for visual RAG, focusing on the complete workflow of "retrieving the appropriate page from long multi-page documents and then answering." Benchmarking Retrieval-Augmented Multimodal Generation for Document QA [67] focuses on mixed image-text information in real complex documents (long PDFs, reports, papers, etc.), including text, formulas, charts, tables, infographics, etc., with complex layouts. Each sample consists of a question, a short answer, and an evidence chain with layout positions.

*Evidence composition across sources.* Retrieval for multi-hop and complex reasoning is also gradually developing. MultiHop-RAG [288] is a benchmark and evaluation suite for multi-hop RAG, used to systematically

evaluate the retrieval and reasoning capabilities of RAG in complex multi-hop QA scenarios. DocHop-QA [226] focuses on real-world "cross-document, multi-structure, multi-step reasoning" complex information retrieval and reasoning scenarios. Automatically constructed from scientific PDF documents, questions often require aggregating evidence across multiple documents, pages, and structural blocks (paragraphs, tables, captions, etc.) to get the answer, rather than direct lookup in a single text segment. FanOutQA [400] focuses on so-called "fan-out" questions: one question requires simultaneously finding and integrating information across numerous entities and multiple documents. MHTS [147] proposed systematically controlling reasoning difficulty to construct high-quality, diverse, and adjustable-difficulty multi-hop QA benchmarks for finer evaluation of RAG retrieval and generation.

*Tables and heterogeneous sources.* RAG evaluation based on structured heterogeneous datasets is also receiving increasing attention. RAG over Tables [412] refers to a set of evaluation benchmarks and frameworks proposed around RAG tasks on tabular data, oriented toward multi-table QA and RAG model evaluation on large-scale tabular corpora. T2-RAGBench [274] is a text-table hybrid RAG evaluation benchmark for the financial domain, used to systematically assess the model's capability in the complete "retrieval followed by numerical reasoning" process. mmRAG [349] is a modular benchmark for heterogeneous/multimodal RAG systems, using a unified framework to evaluate the retrieval and generation capabilities of systems across multiple knowledge sources like text, tables, and knowledge graphs. RAG-based QA over Heterogeneous Data and Text [51] is a set of research and experimental configurations around the QUASAR system for evaluating RAG QA capabilities on heterogeneous data sources.

*Corpus freshness.* Dynamic RAG evaluation datasets based on time have also been proposed. DRAGON [44] is a dynamic RAG evaluation benchmark for news scenarios, mainly focusing on systematically evaluating the retrieval and generation capabilities of RAG on continuously changing news corpora in a Russian environment. FreshStack [293] is an evaluation benchmark and construction framework for technical document retrieval/RAG systems, specifically designed to evaluate the real performance of technical document retrieval and technical RAG QA in 2025 and beyond. It automatically constructs datasets from real community QA, focusing on rapidly evolving and easily contaminated technical fields.

*Full-context controls and aggregation.* Long-context and retrieval-free control evaluations were subsequently proposed. LaRA [153] focuses on evaluating whether LLMs in typical 2025 applications should rely more on ultra-long context input or obtain information through external retrieval. Ko-LongRAG [136] is an evaluation benchmark specifically for Korean long-context RAG. It simulates real long-document retrieval scenarios through a "retrieval-free construction method" to systematically evaluate various large models on Korean long-context RAG tasks. Summary of a Haystack [145] is an evaluation benchmark for long-context large models and RAG systems, focusing on testing the system's robust long-text understanding and aggregation capabilities in million-token contexts. Proposed in 2024, it emphasizes "finding and correctly summarizing important content" in complex multi-document scenarios. Are We on the Right Way for Assessing Document RAG? [261] is a systematic analysis and benchmark design study on document-level RAG evaluation methods. It focuses on the deficiencies of current document RAG benchmarks and proposes a new evaluation system, Double-Bench, as an alternative.

*Perception, structure and language robustness.* In addition to benchmarks directly oriented toward RAG, a series of document visual understanding datasets have systematically characterized the complexity of real documents at visual, structural, and linguistic levels in parallel evolution. These resources characterize perceptual and structural difficulty; their results should not be read as direct measurements of downstream RAG answer quality. These include RoDLA [37], a robustness benchmark for document layout analysis. It systematically evaluates the stability of layout detection/segmentation model performance under real interference conditions, making it an important robustness evaluation benchmark in the current DLA field. U-DIADS-Bib [410] is a document layout analysis benchmark for ancient manuscripts, focusing on pixel-level semantic layout segmentation to evaluate and drive algorithm development for tasks such as codex layout understanding, OCR preprocessing, and automatic transcription. M6Doc [40] is an open dataset for modern document layout analysis, particularly emphasizing real scenarios, multiple formats, multiple languages, and

complex layouts, significantly impacting document understanding and OCR preprocessing. MosaicDoc [28] is a large-scale Chinese-English bilingual benchmark for visually rich document understanding, collecting images from newspapers and magazines, containing highly heterogeneous visual elements such as illustrations, titles, subtitles, columns, and advertisement blocks. HW-MLVQA [223] is a visual QA dataset and benchmark for multilingual handwritten document understanding, used to evaluate and drive the cross-modal and cross-lingual understanding capabilities of models on real handwritten documents. MTVQA [287] is a benchmark for multilingual text-centric visual QA, used to systematically assess the capabilities of multimodal large models in multilingual scene text understanding and QA. All images come from real-world "text-rich scenes," covering over 20 scene types such as posters, signboards, document screenshots, product packaging, and interface screenshots. IconQA [171] is a large-scale visual QA dataset for "diagram reasoning," focusing on iconic scenarios such as abstract charts and textbook illustrations rather than natural images. A Comparative Review [210] is a survey work that systematically reviews the evolution of visual document understanding from traditional methods to deep learning and then to multimodal Transformers in recent years. It points out that real-world documents such as invoices, receipts, tables, research reports, and questionnaires contain text, layout, and visual elements simultaneously, thus requiring a concentrated, comparative review for visual document understanding. Together, these works constitute the perceptual and structural foundation for document-level and multimodal RAG systems, explaining why RAG performance in real-world documents is often limited by input parsing and evidence structuring capabilities rather than just the retrieval or generation modules themselves.

# 7 Future Research Directions and Conclusion

The approaches reviewed in this survey distribute recognition, retrieval, and reasoning across different interfaces. Their remaining limitations suggest three connected research directions: separating the properties being verified, allocating computation to unresolved evidence, and evaluating transfer under explicit deployment constraints.

## 7.1 Separating Localization, Support, and Execution

An answer accompanied by a page citation exposes an inspectable source, but that citation alone does not establish that the page supports the answer or that the model relied on it. Similarly, a SQL query can execute successfully while selecting the wrong table, column, unit, or aggregation. Four properties should therefore be evaluated separately: answer correctness, localization of the relevant evidence, support of the answer by that evidence, and correctness of any executable computation. Counterfactual evidence replacement or removal can additionally test dependence on the claimed source; an explanatory trace alone is insufficient for that purpose.

Benchmarks already provide parts of this supervision. Cross-page and unanswerable questions in MMLongBench-Doc [179], multimodal citation evaluation [186], and document-level locating tasks [58] make different failures observable. A useful next step is to combine these properties in controlled settings: preserve the answer-bearing value while changing a distractor, move a supporting footnote to another page, or make the required evidence unavailable. Evaluating answer change, evidence selection, and abstention separately would help distinguish successful retrieval from unsupported answer generation.

## 7.2 Selective Perception and Budget-Aware Evidence Acquisition

Recognition and reasoning need not consume the same representation or the same amount of computation for every document. Dense text may benefit from explicit OCR; a chart or visually encoded relation may require image evidence; a calculation may benefit from an executable tool. A hybrid system should decide which representation is needed for the question and where additional observation is justified. The design problem includes preserving coordinates and units when converting between text, cells, and images.

Future comparisons should vary OCR quality, image resolution, document length, and retrieval difficulty while controlling model version and inference budget. Relevant baselines include full-context processing, one-shot retrieval, and iterative retrieval with the same available sources. Tool calls should be assessed by the evidence they add, their latency and computational cost, and their effect on failure recovery. Such comparisons can reveal when revisiting a page is useful and when extra iterations merely repeat the same unsupported

assumption. The running table-and-footnote example illustrates why arithmetic verification must follow, rather than substitute for, correct evidence selection.

## 7.3 Transfer, Uncertainty, and Reproducible Evaluation

Document benchmarks increasingly include long contexts, multilingual content, retrieval, and imperfect input. Their remaining gaps should be described as specific combinations of conditions. Examples include cross-page reasoning under degraded scans, evidence support across a table and a figure, or retrieval over a changing multilingual collection. Broad claims that existing evaluations only measure clean-page accuracy overlook these developments.

A reproducible evaluation should record the document and annotation versions, split, model checkpoint or API version, permitted input representations, external knowledge access, page and token budgets, retrieval settings, and metric implementation. Reports should separate the effect of source parsing from retrieval and answer generation. For systems that abstain or report confidence, accuracy should be evaluated together with coverage and the treatment of unanswerable questions. Releasing predictions, retrieved evidence identifiers, and executable evaluation code would permit error diagnosis without assuming that identical headline metrics imply identical capabilities.

## 7.4 Conclusion

Document intelligence connects page perception with evidence-based reasoning across text, layout, tables, and images. We have reviewed this landscape through input representation, context span, evidence granularity, inference control, and validation. These axes clarify how OCR pipelines, direct-visual models, retrieval systems, and agentic controllers can be combined and where their interfaces can lose information.

The reviewed literature supports a conditional view of system design: appropriate representations and inference mechanisms depend on the evidence required by the task and on available resources. Progress should be demonstrated through comparisons that preserve these conditions and distinguish answer accuracy from evidence support and execution correctness. This perspective turns evidence preservation and verification into concrete design and evaluation questions spanning the entire document intelligence workflow.

## References


[1] Wiam Adnan, Joel Tang, Yassine Bel Khayat Zouggari, Seif Edinne Laatiri, Laurent Lam, and Fabien Caspani. A layoutlmv3-based model for enhanced relation extraction in visually-rich documents. In *International Conference on Document Analysis and Recognition*, pages 160–174. Springer, 2024.

[2] Weronika T Adrian, Nicola Leone, Marco Manna, and Cinzia Marte. Document layout analysis for semantic information extraction. In *Conference of the Italian association for artificial intelligence*, pages 269–281. Springer, 2017.

[3] Armen Aghajanyan, Bernie Huang, Candace Ross, Vladimir Karpukhin, Hu Xu, Naman Goyal, Dmytro Okhonko, Mandar Joshi, Gargi Ghosh, Mike Lewis, et al. Cm3: A causal masked multimodal model of the internet. *arXiv preprint arXiv:2201.07520*, 2022.

[4] Hayato Aida, Kosuke Takahashi, and Takahiro Omi. Enhancing large vision-language models with layout modality for table question answering on japanese annual securities reports. *arXiv preprint arXiv:2505.17625*, 2025.

[5] Nurmukhammed Aitymbetov, Min-Ho Lee, and Nguyen Anh Tu. Multi-document question answering with lightweight embeddings-based document reranker. In *2024 International Conference on Advanced Technologies for Communications (ATC)*, pages 707–712. IEEE, 2024.

[6] Adem Akdoğan and Murat Kurt. Exttnet: A deep learning algorithm for extracting table texts from invoice images. *arXiv preprint arXiv:2402.02246*, 2024.

[7] J Amudha, Manmohan Singh Thakur, Anupriya Shrivastava, Shubham Gupta, Deepa Gupta, and Kshitij Sharma. Wild ocr: Deep learning architecture for text recognition in images. In *Proceedings of International Conference on Computing and Communication Networks: ICCCN 2021*, pages 499–506. Springer, 2022.

[8] Avinash Anand, Raj Jaiswal, Pijush Bhuyan, Mohit Gupta, Siddhesh Bangar, Md Modassir Imam, Rajiv Ratn Shah, and Shin'ichi Satoh. Tc-ocr: Tablecraft ocr for efficient detection & recognition of table structure & content. In *Proceedings of the 1st international workshop on deep multimodal learning for information retrieval*, pages 11–18, 2023.

[9] Aresha Arshad, Momina Moetesum, Faisal Shafait, et al. A graph-augmented multi-stage transformer model for document layout understanding. *International Journal on Document Analysis and Recognition (IJDAR)*, pages 1–14, 2025.

[10] Nicolas Audebert, Catherine Herold, Kuider Slimani, and Cédric Vidal. Multimodal deep networks for text and image-based document classification. In *Joint European conference on machine learning and knowledge discovery in databases*, pages 427–443. Springer, 2019.

[11] Christoph Auer, Ahmed Nassar, Maksym Lysak, Michele Dolfi, Nikolaos Livathinos, and Peter Staar. Icdar 2023 competition on robust layout segmentation in corporate documents. In *International Conference on Document Analysis and Recognition*, pages 471–482. Springer, 2023.

[12] Jinze Bai, Jinpeng Wang, Shuai Zhang, et al. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*, 2023.

[13] Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, Mei Li, Kaixin Li, Zicheng Lin, Junyang Lin, Xuejing Liu, Jiawei Liu, Chenglong Liu, Yang Liu, Dayiheng Liu, Shixuan Liu, Dunjie Lu, Ruilin Luo, Chenxu Lv, Rui Men, Lingchen Meng, Xuancheng Ren, Xingzhang Ren, Sibo Song, Yuchong Sun, Jun Tang, Jianhong Tu, Jianqiang Wan, Peng Wang, Pengfei Wang, Qiuyue Wang, Yuxuan Wang, Tianbao Xie, Yiheng Xu, Haiyang Xu, Jin Xu, Zhibo Yang, Mingkun Yang, Jianxin Yang, An Yang, Bowen Yu, Fei Zhang, Hang Zhang, Xi Zhang, Bo Zheng, Humen Zhong, Jingren Zhou, Fan Zhou, Jing Zhou, Yuanzhi Zhu, and Ke Zhu. Qwen3-vl technical report. In *arXiv preprint arXiv:2511.21631*, 2025.

[14] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2. 5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025.

[15] Aditya Bangar, Ankur Kumar, Shlok Mishra, and Ashutosh Modi. Exploration lab iitk at semeval-2025 task 8: Multi-llm agent qa over tabular data. In *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*, pages 2165–2169, 2025.

[16] L Viviana Beltrán Beltrán, Juan C Caicedo, Nicholas Journet, Mickaël Coustaty, François Lecellier, and Antoine Doucet. Deep multimodal learning for cross-modal retrieval: One model for all tasks. *Pattern Recognition Letters*, 146:38–45, 2021.

[17] Diego Belzarena, Seginus Mowlavi, Aitor Artola, Camilo Mariño, Marina Gardella, Ignacio Ramírez, Antoine Tadros, Roy He, Natalia Bottaioli, Boshra Rajaei, et al. Improving ocr using internal document redundancy. In *International Conference on Document Analysis and Recognition*, pages 244–260. Springer, 2025.

[18] Ali Furkan Biten, Ruben Tito, Lluis Gomez, Ernest Valveny, and Dimosthenis Karatzas. Ocr-idl: Ocr annotations for industry document library dataset. In *European Conference on Computer Vision*, pages 241–252. Springer, 2022.

[19] Łukasz Borchmann, Michał Pietruszka, Tomasz Stanislawek, Dawid Jurkiewicz, Michał Turski, Karolina Szyndler, and Filip Graliński. Due: End-to-end document understanding benchmark. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.

[20] Zeyd Boukhers and Azeddine Bouabdallah. Vision and natural language for metadata extraction from scientific pdf documents: a multimodal approach. In *Proceedings of the 22nd ACM/IEEE Joint Conference on Digital Libraries*, pages 1–5, 2022.

[21] Thomas M Breuel. The ocropus open source ocr system. In *Document recognition and retrieval XV*, volume 6815, pages 120–134. SPIE, 2008.

[22] Lang Cao, Jingxian Xu, Hanbing Liu, Jinyu Wang, Mengyu Zhou, Haoyu Dong, Shi Han, and Dongmei Zhang. Fortune: Formula-driven reinforcement learning for symbolic table reasoning in language models. *arXiv preprint arXiv:2505.23667*, 2025.

[23] Hong Cai Chen, Yi Pin Xu, and Yang Zhang. Advanced chain-of-thought reasoning for parameter extraction from documents using large language models. *arXiv preprint arXiv:2502.16540*, 2025.

[24] Jian Chen, Ruiyi Zhang, Yufan Zhou, Tong Yu, Franck Dernoncourt, Jiuxiang Gu, Ryan A Rossi, Changyou Chen, and Tong Sun. Lora-contextualizing adaptation of large multimodal models for long document understanding. *arXiv e-prints*, pages arXiv–2411, 2024.

[25] Jian Chen, Ming Li, Jihyung Kil, Chenguang Wang, Tong Yu, Ryan Rossi, Tianyi Zhou, Changyou Chen, and Ruiyi Zhang. Visr-bench: An empirical study on visual retrieval-augmented generation for multilingual long document understanding. *arXiv preprint arXiv:2508.07493*, 2025.

[26] Jifan Chen, Shih-ting Lin, and Greg Durrett. Multi-hop question answering via reasoning chains. *arXiv preprint arXiv:1910.02610*, 2019.

[27] Kaibing Chen, Dong Shen, Hanwen Zhong, Huasong Zhong, Kui Xia, Di Xu, Wei Yuan, Yifei Hu, Bin Wen, Tianke Zhang, et al. Evlm: An efficient vision-language model for visual understanding. *arXiv preprint arXiv:2407.14177*, 2024.

[28] Ketong Chen, Yuhao Chen, and Yang Xue. Mosaicdoc: A large-scale bilingual benchmark for visually rich document understanding. *arXiv preprint arXiv:2511.09919*, 2025.

[29] Longfeng Chen, Zheng Xiao, Juyuan Wang, Zeyu Huang, Yawen Zeng, and Jin Xu. Hear: A holistic extraction and agentic reasoning framework for document understanding. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pages 14376–14382, 2025.

[30] Qian Chen, Xianyin Zhang, Lifan Guo, Feng Chen, and Chi Zhang. Dianjin-ocr-r1: Enhancing ocr capabilities via a reasoning-and-tool interleaved vision-language model. *arXiv preprint arXiv:2508.13238*, 2025.

[31] Song Chen, Xinyu Guo, Yadong Li, Tao Zhang, Mingan Lin, Dongdong Kuang, Youwei Zhang, Lingfeng Ming, Fengyu Zhang, Yuran Wang, et al. Ocean-ocr: Towards general ocr application via a vision-language model. *arXiv preprint arXiv:2501.15558*, 2025.

[32] Wang Chen, Wenhan Yu, Guanqiang Qi, Weikang Li, Yang Li, Lei Sha, Deguo Xia, and Jizhou Huang. Cmrag: Co-modality-based visual document retrieval and question answering. *arXiv preprint arXiv:2509.02123*, 2025.

[33] Wang Chen, Wenhan Yu, Guanqiang Qi, Weikang Li, Yang Li, Lei Sha, Deguo Xia, and Jizhou Huang. Cmrag: Co-modality-based visual document retrieval and question answering. *arXiv preprint arXiv:2509.02123*, 2025.

[34] Xi Chen, Josip Djolonga, Piotr Padlewski, Basil Mustafa, Soravit Changpinyo, Jialin Wu, Carlos Riquelme Ruiz, Sebastian Goodman, Xiao Wang, Yi Tay, et al. Pali-x: On scaling up a multilingual vision and language model. *arXiv preprint arXiv:2305.18565*, 2023.

[35] Xi Chen, Xiao Wang, Lucas Beyer, Alexander Kolesnikov, Jialin Wu, Paul Voigtlaender, Basil Mustafa, Sebastian Goodman, Ibrahim Alabdulmohsin, Piotr Padlewski, et al. Pali-3 vision language models: Smaller, faster, stronger. *arXiv preprint arXiv:2310.09199*, 2023.

[36] Xinyue Chen, Pengyu Gao, Jiangjiang Song, and Xiaoyang Tan. Hiqa: A hierarchical contextual augmentation rag for multi-documents qa. *arXiv preprint arXiv:2402.01767*, 2024.

[37] Yufan Chen, Jiaming Zhang, Kunyu Peng, Junwei Zheng, Ruiping Liu, Philip Torr, and Rainer Stiefelhagen. Rodla: Benchmarking the robustness of document layout analysis models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15556–15566, 2024.

[38] Yung-Hsin Chen and Yuli Zhou. Enhancing ocr performance through post-ocr models: Adopting glyph embedding for improved correction. *arXiv preprint arXiv:2308.15262*, 2023.

[39] Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and test-time scaling. *arXiv preprint arXiv:2412.05271*, 2024.

[40] Hiuyi Cheng, Peirong Zhang, Sihang Wu, Jiaxin Zhang, Qiyuan Zhu, Zecheng Xie, Jing Li, Kai Ding, and Lianwen Jin. M6doc: A large-scale multi-format, multi-type, multi-layout, multi-language, multi-annotation category dataset for modern document layout analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15138–15147, 2023.

[41] Lilu Cheng, Jingjun Lu, Yi Xuan Chan, Quoc Khai Nguyen, John Bi, and Sean Ho. A hybrid architecture for multi-stage claim document understanding: Combining vision-language models and machine learning for real-time processing. *arXiv preprint arXiv:2601.01897*, 2026.

[42] Sirui Cheng, Siyu Zhang, Jiayi Wu, and Muchen Lan. Knvqa: A benchmark for evaluation knowledge-based vqa. *arXiv preprint arXiv:2311.12639*, 2023.

[43] Zhoujun Cheng, Haoyu Dong, Ran Jia, Pengfei Wu, Shi Han, Fan Cheng, and Dongmei Zhang. Fortap: Using formulas for numerical-reasoning-aware table pretraining. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1150–1166, 2022.

[44] Fedor Chernogorskii, Sergei Averkiev, Liliya Kudraleeva, Zaven Martirosian, Maria Tikhonova, Valentin Malykh, and Alena Fenogenova. Dragon: Dynamic rag benchmark on news. *arXiv preprint arXiv:2507.05713*, 2025.

[45] Ce Chi, Xing Wang, Zhendong Wang, Xiaofan Liu, Ce Li, Zhiyan Song, Chen Zhao, Kexin Yang, Boshen Shi, Jingjing Yang, et al. Jt-da: Enhancing data analysis with tool-integrated table reasoning large language models. *arXiv preprint arXiv:2512.06859*, 2025.

[46] Yew Ken Chia, Liying Cheng, Hou Pong Chan, Maojia Song, Chaoqun Liu, Mahani Aljunied, Soujanya Poria, and Lidong Bing. M-longdoc: A benchmark for multimodal super-long document understanding and a retrieval-aware tuning framework. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 9244–9261, 2025.

[47] Jaemin Cho, Debanjan Mahata, Ozan Irsoy, Yujie He, and Mohit Bansal. M3docrag: Multi-modal retrieval is what you need for multi-page multi-document understanding. *arXiv preprint arXiv:2411.04952*, 2024.

[48] Jaemin Cho, Debanjan Mahata, Ozan Irsoy, Yujie He, and Mohit Bansal. M3docvqa: Multi-modal multi-page multi-document understanding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6178–6188, 2025.

[49] Eunsol Choi, Daniel Hewlett, Jakob Uszkoreit, Illia Polosukhin, Alexandre Lacoste, and Jonathan Berant. Coarse-to-fine question answering for long documents. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 209–220, 2017.

[50] V Chowrasia, S Shilakari, and Rajeev Pandey. Implementation of optical character recognition using machine learning. *Int J Comput Sci Eng*, 6(6), 2018.

[51] Philipp Christmann and Gerhard Weikum. Rag-based question answering over heterogeneous data and text. *arXiv preprint arXiv:2412.07420*, 2024.

[52] Cheng Cui, Ting Sun, Suyin Liang, Tingquan Gao, Zelun Zhang, Jiaxuan Liu, Xueqing Wang, Changda Zhou, Hongen Liu, Manhui Lin, et al. Paddleocr-vl: Boosting multilingual document parsing via a 0.9 b ultra-compact vision-language model. *arXiv preprint arXiv:2510.14528*, 2025.

[53] Cheng Cui, Ting Sun, Manhui Lin, Tingquan Gao, Yubo Zhang, Jiaxuan Liu, Xueqing Wang, Zelun Zhang, Changda Zhou, Hongen Liu, et al. Paddleocr 3.0 technical report. *arXiv preprint arXiv:2507.05595*, 2025.

[54] Cheng Cui, Ting Sun, Suyin Liang, Tingquan Gao, Zelun Zhang, Jiaxuan Liu, Xueqing Wang, Changda Zhou, Hongen Liu, Manhui Lin, et al. Paddleocr-vl-1.5: Towards a multi-task 0.9 b vlm for robust in-the-wild document parsing. *arXiv preprint arXiv:2601.21957*, 2026.

[55] Pradeep Dasigi, Kyle Lo, Iz Beltagy, Arman Cohan, Noah A Smith, and Matt Gardner. A dataset of information-seeking questions and answers anchored in research papers. *arXiv preprint arXiv:2105.03011*, 2021.

[56] Nicola De Cao, Wilker Aziz, and Ivan Titov. Question answering by reasoning across documents with graph convolutional networks. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human language technologies, Volume 1 (long and short papers)*, pages 2306–2317, 2019.

[57] Axel De Nardin, Silvia Zottin, Claudio Piciarelli, Gian Luca Foresti, Emanuela Colombi, et al. In-domain versus out-of-domain transfer learning for document layout analysis. *INTERNATIONAL JOURNAL ON DOCUMENT ANALYSIS AND RECOGNITION*, 2024.

[58] Chao Deng, Jiale Yuan, Pi Bu, Peijie Wang, Zhong-Zhi Li, Jian Xu, Xiao-Hui Li, Yuan Gao, Jun Song, Bo Zheng, et al. Longdocurl: a comprehensive multimodal long document benchmark integrating understanding, reasoning, and locating. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1135–1159, 2025.

[59] Naihao Deng and Rada Mihalcea. Rethinking table instruction tuning. *arXiv preprint arXiv:2501.14693*, 2025.

[60] Naihao Deng, Zhenjie Sun, Ruiqi He, Aman Sikka, Yulong Chen, Lin Ma, Yue Zhang, and Rada Mihalcea. Tables as texts or images: Evaluating the table reasoning ability of llms and mllms. *arXiv preprint arXiv:2402.12424*, 2024.

[61] Qilin Deng, Mayire Ibrayim, Askar Hamdulla, Hailong Luo, and Chunhu Zhang. Doc-dino: A transformer model for complex logical document layout analysis. In *International Conference on Document Analysis and Recognition*, pages 76–89. Springer, 2024.

[62] Yihao Ding, Siwen Luo, Hyunsuk Chung, and Soyeon Caren Han. Vqa: A new dataset for real-world vqa on pdf documents. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 585–601. Springer, 2023.

[63] Yihao Ding, Kaixuan Ren, Jiabin Huang, Siwen Luo, and Soyeon Caren Han. Mvqa: A dataset for multimodal information retrieval in pdf-based visual question answering. *arXiv preprint arXiv:2404.12720*, 2024.

[64] Yihao Ding, Lorenzo Vaiani, Caren Han, Jean Lee, Paolo Garza, Josiah Poon, and Luca Cagliero. 3mvrd: multimodal multi-task multi-teacher visually-rich form document understanding. *arXiv preprint arXiv:2402.17983*, 2024.

[65] Jovana Dobreva, Ivana Karasmanakis, Filip Ivanisevic, Tadej Horvat, Dimitar Kitanovski, Matjaz Gams, Kostadin Mishev, and Monika Simjanoska Misheva. Ragcare-qa: A benchmark dataset for evaluating retrieval-augmented generation pipelines in theoretical medical knowledge. *Data in Brief*, page 112146, 2025.

[66] Haoyu Dong, Yue Hu, and Yanan Cao. Reasoning and retrieval for complex semi-structured tables via reinforced relational data transformation. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1382–1391, 2025.

[67] Kuicai Dong, Yujing Chang, Shijie Huang, Yasheng Wang, Ruiming Tang, and Yong Liu. Benchmarking retrieval-augmented multimomal generation for document question answering. *arXiv preprint arXiv:2505.16470*, 2025.

[68] Kuicai Dong, Shurui Huang, Fangda Ye, Wei Han, Zhi Zhang, Dexun Li, Wenjun Li, Qu Yang, Gang Wang, Yichao Wang, et al. Doc-researcher: A unified system for multimodal document parsing and deep research. *arXiv preprint arXiv:2510.21603*, 2025.

[69] Danny Driess, Fei Xia, Mehdi SM Sajjadi, Corey Lynch, Aakanksha Chowdhery, Ayzaan Wahid, Jonathan Tompson, Quan Vuong, Tianhe Yu, Wenlong Huang, et al. Palm-e: An embodied multimodal language model. *arXiv preprint arXiv:2303.03378*, 2023.

[70] Yuning Du, Chenxia Li, Ruoyu Guo, Xiaoting Yin, Weiwei Liu, Jun Zhou, Yifan Bai, Zilin Yu, Yehua Yang, Qingqing Dang, et al. Pp-ocr: A practical ultra lightweight ocr system. *arXiv preprint arXiv:2009.09941*, 2020.

[71] Yuchen Duan, Zhe Chen, Yusong Hu, Weiyun Wang, Shenglong Ye, Botian Shi, Lewei Lu, Qibin Hou, Tong Lu, Hongsheng Li, et al. Docopilot: Improving multimodal models for document-level understanding. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 4026–4037, 2025.

[72] Sayna Ebrahimi, Sercan O Arik, and Tomas Pfister. Test-time adaptation for visual document understanding. *arXiv preprint arXiv:2206.07240*, 2022.

[73] Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitansky, Robert Osazuwa Ness, and Jonathan Larson. From local to global: A graph rag approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*, 2024.

[74] Julian Eisenschlos, Syrine Krichene, and Thomas Müller. Understanding tables with intermediate pre-training. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 281–296, 2020.

[75] Yuwei Fang, Siqi Sun, Zhe Gan, Rohit Pillai, Shuohang Wang, and Jingjing Liu. Hierarchical graph network for multi-hop question answering. In *Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP)*, pages 8823–8838, 2020.

[76] Manuel Faysse, Hugues Sibille, Tony Wu, Bilel Omrani, Gautier Viaud, Céline Hudelot, and Pierre Colombo. Colpali: Efficient document retrieval with vision language models. *arXiv preprint arXiv:2407.01449*, 2024.

[77] Hao Feng, Zijian Wang, Jingqun Tang, Jinghui Lu, Wengang Zhou, Houqiang Li, and Can Huang. Unidoc: A universal large multimodal model for simultaneous text detection, recognition, spotting and understanding. *arXiv preprint arXiv:2308.11592*, 2023.

[78] Hao Feng, Qi Liu, Hao Liu, Jingqun Tang, Wengang Zhou, Houqiang Li, and Can Huang. Docpedia: Unleashing the power of large multimodal model in the frequency domain for versatile document understanding. *Science China Information Sciences*, 67(12):220106, 2024.

[79] David Fleischhacker, Wolfgang Göderle, and Roman Kern. Improving ocr quality in 19th century historical documents using a combined machine learning based approach. *arXiv preprint arXiv:2401.07787*, 2024.

[80] David Fleischhacker, Roman Kern, and Wolfgang Göderle. Enhancing ocr in historical documents with complex layouts through machine learning. *International Journal on Digital Libraries*, 26(1):3, 2025.

[81] Najmeh Forouzandehmehr, Reza Yousefi Maragheh, Sriram Kollipara, Kai Zhao, Topojoy Biswas, Evren Korpeoglu, and Kannan Achan. Cal-rag: Retrieval-augmented multi-agent generation for content-aware layout design. *arXiv preprint arXiv:2506.21934*, 2025.

[82] James Michael Fritz, Nur Ichsan Utama, and Riska Yanu Fa'Rifah. Indocolsmol: Lightweight vision-language models for multimodal indonesian document search. In *2025 International Conference on Data Science and Its Applications (ICoDSA)*, pages 1070–1075. IEEE, 2025.

[83] Chengzhen Fu and Yan Zhang. Ea reader: Enhance attentive reader for cloze-style question answering via multi-space context fusion. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 6375–6382, 2019.

[84] Ling Fu, Zhebin Kuang, Jiajun Song, Mingxin Huang, Biao Yang, Yuzhe Li, Linghao Zhu, Qidi Luo, Xinyu Wang, Hao Lu, et al. Ocrbench v2: An improved benchmark for evaluating large multimodal models on visual text localization and reasoning. *arXiv preprint arXiv:2501.00321*, 2024.

[85] Shaikat Galib, Shanshan Wang, Guanshuo Xu, Pascal Pfeiffer, Ryan Chesler, Mark Landry, and Sri Satish Ambati. H2ovl-mississippi vision language models technical report. *arXiv preprint arXiv:2410.13611*, 2024.

[86] Peng Gao, Shijie Geng, Renrui Zhang, Teli Ma, Rongyao Fang, Yongfeng Zhang, Hongsheng Li, and Yu Qiao. Clip-adapter: Better vision-language models with feature adapters. *International Journal of Computer Vision*, 132(2):581–595, 2024.

[87] Sensen Gao, Shanshan Zhao, Xu Jiang, Lunhao Duan, Yong Xien Chng, Qing-Guo Chen, Weihua Luo, Kaifu Zhang, Jia-Wang Bian, and Mingming Gong. Scaling beyond context: A survey of multimodal retrieval-augmented generation for document understanding. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4458–4489. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.acl-long.204. URL https://aclanthology.org/2026.acl-long.204/. First public preprint: October 2025.

[88] Zhangchi Gao, Shoubin Li, Yangyang Liu, Mingyang Li, Kai Huang, and Yi Ren. Ld-doc: Light-weight domain-adaptive document layout analysis. In *International Workshop on Document Analysis Systems*, pages 124–141. Springer, 2024.

[89] Premanand Ghadekar, Omkar Khanvilkar, Janvi Kharat, Kimaya Joshi, Tejas Kulkarni, and Yash Kulkarni. Automating the grading of handwritten examinations through the integration of optical character recognition and machine learning algorithms. *Journal of Integrated Science and Technology*, 13(6):1128–1128, 2025.

[90] Alejandro Godinez. Hysemrag: A hybrid semantic retrieval-augmented generation framework for automated literature synthesis and methodological gap analysis. *arXiv preprint arXiv:2508.05666*, 2025.

[91] T Gong and X Yao. A deep learning technology based ocr framework for recognition handwritten expression and text. *CONVERTER*, pages 01–10, 2021.

[92] Ziyu Gong, Chengcheng Mai, and Yihua Huang. Mhier-rag: Multi-modal rag for visual-rich document question-answering via hierarchical and multi-granularity reasoning. *arXiv preprint arXiv:2508.00579*, 2025.

[93] Jiuxiang Gu, Ani Nenkova, Nikolaos Barmpalios, Vlad Ion Morariu, Tong Sun, Rajiv Bhawanji Jain, Jason Wen Yong Kuen, and Handong Zhao. Unified pretraining framework for document understanding. *arXiv preprint*, 2025.

[94] Nianlong Gu, Yingqiang Gao, and Richard HR Hahnloser. Memsum-dqa: Adapting an efficient long document extractive summarizer for document question answering. *arXiv preprint arXiv:2310.06436*, 2023.

[95] Zhangxuan Gu, Changhua Meng, Ke Wang, Jun Lan, Weiqiang Wang, Ming Gu, and Liqing Zhang. Xylayoutlm: Towards layout-aware multimodal networks for visually-rich document understanding. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4583–4592, 2022.

[96] Che Guan, Mengyu Huang, and Peng Zhang. Mfort-qa: Multi-hop few-shot open rich table question answering. In *Proceedings of the 2024 10th International Conference on Computing and Artificial Intelligence*, pages 434–442, 2024.

[97] Zirui Guo, Lianghao Xia, Yanhua Yu, Tu Ao, and Chao Huang. Lightrag: Simple and fast retrieval-augmented generation. *arXiv preprint arXiv:2410.05779*, 2024.

[98] Zirui Guo, Xubin Ren, Lingrui Xu, Jiahao Zhang, and Chao Huang. Rag-anything: All-in-one rag framework. *arXiv preprint arXiv:2510.12323*, 2025.

[99] Mrinal Haloi, Shashank Shekhar, Nikhil Fande, Siddhant Swaroop Dash, et al. Table detection in the wild: A novel diverse table detection dataset and method. *arXiv preprint arXiv:2209.09207*, 2022.

[100] Laziz Hamdi, Amine Tamasna, Pascal Boisson, and Thierry Paquet. Vista-ocr: Towards generative and interactive end to end ocr models. *arXiv preprint arXiv:2504.03621*, 2025. URL https://arxiv.org/abs/2504.03621v1. Version 1, titled VISTA-OCR; the later revision is titled PILOT.

[101] Omar Hamed, Souhail Bakkali, Matthew Blaschko, Sien Moens, and Jordy Van Landeghem. Multimodal adaptive inference for document image classification with anytime early exiting. In *International Conference on Document Analysis and Recognition*, pages 270–286. Springer, 2024.

[102] Tanveer Hannan, Dimitrios Mallios, Parth Pathak, Faegheh Sardari, Thomas Seidl, Gedas Bertasius, Mohsen Fayyaz, and Sunando Sengupta. Docslm: A small vision-language model for long multimodal document understanding. *arXiv preprint arXiv:2511.11313*, 2025.

[103] Jianing Hao, Zhuowen Liang, Chunting Li, Yuyu Luo, Jie Li, and Wei Zeng. Vistr: Visualizations as representations for time-series table reasoning. *arXiv preprint arXiv:2406.03753*, 2024.

[104] Adam Hazimeh, Ke Wang, Mark Collier, Gilles Baechler, Efi Kokiopoulou, and Pascal Frossard. Semantic document derendering: Svg reconstruction via vision-language modeling. *arXiv preprint arXiv:2511.13478*, 2025.

[105] Zijian Hei, Weiling Liu, Wenjie Ou, Juyi Qiao, Junming Jiao, Guowen Song, Ting Tian, and Yi Lin. Dr-rag: Applying dynamic document relevance to retrieval-augmented generation for question-answering. *arXiv preprint arXiv:2406.07348*, 2024.

[106] Hunter Heidenreich, Yosheb Getachew, Olivia Dinica, and Ben Elliott. Pubmed-ocr: Pmc open access ocr annotations. *arXiv preprint arXiv:2601.11425*, 2026.

[107] Khalil Hennara, Muhammad Hreden, Mohamed Motasim Hamed, Ahmad Bastati, Zeina Aldallal, Sara Chrouf, and Safwan AlModhayan. Baseer: A vision-language model for arabic document-to-markdown ocr. *arXiv preprint arXiv:2509.18174*, 2025.

[108] Wenyi Hong, Weihan Wang, Qingsong Lv, Jiazheng Xu, Wenmeng Yu, Junhui Ji, Yan Wang, Zihan Wang, Yuxiao Dong, Ming Ding, et al. Cogagent: A visual language model for gui agents. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14281–14290, 2024.

[109] Maximiliano Hormazábal Lagos, Álvaro Bueno Sáez, Pedro Alonso Doval, Jorge Alcalde Vesteiro, and Héctor Cerezo-Costas. Explicit-qa: Explainable code-based image table question answering. In *EPIA Conference on Artificial Intelligence*, pages 339–351. Springer, 2025.

[110] Anwen Hu, Yaya Shi, Haiyang Xu, Jiabo Ye, Qinghao Ye, Ming Yan, Chenliang Li, Qi Qian, Ji Zhang, and Fei Huang. mplug-paperowl: Scientific diagram analysis with the multimodal large language model. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pages 6929–6938, 2024.

[111] Anwen Hu, Haiyang Xu, Jiabo Ye, Ming Yan, Liang Zhang, Bo Zhang, Ji Zhang, Qin Jin, Fei Huang, and Jingren Zhou. mplug-docowl 1.5: Unified structure learning for ocr-free document understanding. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 3096–3120, 2024.

[112] Anwen Hu, Haiyang Xu, Liang Zhang, Jiabo Ye, Ming Yan, Ji Zhang, Qin Jin, Fei Huang, and Jingren Zhou. mplug-docowl2: High-resolution compressing for ocr-free multi-page document understanding. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5817–5834, 2025.

[113] Jing Huang, Guan Pang, Rama Kovvuri, Mandy Toh, Kevin J Liang, Praveen Krishnan, Xi Yin, and Tal Hassner. A multiplexed network for end-to-end, multilingual ocr. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4547–4557, 2021.

[114] Kui Huang, Xinrong Chen, Wenyu Lv, Jincheng Liao, Guanzhong Wang, and Yi Liu. Pp-docbee2: Improved baselines with efficient data for multimodal document understanding. *arXiv preprint arXiv:2506.18023*, 2025.

[115] Xinyue Huang, Ziqi Lin, Fang Sun, Wenchao Zhang, Kejian Tong, and Yunbo Liu. Enhancing document-level question answering via multi-hop retrieval-augmented generation with llama 3. *arXiv preprint arXiv:2506.16037*, 2025.

[116] Geeta S Hukkeri, RH Goudar, Prashant Janagond, and Pooja S Patil. Machine learning in ocr technology: Performance analysis of different ocr methods for slide-to-text conversion in lecture videos. *International Journal of Advanced Computer Science and Applications*, 13(8), 2022.

[117] Ms Janani, H Laya, and B Mathishree. Ocr text recognition and recommendation using machine learning. In *2025 International Conference on Visual Analytics and Data Visualization (ICVADV)*, pages 804–807. IEEE, 2025.

[118] Vishal Jayaswal, Sharma Ji, Ashish Kumar, Varun Kumar, and Ayushi Prakash. Ocr based deep learning approach for image captioning. In *2024 IEEE International Conference on Computing, Power and Communication Technologies (IC2PCT)*, volume 5, pages 239–244. IEEE, 2024.

[119] Youngseung Jeon, Ziwen Li, Thomas Li, JiaSyuan Chang, Morteza Ziyadi, and Xiang'Anthony' Chen. Ragppi: Rag benchmark for protein-protein interactions in drug discovery. *arXiv preprint arXiv:2505.23823*, 2025.

[120] Chuang Jiang, Mingyue Cheng, Xiaoyu Tao, Qingyang Mao, Jie Ouyang, and Qi Liu. Tablemind: An autonomous programmatic agent for tool-augmented table reasoning. *arXiv preprint arXiv:2509.06278*, 2025.

[121] Jun-Peng Jiang, Tao Zhou, De-Chuan Zhan, and Han-Jia Ye. Compositional condition question answering in tabular understanding. In *Forty-second International Conference on Machine Learning*, 2025.

[122] Xin Jiang, Junwei Zheng, Ruiping Liu, Jiahang Li, Jiaming Zhang, Sven Matthiesen, and Rainer Stiefelhagen. @ bench: Benchmarking vision-language models for human-centered assistive technology. In *2025 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 3934–3943. IEEE, 2025.

[123] Yichen Jiang, Nitish Joshi, Yen-Chun Chen, and Mohit Bansal. Explore, propose, and assemble: An interpretable model for multi-hop reading comprehension. *arXiv preprint arXiv:1906.05210*, 2019.

[124] Yuxiang Jiang, Haiwei Dong, and Abdulmotaleb El Saddik. Baidu meizu deep learning competition: Arithmetic operation recognition using end-to-end learning ocr technologies. *IEEE Access*, 6:60128–60136, 2018.

[125] Zhengbao Jiang, Yi Mao, Pengcheng He, Graham Neubig, and Weizhu Chen. Omnitab: Pretraining with natural and synthetic data for few-shot table-based question answering. *arXiv preprint arXiv:2207.03637*, 2022.

[126] Zhouqiang Jiang, Bowen Wang, Junhao Chen, and Yuta Nakashima. Relayout: Towards real-world document understanding via layout-enhanced pre-training. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 3778–3793, 2025.

[127] Congyun Jin, Ming Zhang, Weixiao Ma, Yujiao Li, Yingbo Wang, Yabo Jia, Yuliang Du, Tao Sun, Haowen Wang, Cong Fan, et al. Rjua-meddqa: A multimodal benchmark for medical document question answering and clinical reasoning. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 5218–5229, 2024.

[128] B Kalaimathi, S Jayanthy, G Bharathkumar, AVR Akshaya, and P Dharanya. Efficient vehicle tracking and authentication with yolov8: Integrating deep learning and ocr for real-time license plate detection. In *2024 4th International Conference on Sustainable Expert Systems (ICSES)*, pages 1255–1262. IEEE, 2024.

[129] Hengrui Kang, Zhuangcheng Gu, Zhiyuan Zhao, Zichen Wen, Bin Wang, Weijia Li, and Conghui He. Omnidoclayout: Towards diverse document layout generation via coarse-to-fine llm learning. *arXiv preprint arXiv:2510.26213*, 2025.

[130] Yannis Katsis, Saneem Chemmengath, Vishwajeet Kumar, Samarth Bharadwaj, Mustafa Canim, Michael Glass, Alfio Gliozzo, Feifei Pan, Jaydeep Sen, Karthik Sankaranarayanan, et al. Ait-qa: Question answering dataset over complex tables in the airline industry. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies: Industry Track*, pages 305–314, 2022.

[131] Arsh Khan, Utsav Rai, Shashank Shekhar Singh, Yukinori Yamamoto, Xabier Granja Ibarreche, Harrison Meadows, and Sergei Gleyzer. Ocr approaches for humanities: Applications of artificial intelligence/machine learning on transcription and transliteration of historical documents. *Digital Studies in Language and Literature*, 1(1-2):85–112, 2024.

[132] Rohit Khoja, Devanshu Gupta, Yanjie Fu, Dan Roth, and Vivek Gupta. Weaver: Interweaving sql and llm for table reasoning. *arXiv preprint arXiv:2505.18961*, 2025.

[133] Dongyoun Kim, Hyung-do Choi, Youngsun Jang, and John Kim. Extracting information from scientific literature via visual table question answering models. In *Proceedings of the International Conference on Research in Adaptive and Convergent Systems*, pages 192–198, 2024.

[134] Geewook Kim, Teakgyu Hong, Moonbin Yim, JeongYeon Nam, Jinyoung Park, Jinyeong Yim, Wonseok Hwang, Sangdoo Yun, Dongyoon Han, and Seunghyun Park. Ocr-free document understanding transformer. In *European Conference on Computer Vision*, pages 498–517. Springer, 2022.

[135] Hyebin Kim, Eunseon Seong, Harim Lee, Dong-Kyu Chae, and Sugie Lee. Decoding multiculturalism through linguistic landscapes: a deep learning–based ocr analysis of street view images. *Urban Informatics*, 4(1):1–16, 2025.

[136] Yongil Kim, Heuiyeen Yeen, Hyeongu Yun, and Jinsik Lee. Ko-longrag: A korean long-context rag benchmark built with a retrieval-free approach. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 17317–17329, 2025.

[137] Alex Kogan. Improving inference performance of machine learning with the divide-and-conquer principle. *arXiv preprint arXiv:2301.05099*, 2023.

[138] Adithya S Kolavi, Vyoman Jain, et al. Nayana: A foundation for document-centric vision-language models via multi-task, multimodal, and multilingual data synthesis. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1678–1687, 2025.

[139] Kezhi Kong, Jiani Zhang, Zhengyuan Shen, Balasubramaniam Srinivasan, Chuan Lei, Christos Faloutsos, Huzefa Rangwala, and George Karypis. Opentab: Advancing large language models as open-domain table reasoners. *arXiv preprint arXiv:2402.14361*, 2024.

[140] Karolina Konopka, Michał Turski, and Filip Graliński. Arxiv tables: Document understanding challenge linking texts and tables. In *International Conference on Document Analysis and Recognition*, pages 94–107. Springer, 2023.

[141] Satyapriya Krishna, Kalpesh Krishna, Anhad Mohananey, Steven Schwarcz, Adam Stambler, Shyam Upadhyay, and Manaal Faruqui. Fact, fetch, and reason: A unified evaluation of retrieval-augmented generation. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 4745–4759, 2025.

[142] Rohan Lal Kshetry. Image preprocessing and modified adaptive thresholding for improving ocr. *arXiv preprint arXiv:2111.14075*, 2021.

[143] B Anand Kumar, S Tamilarasan, Ajmeera Kiran, Bagepally Tejaswi, Manikonda Geethika Sree, and Mallikarjun Dasarla. Optical character recognition technology using machine learning. In *2023 International Conference on Computer Communication and Informatics (ICCCI)*, pages 1–4. IEEE, 2023.

[144] Souvik Kundu, Tushar Khot, Ashish Sabharwal, and Peter Clark. Exploiting explicit paths for multi-hop reading comprehension. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 2737–2747, 2019.

[145] Philippe Laban, Alexander Richard Fabbri, Caiming Xiong, and Chien-Sheng Wu. Summary of a haystack: A challenge to long-context llms and rag systems. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 9885–9903, 2024.

[146] Marcel Lamott, Yves-Noel Weweler, Adrian Ulges, Faisal Shafait, Dirk Krechel, and Darko Obradovic. Lapdoc: Layout-aware prompting for documents. In *International Conference on Document Analysis and Recognition*, pages 142–159. Springer, 2024.

[147] Jeongsoo Lee, Daeyong Kwon, Kyohoon Jin, Junnyeong Jeong, Minwoo Sim, and Minwoo Kim. Mhts: Multi-hop tree structure framework for generating difficulty-controllable qa datasets for rag evaluation. *arXiv preprint arXiv:2504.08756*, 2025.

[148] Kenton Lee, Mandar Joshi, Iulia Raluca Turc, Hexiang Hu, Fangyu Liu, Julian Martin Eisenschlos, Urvashi Khandelwal, Peter Shaw, Ming-Wei Chang, and Kristina Toutanova. Pix2struct: Screenshot parsing as pretraining for visual language understanding. In *International Conference on Machine Learning*, pages 18893–18912. PMLR, 2023.

[149] Fangyu Lei, Jinxiang Meng, Yiming Huang, Tinghong Chen, Yun Zhang, Shizhu He, Jun Zhao, and Kang Liu. Reasoning-table: Exploring reinforcement learning for table reasoning. *arXiv preprint arXiv:2506.01710*, 2025.

[150] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, 2020. URL https://papers.nips.cc/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html.

[151] Ce Li, Xiaofan Liu, Zhiyan Song, Ce Chi, Chen Zhao, Jingjing Yang, Zhendong Wang, Kexin Yang, Boshen Shi, Xing Wang, et al. Treb: A comprehensive benchmark for evaluating table reasoning capabilities of large language models. *arXiv preprint arXiv:2506.18421*, 2025.

[152] Jiawei Li, Mucheng Ren, Yang Gao, and Yizhe Yang. Ask to understand: Question generation for multi-hop question answering. In *China National Conference on Chinese Computational Linguistics*, pages 19–36. Springer, 2023.

[153] Kuan Li, Liwen Zhang, Yong Jiang, Pengjun Xie, Fei Huang, Shuai Wang, and Minhao Cheng. Lara: Benchmarking retrieval-augmented generation and long-context llms–no silver bullet for lc or rag routing. *arXiv preprint arXiv:2502.09977*, 2025.

[154] Minghao Li, Yiheng Xu, Lei Cui, Shaohan Huang, Furu Wei, Zhoujun Li, and Ming Zhou. Docbank: A benchmark dataset for document layout analysis. *arXiv preprint arXiv:2006.01038*, 2020.

[155] Peng Li, Yeye He, Dror Yashar, Weiwei Cui, Song Ge, Haidong Zhang, Danielle Rifinski Fainman, Dongmei Zhang, and Surajit Chaudhuri. Table-GPT: Table-tuned GPT for diverse table tasks. *arXiv preprint arXiv:2310.09263*,

2023. URL https://arxiv.org/abs/2310.09263. Preprint; a revised version appeared at SIGMOD 2024 as Table-GPT: Table Fine-tuned GPT for Diverse Table Tasks.

[156] Xin Li, Yunfei Wu, Xinghua Jiang, Zhihao Guo, Mingming Gong, Haoyu Cao, Yinsong Liu, Deqiang Jiang, and Xing Sun. Enhancing visual document understanding with contrastive learning in large visual-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15546–15555, 2024.

[157] Yinglu Li, Zhiying Lu, Zhihang Liu, Chuanbin Liu, and Hongtao Xie. Regionrag: Region-level retrieval-augmented generation for visual document understanding. *arXiv preprint arXiv:2510.27261*, 2025.

[158] Yumeng Li, Guang Yang, Hao Liu, Bowen Wang, and Colin Zhang. dots. ocr: Multilingual document layout parsing in a single vision-language model. *arXiv preprint arXiv:2512.02498*, 2025.

[159] Zhang Li, Biao Yang, Qiang Liu, Zhiyin Ma, Shuo Zhang, Jingxu Yang, Yabo Sun, Yuliang Liu, and Xiang Bai. Monkey: Image resolution and text label are important things for large multi-modal models. In *proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 26763–26773, 2024.

[160] Zhang Li, Yuliang Liu, Qiang Liu, Zhiyin Ma, Ziyang Zhang, Shuo Zhang, Zidun Guo, Jiarui Zhang, Xinyu Wang, and Xiang Bai. Monkeyocr: Document parsing with a structure-recognition-relation triplet paradigm. *arXiv preprint arXiv:2506.05218*, 2025.

[161] Xinyi Liang, Rui Hu, Yu Liu, and Konglin Zhu. Open-domain question answering over tables with large language models. In *International Conference on Intelligent Computing*, pages 347–358. Springer, 2024.

[162] Gyubeum Lim, Yemo Koo, and Vijay Krishna Madisetti. Scope vlm: Selective context processing for efficient document navigation in vision-language models. *arXiv preprint arXiv:2510.21850*, 2025.

[163] Chao Liu, Shuang Yang, Xi Wang, Feng Xu, Yiran Zhai, Dingwen Zhang, Shuxiu Liu, and Ning Li. Power big data imbalance analysis based on deep learning ocr algorithm. In *2025 International Conference on Electrical Automation and Artificial Intelligence (ICEAAI)*, pages 269–273. IEEE, 2025.

[164] Fangyu Liu, Julian Eisenschlos, Francesco Piccinno, Syrine Krichene, Chenxi Pang, Kenton Lee, Mandar Joshi, Wenhu Chen, Nigel Collier, and Yasemin Altun. Deplot: One-shot visual language reasoning by plot-to-table translation. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 10381–10399, 2023.

[165] Huicong Liu, Miao Tian, Shengbo Huang, Zini Zhuang, Xinzhi Tan, and Xiongsheng Dong. Vehicle vin code recognition based on deep learning and ocr. In *International Conference on Image, Signal Processing, and Pattern Recognition (ISPP 2025)*, volume 13664, pages 708–712. SPIE, 2025.

[166] Shuochen Liu, Pengfei Luo, Chao Zhang, Yuhao Chen, Haotian Zhang, Qi Liu, Xin Kou, Tong Xu, and Enhong Chen. Look as you think: Unifying reasoning and visual evidence attribution for verifiable document rag via reinforcement learning. *arXiv preprint arXiv:2511.12003*, 2025.

[167] Yuan Liu, Zhongyin Zhao, Le Tian, Haicheng Wang, Xubing Ye, Yangxiu You, Zilin Yu, Chuhan Wu, Zhou Xiao, Yang Yu, et al. Points-reader: Distillation-free adaptation of vision-language models for document conversion. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 1576–1601, 2025.

[168] Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xu-Cheng Yin, Cheng-Lin Liu, Lianwen Jin, and Xiang Bai. Ocrbench: on the hidden mystery of ocr in large multimodal models. *Science China Information Sciences*, 67(12):220102, 2024.

[169] Yuliang Liu, Biao Yang, Qiang Liu, Zhang Li, Zhiyin Ma, Shuo Zhang, and Xiang Bai. Textmonkey: An ocr-free large multimodal model for understanding document. *arXiv preprint arXiv:2403.04473*, 2024.

[170] Nikolaos Livathinos, Christoph Auer, Ahmed Nassar, Rafael Teixeira de Lima, Maksym Lysak, Brown Ebouky, Cesar Berrospi, Michele Dolfi, Panagiotis Vagenas, Matteo Omenetti, et al. Advanced layout analysis models for docling. *arXiv preprint arXiv:2509.11720*, 2025.

[171] Pan Lu, Liang Qiu, Jiaqi Chen, Tony Xia, Yizhou Zhao, Wei Zhang, Zhou Yu, Xiaodan Liang, and Song-Chun Zhu. Iconqa: A new benchmark for abstract diagram understanding and visual language reasoning. *arXiv preprint arXiv:2110.13214*, 2021.

[172] Xinyuan Lu, Liangming Pan, Yubo Ma, Preslav Nakov, and Min-Yen Kan. Tart: An open-source tool-augmented framework for explainable table-based reasoning. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 4323–4339, 2025.

[173] Chuwei Luo, Yufan Shen, Zhaoqing Zhu, Qi Zheng, Zhi Yu, and Cong Yao. Layoutllm: Layout instruction tuning with large language models for document understanding. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 15630–15640, 2024.

[174] Chuwei Luo, Guozhi Tang, Qi Zheng, Cong Yao, Lianwen Jin, Chenliang Li, Yang Xue, and Luo Si. Bi-vldoc: Bidirectional vision-language modeling for visually-rich document understanding. *International Journal on Document Analysis and Recognition (IJDAR)*, pages 1–12, 2025.

[175] Haoran Luo, Guanting Chen, Yandan Zheng, Xiaobao Wu, Yikai Guo, Qika Lin, Yu Feng, Zemin Kuang, Meina Song, Yifan Zhu, et al. Hypergraphrag: Retrieval-augmented generation via hypergraph-structured knowledge representation. *arXiv preprint arXiv:2503.21322*, 2025.

[176] Yuanjie Lyu, Zhiyu Li, Simin Niu, Feiyu Xiong, Bo Tang, Wenjin Wang, Hao Wu, Huanyong Liu, Tong Xu, and Enhong Chen. Crud-rag: A comprehensive chinese benchmark for retrieval-augmented generation of large language models. *ACM Transactions on Information Systems*, 43(2):1–32, 2025.

[177] Xueguang Ma, Sheng-Chieh Lin, Minghan Li, Wenhu Chen, and Jimmy Lin. Unifying multimodal retrieval via document screenshot embedding. *arXiv preprint arXiv:2406.11251*, 2024.

[178] Yiran Rex Ma. Paneltr: Zero-shot table reasoning framework through multi-agent scientific discussion. In *2025 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE, 2025.

[179] Yubo Ma, Yuhang Zang, Liangyu Chen, Meiqi Chen, Yizhu Jiao, Xinze Li, Xinyuan Lu, Ziyu Liu, Yan Ma, Xiaoyi Dong, et al. Mmlongbench-doc: Benchmarking long-context document understanding with visualizations. *Advances in Neural Information Processing Systems*, 37:95963–96010, 2024.

[180] Amanda Major and Tina Calandrino. Beyond chunking: Microlearning secrets for effective online design. *Distance Learning*, 15(2):27–30, 2018.

[181] Haq Nawaz Malik. 600k-ks-ocr: a large-scale synthetic dataset for optical character recognition in kashmiri script. *arXiv preprint arXiv:2601.01088*, 2026.

[182] Adnan Ben Mansour, Ayoub Karine, and David Naccache. Interpret, prune and distill donut: towards lightweight vlms for vqa on document. *arXiv preprint arXiv:2509.26235*, 2025.

[183] Qingyang Mao, Qi Liu, Zhi Li, Mingyue Cheng, Zheng Zhang, and Rui Li. Potable: Towards systematic thinking via stage-oriented plan-then-execute reasoning on tables. *arXiv preprint arXiv:2412.04272*, 2024.

[184] Qingyang Mao, Qi Liu, Zhi Li, Mingyue Cheng, Zheng Zhang, and Rui Li. Potable: Programming standardly on table-based reasoning like a human analyst. *arXiv preprint arXiv:2412.04272v1*, 2024.

[185] Zhiming Mao, Haoli Bai, Lu Hou, Lifeng Shang, Xin Jiang, Qun Liu, and Kam-Fai Wong. Visually guided generative text-layout pre-training for document intelligence. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 4713–4730, 2024.

[186] Alexander Martin, William Walden, Reno Kriz, Dengjia Zhang, Kate Sanders, Eugene Yang, Chihsheng Jin, and Benjamin Van Durme. Seeing through the mirage: Evaluating multimodal retrieval augmented generation. *arXiv preprint arXiv:2510.24870*, 2025.

[187] Lionel Martis. Luminirag: Vision-enhanced graph rag for complex multi-modal document understanding. *Authorea Preprints*, 2024.

[188] Ahmed Masry and Amir Hajian. Longfin: A multimodal document understanding model for long financial domain documents. *arXiv preprint arXiv:2401.15050*, 2024.

[189] Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 2200–2209, 2021.

[190] Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 2200–2209, 2021.

[191] Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and C. V. Jawahar. InfographicVQA. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 1697–1706, 2022. URL https://openaccess.thecvf.com/content/WACV2022/html/Mathew_InfographicVQA_WACV_2022_paper.html. First public preprint: April 2021.

[192] Puneet Mathur, Vlad I Morariu, Aparna Garimella, Franck Dernoncourt, Jiuxiang Gu, Ramit Sawhney, Preslav Nakov, Dinesh Manocha, and Rajiv Jain. Docscript: Document-level script event prediction. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 5140–5155, 2024.

[193] Jie Mei, Aminul Islam, Yajing Wu, Abidalrahman Moh'd, and Evangelos E Milios. Statistical learning for ocr text correction. *arXiv preprint arXiv:1611.06950*, 2016.

[194] Jiabei Meng. Structured multimodal rag: Document-aware retrieval and alignment for hallucination mitigation. In *2025 5th International Conference on Artificial Intelligence, Automation and High Performance Computing (AIAHPC)*, pages 1015–1018. IEEE, 2025.

[195] Dehai Min, Nan Hu, Rihui Jin, Nuo Lin, Jiaoyan Chen, Yongrui Chen, Yu Li, Guilin Qi, Yun Li, Nijun Li, et al. Exploring the impact of table-to-text methods on augmenting llm-based question answering with domain hybrid data. *arXiv preprint arXiv:2402.12869*, 2024.

[196] Mohammad Minouei, Mohammad Reza Soheili, and Didier Stricker. Document layout analysis with an enhanced object detector. In *2021 5th International Conference on Pattern Recognition and Image Analysis (IPRIA)*, pages 1–5. IEEE, 2021.

[197] Piyush Mishra, Pratik Pai, Mihir Patel, and Reena Sonkusare. Extraction of information from handwriting using optical character recognition and neural networks. In *2020 4th International Conference on Electronics, Communication and Aerospace Technology (ICECA)*, pages 1328–1333. IEEE, 2020.

[198] Ahmad Mohammadshirazi, Ali Nosrati Firoozsalari, Mengxi Zhou, Dheeraj Kulshrestha, and Rajiv Ramnath. Docparsenet: Advanced semantic segmentation and ocr embeddings for efficient scanned document annotation. *arXiv preprint arXiv:2406.17591*, 2024.

[199] Menna Hossameldin Mokdam, Maram Hossameldin Abdelsadek, Mohamed N Saad, and Tamer M Nassef. Document digitization using deep learning: Classification, preprocessing, and ocr optimization. In *2025 5th International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME)*, pages 1–6. IEEE, 2025.

[200] Lamia Mosbah, Ikram Moalla, Tarek M Hamdani, Bilel Neji, Taha Beyrouthy, and Adel M Alimi. Adocrnet: a deep learning ocr for arabic documents recognition. *IEEE Access*, 12:55620–55631, 2024.

[201] Oliver Mothes and Joachim Denzler. Self-supervised data bootstrapping for deep optical character recognition of identity documents. *arXiv preprint arXiv:1908.04027*, 2019.

[202] Osama Mustafa, Muhammad Khizer Ali, Momina Moetesum, and Imran Siddiqi. Charteye: A deep learning framework for chart information extraction. In *2023 International Conference on Digital Image Computing: Techniques and Applications (DICTA)*, pages 554–561. IEEE, 2023.

[203] Omer Nacar, Yasser Al-Habashi, Serry Sibaee, Adel Ammar, and Wadii Boulila. Sard: A large-scale synthetic arabic ocr dataset for book-style text recognition. *arXiv preprint arXiv:2505.24600*, 2025.

[204] Muhammad Ferjad Naeem, Muhammad Gul Zain Ali Khan, Yongqin Xian, Muhammad Zeshan Afzal, Didier Stricker, Luc Van Gool, and Federico Tombari. I2mvformer: Large language model generated multi-view document supervision for zero-shot image classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15169–15179, 2023.

[205] Khalid MO Nahar, Izzat Alsmadi, Rabia Emhamed Al Mamlook, Ahmad Nasayreh, Hasan Gharaibeh, Ali Saeed Almuflih, and Fahad Alasim. Recognition of arabic air-written letters: machine learning, convolutional neural networks, and optical character recognition (ocr) techniques. *Sensors*, 23(23):9475, 2023.

[206] Md Mahadi Hasan Nahid. Improving table reasoning through table decomposition and normalization. Msc thesis, University of Alberta, Edmonton, Canada, 2024.

[207] Md Mahadi Hasan Nahid and Davood Rafiei. Tabsqlify: Enhancing reasoning capabilities of llms through table decomposition. *arXiv preprint arXiv:2404.10150*, 2024.

[208] Rayyan Najam and Safiullah Faizullah. Analysis of recent deep learning techniques for arabic handwritten-text ocr and post-ocr correction. *Applied Sciences*, 13(13):7568, 2023.

[209] Linyong Nan, Chiachun Hsieh, Ziming Mao, Xi Victoria Lin, Neha Verma, Rui Zhang, Wojciech Kryściński, Hailey Schoelkopf, Riley Kong, Xiangru Tang, et al. Fetaqa: Free-form table question answering. *Transactions of the Association for Computational Linguistics*, 10:35–49, 2022.

[210] Kalyan Nandi and S Siva Sathya. Visual document understanding: A comparative review of modern methods. In *International Conference on Computer Vision and Image Processing*, pages 411–427. Springer, 2024.

[211] Tayyab Nasir, Muhammad Kamran Malik, and Khurram Shahzad. Mmu-ocr-21: towards end-to-end urdu text recognition using deep learning. *IEEE Access*, 9:124945–124962, 2021.

[212] Ahmed Nassar, Andres Marafioti, Matteo Omenetti, Maksym Lysak, Nikolaos Livathinos, Christoph Auer, Lucas Morin, Rafael Teixeira de Lima, Yusik Kim, A Said Gurbuz, et al. Smoldocling: An ultra-compact vision-language model for end-to-end multi-modal document conversion. *arXiv preprint arXiv:2503.11576*, 2025.

[213] Giang Nguyen, Ivan Brugere, Shubham Sharma, Sanjay Kariyappa, Anh Totti Nguyen, and Freddy Lecue. Interpretable llm-based table question answering. *arXiv preprint arXiv:2412.12386*, 2024.

[214] Phuc Nguyen, Nam Tuan Ly, Hideaki Takeda, and Atsuhiro Takasu. Tabiqa: Table questions answering on business document images. *arXiv preprint arXiv:2303.14935*, 2023.

[215] Thang Nguyen, Peter Chin, and Yu-Wing Tai. Ma-rag: Multi-agent retrieval-augmented generation via collaborative chain-of-thought reasoning. *arXiv preprint arXiv:2505.20096*, 2025.

[216] Yuxiang Nie, He-Yan Huang, Wei Wei, and Xian-Ling Mao. Capturing global structural information in long document question answering with compressive graph selector network. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 5036–5047, 2022.

[217] Junbo Niu, Zheng Liu, Zhuangcheng Gu, Bin Wang, Linke Ouyang, Zhiyuan Zhao, Tao Chu, Tianyao He, Fan Wu, Qintong Zhang, et al. Mineru2. 5: A decoupled vision-language model for efficient high-resolution document parsing. *arXiv preprint arXiv:2509.22186*, 2025.

[218] Joel Odd and Emil Theologou. Utilize ocr text to extract receipt data and classify receipts with common machine learning algorithms, 2018.

[219] Lawrence O'Gorman. The document spectrum for page layout analysis. *IEEE Transactions on pattern analysis and machine intelligence*, 15(11):1162–1173, 2002.

[220] Linke Ouyang, Yuan Qu, Hongbin Zhou, Jiawei Zhu, Rui Zhang, Qunshu Lin, Bin Wang, Zhiyuan Zhao, Man Jiang, Xiaomeng Zhao, et al. Omnidocbench: Benchmarking diverse pdf document parsing with comprehensive annotations. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 24838–24848, 2025.

[221] Prasanna Pabba, Abhinav Ram, L Saiprasad, Mr Sathwik, et al. Automatic number plate detection using deep learning and ocr. In *2024 IEEE 4th International Conference on ICT in Business Industry & Government (ICTBIG)*, pages 1–5. IEEE, 2024.

[222] P Padmavathi, Bunny Bharadwaj Mahadas, Shyam Sundhar Kalluri, Praveen Devarapu, and Sowndarya Lakshmi Bandi. Optical character recognition and text to speech generation system using machine learning. In *2023 2nd International Conference on Applied Artificial Intelligence and Computing (ICAAIC)*, pages 1–6. IEEE, 2023.

[223] Aniket Pal, Ajoy Mondal, and CV Jawahar. Hw-mlvqa: a novel handwritten multilingual dataset for visual question answering and evaluation. *International Journal on Document Analysis and Recognition (IJDAR)*, pages 1–15, 2025.

[224] Chae-Won Park, Vikas Palakonda, Sangseok Yun, Il-Min Kim, and Jae-Mo Kang. Ocr-diff: A two-stage deep learning framework for optical character recognition using diffusion model in industrial internet of things. *IEEE Internet of Things Journal*, 11(15):25997–26000, 2024.

[225] Jaewoo Park, Eunji Lee, Yoonsik Kim, Isaac Kang, Hyung Il Koo, and Nam Ik Cho. Multi-lingual optical character recognition system using the reinforcement learning of character segmenter. *Ieee Access*, 8:174437–174448, 2020.

[226] Jiwon Park, Seohyun Pyeon, Jinwoo Kim, Rina Carines Cabal, Yihao Ding, and Soyeon Caren Han. Dochop-qa: Towards multi-hop reasoning over multimodal document collections. *arXiv preprint arXiv:2508.15851*, 2025.

[227] Sangwoo Park, Jinheon Baek, Soyeong Jeong, and Sung Ju Hwang. Chain of retrieval: Multi-aspect iterative search expansion and post-order search aggregation for full paper retrieval. *arXiv preprint arXiv:2507.10057*, 2025.

[228] Sameer M Patel, SS Pai, MB Jain, and VP Vasani. Optical charater recognition for electronic invoices using aws services. *International Journal of Engineering Applied Sciences and Technology*, 6(5):2455–2143, 2021.

[229] Sohan Patnaik, Heril Changwal, Milan Aggarwal, Sumit Bhatia, Yaman Kumar, and Balaji Krishnamurthy. Cabinet: Content relevance based noise reduction for table question answering. *arXiv preprint arXiv:2402.01155*, 2024.

[230] Jovan Pavlović, Miklós Krész, and László Hajdu. Leveraging spreading activation for improved document retrieval in knowledge-graph-based rag systems. *arXiv preprint arXiv:2512.15922*, 2025.

[231] Qiming Peng, Yinxu Pan, Wenjin Wang, Bin Luo, Zhenyu Zhang, Zhengjie Huang, Yuhui Cao, Weichong Yin, Yongfeng Chen, Yin Zhang, et al. Ernie-layout: Layout knowledge enhanced pre-training for visually-rich document understanding. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 3744–3756, 2022.

[232] Xiangyu Peng, Prafulla Kumar Choubey, Caiming Xiong, and Chien-Sheng Wu. Unanswerability evaluation for retrieval augmented generation. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8452–8472, 2025.

[233] Xiangyu Peng, Can Qin, Zeyuan Chen, Ran Xu, Caiming Xiong, and Chien-Sheng Wu. Unidoc-bench: A unified benchmark for document-centric multimodal rag. *arXiv preprint arXiv:2510.03663*, 2025.

[234] Subbaraju Pericherla and E Ilavarasan. Overcoming the challenge of cyberbullying detection in images: a deep learning approach with image captioning and ocr integration. *International Journal of Computing and Digital Systems*, 15(1):393–401, 2024.

[235] B Pfitzmann, C Auer, M Dolfi, AS Nassar, and PWJ Staar. Doclaynet: A large humanannotated dataset for document-layout analysis. *arXiv preprint arXiv:2206.02816*, 2022.

[236] Nicholas Pipitone and Ghita Houir Alami. Legalbench-rag: A benchmark for retrieval-augmented generation in the legal domain. *arXiv preprint arXiv:2408.10343*, 2024.

[237] Gabriele Prato, Shagun Sodhani, Alessandro Sordoni, and Sarath Chandar. Effect of document packing on the latent multi-hop reasoning capabilities of large language models. *arXiv preprint arXiv:2512.14427*, 2025.

[238] Zehan Qi, Rongwu Xu, Zhijiang Guo, Cunxiang Wang, Hao Zhang, and Wei Xu. Long$^2$RAG: Evaluating long-context and long-form retrieval-augmented generation with key point recall. *arXiv preprint arXiv:2410.23000*, 2024.

[239] Man Qin, Qiang Sun, Tim French, and Wei Liu. Enhancing rag system performance through semantic layout chunking. In *Australasian Joint Conference on Artificial Intelligence*, pages 28–39. Springer, 2025.

[240] Kautuk Raj and Pierre Maret. From liberating to questioning tabular data in documents using knowledge graphs. In *European Semantic Web Conference*, pages 291–295. Springer, 2024.

[241] Sachin Raja, Ajoy Mondal, and CV Jawahar. Visual understanding of complex table structures from document images. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2299–2308, 2022.

[242] Steven I Reeves, Dongwook Lee, Anurag Singh, and Kunal Verma. A gaussian process upsampling model for improvements in optical character recognition. In *International Symposium on Visual Computing*, pages 263–274. Springer, 2020.

[243] Christian Reisswig, Anoop R Katti, Marco Spinaci, and Johannes Höhne. Chargrid-ocr: End-to-end trainable optical character recognition for printed documents using instance segmentation. *arXiv preprint arXiv:1909.04469*, 2019.

[244] Xiaofeng Ren and Matthai Philipose. Egocentric recognition of handled objects: Benchmark and analysis. In *2009 IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*, pages 1–8. IEEE, 2009.

[245] Stephen V Rice, Frank R Jenkins, and Thomas A Nartker. The fourth annual test of ocr accuracy. Technical report, Technical Report 95, 1995.

[246] Stephen V Rice, Frank R Jenkins, and Thomas A Nartker. *The fifth annual test of OCR accuracy.* Information Science Research Institute Los Angeles, 1996.

[247] Jon Saad-Falcon, Joe Barrow, Alexa Siu, Ani Nenkova, Seunghyun Yoon, Ryan A Rossi, and Franck Dernoncourt. Pdftriage: Question answering over long, structured documents. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 153–169, 2024.

[248] Anik Saha, Catherine Finegan-Dollak, and Ashish Verma. Position masking for improved layout-aware document understanding. In *Proceedings of the Document Intelligence Workshop at KDD*, 2021.

[249] Anish Salvi, Leo Arnal, Kevin Ly, Gabriel Ferreira, Sophia Y Wang, Curtis Langlotz, Vinit Mahajan, and Chase A Ludwig. Ocular biometry ocr: a machine learning algorithm leveraging optical character recognition to extract intra ocular lens biometry measurements. *Frontiers in Artificial Intelligence*, 7:1428716, 2025.

[250] Fawaz Sammani, Tanmoy Mukherjee, and Nikos Deligiannis. Nlx-gpt: A model for natural language explanations in vision and vision-language tasks. In *proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8322–8332, 2022.

[251] Amany M Sarhan, Hesham A Ali, Mariam Wagdi, Bassant Ali, Aliaa Adel, Rahf Osama, and Dina M Ibrahim. Cv content recognition using yolov8 and tesseract-ocr deep learning. *The Computer Journal*, page bxaf124, 2025.

[252] Naragudem Sarika and NageswaraRao Sirisala. Deep learning techniques for optical character recognition. In *Sustainable Communication Networks and Application: Proceedings of ICSCN 2020*, pages 339–349. Springer, 2021.

[253] Cagrı Sayallar, Ahmet Sayar, and Nurcan Babalık. An ocr engine for printed receipt images using deep learning techniques. *International Journal of Advanced Computer Science and Applications*, 14(2), 2023.

[254] Pit Schneider and Yves Maurer. Rerunning ocr: A machine learning approach to quality assessment and enhancement prediction. *Journal of Data Mining & Digital Humanities*, 2022(Digital humanities in languages), 2022.

[255] Kwangwook Seo, Jinyoung Yeo, and Dongha Lee. Unveiling implicit table knowledge with question-then-pinpoint reasoner for insightful table summarization. *arXiv preprint arXiv:2406.12269*, 2024.

[256] Yash Shambharkar, Shailaja Salagrama, Kanhaiya Sharma, Om Mishra, and Deepak Parashar. An automatic framework for number plate detection using ocr and deep learning approach. *International Journal of Advanced Computer Science and Applications*, 14(4), 2023.

[257] Ashwini Sharma, Navya Sharma, and Kiran Malik. Resume content recognition and organization framework using yolov8 and tesseract ocr deep learning models. In *International Conference on Data Analytics & Management*, pages 33–41. Springer, 2025.

[258] Parikshit Sharma et al. Advancements in ocr: a deep learning algorithm for enhanced text recognition. *International Journal of Inventive Engineering and Sciences*, 10(8):1–7, 2023.

[259] Tahira Shehzadi, Didier Stricker, and Muhammad Zeshan Afzal. A hybrid approach for document layout analysis in document images. In *International Conference on Document Analysis and Recognition*, pages 21–39. Springer, 2024.

[260] Qianwen Shen, Zeyu Ma, and Mingang Chen. From chart to qa pairs: A context-aware generation framework for chart-containing documents. In *Proceedings of the 2025 2nd International Conference on Generative Artificial Intelligence and Information Security*, pages 101–107, 2025.

[261] Wenxuan Shen, Mingjia Wang, Yaochen Wang, Dongping Chen, Junjie Yang, Yao Wan, and Weiwei Lin. Are we on the right way for assessing document retrieval-augmented generation? *arXiv preprint arXiv:2508.03644*, 2025.

[262] Ashish Shetty and Sanjeev Sharma. Ensemble deep learning model for optical character recognition. *Multimedia Tools and Applications*, 83(4):11411–11431, 2024.

[263] Hengyu Shi, Junhao Su, Junfeng Luo, and Jialin Gao. Layoutcot: Unleashing the deep reasoning potential of large language models for layout generation. *arXiv preprint arXiv:2504.10829*, 2025.

[264] Peng Shi, Patrick Ng, Feng Nan, Henghui Zhu, Jun Wang, Jiarong Jiang, Alexander Hanbo Li, Rishav Chakravarti, Donald Weidner, Bing Xiang, et al. Generation-focused table-based intermediate pre-training for free-form question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 11312–11320, 2022.

[265] Yuzhi Shi, Mijung Kim, and Yeongnam Chae. Multi-scale cell-based layout representation for document understanding. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 3670–3679, 2023.

[266] Jacob Si, Mike Qu, Michelle Lee, and Yingzhen Li. Tabrag: Tabular document retrieval via structured language representations. *arXiv preprint arXiv:2511.06582*, 2025.

[267] Michael Siek and Rafi Soeharto. Developing automated optical character recognition system using machine learning algorithm to solve payment verification issues. In *2021 3rd International Conference on Cybernetics and Intelligent System (ICORIS)*, pages 1–6. IEEE, 2021.

[268] Amanpreet Singh, Ronghang Hu, Vedanuj Goswami, Guillaume Couairon, Wojciech Galuba, Marcus Rohrbach, and Douwe Kiela. Flava: A foundational language and vision alignment model. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 15638–15650, 2022.

[269] Ananya Singha, José Cambronero, Sumit Gulwani, Vu Le, and Chris Parnin. Tabular representation, noisy operators, and impacts on table structure understanding tasks in llms. *arXiv preprint arXiv:2310.10358*, 2023.

[270] Vivaan Singhvi, Langalibalele Lunga, Pragya Nidhi, Chris Keum, and Varrun Prakash. High-throughput phenotyping using computer vision and machine learning. *arXiv preprint arXiv:2407.06354*, 2024.

[271] Shangeetha Sivasothy, Scott Barnett, Stefanus Kurniawan, Zafaryab Rasool, and Rajesh Vasa. Ragprobe: An automated approach for evaluating rag applications. *arXiv preprint arXiv:2409.19019*, 2024.

[272] Carlos Soto and Shinjae Yoo. Visual detection with context for document layout analysis. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3464–3470, 2019.

[273] Zhivar Sourati, Zheng Wang, Marianne Menglin Liu, Yazhe Hu, Mengqing Guo, Sujeeth Bharadwaj, Kyu Han, Tao Sheng, Sujith Ravi, Morteza Dehghani, et al. Lad-rag: layout-aware dynamic rag for visually-rich document understanding. *arXiv preprint arXiv:2510.07233*, 2025.

[274] Jan Strich, Enes Kutay Isgorur, Maximilian Trescher, Chris Biemann, and Martin Semmann. $T^2$-RAGBench: Text-and-table benchmark for evaluating retrieval-augmented generation. *arXiv preprint arXiv:2506.12071*, 2025.

[275] Aofeng Su, Aowen Wang, Chao Ye, Chen Zhou, Ga Zhang, Gang Chen, Guangcheng Zhu, Haobo Wang, Haokai Xu, Hao Chen, et al. Tablegpt2: A large multimodal model with tabular data integration. *arXiv preprint arXiv:2411.02059*, 2024.

[276] Xin Su, Tiep Le, Steven Bethard, and Phillip Howard. Semi-structured chain-of-thought: Integrating multiple sources of knowledge for improved language model reasoning. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8597–8613, 2024.

[277] Lya Hulliyyatus Suadaa, Hidetaka Kamigaito, Kotaro Funakoshi, Manabu Okumura, and Hiroya Takamura. Towards table-to-text generation with numerical reasoning. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1451–1465, 2021.

[278] Yuan Sui, Jiaru Zou, Mengyu Zhou, Xinyi He, Lun Du, Shi Han, and Dongmei Zhang. Tap4llm: Table provider on sampling, augmenting, and packing semi-structured data for large language model reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 10306–10323, 2024.

[279] Tofayet Sultan, Nusrat Jahan, Ritu Basak, Mohammed Shaheen Alam Jony, and Rashidul Hasan Nabil. Machine learning in cyberbullying detection from social-media image or screenshot with optical character recognition. *International Journal of Intelligent Systems and Applications*, 10(2):1, 2023.

[280] Qiang Sun, Tingting Bi, Sirui Li, Eun-Jung Holden, Paul Duuring, Kai Niu, and Wei Liu. Symbioticrag: Enhancing document intelligence through human-llm symbiotic collaboration. *arXiv preprint arXiv:2505.02418*, 2025.

[281] Ting Sun, Cheng Cui, Yuning Du, and Yi Liu. Pp-doclayout: A unified document layout detection model to accelerate large-scale data construction. *arXiv preprint arXiv:2503.17213*, 2025.

[282] Zhenjie Sun, Naihao Deng, Haofei Yu, and Jiaxuan You. Table as thought: Exploring structured thoughts in llm reasoning. *arXiv preprint arXiv:2501.02152*, 2025.

[283] Manan Suri, Puneet Mathur, Franck Dernoncourt, Kanika Goswami, Ryan A Rossi, and Dinesh Manocha. Visdom: Multi-document qa with visually rich elements using multimodal retrieval-augmented generation. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 6088–6109, 2025.

[284] Ryota Tanaka, Kyosuke Nishida, Kosuke Nishida, Taku Hasegawa, Itsumi Saito, and Kuniko Saito. Slidevqa: A dataset for document visual question answering on multiple images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 13636–13645, 2023.

[285] Ryota Tanaka, Taichi Iki, Taku Hasegawa, Kyosuke Nishida, Kuniko Saito, and Jun Suzuki. Vdocrag: Retrieval-augmented generation over visually-rich documents. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 24827–24837, 2025.

[286] Hongbo Tang, Shuai Zhao, Jing Luo, Yihang Su, and Jinjian Yang. Layoutkag: Enhancing layout generation in large language models through knowledge-augmented generation. In *2024 3rd International Conference on Artificial Intelligence, Human-Computer Interaction and Robotics (AIHCIR)*, pages 292–299. IEEE, 2024.

[287] Jingqun Tang, Qi Liu, Yongjie Ye, Jinghui Lu, Shu Wei, An-Lan Wang, Chunhui Lin, Hao Feng, Zhen Zhao, Yanjie Wang, et al. Mtvqa: Benchmarking multilingual text-centric visual question answering. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 7748–7763, 2025.

[288] Yixuan Tang and Yi Yang. Multihop-rag: Benchmarking retrieval-augmented generation for multi-hop queries. *arXiv preprint arXiv:2401.15391*, 2024.

[289] Zeyun Tang, Yongliang Shen, Xinyin Ma, Wei Xu, Jiale Yu, and Weiming Lu. Multi-hop reading comprehension across documents with path-based graph convolutional network. *arXiv preprint arXiv:2006.06478*, 2020.

[290] Zineng Tang, Ziyi Yang, Guoxin Wang, Yuwei Fang, Yang Liu, Chenguang Zhu, Michael Zeng, Cha Zhang, and Mohit Bansal. Unifying vision, text, and layout for universal document processing. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 19254–19264, 2023.

[291] Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

[292] Advait Thakur, Khushi Khanchandani, Akshita Shetty, Chaitravi Reddy, and Ritisa Behera. Automated invoice data extraction: Using llm and ocr. *arXiv preprint arXiv:2511.05547*, 2025.

[293] Nandan Thakur, Jimmy Lin, Sam Havens, Michael Carbin, Omar Khattab, and Andrew Drozdov. Freshstack: Building realistic benchmarks for evaluating retrieval on technical documents. *arXiv preprint arXiv:2504.13128*, 2025.

[294] Mokanarangan Thayaparan, Marco Valentino, Viktor Schlegel, and André Freitas. Identifying supporting facts for multi-hop question answering with document graph networks. *arXiv preprint arXiv:1910.00290*, 2019.

[295] Rubèn Tito, Dimosthenis Karatzas, and Ernest Valveny. Document collection visual question answering. In *International Conference on Document Analysis and Recognition*, pages 778–792. Springer, 2021.

[296] Rubèn Tito, Dimosthenis Karatzas, and Ernest Valveny. Hierarchical multimodal transformers for multipage docvqa. *Pattern Recognition*, 144:109834, 2023.

[297] Rubèn Tito, Khanh Nguyen, Marlon Tobaben, Raouf Kerkouche, Mohamed Ali Souibgui, Kangsoo Jung, Joonas Jälkö, Vincent Poulain D'Andecy, Aurelie Joseph, Lei Kang, et al. Privacy-aware document visual question answering. In *International Conference on Document Analysis and Recognition*, pages 199–218. Springer, 2024.

[298] Anyang Tong, Xiang Niu, ZhiPing Liu, Chang Tian, Yanyan Wei, Zenglin Shi, and Meng Wang. Hkrag: Holistic knowledge retrieval-augmented generation over visually-rich documents. *arXiv preprint arXiv:2511.20227*, 2025.

[299] VQAKIE TS. Instructocr2: a lightweight and efficient multi-modal language model for document understanding.

[300] Ming Tu, Kevin Huang, Guangtao Wang, Jing Huang, Xiaodong He, and Bowen Zhou. Select, answer and explain: Interpretable multi-hop reading comprehension over multiple documents. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 9073–9080, 2020.

[301] Yi Tu, Ya Guo, Huan Chen, and Jinyang Tang. Layoutmask: Enhance text-layout interaction in multi-modal pre-training for document understanding. *arXiv preprint arXiv:2305.18721*, 2023.

[302] Jordy Van Landeghem, Rubèn Tito, Łukasz Borchmann, Michał Pietruszka, Pawel Joziak, Rafal Powalski, Dawid Jurkiewicz, Mickaël Coustaty, Bertrand Anckaert, Ernest Valveny, et al. Document understanding dataset and evaluation (dude). In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 19528–19540, 2023.

[303] S Vijayarani and A Sakila. Performance comparison of ocr tools. *International Journal of UbiComp (IJU)*, 6(3): 19–30, 2015.

[304] Vishnou Vinayagame, Gregory Senay, and Luis Martí. Matata: Weakly supervised end-to-end mathematical tool-augmented reasoning for tabular applications. In *International Conference on Document Analysis and Recognition*, pages 428–467. Springer, 2025.

[305] Shafqat Mumtaz Virk, Dana Dannélls, and Azam Sheikh Muhammad. A novel machine learning based approach for post-ocr error detection. In *Proceedings of the International Conference on Recent Advances in Natural Language Processing (RANLP 2021)*, pages 1463–1470, 2021.

[306] Xueyao Wan and Hang Yu. Mmgraphrag: Bridging vision and language with interpretable multimodal knowledge graphs. *arXiv preprint arXiv:2507.20804*, 2025.

[307] Dongsheng Wang, Natraj Raman, Mathieu Sibue, Zhiqiang Ma, Petr Babkin, Simerjot Kaur, Yulong Pei, Armineh Nourbakhsh, and Xiaomo Liu. Docllm: A layout-aware generative language model for multimodal document understanding. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 1: long papers)*, pages 8529–8548, 2024.

[308] Hanjun Wang, Wenda Liu, Qun Wang, Jiaming Xu, Shuai Nie, Yuchen Liu, and Runyu Shi. Light-table-chain: Simplifying and enhancing chain-based table reasoning. In *2024 10th International Conference on Computer and Communications (ICCC)*, pages 269–275. IEEE, 2024.

[309] Haochen Wang, Kai Hu, Haoyu Dong, and Liangcai Gao. Doctabqa: Answering questions from long documents using tables. In *International Conference on Document Analysis and Recognition*, pages 470–487. Springer, 2024.

[310] Jiapeng Wang, Lianwen Jin, and Kai Ding. Lilt: A simple yet effective language-independent layout transformer for structured document understanding. *arXiv preprint arXiv:2202.13669*, 2022.

[311] Jiaqi Wang, Xiao Yang, Kai Sun, Parth Suresh, Sanat Sharma, Adam Czyzewski, Derek Andersen, Surya Appini, Arkav Banerjee, Sajal Choudhary, et al. Crag-mm: Multi-modal multi-turn comprehensive rag benchmark. *arXiv preprint arXiv:2510.26160*, 2025.

[312] Jiawei Wang, Kai Hu, and Qiang Huo. Dlaformer: An end-to-end transformer for document layout analysis. In *International Conference on Document Analysis and Recognition*, pages 40–57. Springer, 2024.

[313] Jilin Wang, Michael Krumdick, Baojia Tong, Hamima Halim, Maxim Sokolov, Vadym Barda, Delphine Vendryes, and Chris Tanner. A graphical approach to document layout analysis. In *International Conference on Document Analysis and Recognition*, pages 53–69. Springer, 2023.

[314] Minzheng Wang, Longze Chen, Fu Cheng, Shengyi Liao, Xinghua Zhang, Bingli Wu, Haiyang Yu, Nan Xu, Lei Zhang, Run Luo, et al. Leave no document behind: Benchmarking long-context llms with extended multi-doc qa. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 5627–5646, 2024.

[315] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*, 2024.

[316] Qiuchen Wang, Ruixue Ding, Zehui Chen, Weiqi Wu, Shihang Wang, Pengjun Xie, and Feng Zhao. Vidorag: Visual document retrieval-augmented generation via dynamic iterative reasoning agents. *arXiv preprint arXiv:2502.18017*, 2025.

[317] Shu Wang, Yingli Zhou, and Yixiang Fang. Bookrag: A hierarchical structure-aware index-based approach for retrieval-augmented generation on complex documents. *arXiv preprint arXiv:2512.03413*, 2025.

[318] Shuting Wang, Jiejun Tan, Zhicheng Dou, and Ji-Rong Wen. Omnieval: An omnidirectional and automatic rag evaluation benchmark in financial domain. In *Proceedings of the 2025 conference on empirical methods in natural language processing*, pages 5737–5762, 2025.

[319] Wanting Wang. Zero-shot complex question-answering on long scientific documents. *arXiv preprint arXiv:2503.02695*, 2025.

[320] Weishi Wang, Hengchang Hu, Zhijie Zhang, Zhaochen Li, Hongxin Shao, and Daniel Dahlmeier. Document intelligence in the era of large language models: A survey. *arXiv preprint arXiv:2510.13366*, 2025. URL https://arxiv.org/abs/2510.13366.

[321] Xinyu Wang, Yanzheng Xiang, Lin Gui, and Yulan He. Garlic: Llm-guided dynamic progress control with hierarchical weighted graph for long document qa. *arXiv preprint arXiv:2410.04790*, 2024.

[322] Yu Wang, Nedim Lipka, Ryan A Rossi, Alexa Siu, Ruiyi Zhang, and Tyler Derr. Knowledge graph prompting for multi-document question answering. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pages 19206–19214, 2024.

[323] Yuxiang Wang, Junhao Gan, Shengxiang Gao, Shenghao Ye, Zhengyi Yang, and Jianzhong Qi. Beyond linearization: Attributed table graphs for table reasoning. *arXiv preprint arXiv:2601.08444*, 2026.

[324] Zhitong Wang, Cheng Gao, Chaojun Xiao, Yufei Huang, Shuzheng Si, Kangyang Luo, Yuzhuo Bai, Wenhao Li, Tangjian Duan, Chuancheng Lv, et al. Document segmentation matters for retrieval-augmented generation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 8063–8075, 2025.

[325] Zilong Wang, Yichao Zhou, Wei Wei, Chen-Yu Lee, and Sandeep Tata. Vrdu: A benchmark for visually-rich document understanding. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 5184–5193, 2023.

[326] Zilong Wang, Hao Zhang, Chun-Liang Li, Julian Martin Eisenschlos, Vincent Perot, Zifeng Wang, Lesly Miculicich, Yasuhisa Fujii, Jingbo Shang, Chen-Yu Lee, et al. Chain-of-table: Evolving tables in the reasoning chain for table understanding. *arXiv preprint arXiv:2401.04398*, 2024.

[327] Navve Wasserman, Roi Pony, Oshri Naparstek, Adi Raz Goldfarb, Eli Schwartz, Udi Barzelay, and Leonid Karlinsky. Real-mm-rag: A real-world multi-modal retrieval benchmark. *arXiv preprint arXiv:2502.12342*, 2025.

[328] Gengchen Wei, Xinle Pang, Tianning Zhang, Yu Sun, Xun Qian, Chen Lin, Han-Sen Zhong, and Wanli Ouyang. Docrelm: Mastering document retrieval with language model. *arXiv preprint arXiv:2405.11461*, 2024.

[329] Haoran Wei, Lingyu Kong, Jinyue Chen, Liang Zhao, Zheng Ge, Jinrong Yang, Jianjian Sun, Chunrui Han, and Xiangyu Zhang. Vary: Scaling up the vision vocabulary for large vision-language model. In *European Conference on Computer Vision*, pages 408–424. Springer, 2024.

[330] Haoran Wei, Lingyu Kong, Jinyue Chen, Liang Zhao, Zheng Ge, En Yu, Jianjian Sun, Chunrui Han, and Xiangyu Zhang. Small language model meets with reinforced vision vocabulary. *arXiv preprint arXiv:2401.12503*, 2024.

[331] Haoran Wei, Chenglong Liu, Jinyue Chen, Jia Wang, Lingyu Kong, Yanming Xu, Zheng Ge, Liang Zhao, Jianjian Sun, Yuang Peng, et al. General ocr theory: Towards ocr-2.0 via a unified end-to-end model. *arXiv preprint arXiv:2409.01704*, 2024.

[332] Haoran Wei, Yaofeng Sun, and Yukun Li. Deepseek-ocr: Contexts optical compression. *arXiv preprint arXiv:2510.18234*, 2025.

[333] Christoph Wick, Christian Reul, and Frank Puppe. Calamari-a high-performance tensorflow-based deep learning package for optical character recognition. *arXiv preprint arXiv:1807.02004*, 2018.

[334] Chengmin Wu, Enrui Hu, Ke Zhan, Lan Luo, Xinyu Zhang, Hao Jiang, Qirui Wang, Zhao Cao, Fan Yu, and Lei Chen. Triple-fact retriever: An explainable reasoning retrieval model for multi-hop qa problem. In *2022 IEEE 38th International Conference on Data Engineering (ICDE)*, pages 1206–1218. IEEE, 2022.

[335] Jian Wu, Yicheng Xu, Börje F Karlsson, and Manabu Okumura. A table question alignment based cell-selection method for table-text qa. *Journal of Natural Language Processing*, 31(1):189–211, 2024.

[336] Jiannan Wu, Muyan Zhong, Sen Xing, Zeqiang Lai, Zhaoyang Liu, Zhe Chen, Wenhai Wang, Xizhou Zhu, Lewei Lu, Tong Lu, et al. Visionllm v2: An end-to-end generalist multimodal large language model for hundreds of vision-language tasks. *Advances in Neural Information Processing Systems*, 37:69925–69975, 2024.

[337] Shihong Wu, Ruiping Wang, Meihang Zhang, Zhigang Wang, Xiaofang Gan, and Yongtao Wu. Htan: A hierarchical table-aware network for complex table visual understanding. In *2025 IEEE International Conference on Pattern Recognition, Machine Vision and Artificial Intelligence (PRMVAI)*, pages 1–5. IEEE, 2025.

[338] Te-Lin Wu, Cheng Li, Mingyang Zhang, Tao Chen, Spurthi Amba Hombaiah, and Michael Bendersky. Lampret: Layout-aware multimodal pretraining for document understanding. *arXiv preprint arXiv:2104.08405*, 2021.

[339] Xinya Wu, Duo Zheng, Ruonan Wang, Jiashen Sun, Minzhen Hu, Fangxiang Feng, Xiaojie Wang, Huixing Jiang, and Fan Yang. A region-based document vqa. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 4909–4920, 2022.

[340] Xixi Wu, Yanchao Tan, Nan Hou, Ruiyang Zhang, and Hong Cheng. Molorag: Bootstrapping document understanding via multi-modal logic-aware retrieval. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 14035–14056, 2025.

[341] Yaxiong Wu, Jianyuan Bo, Yongyue Zhang, Sheng Liang, and Yong Liu. Query-centric graph retrieval augmented generation. *arXiv preprint arXiv:2509.21237*, 2025.

[342] Yin Wu, Quanyu Long, Jing Li, Jianfei Yu, and Wenya Wang. Visual-rag: Benchmarking text-to-image retrieval augmented generation for visual knowledge intensive queries. *arXiv preprint arXiv:2502.16636*, 2025.

[343] Yuxuan Wu, Le Wang, Sanping Zhou, Mengnan Liu, Gang Hua, and Haoxiang Li. Layoutrag: Retrieval-augmented model for content-agnostic conditional layout generation. *arXiv preprint arXiv:2506.02697*, 2025.

[344] Zhenhe Wu, Jian Yang, Jiaheng Liu, Xianjie Wu, Changzai Pan, Jie Zhang, Yu Zhao, Shuangyong Song, Yongxiang Li, and Zhoujun Li. Table-r1: Region-based reinforcement learning for table understanding. *arXiv preprint arXiv:2505.12415*, 2025.

[345] Zhiyu Wu, Xiaokang Chen, Zizheng Pan, Xingchao Liu, Wen Liu, Damai Dai, Huazuo Gao, Yiyang Ma, Chengyue Wu, Bingxuan Wang, et al. Deepseek-vl2: Mixture-of-experts vision-language models for advanced multimodal understanding. *arXiv preprint arXiv:2412.10302*, 2024.

[346] Xudong Xie, Hao Yan, Liang Yin, Yang Liu, Jing Ding, Minghui Liao, Yuliang Liu, Wei Chen, and Xiang Bai. Wukong: A large multimodal model for efficient long pdf reading with end-to-end sparse sampling. *arXiv preprint arXiv:2410.05970*, 2024.

[347] Caiming Xiong, Victor Zhong, and Richard Socher. Dynamic coattention networks for question answering. *arXiv preprint arXiv:1611.01604*, 2016.

[348] Sishi Xiong, Dakai Wang, Yu Zhao, Jie Zhang, Changzai Pan, Haowei He, Xiangyu Li, Wenhan Chang, Zhongjiang He, Shuangyong Song, et al. Tablereasoner: Advancing table reasoning framework with large language models. *arXiv preprint arXiv:2507.08046*, 2025.

[349] Chuan Xu, Qiaosheng Chen, Yutong Feng, and Gong Cheng. mmrag: A modular benchmark for retrieval-augmented generation over text, tables, and knowledge graphs. In *International Semantic Web Conference*, pages 3–21. Springer, 2025.

[350] Qixin Xu, Haozhe Wang, Che Liu, Fangzhen Lin, and Wenhu Chen. Cogdoc: Towards unified thinking in documents. *arXiv preprint arXiv:2512.12658*, 2025.

[351] Ruoxi Xu, Hongyu Lin, Xinyan Guan, Yingfei Sun, and Le Sun. Dlue: Benchmarking document language understanding. In *China National Conference on Chinese Computational Linguistics*, pages 387–401. Springer, 2024.

[352] Yiheng Xu, Minghao Li, Lei Cui, Shaohan Huang, Furu Wei, and Ming Zhou. Layoutlm: Pre-training of text and layout for document image understanding. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 1192–1200, 2020.

[353] Yiheng Xu, Tengchao Lv, Lei Cui, Guoxin Wang, Yijuan Lu, Dinei Florencio, Cha Zhang, and Furu Wei. Layoutxlm: Multimodal pre-training for multilingual visually-rich document understanding. *arXiv preprint arXiv:2104.08836*, 2021.

[354] Aditya Yadav, Shauryan Singh, Muzzamil Siddique, Nileshkumar Mehta, and Archana Kotangale. Ocr using crnn: A deep learning approach for text recognition. In *2023 4th International Conference for Emerging Technology (INCET)*, pages 1–6. IEEE, 2023.

[355] Bohao Yang, Chen Tang, Kun Zhao, Chenghao Xiao, and Chenghua Lin. Effective distillation of table-based reasoning ability from llms. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 5538–5550, 2024.

[356] Chening Yang, Duy-Khanh Vu, Minh-Tien Nguyen, Xuan-Quang Nguyen, Linh Nguyen, and Hung Le. Superrag: Beyond rag with layout-aware graph modeling. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 3: Industry Track)*, pages 544–557, 2025.

[357] Huichen Yang and William Hsu. Transformer-based approach for document layout understanding. In *2022 IEEE International Conference on Image Processing (ICIP)*, pages 4043–4047. IEEE, 2022.

[358] Jiashu Yang, Chi Zhang, Abudukelimu Wuerkaixi, Xuxin Cheng, Cao Liu, Ke Zeng, Xu Jia, and Xunliang Cai. Autothinkrag: Complexity-aware control of retrieval-augmented reasoning for image-text interaction, 2026.

[359] Saisai Yang, Qingyi Huang, Jing Yuan, Liangyu Zha, Kai Tang, Yuhang Yang, Ning Wang, Yucheng Wei, Liyao Li, Wentao Ye, et al. Tablegpt-r1: Advancing tabular reasoning through reinforcement learning. *arXiv preprint arXiv:2512.20312*, 2025.

[360] Xiao Yang, Kai Sun, Hao Xin, Yushi Sun, Nikita Bhalla, Xiangsen Chen, Sajal Choudhary, Rongze D Gui, Ziran W Jiang, Ziyu Jiang, et al. Crag-comprehensive rag benchmark. *Advances in Neural Information Processing Systems*, 37:10470–10490, 2024.

[361] Zheyuan Yang, Lyuhao Chen, Arman Cohan, and Yilun Zhao. Table-r1: Inference-time scaling for table reasoning. *arXiv preprint arXiv:2505.23621*, 2025.

[362] Zukang Yang, Zixuan Zhu, and Jennifer Zhu. Curiousllm: Elevating multi-document question answering with llm-enhanced knowledge graph reasoning. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 3: Industry Track)*, pages 274–286, 2025.

[363] Jiabo Ye, Anwen Hu, Haiyang Xu, Qinghao Ye, Ming Yan, Yuhao Dan, Chenlin Zhao, Guohai Xu, Chenliang Li, Junfeng Tian, et al. mplug-docowl: Modularized multimodal large language model for document understanding. *arXiv preprint arXiv:2307.02499*, 2023.

[364] Yunhu Ye, Binyuan Hui, Min Yang, Binhua Li, Fei Huang, and Yongbin Li. Large language models are versatile decomposers: Decomposing evidence and questions for table-based reasoning. In *Proceedings of the 46th international ACM SIGIR conference on research and development in information retrieval*, pages 174–184, 2023.

[365] Yue Yin, Wei Zhang, Sheng Hong, Jie Yang, Jian Xiong, and Guan Gui. Deep learning-aided ocr techniques for chinese uppercase characters in the application of internet of things. *IEEE Access*, 7:47043–47049, 2019.

[366] Waleed A Yousef. Machine learning construction: implications to cybersecurity. In *Artificial Intelligence for Cyber-Physical Systems Hardening*, pages 7–44. Springer, 2022.

[367] Peiying Yu, Guoxin Chen, and Jingjing Wang. Table-critic: A multi-agent framework for collaborative criticism and refinement in table reasoning. *arXiv preprint arXiv:2502.11799*, 2025.

[368] Shi Yu, Chaoyue Tang, Bokai Xu, Junbo Cui, Junhao Ran, Yukun Yan, Zhenghao Liu, Shuo Wang, Xu Han, Zhiyuan Liu, et al. Visrag: Vision-based retrieval-augmented generation on multi-modality documents. *arXiv preprint arXiv:2410.10594*, 2024.

[369] Xiaohan Yu, Pu Jian, and Chong Chen. Tablerag: A retrieval augmented generation framework for heterogeneous document reasoning. *arXiv preprint arXiv:2506.10380*, 2025.

[370] Ya-Qi Yu, Minghui Liao, Jiwen Zhang, and Jihao Wu. Texthawk2: A large vision-language model excels in bilingual ocr and grounding with 16x fewer tokens. *arXiv preprint arXiv:2410.05261*, 2024.

[371] Vicky Zayats, Kristina Toutanova, and Mari Ostendorf. Representations for question answering from documents with tables and text. *arXiv preprint arXiv:2101.10573*, 2021.

[372] Chong Zhang, Yi Tu, Yixi Zhao, Chenshu Yuan, Huan Chen, Yue Zhang, Mingxu Chai, Ya Guo, Huijia Zhu, Qi Zhang, et al. Modeling layout reading order as ordering relations for visually-rich document understanding. *arXiv preprint arXiv:2409.19672*, 2024.

[373] Chong Zhang, Yixi Zhao, Yulu Xie, Chenshu Yuan, Yi Tu, Ya Guo, Mingxu Chai, Ziyu Shen, Yue Zhang, and Qi Zhang. Unveiling the deficiencies of pre-trained text-and-layout models in real-world visually-rich document information extraction. *arXiv preprint arXiv:2402.02379*, 2024.

[374] Han Zhang, Yuheng Ma, and Hanfang Yang. Alter: Augmentation for large-table-based reasoning. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 179–198, 2025.

[375] Huajian Zhang, Mingyue Cheng, Yucong Luo, and Xiaoyu Tao. Star: Towards cognitive table reasoning via slow-thinking large language models. *arXiv preprint arXiv:2511.11233*, 2025.

[376] Jiarui Zhang, Yuliang Liu, Zijun Wu, Guosheng Pang, Zhili Ye, Yupei Zhong, Junteng Ma, Tao Wei, Haiyang Xu, Weikai Chen, et al. Monkeyocr v1. 5 technical report: Unlocking robust document parsing for complex patterns. *arXiv preprint arXiv:2511.10390*, 2025.

[377] Jiaxin Zhang, Wentao Yang, Songxuan Lai, Zecheng Xie, and Lianwen Jin. Dockylin: A large multimodal model for visual document understanding with efficient visual slimming. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 9923–9932, 2025.

[378] Jinxu Zhang. Read and think: An efficient step-wise multimodal language model for document understanding and reasoning. *arXiv preprint arXiv:2403.00816*, 2024.

[379] Jinxu Zhang, Yongqi Yu, and Yu Zhang. Cream: coarse-to-fine retrieval and multi-modal efficient tuning for document vqa. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pages 925–934, 2024.

[380] Liang Zhang, Anwen Hu, Haiyang Xu, Ming Yan, Yichen Xu, Qin Jin, Ji Zhang, and Fei Huang. Tinychart: Efficient chart understanding with visual token merging and program-of-thoughts learning. *arXiv preprint arXiv:2404.16635*, 2024.

[381] Long Zhang, Tong Zhang, Haibo Zhang, Baosong Yang, Wei Ye, and Shikun Zhang. Multi-hop transformer for document-level machine translation. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3953–3963, 2021.

[382] Peng Zhang, Can Li, Liang Qiao, Zhanzhan Cheng, Shiliang Pu, Yi Niu, and Fei Wu. Vsr: a unified framework for document layout analysis combining vision, semantics and relations. In *International conference on document analysis and recognition*, pages 115–130. Springer, 2021.

[383] Pengchuan Zhang, Xiujun Li, Xiaowei Hu, Jianwei Yang, Lei Zhang, Lijuan Wang, Yejin Choi, and Jianfeng Gao. Vinvl: Revisiting visual representations in vision-language models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5579–5588, 2021.

[384] Xuanliang Zhang, Dingzirui Wang, Longxu Dou, Baoxin Wang, Dayong Wu, Qingfu Zhu, and Wanxiang Che. Flextaf: Enhancing table reasoning with flexible tabular formats. *arXiv preprint arXiv:2408.08841*, 2024.

[385] Xuanliang Zhang, Dingzirui Wang, Keyan Xu, Qingfu Zhu, and Wanxiang Che. Rot: Enhancing table reasoning with iterative row-wise traversals. *arXiv preprint arXiv:2505.15110*, 2025.

[386] Yulong Zhang. Ocr-quality: A human-annotated dataset for ocr quality assessment. *arXiv preprint arXiv:2510.21774*, 2025.

[387] Zhenrong Zhang, Jiefeng Ma, Jun Du, Licheng Wang, and Jianshu Zhang. Multimodal pre-training based on graph attention network for document understanding. *IEEE Transactions on Multimedia*, 25:6743–6755, 2022.

[388] Bowen Zhao, Changkai Ji, Yuejie Zhang, Wen He, Yingwen Wang, Qing Wang, Rui Feng, and Xiaobo Zhang. Large language models are complex table parsers. *arXiv preprint arXiv:2312.11521*, 2023.

[389] Jianbin Zhao, Pengfei Zhang, Yuzhen Wang, Rui Xin, Xiuyuan Lu, Ripeng Li, Shuai Lyu, Zhonghong Ou, and Meina Song. Tqagent: Enhancing table-based question answering with knowledge graphs and tree-structured reasoning. *Applied Sciences (2076-3417)*, 15(7), 2025.

[390] Weichao Zhao, Hao Feng, Qi Liu, Jingqun Tang, Binghong Wu, Lei Liao, Shu Wei, Yongjie Ye, Hao Liu, Wengang Zhou, et al. Tabpedia: Towards comprehensive visual table understanding with concept synergy. *Advances in Neural Information Processing Systems*, 37:7185–7212, 2024.

[391] Wenting Zhao, Justin Chiu, Claire Cardie, and Alexander M Rush. Hop, union, generate: Explainable multi-hop reasoning without rationale supervision. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 16119–16130, 2023.

[392] Wenting Zhao, Ye Liu, Yao Wan, Yibo Wang, Zhongfen Deng, and Philip S Yu. Localize, retrieve and fuse: A generalized framework for free-form question answering over tables. *arXiv preprint arXiv:2309.11049*, 2023.

[393] Yilun Zhao, Yunxiang Li, Chenying Li, and Rui Zhang. Multihiertt: Numerical reasoning over multi hierarchical tabular and textual data. *arXiv preprint arXiv:2206.01347*, 2022.

[394] Yilun Zhao, Linyong Nan, Zhenting Qi, Rui Zhang, and Dragomir Radev. Reastap: Injecting table reasoning skills during pre-training via synthetic reasoning examples. *arXiv preprint arXiv:2210.12374*, 2022.

[395] Yilun Zhao, Lyuhao Chen, Arman Cohan, and Chen Zhao. Tapera: Enhancing faithfulness and interpretability in long-form table qa by content planning and execution-based reasoning. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12824–12840, 2024.

[396] Zhiyuan Zhao, Hengrui Kang, Bin Wang, and Conghui He. Doclayout-yolo: Enhancing document layout analysis through diverse synthetic data and global-to-local adaptive perception. *arXiv preprint arXiv:2410.12628*, 2024.

[397] Xu Zhong, Jianbin Tang, and Antonio Jimeno Yepes. Publaynet: largest dataset ever for document layout analysis. In *2019 International conference on document analysis and recognition (ICDAR)*, pages 1015–1022. IEEE, 2019.

[398] Yu Zhong, Bo Shen, and Tao Wang. Advancing document-level relation extraction with a syntax-enhanced multi-hop reasoning network. *Journal of Intelligent & Fuzzy Systems*, 46(4):9155–9171, 2024.

[399] Ejian Zhou, Xingjiao Wu, Luwei Xiao, Xiangcheng Du, Tianlong Ma, and Liang He. Document layout analysis via positional encoding. In *2022 IEEE International Conference on Image Processing (ICIP)*, pages 1156–1160. IEEE, 2022.

[400] Andrew Zhu, Alyssa Hwang, Liam Dugan, and Chris Callison-Burch. Fanoutqa: A multi-hop, multi-document question answering benchmark for large language models. *arXiv preprint arXiv:2402.14116*, 2024.

[401] Dawei Zhu, Rui Meng, Jiefeng Chen, Sujian Li, Tomas Pfister, and Jinsung Yoon. Doclens: A tool-augmented multi-agent framework for long visual document understanding. *arXiv preprint arXiv:2511.11552*, 2025.

[402] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *arXiv preprint arXiv:2304.10592*, 2023.

[403] Fengbin Zhu, Wenqiang Lei, Fuli Feng, Chao Wang, Haozhou Zhang, and Tat-Seng Chua. Towards complex document understanding by discrete reasoning. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 4857–4866, 2022.

[404] Fengbin Zhu, Moxin Li, Junbin Xiao, Fuli Feng, Chao Wang, and Tat Seng Chua. Soargraph: Numerical reasoning over financial table-text data via semantic-oriented hierarchical graphs. In *Companion Proceedings of the ACM Web Conference 2023*, pages 1236–1244, 2023.

[405] Fengbin Zhu, Ziyang Liu, Fuli Feng, Chao Wang, Moxin Li, and Tat Seng Chua. Tat-llm: A specialized language model for discrete reasoning over financial tabular and textual data. In *Proceedings of the 5th ACM International Conference on AI in Finance*, pages 310–318, 2024.

[406] Fengbin Zhu, Ziyang Liu, Xiang Yao Ng, Haohui Wu, Wenjie Wang, Fuli Feng, Chao Wang, Huanbo Luan, and Tat Seng Chua. Mmdocbench: Benchmarking large vision-language models for fine-grained visual document understanding. *arXiv preprint arXiv:2410.21311*, 2024.

[407] Shiding Zhu, Wenhui Dong, Jun Song, Yingbo Wang, Yanan Guo, and Bo Zheng. Fila: Fine-grained vision language models. *arXiv preprint arXiv:2412.08378*, 2024.

[408] Xi Zhu, Xue Han, Shuyuan Peng, Shuo Lei, Chao Deng, and Junlan Feng. Beyond layout embedding: Layout attention with gaussian biases for structured document understanding. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 7773–7784, 2023.

[409] Jin Ziqi and Wei Lu. Tab-cot: Zero-shot tabular chain of thought. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 10259–10277, 2023.

[410] Silvia Zottin, Axel De Nardin, Emanuela Colombi, Claudio Piciarelli, Filippo Pavan, and Gian Luca Foresti. U-diads-bib: a full and few-shot pixel-precise dataset for document layout analysis of ancient manuscripts. *Neural Computing and Applications*, 36(20):11777–11789, 2024.

[411] Anni Zou, Wenhao Yu, Hongming Zhang, Kaixin Ma, Deng Cai, Zhuosheng Zhang, Hai Zhao, and Dong Yu. Docbench: A benchmark for evaluating llm-based document reading systems. In *Proceedings of the 4th International Workshop on Knowledge-Augmented Methods for Natural Language Processing*, pages 359–373, 2025.

[412] Jiaru Zou, Dongqi Fu, Sirui Chen, Xinrui He, Zihao Li, Yada Zhu, Jiawei Han, and Jingrui He. Rag over tables: Hierarchical memory index, multi-stage retrieval, and benchmarking. In *Proceedings of arXiv preprint*, 2025.