The assignment: this looks like a title

Topic:	Very Difficult Course (VDC)	
Due:	Jan. 01, 1970 by 23:59 hours	
Author:	James Holden	holden@roci.edu
	Naomi Nagata	nagata@roci.edu
	Amos Burton	burton@roci.edu
	Alex Kamal	kamal@roci.edu
Lecturer:	Dr. Praxideke Meng	pmeng@ganymede.org
	Chrisjen Avasarala	avasarala@unn.gov
Dated:	Jan. 01, 2000	

Contents

1 A section **1**

1.1 A subsection 1

2 Math **1**

3 Figures and Tables **1**

A Code Listing **2**

1 A section

This is a section.

1.1 A subsection

This is a subsection

2 Math

Write numbered equations with labelling quickly with:

```
\[
    E = m c^2
    \label{eq:einstein}
\]
```

This becomes:

$$E = mc^2 \tag{1}$$

Inline math is simply `$ a =1 $`, rendered as $a = 1$. And we can refer to the labeled entries via `\cref{}`. Let us look at eq. (1).

3 Figures and Tables

We include an image placed here:

```
\begin{figure}[h]
    \centering
    \includegraphics[width=0.25\linewidth]{fig/test.png}
    \caption[A short caption]{A long caption with more information}
    \label{fig:an_img}
\end{figure}
```



Figure 1: A long caption with more information

How about a table?

```
begin{table}[h]
    \centering
    \begin{tabular}{l c}
        \hline
        Parameter & Requirement \\
        \hline
        entry & 1\\
        \hline
        another entry & 2\\
        \hline
    \end{tabular}
    \caption[A short caption]{A long caption}
```

```
        \label{tab:a_tab}
    \end{table}
```

Parameter	Requirement
entry	1
another entry	2

Table 1: A long caption

A Code Listing

A code file can also be listed.

```
    \lstinputlisting[
        language=Python,
        caption={code/example.py},
        label={list:example.py}]
    {code/example.py}
```

Listing 1: code/example.py

```python
"""
This is an example python code for Typst assognment tempalte.
"""

# import
import numpy as np

# func


def simple_fn(a: np.ndarray, b: np.ndarray) -> np.ndarray:
    """This is a simple function that goes a+b -> c"""
    return a + b


# main

if __name__ == "__main__":
    a = np.asarray([1, 2, 3])
    b = np.asarray([2, 4, 6])
    simple_fn(a, b)
```