

Lecture 7: Function Approximation

Chong Li

Outline

- Introduction & Preliminaries
- RL Prediction with Function Approximation
- RL Control with Function Approximation
- Batch Method for RL Applications

*materials are modified from David Silver's RL lecture notes

Outline

- Introduction & Preliminaries
- RL Prediction with Function Approximation
- RL Control with Function Approximation
- Batch Method for RL Applications

Motivation

- How to solve large-scale reinforcement learning problems:
 - Backgammon: 10^{20} states
 - Computer GO: 10^{170} states
 - Autonomous driving: continuous state space
- Curse of dimensionality

Value Function Approximation


- So far we have represented value function by a *lookup table*
 - Every state s has an entry $V(s)$
 - Or every state-action pair s, a has an entry $Q(s, a)$
- Problem with large MDPs:
 - There are too many states and/or actions to store in memory
 - It is too slow to learn the value of each state individually
- Solution for large MDPs:
 - Estimate value function with *function approximation*

$$\hat{v}(s, \mathbf{w}) \approx v_{\pi}(s)$$

or $\hat{q}(s, a, \mathbf{w}) \approx q_{\pi}(s, a)$

Generalise from seen states to unseen states
Update parameter \mathbf{w} using MC or TD learning

Types of Approximation



Which Function Approximator?

- There are many function approximators:
 - Linear: linear combinations of features
 - Non-linear: neural network
 - Decision tree
 -
- We consider ***differentiable*** function approximators in this lecture:
 - Linear: linear combinations of features
 - Non-linear: neural network



Gradient Descent

- Let $J(\mathbf{w})$ be a differentiable function of parameter vector \mathbf{w}
- Define the *gradient* of $J(\mathbf{w})$ to be

$$\nabla_{\mathbf{w}} J(\mathbf{w}) = \begin{pmatrix} \frac{\partial J(\mathbf{w})}{\partial w_1} \\ \vdots \\ \frac{\partial J(\mathbf{w})}{\partial w_n} \end{pmatrix}$$

- To find a local minimum of $J(\mathbf{w})$
- Adjust \mathbf{w} in direction of -ve gradient

$$\Delta \mathbf{w} = -\frac{1}{2} \alpha \nabla_{\mathbf{w}} J(\mathbf{w})$$



Stochastic Gradient Descent

- Goal: find parameter vector \mathbf{w} minimising mean-squared error between approximate value fn $\hat{v}(s, \mathbf{w})$ and true value fn $v_\pi(s)$

$$J(\mathbf{w}) = \mathbb{E}_\pi [(v_\pi(S) - \hat{v}(S, \mathbf{w}))^2]$$

- Gradient descent finds a local minimum

$$\begin{aligned}\Delta \mathbf{w} &= -\frac{1}{2} \alpha \nabla_{\mathbf{w}} J(\mathbf{w}) \\ &= \alpha \mathbb{E}_\pi [(v_\pi(S) - \hat{v}(S, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S, \mathbf{w})]\end{aligned}$$

- Stochastic gradient descent *samples* the gradient

$$\Delta \mathbf{w} = \alpha (v_\pi(S) - \hat{v}(S, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S, \mathbf{w})$$

- Expected update is equal to full gradient update

Stochastic Gradient Descent - Example

- Suppose we want to fit a straight line

$$y = w_1 + w_2 x$$

- Use data set

$$(x_1, y_1), \dots, (x_n, y_n)$$

- Objective function

$$Q(w) = \sum_{i=1}^n Q_i(w) = \sum_{i=1}^n (w_1 + w_2 x_i - y_i)^2$$

- SGD: sweep through the training set

$$\begin{bmatrix} w_1 \\ w_2 \end{bmatrix} := \begin{bmatrix} w_1 \\ w_2 \end{bmatrix} - \eta \begin{bmatrix} 2(w_1 + w_2 x_i - y_i) \\ 2x_i(w_1 + w_2 x_i - y_i) \end{bmatrix}$$

Outline

- Introduction & Preliminaries
- **RL Prediction with Function Approximation**
- RL Control with Function Approximation
- Batch Method for RL Applications

RL Prediction with Value Approximation

- Have assumed true value function $v_\pi(s)$ given by supervisor
- But in RL there is no supervisor, only rewards
- In practice, we substitute a *target* for $v_\pi(s)$
 - For MC, the target is the return G_t

$$\Delta \mathbf{w} = \alpha(\textcolor{red}{G}_t - \hat{v}(S_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S_t, \mathbf{w})$$

- For TD(0), the target is the TD target $R_{t+1} + \gamma \hat{v}(S_{t+1}, \mathbf{w})$

$$\Delta \mathbf{w} = \alpha(\textcolor{red}{R}_{t+1} + \gamma \hat{v}(\textcolor{red}{S}_{t+1}, \mathbf{w}) - \hat{v}(S_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S_t, \mathbf{w})$$

- For TD(λ), the target is the λ -return G_t^λ

$$\Delta \mathbf{w} = \alpha(\textcolor{red}{G}_t^\lambda - \hat{v}(S_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S_t, \mathbf{w})$$

How to compute the gradient?

$$\Delta \mathbf{w} = \alpha (v_{\pi}(S) - \hat{v}(S, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S, \mathbf{w})$$

- We can compute it for
 - Linear: linear combinations of features
 - Non-linear: neural network

Feature Vectors

- Represent state by a *feature vector*

$$\mathbf{x}(S) = \begin{pmatrix} \mathbf{x}_1(S) \\ \vdots \\ \mathbf{x}_n(S) \end{pmatrix}$$

- For example:
 - Distance of robot from landmarks
 - Trends in the stock market
 - Piece and pawn configurations in chess

- Ways to combine features
 - Polynomials
 - Fourier basis
 - Coding techniques
 - Radical basis functions
 -

Linear Approximation

- Represent value function by a linear combination of features

$$\hat{v}(S, \mathbf{w}) = \mathbf{x}(S)^\top \mathbf{w} = \sum_{j=1}^n \mathbf{x}_j(S) \mathbf{w}_j$$

- Objective function is quadratic in parameters \mathbf{w}

$$J(\mathbf{w}) = \mathbb{E}_\pi \left[(v_\pi(S) - \mathbf{x}(S)^\top \mathbf{w})^2 \right]$$

- Stochastic gradient descent converges on *global* optimum
- Update rule is particularly simple

$$\nabla_{\mathbf{w}} \hat{v}(S, \mathbf{w}) = \mathbf{x}(S)$$

$$\Delta \mathbf{w} = \alpha (v_\pi(S) - \hat{v}(S, \mathbf{w})) \mathbf{x}(S)$$

Update = *step-size* \times *prediction error* \times *feature value*

Table Lookup Features

- Table lookup is a special case of linear value function approximation
- Using *table lookup features*


$$\mathbf{x}^{table}(S) = \begin{pmatrix} \mathbf{1}(S = s_1) \\ \vdots \\ \mathbf{1}(S = s_n) \end{pmatrix}$$

- Parameter vector \mathbf{w} gives value of each individual state

$$\hat{v}(S, \mathbf{w}) = \begin{pmatrix} \mathbf{1}(S = s_1) \\ \vdots \\ \mathbf{1}(S = s_n) \end{pmatrix} \cdot \begin{pmatrix} \mathbf{w}_1 \\ \vdots \\ \mathbf{w}_n \end{pmatrix}$$

Non-linear Approximation

- Neural network



Monte-Carlo with Value Function Approximation

- Return G_t is an unbiased, noisy sample of true value $v_\pi(S_t)$
- Can therefore apply supervised learning to “training data”:

$$\langle S_1, G_1 \rangle, \langle S_2, G_2 \rangle, \dots, \langle S_T, G_T \rangle$$

- For example, using *linear Monte-Carlo policy evaluation*

$$\begin{aligned}\Delta \mathbf{w} &= \alpha(\textcolor{red}{G}_t - \hat{v}(S_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S_t, \mathbf{w}) \\ &= \alpha(G_t - \hat{v}(S_t, \mathbf{w})) \mathbf{x}(S_t)\end{aligned}$$

- Monte-Carlo evaluation converges to a local optimum
- Even when using non-linear value function approximation

TD(0) with Value Function Approximation

- The TD-target $R_{t+1} + \gamma \hat{v}(S_{t+1}, \mathbf{w})$ is a *biased* sample of true value $v_\pi(S_t)$
- Can still apply supervised learning to “training data”:

$$\langle S_1, R_2 + \gamma \hat{v}(S_2, \mathbf{w}) \rangle, \langle S_2, R_3 + \gamma \hat{v}(S_3, \mathbf{w}) \rangle, \dots, \langle S_{T-1}, R_T \rangle$$

- For example, using *linear TD(0)*

$$\begin{aligned} \Delta \mathbf{w} &= \alpha(R + \gamma \hat{v}(S', \mathbf{w}) - \hat{v}(S, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S, \mathbf{w}) \\ &= \alpha \delta \mathbf{x}(S) \end{aligned}$$

- Linear TD(0) converges (close) to global optimum

TD(λ) with Value Function Approximation

- The λ -return G_t^λ is also a biased sample of true value $v_\pi(s)$
- Can again apply supervised learning to “training data”:

$$\langle S_1, G_1^\lambda \rangle, \langle S_2, G_2^\lambda \rangle, \dots, \langle S_{T-1}, G_{T-1}^\lambda \rangle$$

- Forward view linear TD(λ)

$$\begin{aligned}\Delta \mathbf{w} &= \alpha(\mathbf{G}_t^\lambda - \hat{v}(S_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(S_t, \mathbf{w}) \\ &= \alpha(\mathbf{G}_t^\lambda - \hat{v}(S_t, \mathbf{w})) \mathbf{x}(S_t)\end{aligned}$$

- Backward view linear TD(λ)

$$\begin{aligned}\delta_t &= R_{t+1} + \gamma \hat{v}(S_{t+1}, \mathbf{w}) - \hat{v}(S_t, \mathbf{w}) \\ E_t &= \gamma \lambda E_{t-1} + \mathbf{x}(S_t) \\ \Delta \mathbf{w} &= \alpha \delta_t E_t\end{aligned}$$

TD(λ) with Value Function Approximation

```
Initialize  $\mathbf{w}$  as appropriate for the problem, e.g.,  $\mathbf{w} = \mathbf{0}$ 
Repeat (for each episode):
   $\mathbf{z} = \mathbf{0}$ 
   $S \leftarrow$  initial state of episode
  Repeat (for each step of episode):
     $A \leftarrow$  action given by  $\pi$  for  $S$ 
    Take action  $A$ , observe reward,  $R$ , and next state,  $S'$ 
     $\delta \leftarrow R + \gamma \hat{v}(S', \mathbf{w}) - \hat{v}(S, \mathbf{w})$ 
     $\mathbf{z} \leftarrow \gamma \lambda \mathbf{z} + \nabla_{\mathbf{w}} \hat{v}(S, \mathbf{w})$ 
     $\mathbf{w} \leftarrow \mathbf{w} + \alpha \delta \mathbf{z}$ 
     $S \leftarrow S'$ 
  until  $S'$  is terminal
```

Convergence of Prediction Algorithms

On/Off-Policy	Algorithm	Table Lookup	Linear	Non-Linear
On-Policy	MC	✓	✓	✓
	TD(0)	✓	✓	✗
	TD(λ)	✓	✓	✗
Off-Policy	MC	✓	✓	✓
	TD(0)	✓	✗	✗
	TD(λ)	✓	✗	✗


See Baird's counter-example (in the textbook) which shows the divergence of TD algorithm

Gradient TD algorithm resolved the divergence problem. See paper "Fast Gradient-Descent Methods for Temporal-Difference Learning with Linear Function Approximation" by Richard Sutton etc.

Outline

- Introduction & Preliminaries
- RL Prediction with Function Approximation
- **RL Control with Function Approximation**
- Batch Method for RL Applications

RL Control



Policy evaluation **Approximate** policy evaluation, $\hat{q}(\cdot, \cdot, \mathbf{w}) \approx q_\pi$

Policy improvement ϵ -greedy policy improvement

Action-value Function Approximation

- Approximate the action-value function

$$\hat{q}(S, A, \mathbf{w}) \approx q_\pi(S, A)$$

- Minimise mean-squared error between approximate action-value fn $\hat{q}(S, A, \mathbf{w})$ and true action-value fn $q_\pi(S, A)$

$$J(\mathbf{w}) = \mathbb{E}_\pi [(q_\pi(S, A) - \hat{q}(S, A, \mathbf{w}))^2]$$

- Use stochastic gradient descent to find a local minimum

$$-\frac{1}{2} \nabla_{\mathbf{w}} J(\mathbf{w}) = (q_\pi(S, A) - \hat{q}(S, A, \mathbf{w})) \nabla_{\mathbf{w}} \hat{q}(S, A, \mathbf{w})$$

$$\Delta \mathbf{w} = \alpha (q_\pi(S, A) - \hat{q}(S, A, \mathbf{w})) \nabla_{\mathbf{w}} \hat{q}(S, A, \mathbf{w})$$

Linear Action-value Function Approximation

- Represent state *and* action by a *feature vector*

$$\mathbf{x}(S, A) = \begin{pmatrix} \mathbf{x}_1(S, A) \\ \vdots \\ \mathbf{x}_n(S, A) \end{pmatrix}$$

- Represent action-value fn by linear combination of features

$$\hat{q}(S, A, \mathbf{w}) = \mathbf{x}(S, A)^\top \mathbf{w} = \sum_{j=1}^n \mathbf{x}_j(S, A) \mathbf{w}_j$$

- Stochastic gradient descent update

$$\nabla_{\mathbf{w}} \hat{q}(S, A, \mathbf{w}) = \mathbf{x}(S, A)$$

$$\Delta \mathbf{w} = \alpha (q_\pi(S, A) - \hat{q}(S, A, \mathbf{w})) \mathbf{x}(S, A)$$

RL Control with Value Approximation

- For MC, the target is the return G_t

$$\Delta \mathbf{w} = \alpha(G_t - \hat{q}(S_t, A_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{q}(S_t, A_t, \mathbf{w})$$

- For TD(0), the target is the TD target $R_{t+1} + \gamma Q(S_{t+1}, A_{t+1})$

$$\Delta \mathbf{w} = \alpha(R_{t+1} + \gamma \hat{q}(S_{t+1}, A_{t+1}, \mathbf{w}) - \hat{q}(S_t, A_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{q}(S_t, A_t, \mathbf{w})$$

- For forward-view TD(λ), target is the action-value λ -return

$$\Delta \mathbf{w} = \alpha(q_t^\lambda - \hat{q}(S_t, A_t, \mathbf{w})) \nabla_{\mathbf{w}} \hat{q}(S_t, A_t, \mathbf{w})$$

- For backward-view TD(λ), equivalent update is

$$\delta_t = R_{t+1} + \gamma \hat{q}(S_{t+1}, A_{t+1}, \mathbf{w}) - \hat{q}(S_t, A_t, \mathbf{w})$$

$$E_t = \gamma \lambda E_{t-1} + \nabla_{\mathbf{w}} \hat{q}(S_t, A_t, \mathbf{w})$$

$$\Delta \mathbf{w} = \alpha \delta_t E_t$$

Convergence of Control Algorithms

Algorithm	Table Lookup	Linear	Non-Linear
Monte-Carlo Control	✓	(✓)	✗
Sarsa	✓	(✓)	✗
Q-learning	✓	✗	✗

(✓) = chatters around near-optimal value function

Outline

- Introduction & Preliminaries
- RL Prediction with Function Approximation
- RL Control with Function Approximation
- Batch Method for RL Applications

Motivation

- Gradient descent is simple and appealing
- But it is *not* sample efficient
- Batch methods seek to find the best fitting value function
- Given the agent's experience (“training data”)

Least Square Prediction

- Given value function approximation $\hat{v}(s, \mathbf{w}) \approx v_\pi(s)$
- And *experience* \mathcal{D} consisting of $\langle \text{state}, \text{value} \rangle$ pairs

$$\mathcal{D} = \{ \langle s_1, v_1^\pi \rangle, \langle s_2, v_2^\pi \rangle, \dots, \langle s_T, v_T^\pi \rangle \}$$

- Which parameters \mathbf{w} give the *best fitting* value fn $\hat{v}(s, \mathbf{w})$?
- **Least squares** algorithms find parameter vector \mathbf{w} minimising sum-squared error between $\hat{v}(s_t, \mathbf{w})$ and target values v_t^π ,

$$\begin{aligned} LS(\mathbf{w}) &= \sum_{t=1}^T (v_t^\pi - \hat{v}(s_t, \mathbf{w}))^2 \\ &= T \mathbb{E}_{\mathcal{D}} [(v^\pi - \hat{v}(s, \mathbf{w}))^2] \end{aligned}$$

Experience Replay

- Given experience consisting of $\langle state, value \rangle$ pairs

$$\mathcal{D} = \{ \langle s_1, v_1^\pi \rangle, \langle s_2, v_2^\pi \rangle, \dots, \langle s_T, v_T^\pi \rangle \}$$

- Repeat:
 - Sample state, value from experience

$$\langle s, v^\pi \rangle \sim \mathcal{D}$$

- Apply stochastic gradient descent update

$$\Delta \mathbf{w} = \alpha (v^\pi - \hat{v}(s, \mathbf{w})) \nabla_{\mathbf{w}} \hat{v}(s, \mathbf{w})$$

- Converges to least squares solution

$$\mathbf{w}^\pi = \underset{\mathbf{w}}{\operatorname{argmin}} LS(\mathbf{w})$$

Experience Replay in Deep Q-Network (DQN)

DQN uses **experience replay** and **fixed Q-targets**


- Take action a_t according to ϵ -greedy policy
- Store transition $(s_t, a_t, r_{t+1}, s_{t+1})$ in replay memory \mathcal{D}
- Sample random mini-batch of transitions (s, a, r, s') from \mathcal{D}
- Compute Q-learning targets w.r.t. old, fixed parameters w^-
- Optimise MSE between Q-network and Q-learning targets

$$\mathcal{L}_i(w_i) = \mathbb{E}_{s,a,r,s' \sim \mathcal{D}_i} \left[\left(r + \gamma \max_{a'} Q(s', a'; w_i^-) - Q(s, a; w_i) \right)^2 \right]$$

- Using variant of stochastic gradient descent

DQN in Atari Games

- End-to-end learning of values $Q(s, a)$ from pixels s
- Input state s is stack of raw pixels from last 4 frames
- Output is $Q(s, a)$ for 18 joystick/button positions
- Reward is change in score for that step



Network **architecture** and **hyperparameters** do not change across games

See paper “Human-level control through deep reinforcement learning” Nature, 2015