

WISDM Smartphone and Smartwatch Activity and Biometrics Dataset

By

Chenye Yang

Bingzhao Wang

Zhuoyue Xing

Data Set:

WISDM Smartphone and Smartwatch
Activity and Biometrics Data Set

Paper:

Smartphone and Smartwatch-Based
Biometrics Using Activities of Daily
Living

Introduction



Background and application area

Biometric identifiers:

Unique physical or behavioral characteristics of people.

Used to distinguish an Individual (identification or authentication).

Can't be stolen, unlike password or ID card.

Physical biometric methods use

physiological identifiers like fingerprints, face, iris and DNA.

Sometimes hard to use.

Behavioral biometric methods use

behavioral identifiers like walking, handwaving, signature and voice.

Related to daily life and can be measured by common device.

Single identifier:

Gait: vision-based, floor-based, and wearable sensor-base

Soft touchscreen gestures like tap and drag

Soft keystroke gestures like duration and pressure

Sound properties

Gestures when people writing specific words or their signatures

More than one identifiers:

a few identifiers: walking, standing, jogging, sitting and running

Only smartphone as the measurement device

Problems considered

Importance of evaluating daily identifiers:

Find a base behavioral identifier which can be used individually to build a biometric system for identification or authentication.

Build a biometric system which uses normal daily behavioral identifiers to do identification or authentication.

E.g.

The daily behavioral data collected by smartphone can be used to secure the smartphone, or secure other devices like cars and house.

The paper we choose:

Analyzed 18 normal daily activities for behavioral biometric methods, and used the accelerometer and gyroscope sensors on smartphone and smartwatch to do identification and authentication.

Problems focused:

1. The value of smartphone, smartwatch and their combination for behavioral biometric methods.
2. The choose of accelerometer and gyroscope sensors on smartphone and smartwatch.
3. The performance of behavioral biometric methods for identification and authentication.
4. The performance of daily behavioral identifiers for biometric system.
5. The amount of training data.

Data Set and Paper



Data in detail

The "WISDM Smartphone and Smartwatch Activity and Biometrics Data Set" is collected by Wireless Sensor Data Mining (WISDM) Lab in the Department of Computer and Information Science of Fordham University.

Table 1: Summary Information about Data Set [26]

Attribute	Value
Number of subjects	51
Number of activities	18
Minutes collected per activity	3
Sensor polling rate	20Hz
Smartphone used	Google Nexus 5/5x or Samsung Galaxy S5
Smartwatch used	LG G Watch
Number raw measurements	15,630,426

Table 2: Activities and Their Codes [26]


Activity	Code	Activity	Code	Activity	Code
Walking	A	Brushing Teeth	G	Kicking (Soccer Ball)	M
Jogging	B	Eating Soup	H	Playing Catch w/Tennis Ball	O
Stairs	C	Eating Chips	I	Dribbling (Basketball)	P
Sitting	D	Eating Pasta	J	Writing	Q
Standing	E	Drinking from Cup	K	Clapping	R
Typing	F	Eating Sandwich	L	Folding Clothes	S

Raw sensor data format:

< Subject ID, Activity Code, Timestamp, x, y, z >
 1608,A,11154584427476,4.319275,9.2408905,-0.77568054;

Table 3: Definition of Elements in Raw Data Measurements [26]

Field Name	Description
Subject ID	Integer. Uniquely identifies the subject. Range: 1600-1650.
Activity Code	Letter. Identifies a specific activity listed in Table 2. Range: A-S (no "N")
Timestamp	Integer. Unix time
x/y/z	Real. Sensor value for x/y/z axis. May be positive or negative.




Data in detail

Time-series data



Labeled examples



Periodic:

Use 10 second data (200 items) to form a new example with 92 features and 1 label.

Labeled example data format:

Table 4: Definition of Elements in Arff Data [26]

Features	Description
ACTIVITY	The activity performed using one of the activity codes from Table 2
X{0-9}; Y{0-9}, Z{0-9}	The distribution of values over the x, y, and z axes
{X,Y,Z}AVG	Average sensor value over the window
{X,Y,Z}PEAK	Time in milliseconds between the peaks in the wave associated with most activities
{X,Y,Z}ABSOLDEV	Average absolute difference between each of the 200 readings and the mean of those values
{X,Y,Z}STANDDEV	Standard deviation of the 200 values
{X,Y,Z}VAR	Variance of the values
XMFCF{0-12}, YMFCF{0-12}, ZMFCF{0-12}	MFCCs represent short-term power spectrum of a wave
{XY, XZ, YZ}COS	The cosine distances between sensor values for pairs of axes
{XY, XZ, YZ}COR	The correlation between sensor values for pairs of axes
RESULTANT	Average resultant value, computed by squaring each matching x, y, and z value, summing them, taking the square root, and then averaging these values over the 200 readings
Class	Subject ID

What was done in paper

Authentication:

The authentication task involves distinguishing an authorized subject from an imposter. Hence authentication is a classification problem involving two classes.

Training set:

Authorized subject	Other subject
90 seconds	270 seconds

Testing set:

The unauthorized subject data not overlap with that in training set.

Performance evaluation:

Equal Error Rate (EER)/Accuracy

Identification:

Each subject represents a different class—for the identification data set there are fifty-one classes.

Training set:

The training set must have data from all subjects.

Testing set:

Partitioned using 10-fold cross validation

Statistical tools used in paper

Classification Algorithm:

K-NN

K = 5

Uniform weights

Minkowski distance

Decision Tree

Random Forest

Maximum number of features considered is the square root of the number of features in the data

Number of decision trees in the forest is set to 10

Data set partition:

10-fold cross validation

Reproduce Result



Subject Authentication

Subject authentication is **a two-class task** which judges whether the activity data is from the person we select.

Three approaches to classification: **K Nearest Neighbor, Decision Tree** and **Random Forest**.

The paper shows results of the best algorithm (Random Forest) with 9 sensor combinations per activity and in average.

We reproduce results of all three algorithms.

Subject Authentication

Reproduced result using Random Forest

Activity Code	Accel Phone	Gyro Phone	Accel Watch	Gyro Watch	Phone	Watch	Accel	Gyro	All
A	86.1	89.2	87.5	75.0	82.5	84.9	87.5	84.6	86.0
B	92.8	83.1	84.4	79.2	89.7	82.8	91.8	82.9	87.9
C	97.8	83.1	88.9	85.3	90.6	83.1	88.8	80.4	85.2
D	77.5	85.8	86.1	83.1	85.6	84.7	89.2	77.9	85.2
E	86.7	84.2	88.6	82.2	88.9	80.0	92.2	82.5	87.7
F	91.7	84.2	89.7	82.8	91.3	84.2	80.0	80.0	85.0
G	96.4	78.9	90.3	77.5	90.1	84.3	86.9	77.5	87.7
H	90.3	88.3	87.2	80.3	88.8	82.8	87.1	80.0	87.3
I	90.8	86.7	84.7	82.8	88.9	82.8	89.3	80.0	86.9
G	85.8	84.7	83.6	83.1	87.2	86.4	85.3	79.2	86.3
K	96.1	83.1	81.7	80.8	84.0	85.8	86.9	80.0	89.4
L	99.2	84.2	85.0	75.0	91.9	83.1	92.5	79.6	86.5
M	91.1	86.9	89.2	83.3	87.8	86.5	87.9	79.2	87.1
O	91.1	86.4	86.9	80.6	84.4	83.6	86.7	77.9	86.3
P	96.7	86.9	87.2	82.5	91.8	83.2	86.0	80.0	84.0
Q	97.2	78.3	88.6	80.6	92.8	83.1	90.7	85.8	86.0
R	96.7	85.6	81.7	75.0	83.9	83.6	92.1	80.0	86.3
S	95.6	86.7	90.0	77.5	89.0	83.8	90.7	82.5	86.5

Subject Authentication

Reproduced result using K Nearest Neighbor

Activity Code	Accel Phone	Gyro Phone	Accel Watch	Gyro Watch	Phone	Watch	Accel	Gyro	All
A	80.8	80.0	80.8	71.9	80.0	74.7	82.2	76.1	81.3
B	84.4	77.8	81.1	74.2	83.6	79.0	88.8	75.3	81.0
C	91.1	79.4	79.7	76.9	81.5	79.6	86.4	75.0	80.4
D	82.8	83.9	83.1	76.1	79.6	74.4	85.4	75.1	81.8
E	82.5	79.7	84.2	78.3	85.0	73.5	89.0	76.9	78.5
F	86.4	74.7	79.2	70.8	81.0	77.5	81.0	76.8	78.5
G	93.1	70.6	82.2	72.5	79.6	78.2	81.8	75.8	78.8
H	77.2	76.1	83.3	71.4	81.1	76.4	84.0	77.1	82.5
I	81.4	75.8	78.9	67.5	81.1	77.6	82.2	73.8	80.5
G	81.4	82.8	78.1	74.7	82.2	78.6	82.1	74.2	80.8
K	93.1	76.7	75.6	76.9	72.9	74.2	80.8	77.2	80.8
L	93.1	78.3	78.9	75.3	85.0	78.1	86.8	77.6	82.5
M	90.3	76.1	85.6	77.2	84.6	76.4	84.7	76.1	80.0
O	83.9	79.4	80.6	75.0	80.8	74.6	80.8	77.9	78.6
P	95.3	78.3	79.7	72.8	82.9	78.1	86.9	73.1	79.0
Q	93.9	70.0	79.2	75.6	86.7	77.8	85.8	73.8	79.4
R	94.2	82.2	77.8	76.9	77.2	79.9	85.6	75.4	79.7
S	89.2	73.6	81.1	70.6	80.8	78.3	86.3	77.1	78.3

Subject Authentication

Reproduced result using Decision Tree

Activity Code	Accel Phone	Gyro Phone	Accel Watch	Gyro Watch	Phone	Watch	Accel	Gyro	All
A	82.8	75.0	80.3	75.0	81.9	75.0	78.1	75.0	77.6
B	85.3	81.7	78.9	75.0	79.2	73.5	79.9	76.8	77.8
C	90.6	72.8	75.0	75.0	86.0	75.0	82.5	80.0	77.6
D	78.1	78.1	82.8	75.0	75.8	75.0	79.2	75.0	76.7
E	81.9	76.1	81.1	75.0	85.1	75.0	80.8	75.0	78.3
F	87.2	79.2	77.5	75.0	81.4	75.0	81.4	75.0	73.8
G	96.1	78.6	80.0	75.0	81.1	75.0	79.2	76.5	77.4
H	83.1	75.0	78.6	75.0	85.4	75.0	82.5	75.0	79.0
I	87.8	78.3	75.8	75.0	81.9	78.3	80.6	75.0	78.2
G	84.4	79.7	69.7	75.0	82.4	75.0	82.2	75.6	76.8
K	96.7	71.7	78.6	75.0	81.8	75.3	76.9	76.0	77.3
L	83.3	80.8	76.1	75.0	81.1	75.0	78.1	75.0	77.6
M	85.3	76.7	77.8	75.0	81.1	75.0	80.0	75.0	76.7
O	89.7	77.5	75.0	75.0	78.2	75.0	82.9	75.0	78.8
P	91.4	84.4	79.4	75.0	81.8	75.0	78.8	75.0	76.7
Q	92.5	72.5	80.6	75.0	78.9	75.0	84.7	75.0	78.9
R	96.1	83.1	76.9	75.0	82.5	75.0	79.9	75.0	76.7
S	89.2	81.4	79.2	75.0	82.6	74.3	82.6	79.3	80.6

Subject Identification

Subject identification is **a multi-class task** which distinguishes subjects in each activity.

Three approaches to classification: **K Nearest Neighbor, Decision Tree** and **Random Forest**.

The paper shows the accuracy results of the best algorithm (Random Forest) with 9 sensor combinations per activity and in average.

We reproduce results of all three algorithms.

Subject Identification

Result from paper using Random Forest

Activity	Ac-p	Gy-p	Ac-w	Gy-w	Phone	Watch	Accel	Gyro	All
Walking	96.1	94.7	75.1	67.0	96.8	78.9	96.5	95.3	97.4
Jogging	94.7	92.5	75.0	74.3	96.0	82.1	95.7	95.2	98.0
Stairs	90.8	81.2	52.4	39.2	92.7	58.7	92.6	80.9	95.1
Sitting	90.1	56.3	70.4	30.1	91.5	69.3	93.1	55.9	92.0
Standing	85.8	47.1	64.1	27.0	86.8	61.2	90.5	46.6	89.9
Kicking	87.4	67.2	54.3	38.3	88.6	59.8	92.1	72.7	92.1
Dribbling	88.3	66.0	72.3	74.8	89.5	80.3	93.9	82.1	94.4
Catch	90.0	67.2	69.1	71.3	90.3	75.4	94.1	82.0	93.7
Typing	94.8	71.7	81.2	51.2	94.6	84.2	95.6	76.5	95.7
Writing	92.8	69.1	79.6	47.6	93.1	79.1	94.2	73.0	93.9
Clapping	94.8	72.8	83.4	73.9	93.8	85.3	96.6	86.1	96.7
Teeth	92.2	69.5	70.0	56.3	93.7	76.1	95.2	74.5	95.4
Folding	90.7	65.8	60.0	38.8	92.0	63.0	93.6	72.7	93.8
Pasta	94.1	56.9	67.2	38.1	94.0	71.6	96.6	61.1	96.3
Soup	94.3	56.5	74.1	50.4	95.8	76.6	96.3	66.9	96.6
Sandwich	92.9	62.8	61.9	37.6	92.6	62.1	95.9	68.5	95.2
Chips	93.3	56.8	62.6	38.7	93.2	62.4	96.0	66.3	94.9
Drinking	93.9	57.4	63.9	41.3	93.8	65.3	95.4	60.6	94.7
Avg	92.1	67.3	68.7	49.8	92.7	71.7	94.7	73.2	94.8

Subject Identification

Reproduced result using Random Forest

Activity	Ac_p	Gy_p	Ac_w	Gy_w	Phone	Watch	Accel	Gyro	All
Walking	98.5	96.1	86.3	73.1	98.9	88.6	98.8	98.9	98.8
Jogging	95.9	93.0	86.3	85.5	95.8	92.0	96.1	95.5	95.1
Stairs	93.9	83.1	71.6	49.7	94.6	78.3	95.3	94.9	94.5
Sitting	95.9	64.9	80.8	47.9	94.2	80.5	95.0	94.1	94.0
Standing	94.0	58.1	81.0	36.2	94.1	79.0	96.3	94.3	94.1
Kicking	98.3	77.5	89.3	59.3	97.3	92.2	98.2	97.7	97.6
Dribbling	96.9	77.3	81.9	63.1	95.9	81.9	96.7	96.2	96.2
Catch	96.9	64.6	86.8	64.8	96.7	90.0	97.8	96.6	96.4
Typing	97.6	65.1	80.6	47.7	96.7	84.4	97.7	96.8	96.2
Writing	97.2	64.5	84.1	50.9	97.3	87.5	98.1	97.1	97.3
Clapping	97.6	67.2	81.7	49.2	96.8	84.3	97.6	96.4	96.4
Teeth	97.1	67.0	78.9	41.6	97.3	80.1	98.0	97.0	97.0
Folding	92.2	68.3	64.1	43.7	92.9	72.1	93.8	93.9	93.7
Pasta	96.1	69.4	82.3	81.6	96.2	88.9	97.8	95.7	95.6
Soup	96.9	68.2	87.0	86.6	97.1	92.6	98.4	97.2	96.9
Sandwich	95.9	78.9	88.2	66.0	94.0	89.4	94.6	93.9	94.3
Chips	97.3	76.9	90.3	86.1	96.0	93.6	97.6	96.2	96.3
Drinking	94.0	68.8	70.7	49.8	94.3	80.3	96.0	93.4	93.9
Avg	96.2	72.7	81.8	60.1	95.9	85.3	96.9	95.9	95.8

Subject Identification

Reproduced result using K Nearest Neighbor

Activity	Ac_p	Gy_p	Ac_w	Gy_w	Phone	Watch	Accel	Gyro	All
Walking	88.6	51.3	49.1	29.7	94.2	59.1	89.5	59.1	93.6
Jogging	88.1	63.8	59.2	33.1	90.3	68.0	85.9	74.3	89.1
Stairs	72.7	25.6	30.2	21.2	77.5	37.9	70.2	45.3	78.6
Sitting	87.7	30.7	60.4	22.4	76.2	55.8	85.6	44.4	74.0
Standing	70.4	24.4	47.3	18.8	60.4	44.7	76.6	38.3	62.6
Kicking	87.1	28.0	59.6	18.5	84.4	62.1	91.0	46.6	83.6
Dribbling	81.9	24.5	51.4	24.3	79.3	58.8	85.4	46.4	82.2
Catch	86.3	20.4	50.4	22.0	73.9	57.8	88.5	41.0	72.7
Typing	82.9	24.5	52.8	16.7	75.8	52.8	89.5	42.1	78.3
Writing	84.8	17.9	51.9	13.7	72.4	48.9	89.1	32.2	73.0
Clapping	87.7	20.8	52.6	18.5	73.6	53.2	89.5	36.0	74.6
Teeth	85.8	24.1	49.8	12.0	75.7	45.9	88.3	39.3	77.5
Folding	73.2	20.1	26.7	14.4	72.9	32.2	68.8	37.0	72.8
Pasta	80.0	26.5	51.3	21.2	77.0	49.9	82.8	47.0	76.3
Soup	79.7	27.6	55.6	31.6	80.7	61.3	88.0	59.3	80.5
Sandwich	88.1	30.5	58.1	16.8	85.6	55.4	90.4	41.6	85.1
Chips	87.2	25.1	79.3	43.2	83.3	83.3	94.1	57.9	83.3
Drinking	80.3	24.6	42.2	13.8	78.0	40.2	80.6	39.3	78.3
Avg	82.9	28.4	51.5	21.8	78.4	53.7	85.2	45.9	78.7

Subject Identification

Reproduced result using Decision Tree

Activity	Ac_p	Gy_p	Ac_w	Gy_w	Phone	Watch	Accel	Gyro	All
Walking	92.9	87.3	66.6	53.9	91.9	69.3	89.9	86.0	91.7
Jogging	89.7	83.4	62.8	63.3	88.8	70.3	87.6	82.3	89.4
Stairs	84.8	60.3	44.8	30.6	85.5	46.1	83.2	61.1	85.1
Sitting	94.1	49.6	75.6	27.7	91.1	72.1	93.0	45.4	91.6
Standing	92.4	38.3	71.4	22.4	89.3	68.4	91.2	37.8	90.3
Kicking	96.8	58.3	79.3	38.3	94.8	82.6	94.3	60.5	94.6
Dribbling	95.7	58.9	62.0	48.9	92.0	60.8	92.7	65.7	93.4
Catch	95.6	46.4	72.2	43.4	93.2	73.0	95.4	51.8	93.7
Typing	96.4	43.1	59.8	26.8	94.5	61.2	92.6	47.3	94.0
Writing	93.3	42.2	67.0	29.6	94.3	66.9	93.5	44.5	94.0
Clapping	95.5	47.3	67.7	29.2	93.8	65.5	93.3	51.1	93.6
Teeth	95.9	48.1	57.3	24.1	93.4	55.7	94.3	44.6	93.6
Folding	82.2	43.4	43.8	25.0	80.2	47.1	83.9	46.9	81.1
Pasta	87.8	43.8	54.0	50.5	86.1	59.8	89.2	54.4	86.9
Soup	92.5	47.2	63.1	66.3	89.1	72.5	89.0	69.9	90.9
Sandwich	93.9	60.5	78.3	42.0	90.9	78.1	92.2	58.1	91.3
Chips	95.3	60.5	77.1	68.6	92.4	76.6	93.6	75.8	93.6
Drinking	89.2	45.9	44.4	23.3	85.8	50.3	86.3	49.7	85.0
Avg	92.4	53.6	63.7	39.7	90.4	65.4	90.8	57.4	90.8

Different Techniques



Subject Authentication

Using Support Vector Machine to identify subjects

Activity Code	Accel Phone	Gyro Phone	Accel Watch	Gyro Watch	Phone	Watch	Accel	Gyro	All
A	89.7	80.3	83.6	75.6	81.7	72.5	84.6	75.0	77.7
B	89.2	78.6	84.4	75.3	79.2	70.4	75.0	73.8	76.9
C	88.9	76.9	78.9	76.7	79.6	74.2	79.2	76.7	75.8
D	81.1	76.7	85.0	76.9	75.0	72.5	79.6	74.6	78.3
E	87.5	75.6	89.2	75.8	79.6	74.2	83.8	74.2	76.5
F	88.1	78.3	80.8	73.9	70.4	69.6	78.8	75.0	78.8
G	96.9	70.6	85.0	73.3	71.7	69.2	82.5	70.0	78.3
H	89.2	80.6	84.2	76.4	78.8	75.4	84.6	75.0	77.5
I	91.4	75.3	82.5	73.6	77.5	71.3	81.3	73.3	76.3
G	83.9	77.8	80.0	75.0	77.9	70.8	83.8	74.2	72.5
K	94.4	77.8	72.5	76.9	81.3	71.7	77.5	72.5	77.7
L	91.7	71.7	84.2	75.0	85.8	78.8	77.9	72.1	75.4
M	89.4	77.2	83.9	78.3	82.1	70.8	76.3	72.9	78.3
O	89.4	79.4	82.2	74.4	76.7	67.1	84.6	69.6	77.7
P	95.8	76.7	77.8	74.7	81.3	78.8	79.2	75.0	76.5
Q	96.7	65.6	84.4	75.0	82.5	69.2	85.0	75.0	77.5
R	91.9	71.1	83.1	75.0	79.6	72.5	78.3	70.8	80.2
S	90.8	75.3	81.9	70.0	76.3	72.5	77.5	75.0	76.7

Subject Identification

Using Support Vector Machine to identify subjects

Activity	Ac_p	Gy_p	Ac_w	Gy_w	Phone	Watch	Accel	Gyro	All
Walking	98.2	74.7	89.1	48.3	95.6	74.2	98.6	77.8	96.0
Jogging	96.3	77.9	89.6	60.0	92.8	82.8	96.6	83.0	93.0
Stairs	93.8	49.5	71.1	36.5	89.9	60.7	95.4	57.6	88.8
Sitting	94.9	39.7	70.1	25.9	88.5	68.1	92.5	47.9	89.0
Standing	89.4	34.4	68.2	23.2	85.8	63.8	89.4	46.4	85.8
Kicking	97.4	43.2	76.4	24.5	92.1	80.9	96.8	51.5	92.7
Dribbling	94.2	37.1	80.0	42.8	87.7	71.1	93.1	56.5	88.5
Catch	96.3	31.8	73.6	32.5	90.9	74.8	95.2	50.3	91.8
Typing	95.8	37.2	65.1	26.3	90.6	71.6	95.0	46.5	92.6
Writing	96.6	32.8	74.3	27.1	90.7	72.3	96.5	43.3	90.5
Clapping	96.2	34.8	70.6	22.4	91.1	70.2	95.6	43.5	91.7
Teeth	94.1	39.4	61.9	21.2	91.5	64.4	95.0	44.0	92.1
Folding	91.9	33.7	65.5	33.3	85.8	55.3	92.7	49.7	85.3
Pasta	95.3	36.9	84.0	53.4	88.5	68.9	98.1	57.5	89.3
Soup	96.3	38.3	89.2	64.5	87.6	78.6	98.3	70.3	88.9
Sandwich	93.8	44.2	81.3	23.7	90.4	74.0	92.9	49.7	90.9
Chips	95.9	37.9	90.7	56.9	93.3	85.3	97.1	66.1	93.1
Drinking	93.1	32.4	74.2	27.0	87.3	62.8	93.3	47.7	87.0
Avg	95.0	42.0	76.4	36.1	90.0	71.1	95.1	55.0	90.4

Discussion and Conclusion



Compare results of different techniques

K Nearest Neighbors

- **High interpretability**
- **Rather fast**
- **Relatively low accuracy**

Decision Tree

- **High interpretability**
- **Rather fast**
- **Unstable with small change in data**

Random Forest

- **More time-consuming to train**
- **Covariance reducing**
- **High accuracy**

Support Vector Machine

- **Not easy to interpret**
- **Not good performance in multi-class classification**

Method	Ac_p	Gy_p	Ac_w	Gy_w	Phone	Watch	Accel	Gyro	All
KNN	82.9	51.5	28.4	21.8	78.4	53.7	85.2	45.9	78.7
Tree	92.4	63.7	53.6	39.7	90.4	65.4	90.8	57.4	90.8
RF	96.2	81.8	72.7	60.1	95.9	85.3	96.9	95.9	95.8
SVM	95.0	42.0	76.4	36.1	90.0	71.1	95.1	55.0	90.4

Average accuracy among 18 activities with different method

Future work

Try different parameters of K-NN, Decision Tree, Random Forest, SVM.

Try other statistical learning techniques.

Try different feature extraction methods for time-series data.

Reference

- [1] A. Jain, L. Hong, and S. Pankanti, "Biometric identification," *Communications of the ACM*, vol. 43, no. 2, pp. 90–98, 2000.
- [2] A. Jain, R. Bolle, and S. Pankanti, "Introduction to biometrics," in *Biometrics*, pp. 1–41, Springer, 1996.
- [3] L. O’Gorman, "Comparing passwords, tokens, and biometrics for user authentication," *Proceedings of the IEEE*, vol. 91, pp. 2021–2040, Dec 2003.
- [4] K. Delac and M. Grgic, "A survey of biometric recognition methods," in *Proceedings. Elmar-2004. 46th International Symposium on Electronics in Marine*, pp. 184–193, IEEE, 2004.
- [5] A. K. Jain and A. Kumar, "Biometric recognition: an overview," in *Second generation biometrics: The ethical, legal and social context*, pp. 49–79, Springer, 2012.
- [6] I. Bouchrika, "A survey of using biometrics for smart visual surveillance: Gait recognition," In *Surveillance in Action*, pp. 3–23, Springer, 2018.
- [7] R. Cappelli, D. Maio, D. Maltoni, J. L. Wayman, and A. K. Jain, "Performance evaluation of fingerprint verification systems," *IEEE transactions on pattern analysis and machine intelligence*, vol. 28, no. 1, pp. 3–18, 2005.
- [8] G. M. Weiss, K. Yoneda, and T. Hayajneh, "Smartphone and smartwatch-based biometrics using activities of daily living," *IEEE Access*, vol. 7, pp. 133190–133202, 2019.
- [9] A. Alzubaidi and J. Kalita, "Authentication of smartphone users using behavioral biometrics," *IEEE Communications Surveys Tutorials*, vol. 18, pp. 1998–2026, thirdquarter 2016.
- [10] D. Gafurov, "A survey of biometric gait recognition: Approaches, security and challenges," in *Annual Norwegian computer science conference*, pp. 19–21, Annual Norwegian Computer Science Conference Norway, 2007.
- [11] M. O. Derawi, C. Nickel, P. Bours, and C. Busch, "Unobtrusive user-authentication on mobile phones using biometric gait recognition," in *2010 Sixth International Conference on Intelligent Information Hiding and Multimedia Signal Processing*, pp. 306–311, Oct 2010.
- [12] C. Nickel, H. Brandt, and C. Busch, "Benchmarking the performance of svms and hmms for accelerometer-based biometric gait recognition," in *2011 IEEE International Symposium on Signal Processing and Information Technology (ISSPIT)*, pp. 281–286, Dec 2011.
- [13] F. Juefei-Xu, C. Bhagavatula, A. Jaech, U. Prasad, and M. Savvides, "Gait-id on the move: Pace independent human identification using cell phone accelerometer dynamics," in *2012 IEEE Fifth International Conference on Biometrics: Theory, Applications and Systems (BTAS)*, pp. 8–15, Sep. 2012.
- [14] T. Hoang, T. D. Nguyen, C. Luong, S. Do, and D. Choi, "Adaptive cross-device gait recognition using a mobile accelerometer.," *JIPS*, vol. 9, no. 2, p. 333, 2013.
- [15] A. H. Johnston and G. M. Weiss, "Smartwatch-based biometric gait recognition," in *2015 IEEE 7th International Conference on Biometrics Theory, Applications and Systems (BTAS)*, pp. 1–6, Sep. 2015.
- [16] N. Al-Naffakh, N. Clarke, F. Li, and P. Haskell-Dowland, "Unobtrusive gait recognition using smartwatches," in *2017 International Conference of the Biometrics Special Interest Group (BIOSIG)*, pp. 1–5, Sep. 2017.
- [17] G. Cola, M. Avvenuti, F. Musso, and A. Vecchio, "Gait-based authentication using a wrist-worn device," in *Proceedings of the 13th International Conference on Mobile and Ubiquitous Systems: Computing, Networking and Services, MOBIQUITOUS 2016, (New York, NY, USA)*, pp. 208–217, ACM, 2016.
- [18] T. Feng, Z. Liu, K.-A. Kwon, W. Shi, B. Carburnar, Y. Jiang, and N. Nguyen, "Continuous mobile authentication using touchscreen gestures," in *2012 IEEE Conference on Technologies for Homeland Security (HST)*, pp. 451–456, IEEE, 2012.
- [19] B. Draffin, J. Zhu, and J. Zhang, "Keysens: Passive user authentication through micro-behavior modeling of soft keyboard interaction," in *Mobile Computing, Applications, and Services (G. Memmi and U. Blanke, eds.), (Cham)*, pp. 184–201, Springer International Publishing, 2014.
- [20] A. Buriro, B. Crispo, F. Del Frari, and K. Wrona, "Touchstroke: Smartphone user authentication based on touch-typing biometrics," in *International Conference on Image Analysis and Processing*, pp. 27–34, Springer, 2015.
- [21] M. Kunz, K. Kasper, H. Reininger, M. Möbius, and J. Ohms, "Continuous speaker verification in realtime," *BIOSIG 2011–Proceedings of the Biometrics Special Interest Group*, 2011.
- [22] Y. Yang, F. Hong, Y. Zhang, and Z. Guo, "Person authentication using finger snapping—anew biometric trait," in *Chinese Conference on Biometric Recognition*, pp. 765–774, Springer, 2016.
- [23] F. Ciuffo and G. M. Weiss, "Smartwatch-based transcription biometrics," in *2017 IEEE 8th Annual Ubiquitous Computing, Electronics and Mobile Communication Conference (UEM-CON)*, pp. 145–149, Oct 2017.
- [24] J. R. Kwapisz, G. M. Weiss, and S. A. Moore, "Cell phone-based biometric identification," in *2010 Fourth IEEE International Conference on Biometrics: Theory, Applications and Systems (BTAS)*, pp. 1–7, Sep. 2010.
- [25] M. Ehatishamul Haq, M. A. Azam, J. Loo, K. Shuang, S. Islam, U. Naeem, and Y. Amin, "Authentication of smartphone users based on activity recognition and mobile sensing," *Sensors*, vol. 17, no. 9, p. 2043, 2017.
- [26] D. Dheeru and E. K. Taniskidou, "Uci machine learning repository." <http://archive.ics.uci.edu/ml/>, 2017. Accessed: 2019-12-16.
- [27] D. Dheeru and E. K. Taniskidou, "Uci machine learning repository." <http://archive.ics.uci.edu/ml/>, 2017. Accessed: 2019-12-16.

Thank you!

Q & A