



HW-6239

RIKEN KEIKI Sensor Specification



This sensor utilizes calorific values when combustible gases burn on the oxidation catalyst. Combustible gas and vapor mixed with air can be detected up to lower explosive limit (LEL). This sensor has in principle a sensitivity for almost combustible gas and vapor.

Storage

Temperature Range	0 to +35 °C	Humidity Range	85%RH or less
-------------------	-------------	----------------	---------------

Key Features

- Quick response
- Excellent accuracy and reproducibility
- Excellent long-term stability
- No significant effect against pressure, temperature and humidity in the surrounding atmosphere.

Applications

Site	Petro chemical plant	Gas storage and consumption facilities	Utility tunnel
			

Products



SD-1 GP



SD/GD-D58 series



GD-A80




Technical Specifications

Model sensor	HW-6239
Gas detection	Methane (CH4)
Detection range	0 - 100.0 %LEL
Accuracy *	Less than ±2.0% LEL
Responses time (T90) *	Less than 20 sec
Repeatability @ 50% *	1.0% LEL
Adjustment gas	CH4 50%LEL
Sensor life **	5 years
Operating temperature	-20~60°C(non-rapidly-vary)
Operating humidity	Less than 95%RH(non-condensing)

* The test results were performed based on the test methods specified in the IEC/EN 60079-29-1 standard

** Actual device performance and expected lifespan depend on operating conditions and strict adherence to manufacturer's recommended maintenance.

Dimension



View

Top

Bottom

Unit: mm



RIKEN VIET
GAS DETECTOR TECHNOLOGY CO., LTD
ISO/IEC 17025:2017 (VLAC 1.0271)

Tel (+84) 28 3526 2986
Email info@rikenviet.vn
Web https://rikenviet.vn



Hotline
(+84) 961 55 69 05
Scan code to contact
(Zalo, WhatsApp, LinkedIn,...)

Cautions

- ❖ This document is compiled based on special documentation provided by Riken Keiki to Riken Viet.
- ❖ This document is the property of Riken Viet. Any misuse or copying without Riken Viet's consent is illegal.