

Accelerator Programming with OpenMP



 In a perfect world we would like the OpenMP work-sharing directives to automatically run on an accelerator

```
#include <stdio.h>
#include <stdlib.h>
int main(int argc, char **argv) {
  const int n = 100;
  double *a = (double *) malloc(n * sizeof(double));
  double *b = (double *) malloc(n * sizeof(double));
  double *c = (double *) malloc(n * sizeof(double));
  for (int i = 0; i < n; i++) {
    a[i] = 1 + i;
    b[i] = 1 - i;
#pragma omp parallel for
  for (int i = 0; i < n; i++)
    c[i] = a[i] + b[i];
  for (int i = 0; i < 5; i++) {
    printf("c[\%d] = \%g\n", i, c[i]);
  printf("c[%d] = %g\n", n-1, c[n-1]);
  free(a);
  free(b);
  free(c);
```



 In a perfect world we would like the OpenMP work-sharing directives to automatically run on an accelerator

```
#include <stdio.h>
#include <stdlib.h>
int main(int argc, char **argv) {
  const int n = 100;
  double *a = (double *) malloc(n * sizeof(double));
  double *b = (double *) malloc(n * sizeof(double));
  double *c = (double *) malloc(n * sizeof(double));
  for (int i = 0; i < n; i++) {
   a[i] = 1 + i;
   b[i] = 1 - i;
#pragma omp parallel for
  for (int i = 0; i < n; i++) {
   c[i] = a[i] + b[i];
  for (int i = 0; i < 5; i++) {
    printf("c[\%d] = \%g\n", i, c[i]);
  printf("c[%d] = %g\n", n-1, c[n-1]);
 free(a);
 free(b);
 free(c);
```

Device

SOH



- In a perfect world we would like the OpenMP work-sharing directives to automatically run on an accelerator
- OpenMP offload constructs are a set of directives for C/C++ and Fortran to offload work to an accelerator

 The target construct offloads the enclosed code to the accelerator and map transfers data

But how is it executed?

```
int main(int argc, char **argv) {
  const int n = 100;
  double *a = (double *) malloc(n * sizeof(double));
  double *b = (double *) malloc(n * sizeof(double));
  double *c = (double *) malloc(n * sizeof(double));
  for (int i = 0; i < n; i++) {
    a[i] = 1 + i;
    b[i] = 1 - i:
#pragma omp target map(a[0:n],b[0:n],c[0:n])
  for (int i = 0; i < n; i++) {
    c[i] = a[i] + b[i];
  for (int i = 0; i < 5; i++) {
    printf("c[\%d] = \%q \ n", i, c[i]);
  printf("c[%d] = %g\n", n-1, c[n-1]);
 free(a);
 free(b);
 free(c);
```

#include <stdio.h>

a[0:n]

b[0:n]

c[0:n]

a[0:n]

b[0:n] c[0:n] #include <stdlib.h>




- In a perfect world we would like the OpenMP work-sharing directives to automatically run on an accelerator
- OpenMP offload constructs are a set of directives for C/C++ and Fortran to offload work to an accelerator

 The target construct offloads the enclosed code to the accelerator and map transfers data

But how is it executed?

 Without additional directives expressing parallelism the kernel will run in serial!



a[0:n]

b[0:n]

c[0:n]

a[0:n]

b[0:n]


c[0:n]

```
#include <stdio.h>
#include <stdlib.h>
int main(int argc, char **argv) {
  const int n = 100;
  double *a = (double *) malloc(n * sizeof(double));
  double *b = (double *) malloc(n * sizeof(double));
  double *c = (double *) malloc(n * sizeof(double)):
  for (int i = 0; i < n; i++) {
    a[i] = 1 + i;
    b[i] = 1 - i:
#pragma omp target map(a[0:n],b[0:n],c[0:n])
  for (int i = 0; i < n; i++) {
    c[i] = a[i] + b[i]:
  for (int i = 0; i < 5; i++) {
    printf("c[\%d] = \%q \ n", i, c[i]);
  printf("c[%d] = %g\n", n-1, c[n-1]);
 free(a);
 free(b);
 free(c);
```



OpenMP offload target parallelism

Several different combinations of device execution directives (we will only cover some of them)





OpenMP offload target parallelism

- The target construct offloads the code to the accelerator
- The teams construct creates a set of teams (but still no work-sharing within the teams)
- With the distribute construct work can be distributed between teams (e.g. target teams distribute), but still no work-sharing within the teams
- Using a parallel for/do construct, work can be distributed within each team (e.g. target teams distribute parallel for/do)
- Or use the modern (OpenMP 5) construct omp target teams loop to use the full GPU (similar to the target teams distribute parallel for/do construct)



OpenMP device memory

Controlling and minimising data movement to/from the device is the most important step when optimising an OpenMP offloading program

- The map clause can be used to control data movement
- Various form of the clause:
 - map(to:list) copy data to the device when entering the region
 - map(from:list) copy data back to the host when leaving the region
 - map(tofrom:list) combination of the above to and from clause
 - map(alloc:list) allocate data when entering the region

Note: In Fortran nothing special needs to be done to move dynamically allocated memory, while in C/C++ the dimension has to be specified e.g. map(to:a[0:n])

Hint: Vendors often provide tools to show data movement, on a HPE Cray set the environment variable $CRAY_ACC_DEBUG=1$, 2 or 3



OpenMP device memory

The **target data** construct creates a data region, to keep the data on the device between different target offload regions (use **map** to control data movement)

```
!$omp target data map(a,b) <- move data to device
!$omp target
   do a lot of work on the device with a,b

do something on the host
!$omp target
   do a lot of work on the device with a,b
!$omp end target data <- move data back to host</pre>
```

Update data to/from a device using the target update to(list)/from(list) clause



References

OpenMP specifications:

http://www.openmp.org/specifications/

OpenMP API syntax reference guide

https://www.openmp.org/wp-content/uploads/OpenMPRefGuide-5.2-Web-2024.pdf