

M02 - JavaScript Fundamentals

...

Data Types

Data Types

1. Definition
2. Number
3. BigInt
4. String
5. Boolean
6. Null and Undefined
7. Object and Symbol
8. Type Conversions

Data Types

1. Definition

Data Types

1. Definition

- A value in JavaScript is always of a certain type (e.g. a string, number)
- There are eight basic data types in JavaScript:
 - **Number** for numbers of any type: integer or floating point
 - **BigInt** to represent integers of arbitrary length
 - **String** for texts. Can have one or more characters, there is no separate single character type
 - **Boolean** for true/false
 - **null** for unknown values: an independent type that has a single null value
 - **undefined** for unassigned values: an independent type that has a single undefined value
 - **Object** for more complex data structures
 - **Symbol** for unique identifiers

Data Types

1. Definition

- Type checking is done by the `typeof` operator
- Returns the type of the argument. It is useful when we want to process values of different types differently or just do a quick check.
- Supports two forms of syntax:
 - As an operator: `typeof x`
 - As a function: `typeof(x)`
- The return is a string with the type name

```
typeof undefined; // "undefined"  
typeof 0; // "number"  
typeof true; // "boolean"  
typeof "foo"; // "string"  
typeof Symbol("id"); // "symbol"  
typeof Math; // "object" (built-in object)  
typeof null; // "object" (JavaScript bug)  
typeof alert; // "function"
```

Data Types

2. Number

Data Types

2. Number

- The number type represents integers and floating point numbers

```
Let a = 123;  
Let b = 12.345;
```

- In addition to regular numbers, there are so-called “special numeric values” that also belong to this type of data: **Infinity**, **-Infinity** and **NaN**

Data Types

2. Number

- The **Infinity** value represents the mathematical infinity ∞ . It is a special value that is greater than any number. We can get it as a result of a division by zero:

```
console.log(1 / 0); // Infinity
console.log(Infinity); // Infinity
console.log(-1 / 0); // -Infinity
```

- The **NaN** (Not a Number) value represents a computational error - incorrect or undefined mathematical operation:

```
console.log("100" * 10); // 1000
console.log("not a number" * 2); // NaN
console.log(isNaN("ESMAD" * 3)); // true (use of the function isNaN(expr))
```


Data Types

3. BigInt

Data Types

3. BigInt

- In JavaScript, the “number” type cannot represent integer values larger than $(2^{53}-1)$ (that’s 9007199254740991), or less than $-(2^{53}-1)$ for negatives
- For most purposes that’s quite enough, but sometimes we need really big numbers, e.g. for cryptography or microsecond-precision timestamps.
- **BigInt** type represents integers of arbitrary length.
- A BigInt value is created by appending n to the end of an integer:

```
// the "n" at the end means it's a BigInt  
const bigInt = 1234567890123456789012345678901234567890n
```

Data Types

4. String

Data Types

4. String

- Used to store and manipulate text (string of alphanumeric characters)
- A **string** value can be between:
 - Double quotes: "Olá"
 - Single quotes: 'Olá'
 - Backticks: `Olá`
- There is no difference between double quotes and single quotes in JavaScript

```
let str = "Hello"  
let str2 = 'Single quotes are ok too'
```

Data Types

4. String

- **Backticks** are “extended functionality” quotes because they allow you to incorporate variables and expressions in a string, wrapping them in `${...}`

```
let name = "John"

// include a variable
alert(`Hello, ${name}!`) //Hello, John!

// include an expression
alert(`the result is ${1 + 2}`) // the result is 3
```

Data Types

5. Boolean

Data Types

5. Boolean

- The **boolean** type has only two values: **true** and **false**
- This type is commonly used to store yes/no values: true means "yes, correct" and false means "no, incorrect"

```
Let nameFieldChecked = true  
Let ageFieldChecked = false
```

- Boolean values also appear as a result of comparisons:

```
Let isGreater = 4 > 1  
alert(isGreater) // true
```

Data Types

6. Null and Undefined

Data Types

6. Null and Undefined

- Null
 - The **null** value does not belong to any of the types described previously
 - It forms a separate type that contains only the null value:

```
Let age = null
```

- It is not a “reference to a non-existent object” or “null pointer” as in other languages
- It is just a special value that represents "nothing", "empty" or "unknown value"
- The above code indicates that the age is unknown or is empty for some reason

Data Types

6. Null and Undefined

- Undefined
 - Means “unassigned value”
 - If a variable is declared, but no value is assigned, its value is undefined:

```
Let x  
console.log(x) // "undefined"
```

- Good practices:
 - use **null** to assign a value "empty" or "unknown" to a variable
 - use **undefined** to check if a value has been assigned to a variable

Data Types

7. Object and Symbol

Data Types

7. Object and Symbol

- Object
 - The **object** type is special
 - All other types are called "primitives" because their values can contain only one thing (be it a string or a number...)
 - Objects are used to store collections of data/complex entities
- Symbol
 - Special type used to create unique identifiers for objects
- Both types will be discussed later in these slides

```
let person = {  
  nam: 'John',  
  age: 32  
}
```

Data Types

8. Type Conversions

Data Types

8. Type Conversions

- Most of the time, operators and functions automatically convert the values assigned to them to the correct type. This is called **type conversion**.
- For example, the **alert** automatically converts any value to a string in order to display it. Mathematical operations convert values into numbers.
- The three most used type conversions are:
 - conversion to string
 - conversion to number
 - conversion to boolean

Data Types

8. Type Conversions

- Conversion to string
 - String conversion happens when we need the string form of a value
 - For example, `alert(value)` does this to show the value
 - We can also call the `String(value)` function to convert a value to a string:

```
let value = true
console.log(typeof value) // boolean

value = String(value) // at this point value is a string: "true"
console.log(typeof value) // string
```

Data Types

8. Type Conversions

- Conversion to number
 - Numeric conversion happens automatically in mathematical functions and expressions
 - For example, when multiplication `*` is applied to non-numbers:

```
console.log('6' * '2') // 12, strings are converted to numbers
```

- We can use the `Number(value)` function to explicitly convert a value to a number

```
let str = "123"  
console.log(typeof str) //string  
  
let num = Number(str) // variable num gets number 123  
console.log(typeof num) // number
```


Data Types

8. Type Conversions

- Conversion to number (rules)

```
console.log(Number(" 123 ")) // 123
console.log(Number("123z")) // NaN
console.log(Number(true)) // 1
console.log(Number(false)) // 0
```

Value	Result
undefined	NaN
null	0
true / false	1 / 0
string	The string is read "as is", blanks on both sides are ignored. An empty string is 0. An error gives NaN.

Data Types

8. Type Conversions

- Conversion to number
 - Almost all mathematical operations convert values into numbers.
 - A notable exception is the addition `+`. If one of added values is a string, the other is also converted to a string by joining them:

```
console.log(3 * "2") // 6  
console.log(3 + "2") // 32
```

- Using the `+` sign immediately before a string it will try to convert to number

```
console.log(typeof '3') // string  
console.log(typeof +'3') // number
```

Data Types

8. Type Conversions

- Conversion to boolean
 - In logical operations (later, we will learn about condition tests and similar things)
 - It can also be performed explicitly with the `Boolean(value)` function

```
console.log(Boolean(1)) // true  
console.log(Boolean(0)) // false
```

```
console.log(Boolean("hello")) // true  
console.log(Boolean("")) // false
```

```
console.log(Boolean("0")) // true  
console.log(Boolean(" ")) // true - any string non empty is true
```

Value	Result
0, null, undefined, NaN, ""	false
any other value	true