

Champions apunadores

Problemas

```
#include <stdio.h>
```

```
int main() {  
    int arr[] = {10, 20, 30, 40, 50};  
    int *ptr = arr;  
  
    *ptr = 100;  
    *(ptr + 2) = 300;  
    ptr[4] = 500;  
  
    return 0;  
}
```

```
#include <stdio.h>
```

```
int main() {  
    char cadena[] = "ABCDEFGHJIJ";  
    char *p = cadena;  
  
    p += 3;  
    *p = 'X';  
    p--;  
    *p = 'W';  
    p += 5;  
    *p = 'Z';  
  
    // Pregunta: ¿Qué imprimirá esto?  
    printf("%s\n", cadena);  
    printf("%c\n", *p);  
  
    return 0;  
}
```

```
#include <stdio.h>

int main() {
    int arr[] = {10, 20, 30, 40, 50};
    int *p = arr;
    *p = 100;
    *(p + 2) = 300;
    p += 4;
    *p = 500;
    p -= 3;
    *p = 200;
    printf("%d %d %d %d %d", arr[0], arr[1], arr[2], arr[3], arr[4]);
    return 0;
}

/* Resultado: 100 200 300 40 500 */
```

```
#include <stdio.h>

int main() {
    char str[] = "abcdefghij";
    char *ptr = str;
    *ptr = 'A';
    ptr += 3;
    *ptr = 'D';
    ptr += 2;
    *ptr = 'F';
    ptr--;
    *ptr = 'E';
    printf("%s", str);
    return 0;
}
/* Resultado: "AbcDeFghij" */
```

```
#include <stdio.h>

int main() {
    float nums[] = {1.1, 2.2, 3.3, 4.4, 5.5};
    float *p = nums;
    *p *= 2;
    *(p + 2) += 1.5;
    p += 4;
    *p -= 2.5;
    p -= 3;
    *p = 0.0;
    printf("%.1f %.1f %.1f %.1f %.1f", nums[0], nums[1], nums[2], nums[3], nums[4]);
    return 0;
}

/* Resultado: 2.2 0.0 4.8 4.4 3.0 */
```

```
#include <stdio.h>

int main() {
    int mat[2][2] = {{1, 2}, {3, 4}};
    int *p = &mat[0][0];
    *p = 10;
    *(p + 1) = 20;
    *(p + 2) = 30;
    *(p + 3) = 40;
    printf("%d %d\n%d %d", mat[0][0], mat[0][1], mat[1][0], mat[1][1]);
    return 0;
}

/* Resultado: 10 20 30 40 */
```

```
#include <stdio.h>

int main() {
    double vals[] = {1.5, 2.5, 3.5, 4.5};
    double *p = vals;
    *p += 0.5;
    p += 2;
    *p -= 1.0;
    p--;
    *p *= 2.0;
    p += 3;
    *p /= 1.5;
    printf("%.1f %.1f %.1f %.1f", vals[0], vals[1], vals[2], vals[3]);
    return 0;
}
/* Resultado: 2.0 5.0 2.5 3.0 */
```

```
#include <stdio.h>

int main() {
    char palabra[] = "ordenador";
    char *p = palabra;
    *p = 'O';
    p += 3;
    *p = 'D';
    p += 2;
    *p = 'N';
    p += 2;
    *p = 'R';
    printf("%s", palabra);
    return 0;
}
/* Resultado: "OrDenadNR" */
```



```
#include <stdio.h>

int main() {
    int nums[] = {1, 3, 5, 7, 9};
    int *p = nums;
    *p += 1;
    *(p + 2) *= 2;
    p += 4;
    *p -= 3;
    p -= 1;
    *p = 0;
    printf("%d %d %d %d %d", nums[0], nums[1], nums[2], nums[3], nums[4]);
    return 0;
}
/* Resultado: 2 3 10 0 6 */
```

```
#include <stdio.h>

int main() {
    float temp[] = {22.5, 23.0, 24.5, 25.0};
    float *p = temp;
    *p += 0.5;
    p += 2;
    *p -= 1.0;
    p--;
    *p = 0.0;
    p += 3;
    *p *= 2.0;
    printf("%.1f %.1f %.1f %.1f", temp[0], temp[1], temp[2], temp[3]);
    return 0;
}
/* Resultado: 23.0 0.0 23.5 50.0 */
```

```
#include <stdio.h>

int main() {
    char abc[] = "abcdefghij";
    char *p = abc;
    *p = 'A';
    p += 5;
    *p = 'F';
    p -= 2;
    *p = 'D';
    p += 4;
    *p = 'J';
    printf("%s", abc);
    return 0;
}
/* Resultado: "AbcdDfgghij" */
```

```
#include <stdio.h>

int main() {
    int datos[] = {100, 200, 300, 400};
    int *p = datos;
    *p /= 10;
    *(p + 1) += 50;
    p += 3;
    *p -= 100;
    p -= 2;
    *p *= 2;
    printf("%d %d %d %d", datos[0], datos[1], datos[2], datos[3]);
    return 0;
}

/* Resultado: 10 250 600 300 */
```

```
#include <stdio.h>

int main() {
    double medidas[] = {1.1, 2.2, 3.3, 4.4, 5.5};
    double *p = medidas;
    *p += 0.1;
    *(p + 2) -= 0.3;
    p += 4;
    *p /= 1.1;
    p -= 3;
    *p = 0.0;
    printf("%.1f %.1f %.1f %.1f %.1f", medidas[0], medidas[1], medidas[2], medidas[3], medidas[4]);
    return 0;
}

/* Resultado: 1.2 0.0 3.0 4.4 5.0 */
```

```
#include <stdio.h>

int main() {
    char frase[] = "punteros en C";
    char *p = frase;
    *p = 'P';
    p += 8;
    *p = 'E';
    p += 2;
    *p = 'C';
    p -= 5;
    *p = 'N';
    printf("%s", frase);
    return 0;
}
/* Resultado: "PunteroN En C" */
```

```
#include <stdio.h>

int main() {
    int valores[] = {5, 10, 15, 20, 25};
    int *p = valores;
    *p *= 2;
    *(p + 1) += 5;
    p += 3;
    *p -= 10;
    p--;
    *p /= 5;
    printf("%d %d %d %d %d", valores[0], valores[1], valores[2], valores[3], valores[4]);
    return 0;
}
/* Resultado: 10 15 3 10 25 */
```

```
#include <stdio.h>

int main() {
    float notas[] = {4.5, 6.0, 7.5, 9.0};
    float *p = notas;
    *p += 0.5;
    *(p + 2) -= 1.0;
    p += 3;
    *p /= 3.0;
    p -= 2;
    *p = 0.0;
    printf("%.1f %.1f %.1f %.1f", notas[0], notas[1], notas[2], notas[3]);
    return 0;
}
/* Resultado: 5.0 0.0 6.5 3.0 */
```



```
#include <stdio.h>

int main() {
    char palabra[] = "ejercicios";
    char *p = palabra;
    *p = 'E';
    p += 3;
    *p = 'R';
    p += 2;
    *p = 'I';
    p += 2;
    *p = 97;
    printf("%s", palabra);
    return 0;
}
/* Resultado: "EjeRcIciOs" */
```