

Course 1: Introduction to Some Computational Concepts

Yasuyuki Sawada, Yaolang Zhong

University of Tokyo

October 1, 2025

The Economics of Computation

- ▶ Idea: Economics studies the allocation of scarce resources; computation allocates time and memory to reach a target accuracy.
- ▶ Research trade-offs:
 - ▶ accuracy vs. cost/time
 - ▶ generality vs. problem-specific efficiency
- ▶ Remarks:
 - ▶ total time = human coding time + machine runtime
 - ▶ hardware and algorithms jointly determine runtime
 - ▶ tolerances formalize what counts as “accurate enough”: what error tolerance is defensible for this task?
- ▶ Two sources of errors:
 - ▶ Round-off error: from finite-precision arithmetic and representation.
 - ▶ Truncation error: from approximating a mathematical object by a finite or discrete

Round-off error: essentials

- ▶ Floating point in one line: numbers are stored with a sign, a few significant digits, and a scale (like $\times 10^k$ or $\times 2^k$). Only finitely many reals are representable and spacing is uneven.
- ▶ Machine epsilon $\varepsilon_{\text{mach}}$: smallest ε such that the machine recognizes $1 + \varepsilon > 1$ and $1 - \varepsilon < 1$; a local measure of rounding granularity near 1.
- ▶ Machine infinity and machine zero: the largest and smallest magnitudes still representable (in absolute value). Overflow occurs when a result exceeds machine infinity; underflow occurs when a nonzero result is rounded to machine zero.
- ▶ **Example 1:** 32 and 64 bit in laptop
 - ▶ 32-bit single: about 7 decimal digits; $\varepsilon_{\text{mach}} \approx 1.2 \times 10^{-7}$; representable magnitudes roughly 10^{-38} to 10^{38} .
 - ▶ 64-bit double: about 16 decimal digits; $\varepsilon_{\text{mach}} \approx 2.2 \times 10^{-16}$; magnitudes roughly 10^{-308} to 10^{308} .

Round-off: cancellation and remedies

- ▶ Error propagation: small initial errors can be magnified by arithmetic, especially subtraction of nearly equal numbers (cancellation).
- ▶ **Example 2:** solve $x^2 - 26x + 1 = 0$ for the small root.
 - ▶ True small root: $x^* = 13 - \sqrt{168} \approx 0.0385186 \dots$
 - ▶ Five-digit arithmetic (naive subtraction):

$$x^* \doteq 13.000 - 12.961 = 0.039 \equiv \hat{x}_1$$

- ▶ Algebraically stable form (avoids subtracting close numbers):

$$13 - \sqrt{168} = \frac{1}{13 + \sqrt{168}} \doteq \frac{1}{25.961} \doteq 0.038519 \equiv \hat{x}_2$$

Round-off: cancellation and remedies

- ▶ Practical habits to limit round-off:
 - ▶ rescale variables to typical magnitudes
 - ▶ avoid nearly singular transformations; prefer stable primitives
 - ▶ **Example 3:**
 - ▶ `hypot(a,b)`: computes $\sqrt{a^2 + b^2}$ using scaling to avoid overflow/underflow and loss of significance when $|a|$ and $|b|$ differ greatly. Example: `hypot(3e200,4e200)` is finite, while $\sqrt{(3 \cdot 10^{200})^2 + (4 \cdot 10^{200})^2}$ overflows.
 - ▶ `log1p(x)`: computes $\log(1 + x)$ accurately for small $|x|$, avoiding cancellation when $1 + x \approx 1$. Near zero it matches the series $x - \frac{x^2}{2} + \frac{x^3}{3} - \dots$.
 - ▶ `expm1(x)`: computes $e^x - 1$ accurately for small $|x|$, avoiding cancellation in $\exp(x) - 1$. Near zero it matches $x + \frac{x^2}{2} + \frac{x^3}{6} + \dots$ and preserves tiny negative results.
 - ▶ prefer additions of similar-scale terms; defer subtractions of nearly equal numbers via algebraic reformulation

Truncation error

- ▶ Truncation arises when replacing a continuous or infinite object by a finite one: finite differences for derivatives, finite time steps, or truncated series.
- ▶ **Example 4:** the exponential function

$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!}$$

must be approximated by a finite sum

$$\sum_{n=0}^N \frac{x^n}{n!}$$

with a remainder that shrinks as N grows (up to round-off limits).

- ▶ Choosing N or a step size is a trade-off: more terms or smaller steps reduce truncation error but may increase round-off and cost.

Conditioning

Conditioning (of the problem): how much the true solution can change under small input changes.

- ▶ Setup and notation:
 - ▶ True problem: $Ax = b$. Perturbed problem: $(A + \Delta A)(x + \Delta x) = b + \Delta b$.
 - ▶ Here $\Delta A, \Delta b$ are small data perturbations; Δx is the induced change in the solution.
 - ▶ A standard first-order bound (any consistent norm):

$$\frac{\|\Delta x\|}{\|x\|} \lesssim \kappa(A) \left(\frac{\|\Delta b\|}{\|b\|} + \frac{\|\Delta A\|}{\|A\|} \right), \quad \text{where } \kappa(A) = \|A\| \|A^{-1}\|.$$

Conditioning

Example 5:

- ▶ Well-conditioned matrix (use the 1-norm for concreteness):
 - ▶ $A = I_2$: $\|A\|_1 = 1$, $\|A^{-1}\|_1 = 1 \Rightarrow \kappa_1(A) = 1$.
 - ▶ $A = \text{diag}(1, 2)$: $\|A\|_1 = 2$, $A^{-1} = \text{diag}(1, 1/2)$ so $\|A^{-1}\|_1 = 1 \Rightarrow \kappa_1(A) = 2$.
- ▶ Ill-conditioned matrix (nearly singular 2×2):
 - ▶ $A_\varepsilon = \begin{bmatrix} 1 & 1 \\ 1 & 1 + \varepsilon \end{bmatrix}$, with $\varepsilon > 0$ small. $\det(A_\varepsilon) = \varepsilon$.
 - ▶ $A_\varepsilon^{-1} = \frac{1}{\varepsilon} \begin{bmatrix} 1 + \varepsilon & -1 \\ -1 & 1 \end{bmatrix}$.
 - ▶ $\|A_\varepsilon\|_1 = \max\{2, 2 + \varepsilon\} = 2 + \varepsilon$.
 - ▶ $\|A_\varepsilon^{-1}\|_1 = \max\left\{\frac{2+\varepsilon}{\varepsilon}, \frac{2}{\varepsilon}\right\} = \frac{2+\varepsilon}{\varepsilon}$.
 - ▶ Hence $\kappa_1(A_\varepsilon) = (2 + \varepsilon) \cdot \frac{2+\varepsilon}{\varepsilon} \approx \frac{4}{\varepsilon}$ (blows up as $\varepsilon \rightarrow 0$). $\varepsilon = 10^{-6} \Rightarrow \kappa_1 \approx 4 \times 10^6$: tiny data errors can cause order-one relative errors in x .

Stability: meaning and link to conditioning

Stability (of the algorithm): how much the computation amplifies rounding noise for a given problem.

- ▶ Setup:
 - ▶ True problem $Ax = b$ with exact solution x ; the algorithm returns \hat{x} .
 - ▶ Forward error: how far the answer is from truth, $\|\hat{x} - x\|/\|x\|$.
 - ▶ Backward error: how much inputs must be nudged so \hat{x} becomes exactly right, i.e., smallest $\Delta A, \Delta b$ with $(A + \Delta A)\hat{x} = b + \Delta b$.
- ▶ Backward-stable algorithm:
 - ▶ It promises tiny data nudges: $\|\Delta A\|/\|A\|, \|\Delta b\|/\|b\| = O(\varepsilon_{\text{mach}})$.
 - ▶ Interpretation: the computed \hat{x} is the exact solution of a nearby problem.
- ▶ Link to conditioning:

$$\frac{\|\hat{x} - x\|}{\|x\|} \lesssim \kappa(A) \left(\frac{\|\Delta A\|}{\|A\|} + \frac{\|\Delta b\|}{\|b\|} \right), \quad \kappa(A) = \|A\| \|A^{-1}\|.$$

Stability

- ▶ Remarks:
 - ▶ stability is about the algorithm; conditioning is about the problem
 - ▶ even a stable algorithm can yield large forward error on an ill-conditioned problem
- ▶ Example 6: quadratic roots
 - ▶ Direct formula $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ is unstable for the small root when $b^2 \gg 4ac$ (cancellation).
 - ▶ Stable rearrangement: set $q = -\frac{1}{2}(b + \text{sign}(b)\sqrt{b^2 - 4ac})$, then $x_1 = q/a$ and $x_2 = c/q$. This avoids subtracting nearly equal numbers and behaves like a backward-stable computation.

Rates of convergence

Let e_k be the error at iteration k . If $e_{k+1} \approx C e_k^p$:

- ▶ linear: $p = 1$, $0 < C < 1$ (steady geometric decay)
- ▶ superlinear: $p > 1$ or $C \rightarrow 0$ (faster than linear)
- ▶ quadratic: $p = 2$ (e.g., Newton near the solution)

Example 7: Newton on $f(x) = x^2 - 2$: $x_{k+1} = \frac{1}{2}(x_k + 2/x_k)$. Near $\alpha = \sqrt{2}$, the error satisfies $e_{k+1} \approx \frac{f''(\alpha)}{2f'(\alpha)} e_k^2 = \frac{1}{2\sqrt{2}} e_k^2$ (quadratic). Starting $x_0 = 1$:

$$e_0 \approx -0.4142, \quad e_1 \approx 0.0858, \quad e_2 \approx 2.45 \times 10^{-3}, \quad e_3 \approx 2.1 \times 10^{-6}.$$

Note $e_2 \approx \frac{1}{2\sqrt{2}} e_1^2$, illustrating quadratic decay.

Big-O for sequences

Big-O and little-o (for sequences $a_k, b_k > 0$):

$$a_k = O(b_k) \iff \exists C > 0, k_0 : |a_k| \leq C b_k \text{ for all } k \geq k_0, \quad a_k = o(b_k) \iff \frac{|a_k|}{b_k} \rightarrow 0.$$

Example 8: Polynomial growth: $a_k = 3k^2 + 5k$, $b_k = k^2$. Then $a_k/b_k = 3 + 5/k \leq 8$ for all $k \geq 1$. Hence $a_k = O(b_k)$. Moreover, $5k = o(k^2)$ since $(5k)/k^2 \rightarrow 0$.

Connection to convergence rates: if $e_{k+1} \leq r e_k$ with $r \in (0, 1)$, then $e_k \leq r^k e_0$, so $e_k = O(r^k)$ (linear/geometric convergence).

Efficient Evaluation of Expressions

Example 8: evaluate a polynomial $P_n(x) = \sum_{k=0}^n a_k x^k$ with minimal work. Methods:

- ▶ Direct (naive): compute each x^k via exponentiation and sum the terms.
- ▶ Alternative: expand x^k as $x \cdot x \cdots x$ each time (no exponentiation, but many repeated multiplications).
- ▶ Better method (reuse powers):
 - ▶ build powers once: set $t = 1$; for $k = 1, \dots, n$ do $t \leftarrow t \cdot x$ so $t = x^k$
 - ▶ accumulate: $S \leftarrow a_0$; for $k = 1, \dots, n$ do $S \leftarrow S + a_k t$
 - ▶ intuition: replaces the $n - 1$ exponentiations by $n - 1$ multiplications to form x^k ; avoids recomputing the same power for different terms
- ▶ Horner's method (nested form):

$$a_0 + a_1 x + \cdots + a_n x^n = a_0 + x(a_1 + x(\cdots + x(a_{n-1} + x a_n) \cdots))$$

- ▶ algorithm (top-down): $y \leftarrow a_n$; for $k = n - 1, \dots, 0$: $y \leftarrow a_k + x y$

Operation Counts for $P_n(x) = \sum_{k=0}^n a_k x^k$

Method	additions	multiplications	exponentiations
Direct (naive)	n	n	$n - 1$
Alternative (expand each x^k)	n	$n + \frac{(n-1)n}{2}$	0
Better method (reuse powers)	n	$2n - 1$	0
Horner's method	n	n	0

Notes:

- ▶ Better method: $n - 1$ multiplies to build x^k for $k = 1..n$ plus n multiplies for $a_k x^k$ (no multiply for a_0) gives $2n - 1$.
- ▶ Horner: exactly one multiply and one add per coefficient, so n multiplies and n adds; no powers are formed.
- ▶ Lesson: algebraically equivalent rewrites can change runtime by large constants, even when all methods are $O(n)$.

Finite-Difference Derivatives

For smooth f and small h :

$$\text{Forward: } f'(x) \approx \frac{f(x+h) - f(x)}{h} \quad \text{error } O(h) + O(\varepsilon_{\text{mach}}/h),$$

$$\text{Central: } f'(x) \approx \frac{f(x+h) - f(x-h)}{2h} \quad \text{error } O(h^2) + O(\varepsilon_{\text{mach}}/h).$$

- ▶ **Trade-off:** truncation (\downarrow with h) vs. round-off (\uparrow with $1/h$).
- ▶ Rule-of-thumb: choose h to balance both (often $h \sim \sqrt{\varepsilon_{\text{mach}}}$ in scaled units for central difference).

Direct vs. iterative methods

- ▶ Direct methods (e.g., Gaussian elimination)
 - ▶ pros: predictable error behavior; one-shot solve; good when the matrix is dense and fits in memory
 - ▶ cons: fill-in and memory growth for sparse problems; factorization cost can dominate for very large systems
- ▶ Iterative methods (fixed-point, Newton, Krylov, etc.)
 - ▶ pros: exploit sparsity/structure; matrix–vector products only; early stopping via tolerances
 - ▶ cons: need decent preconditioning/initialization; convergence diagnostics and stopping rules matter
- ▶ Stopping rules
 - ▶ residual norms $\|b - Ax_k\|$, step norms $\|x_k - x_{k-1}\|$, and problem-scale-aware tolerances

Direct vs. iterative methods

Example 9: Solve $Ax = b$ with $A = \begin{bmatrix} 4 & 1 \\ 1 & 3 \end{bmatrix}$, $b = \begin{bmatrix} 1 \\ 2 \end{bmatrix}$.

Direct (solve once):

$$A^{-1} = \frac{1}{11} \begin{bmatrix} 3 & -1 \\ -1 & 4 \end{bmatrix} \Rightarrow x^{\star} = A^{-1}b = \frac{1}{11} \begin{bmatrix} 1 \\ 7 \end{bmatrix} = \begin{bmatrix} 0.0909 \\ 0.6364 \end{bmatrix}.$$

Direct vs. iterative methods

Iterative (Jacobi; start $x^{(0)} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$):

$$x^{(k+1)} = \begin{bmatrix} \frac{1-x_2^{(k)}}{4} \\ \frac{2-x_1^{(k)}}{3} \end{bmatrix}$$
$$x^{(1)} = \begin{bmatrix} 0.25 \\ 0.6667 \end{bmatrix}, \quad x^{(2)} = \begin{bmatrix} 0.0833 \\ 0.5833 \end{bmatrix},$$
$$x^{(3)} = \begin{bmatrix} 0.1042 \\ 0.6389 \end{bmatrix}, \quad x^{(5)} = \begin{bmatrix} 0.0920 \\ 0.6366 \end{bmatrix} \approx x^*.$$

- ▶ direct: one factorization/solve gives x^* exactly (up to round-off)
- ▶ iterative: successive refinements approach x^* ; cost per step is a few multiplies/adds and one matrix–vector pattern (good for sparse A)
- ▶ stopping: halt when $\|b - Ax^{(k)}\|$ or $\|x^{(k)} - x^{(k-1)}\|$ drops below a tolerance tied to data scale

References & Further Reading

- ▶ K. L. Judd, Numerical Methods in Economics, Chapter 2 “Elementary Concepts.”
- ▶ “Notes for Chapter 2: Elementary Concepts” (slides/notes).