Computational Economics

# Lab: Working with AI Agents

Yaolang Zhong yaolang.zhong@e.u-tokyo.ac.jp
Graduate School of Economics, The University of Tokyo

# Lab Overview

- **Choose and direct an agent**
  - Model families, agent applications, and the harness
  - The tool execution loop and a concrete task prompt
- **Manage the information it uses**
  - Context, tokens, compaction, and caching
  - Project instructions and reusable skills
- **Connect, check, and reuse its work**
  - External tools through MCP
  - Inspect the result and rerun the program

## LLM Families and Developers

A **large language model (LLM)** processes context and generates text, code, or requests to perform actions.

- **GPT family** — developed by **OpenAI**.
  Examples: GPT-6 Astra, GPT-6.1 Sol, GPT-6 Luna.
- **Claude family** — developed by **Anthropic**.
  Examples: Claude Fable 5, Claude Opus 5.5, Claude Sonnet 5.5.
- **Gemini family** — developed by **Google DeepMind**.
  Examples: Gemini 4 Argon, Gemini 3.8 Flash.
- **Grok family** — developed by **xAI**.
  Examples: Grok 4.20, Grok 4.7.
- **DeepSeek family** — developed by **DeepSeek**.
  Examples: DeepSeek-V4-Pro, DeepSeek-V4.1-Flash.

# Agent Applications: LLM + Harness

An **agent harness** is the software surrounding an LLM. It provides **tools** and coordinates their use to complete a task. Tools available through a harness can include:

- **Files and coding:** search, read, create, and edit files.
- **Execution:** run Python, terminal commands, and tests.
- **Web access:** search the web, retrieve pages, and operate a browser.
- **External services:** access a database, cloud drive, or other connected service.

The harness prepares the model's context, handles permissions, executes requested tools, and returns their results to the model.

$$\underbrace{\text{LLM}}_{\text{selects actions}} + \underbrace{\text{harness}}_{\text{tools, context, and execution loop}} = \text{AI agent}$$

**Agent applications:** Codex (OpenAI), Claude Code (Anthropic), Cursor Agent (Cursor), Gemini CLI (Google), and GitHub Copilot (GitHub).

# How an Agent Completes a Task

A **task prompt** states what you want done. The agent uses each tool result to decide its next step.




Figure 1: Request, execute, and use the result.

- The model writes a **script**; a tool runs it and returns output or errors. The model checks the result and revises the code.
- A **CLI** accepts text commands, such as `python analysis.py`. The **terminal** hosts the session; the **shell** interprets commands.

**Use programs for repeatable work.** Reuse a checked script on new data; use the model to design, revise, and interpret it.

Reading: CarpeDiem, Code is the most handy tool for AI.

# From a Vague Request to a Concrete Task

To direct this workflow, specify the input, output, constraints, and checks in your prompt.

**Suppose you receive a new temperature file each week.**

Each `data.csv` contains `date` and `temperature_c`. You want a chart now and a procedure you can reuse next week.

**Vague prompt**

“Make a chart from my data.”

**Concrete prompt**

“Write `plot_temperature.py` to read `data.csv`, sort by date, and save a line chart to `results/temperature.png`. Label the axes Date and Temperature (Celsius).

Keep the input unchanged. Use the project Python environment. Run the script, check the dates, values, and units against the CSV, and inspect the chart. Report the files changed and the command used.”

**Result to check:** the chart and a reusable script. Next week, run the same script on the new file.

Reading: OpenAI, Prompt engineering.

# The Prompt Is Part of the Context

**Context** is the input the harness supplies to the model for its next response.




Figure 2: The harness assembles the model input.

- A **token** is a unit of input or output. The **context window** limits how much a call can accommodate.
- The harness loads relevant files and selects or summarizes earlier history.

**"Fix the axis label"** can accompany the CSV, script, and history: a short message can have a large input.

# Keep the Working Context Relevant

**Context engineering** selects and maintains relevant information. Even a large context can contain details the model overlooks.

- **Load what helps.** For a plotting error, retrieve the relevant code and error message.
- **Keep related work together.** Revise the chart in one session; start a new one for unrelated work.
- **Preserve decisions.** **Compaction** replaces earlier detail with a shorter summary. Check that essential requirements survive.
- **Separate lengthy side tasks.** A **subagent** can investigate in a separate context and return a concise result.

## A handoff to a fresh session

"The plotting script runs. Keep dates sorted and use Celsius. Next: compare the chart with `data.csv`."

Saved notes or **memory** help later sessions only when retrieved into their context.

Reading: CarpeDiem, Agent cost-saving tips (Part 1).

# Context Caching Reuses Computation

**Context caching** reuses computation for an unchanged input prefix when a compatible cache is available.

Figure 3: Reuse A + B; process the new C.

- Eligible cached input can cost less to process. Retention and prices depend on the provider.
- Changing earlier instructions or history can invalidate reuse. Cached text still occupies context space.
- Cache expiry requires recomputation; compaction changes which information the model receives.

**Judge the completed task:** a high cache-hit rate alone does not imply low cost or good results.

Reading: CarpeDiem, Agent cost-saving tips (Part 2).

# Reuse Instructions and Procedures

Keep recurring guidance in files the agent can load.

**Project instructions**
Rules for work in this project. Codex uses `AGENTS.md`; filenames and scope vary across applications.

**Chart project rules**

- Keep input data unchanged.
- Include units on axes.
- Save figures in `results/`.

A **skill**
A reusable procedure, with optional code and references. In the Agent Skills format:

```
plot-data/
  SKILL.md
  scripts/
  references/
```

**Plotting procedure:** read columns and units, create the figure, inspect it, and report checks.

The agent discovers a skill by its name and description, then loads its instructions when relevant. The skill guides tool use.

Reading: Agent Skills, Overview.

# Connect External Tools with MCP

Suppose the CSV is stored in a shared cloud folder. The agent needs an authorized way to retrieve it.

**Model Context Protocol (MCP)** standardizes how an AI application communicates with servers exposing tools and context.




Figure 4: An external connection for the same chart task.

- A server can offer **tools** to act, **resources** to read, and **prompt templates** to reuse.
- A drive tool could retrieve the CSV; the agent then uses its existing plotting workflow.
- Local files can use the application's file tools directly. Add an MCP connection when a needed service provides one.

Reading: Model Context Protocol, Architecture overview.

## Verify the Work Before Reusing It

A successful tool call or a confident completion message is evidence to inspect; compare the actual result with the task.

1. **Inspect the changes.** Review the script and confirm the input file was preserved.
2. **Reproduce the run.** Record the command and Python environment; rerun the script.
3. **Check the output.** Compare dates and values with the CSV; inspect axis labels and units.
4. **Keep the checked version.** Commit the script with Git so it can be reused or revised.

**For temperatures of 20, 22, and 21 Celsius,** the chart should preserve the date order and have its highest point at 22.

A **sandbox** restricts execution; **approvals** authorize actions. Retrieved files may contain **prompt injection**: instructions that try to redirect the agent. Treat external content as data to assess.

## Practice: Run, Check, and Reuse

Create a working folder and save this practice file as `data.csv`:

```
date,temperature_c
2026-10-01,20
2026-10-02,22
2026-10-03,21
```

1. Choose an agent application and a supported model. Give it the chart prompt and access to this folder.
2. Follow one tool call: inspect what it reads or runs and the result returned to the model.
3. Review the script, rerun it, and check the chart against the CSV.
4. Add one observation to the practice CSV yourself; rerun the same script.

**Extend the workflow:** save a project rule for axis units, or package the plotting procedure as a skill when supported.

# References and Further Reading


1. **OpenAI, Agent and Codex documentation. [Documentation]**
   - Codex as a platform: build on the open agent harness
   - Prompt engineering
   - Prompt caching
2. **Anthropic, Claude model and Claude Code documentation. [Documentation]**
   - Claude Code: Overview
3. **Microsoft, Visual Studio Code: agent and terminal documentation. [Documentation]**
   - Understand agent harnesses
4. **Model Context Protocol contributors, Model Context Protocol documentation. [Documentation]**
   - Architecture overview

# References and Further Reading


5. **Anthropic (2025), Effective context engineering for AI agents. [Technical article]**
   - Context engineering vs. prompt engineering
6. **Agent Skills contributors, Agent Skills documentation. [Documentation]**
   - Agent Skills Overview
7. **CarpeDiem (2026), AI Learning from Zero: practical agent tutorials. [Video series]**
   - Code is the most handy tool for AI
   - Agent cost-saving tips (Part 1): tokens and context
   - Agent cost-saving tips (Part 2): context caching